

MATERIAL SAFETY DATA SHEET

For R&D use only. Not for drug, household or other uses.

Click <http://www.lookchem.com/cas-685/68553-00-4.html> for suppliers of this product.

Composition/Information on Ingredient

Cas:
68553-00-4
Code:
M

RTECS:

Code:
X

Name:
FUEL OIL, RESIDUAL

Other REC Limits:
NONE RECOMMENDED

OSHA PEL:
NOT ESTABLISHED

Code:
M

OSHA STEL:

Code:

ACGIH TLV:
NOT ESTABLISHED

Code:
M

ACGIHSTEL:
N/P

Code:
1

Control Measures

Respiratory Protection:
NONE NORMALLY REQUIRED. IF IN CONFINED SPACES; USE NIOSH/MSHA APPROVED SUPPLIED AIR RESPIRATOR. IF RESPIRATOR USED, A PROGRAM IN ACCORDANCE WITH 29 CFR 1910.134 MUST BE IMPLEMENTED.

Ventilation:
LOCAL EXHAUST WITH > 30 CFM VELOCITY TO KEEP VAPORS BELOW REGULATORY LIMITS. USE EXPLOSION-PROOF EQUIPMENT.

Protective Gloves:
PROTECT AGAINST HOT LIQUID

Eye Protection:
SAFETY GLASSES

Other Protective Equipment:
Equipment CHEMICAL RESISTANT APRON OR OTHER IMPERVIOUS CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.

Work Hygienic Practices:
WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health:
MINIMIZE BREATHING VAPORS, MIST, OR FUMES. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN OR CLOTHING.

Health Hazards Data

LD50/LC50 Mixture:
ORAL LD50 (RAT) IS UNKNOWN

Route Of Entry Inds - Inhalation:
YES

Skin:
NO

Ingestion:
NO

Carcinogenicity Inds - NTP:
NO

IARC:
NO

OSHA:
NO

Health Hazards Acute And Chronic:
ACUTE: MAY CAUSE SKIN AND EYE IRRITATION OR THERMAL BURNS ON CONTACT. INHALATION OF VAPORS MAY IRRITATE RESPIRATORY SYSTEM OR CAUSE CENTRAL NERVOUS SYSTEM EFFECTS. CHRONIC: SKIN IRRITATION.

Explanation Of Carcinogenicity:
MFR: PRODUCT MAY CONTAIN COMPONENTS OR PETROLEUM FRACTIONS WHICH HAVE BEEN SHOWN TO CAUSE CANCER IN ANIMAL TESTS.

Signs And Symptions Of Overexposure:
INHALED: COUGHING, WHEEZING, SNEEZING, DIZZINESS, HEADACHE, NAUSEA, NERVOUSNESS, UNCONSCIOUSNESS. EYES: TEARING, REDNESS, BURNS (THERMAL), PAIN. SKIN: REDNESS, BURNS, PAIN, ITCHING, DISCOMFORT. INGEST ED: NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated By Exposure:
NONE SPECIFIED BY MANUFACTURER.

First Aid:
INHALED: REMOVE TO FRESH AIR. IF BREATHING STOOED, GIVE ARTIFICIAL RESPIRATION. IF BREATHING DIFFICULT, GIVE OXYGEN. GET IMMEDIATE MEDICAL ATTENTION. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES, WHI LE HOLDING EYELIDS OPEN. SEE DOCTOR. SKIN: IF BURNED, GET IMMEDIATE MEDICAL ATTENTION. IF NOT, WASH WITH SOAP AND WATER. INGESTED: GET IMMEDIATE MEDICAL ATTENTION.

Spill Release Procedures:
ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. KEEP OUT OF SEWERS AND WATERWAYS. CONTAIN SPILL. ABSORB WITH SAND OR OTHER INERT MATERIALS. PLACE IN A CONTAINER FOR LATER DISPOSAL.

Neutralizing Agent:
NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods:
DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Handling And Storage Precautions:
STORE AWAY FROM SOURCES OF IGNITION AND INCOMPATIBLE MATERIALS.

Other Precautions:
"EMPTY" CONTAINERS MAY RETAIN RESIDUE AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Fire and Explosion Hazard Information

Flash Point Method:
PMCC

Flash Point:

Flash Point Text:
140F,60C

Autoignition Temp:

Autoignition Temp Text:
N/A

Lower Limits:
0.3%

Upper Limits:
7%

Extinguishing Media:
FOAM, WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE, AND VAPORIZING LIQUID TYPE EXTINGUISHING AGENTS.

Fire Fighting Procedures:
WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL AND TO DISPERSE VAPORS.

Unusual Fire/Explosion Hazard:
TOXIC FUMES OR VAPORS MAY BE PRODUCED DURING A FIRE.

Physical/Chemical Properties

HCC:
F4

NRC/State LIC No:

Net Prop WT For Ammo:

Boiling Point:

B.P. Text:
450F,232C 3

Melt /Freeze Pt:

M.P/F.P Text:
75.0F,23.9C

Decomp Temp:

Decomp Text:
UNKNOWN

Vapor Pres:
<0.1 MM HG

Vapor Density:
>3 (AIR=1)

Volatile Org Content %:

Spec Gravity:
0.99

VOC Pounds/Gallon:

PH: N/K

VOC Grams/Liter:

Viscosity:
150 SSF

Evaporation Rate & Reference:

Solubility in Water:
NEGLEGIBLE

Appearance and Odor:
BLACK LIQUID, STRONG ASPHALT ODOR

Percent Volatiles by Volume:
NIL

Corrosion Rate:
UNKNOWN

Reactivity Data

Stability Indicator:
YES

Stability Condition To Avoid:
SOURCES OF HIGH TEMPERATURES AND SOURCES OF IGNITION

Materials To Avoid:
STRONG OXIDIZING AGENTS

Hazardous Decomposition Products:
FUMES, CARBON DIOXIDE, CARBON MONOXIDE, SMOKE, HYDROGEN SULFIDE, SULFUR OXIDES, ALDEHYDES, AND OTHER TOXIC PRODUCTS

Hazardous Polymerization Indicator:
NO

Conditions To Avoid Polymerization:
NONE

Toxicological Information

Information:N/P

MSDS Transport Information

Information:N/P

Regulatory Information

Sara Title III Information: N/P

Federal Regulatory Information: N/P

State Regulatory Information: N/P

Other Information

Other Information:N/P