



California State University Long Beach

College of Engineering

Computer Engineering Computer Science Department

Tuesday, November 11, 2019

Sixfold Flat File ArchiveDesign Document V1.0

Group Members:

Michell Kuang (Team Lead)	013421094
Joshua McDaniel	014542786
Jingyan Du	014436615
Peter Park	002948398
Jacen Tan	012393782
Daniel Gione	016513144

Version History

Version	Date	Author(s)	Comments
V1.0	11/10/2019	Jingyan Du	-Original document


Table of Contents

Table of Contents	2
1.Overview	3
2. Feature Life Cycle	3
3. Function Called	4
3.1.Diagram and Description	4
3.2.Error Handling	4
4. Data Collection	4
4.1. Diagram and Description	4
4.2. Error Handling	4
5. Flat File Output	4
5.1 Diagram and Description	4
5.2 Error Handling	4
6. File Store	4
6.1 Diagram and Description	4
6.2 Error Handling	4

Overview


This Document is made to show design concepts of flat file data archive feature of SixFold Household Manager. To use storage space efficiently, archive systems for logs are necessary. Diagrams for data flowing and error handling will be included to guide the developers.

Feature Life Cycle



Date Check


Diagram and Description



The flat file archive shall start on the 1st of each month at 00:00:00:00 UTC, system shall always keep checking if the datetime is eligible to do a flat file data archive. When DateCheck() function is called, it will request a validation to check if the datetime is correct and then return the result. If a TRUE is received, FindDateRange() function shall be called with the current datetime as a parameter to process the data collection phase. If a False is received, no function should be called and the system shall start another checking period.

Data Collection


Diagram and Description



Once the date is validated, the FindDateRange() function shall be called to find a range for logs those are eligible to be archived. Then the system shall request the result set from database based on the datetime range. The result set shall be return as an array.


Error Handling

Mongo DB Connection Exception



If the connection to Mongo DB is failed, the FetchByDateRange() function should throw a MongoConnectionException. After log the error, system should retry connecting to Mongo DB for max of 3 times. If the third time still fail, system should stop this archive, log archive as failure and notify the admin.

Argument Null Exception



If the result set from Mogo DB is null, it means no logs could be found based on the datetime range. In this way, the FileOuPut() function should not create a flat file for the empty array. The FileOutPut() function shall throw an argumentNullException, and the archive process should be stopped since no files could be created. The system admin shall be notified that no logs could be archived.

Flat File Output





Diagram and Description

Once the result set is returned, system shall write the result set to a .csv file for storage. If file is written successfully, the original logs shall be removed to save storage space.


Error Handling

File IOException



If the file output is failed, an IOException shall be throw and original data should not be removed. The system shall retry to create .csv file after logging the error. Up to 3 times if the file output is still failed. The process of data archive should be stopped and the system admin shall be notified.


Mongo DB Connection Exception



If the connection to Mongo DB is failed, then no data could be used to create a flat file. The function shall throw a MongoConnectionException, the error shall be logged and no original logs should be removed. The system shall retry the connection up to 3 times. If the connection is still failed, this archive process shall be stopped and logged as failure, the system admin shall be notified.

File Store


Diagram and Description



System shall try to connect to the storage machine and make a copy of the original flat file. Once the flat file is copied successfully, the original flat file shall be deleted. The period of data archive is finished and it shall be logged as success.


Error Handling

Connection Fail Exception



If the storage machine does not response, it shall be seen as a connection fail, a `ConnectionFailException` shall be thrown. The system shall log the error and try to reconnect to to the storage machine and if it still failed up to 3 times, the archive process shall be stopped. The system shall notify the system admin and log the data archive as failure.

Disk Full Exception



If the disk of storage machine is full, no flat file copy could be created, the function shall throw a `DiskFullException` and notify the system admin. The data archive process shall be stopped to avoid data lost. And this process of data archive shall be logged as failure.