PROBLEM 7 / SIXT + TUM

From company data to trustworthy answers

Calculate answers from fictional company data, explain your method, and submit your answer CSVs.

1 Receive the data

STAGE 1 / PUBLIC

Released at the start

25 CSV files + 200 questions
Rules + column descriptions
10 worked examples (unscored)

STAGE 2 / FINAL


New data, released later

25 CSV files + 200 questions
Own rules + column descriptions

Use each dataset separately.

Orders, payments, stock, returns, support and other linked records.

2 Build your method



1. Read the business rules
2. Link, filter and calculate
3. Check and export answers

Repeat for both stages

Small models welcome!

Use a framework or your own code.
Document models, tools and checks.

3 Submit your work

One row per question

CSV **public_answers.csv**

question_id	answer
P001	...
P002	...

CSV **final_answers.csv**

question_id	answer
F001	...
F002	...

Methods + presentation

Explain how your system works and show evidence of your results.

4 Get evaluated

PRIVATE ANSWER KEY

Reference answers
Hidden from teams

Automatic CSV comparison

Correct = 1; wrong or missing = 0.
All 200 questions count per stage.

DATASET RESULTS

toward the base grade **65 points**

HUMAN JUDGING

Other rubric criteria **35 points**

YOUR TOTAL

65 dataset + 35 judging

Base grade: up to 100 points

+

15-POINT SMALL-MODEL BONUS

Qualifying models: at most 40B total parameters.
Eligibility is verified from your model evidence.

→

UP TO 115

points in total

Inside the dataset score: 35% public accuracy + 65% final accuracy. See the marking scheme for the full formula.

400 scored questions + 10 practice examples. CSV = a spreadsheet-style table saved as a text file.

13 Nov 2026 (CET): Stage 1 at 09:30; Stage 2 and public lock at 14:45; all final work due at 16:45.

PROBLEM 7 / SIXT + TUM

How your score is calculated

A 100-point base grade, plus 15 extra points for a verified small-model workflow. Maximum: 115.

DATASET RESULTS
65 points
Automatic comparison of your answer CSVs
400 scored questions across two separate stages

HUMAN JUDGING
35 points
Five criteria from the event judging rubric

1. Calculate the dataset component

PUBLIC ACCURACY P
100 x public correct / 200

FINAL ACCURACY F
100 x final correct / 200

Dataset score D = 0.35P + 0.65F

Dataset points = 0.65D

Public answers can earn 22.75 points; final answers can earn 42.25.

2. Add judging and any bonus

J = (35 / 75) x raw rubric points

Base grade = 0.65D + J

Final total = base grade + bonus

Bonus = 15 if eligible; otherwise 0.
An eligible team can score up to 115 points.

3. Qualify for the small-model bonus

Use qualifying models substantively in your challenge workflow.
Every generative model used for method/code, answers or validation must have at most 40 billion total parameters, including fallbacks.

Count all MoE experts. Quantization does not reduce parameter count.
Submit exact model IDs, parameter evidence and usage logs.
Larger or undisclosed-size models can still earn the 100 base points.

WORKED GRADING EXAMPLE

160/200 public + 180/200 final correct
P = 80; F = 90; D = 86.5
Dataset points = 56.225
Judging: 60 / 75 -> 28 points

Base: 84.225

With bonus: 99.225 points

Scores are ranked before display rounding.

The +15 replaces the event's general +5 bonus. Add it once; maximum total = 115 points (no cap at 100).

Problem 7: SIXT + TUM Enterprise Data Agent Challenge

Project owner: Ioannis Tzachristas (TUM) · ioannis.tzachristas@tum.de · LinkedIn. On the day, ask on site.

Hackathon: Friday, 13 November 2026, HQ Pullach, Academy. All times below are local **CET (Europe/Berlin)**. Teams have 1 to 3 people; follow the main repository's topic-selection instructions by 10:00.

Turn business questions into correct answers. Build a method, calculate the answers from the supplied company data, and submit a CSV.

Printable student guide · Toy examples · Method report template

Companies store information across many systems. A simple question such as “What was net revenue?” can require linking orders, payments and refunds, applying the right business definitions, and converting currencies at the right time. Your team will build an AI-assisted analysis workflow that does this reliably on a fictional company's data.

Small models working with code, SQL, retrieval and other tools are especially welcome. A useful system does not need a huge model: it needs to find the right records, follow the rules and check its calculations.

What you will do

1. Read the supplied business rules, table descriptions and questions.
2. Use your chosen models and tools to inspect the data, link related records, and calculate an answer for each question.
3. Check the answers and export the required two-column CSV.
4. Explain your architecture, methods, validation and limitations in `SUBMISSION.md` and your demo video or slides.

You may use an existing agent framework, a custom workflow, or a mixture of model calls and ordinary programs. Framework choice alone earns no bonus. There is no requirement to submit a frozen executable solver: the automatically graded deliverable is the answer CSV. Your method and its evidence are assessed separately.

What teams receive and when

Release	Contents	What to submit
Before the Hackathon: 12 Nov	This overview, toy examples, marking policy and method-report template	Prepare your environment and team repository
Stage 1: public, 13 Nov at 09:30	25 data CSV files, business rules, column descriptions, 200 scored questions, 10 unscored worked examples, blank answer template and optional format checker	`public_answers.csv` before the 14:45 lock
Stage 2: final, 13 Nov at 14:45	A separate snapshot with 25 data CSV files, its rules and column descriptions, 200 scored questions and blank answer template	`final_answers.csv`, code, `SUBMISSION.md`, video or slides and method evidence by 16:45

There are **400 scored questions in total**, plus **10 unscored practice examples**. Every question has one scalar answer: a number, count, date, true/false value, or a text label; some questions request an ordered list in one text cell.

Treat the two snapshots separately. Reuse your workflow where helpful, but calculate each stage's answers from that stage's files and rules. Do not concatenate the snapshots.

The organizers share each stage archive and its SHA-256 at the stated release time. At 14:45 they record the latest eligible commit in each team's registered repository and lock the public answers. Later edits do not change that locked submission. At 16:45 they record the final submission. Push your files before each cutoff; keep the repository accessible to the topic owner and organizers. Record the archive filenames, hashes and the code revision used for your calculations in `SUBMISSION.md`; organizers record the locked submission commit IDs separately.

“Public stage” means the first competition stage, not that the repository or answer key is public. Reference answers and answer-level grading details stay private during the event. Any live leaderboard feedback will be announced to all teams on site.

What makes the task interesting

Expect linked tables covering customers, orders, payments, refunds, products, inventory, procurement, support and contracts. Some records should be excluded; some repeated records are legitimate; some joins can accidentally double-count an amount. Dates, changing contract versions, exchange rates and precise definitions can change the answer.

The challenge is to use models and tools to calculate reliably. Plausible prose is not a substitute for an answer that follows the supplied rules. Python, SQL, spreadsheets and deterministic checks can do the arithmetic while a model plans, selects tools, interprets definitions or checks the workflow.

See three fully worked toy examples. These miniature examples are separate from the live competition and can be shared before the event.

Marking scheme

The base grade is **100 points**. Dataset results contribute **65 points** and the event's other judging criteria contribute **35 points**. An eligible small-model workflow receives **15 additional bonus points**, so the maximum is **115**. The bonus is added once; it is not a multiplier and is not capped at 100.

Dataset results: up to 65 points

Let `P` and `F` be public and final accuracies as percentages from 0 to 100:

```
P = 100 × public correct answers / 200
F = 100 × final correct answers / 200
Dataset score D = 0.35 × P + 0.65 × F
Dataset contribution = 0.65 × D
```

The original 35/65 public/final split applies **inside the dataset component**. This makes the public answers worth up to **22.75 points** and final answers worth up to **42.25 points** of the overall grade.

The organizers compare the submitted CSVs with private reference answers. Each correct answer receives 1; a wrong, blank or missing answer receives 0. All 200 questions remain in each stage's denominator. Questions within a stage have equal weight. The format checker only checks file structure; it does not tell you whether an answer is correct.

Other judging criteria: up to 35 points

Problem 7 retains the five non-results criteria from the event rubric, with their original relative weights. Judges score each criterion on its original scale; the total out of 75 is multiplied by `35 / 75` to produce `J`, the judging contribution out of 35. The original 25-point “Results” category is replaced by the 65-point dataset component, so answer accuracy is not counted twice.

Criterion	Raw maximum	Contribution to base grade	What judges look for
Problem understanding	15	7	Understanding of the business problem, data and constraints
Quality of approach	25	11 2/3	A sound, justified method, a baseline comparison where available, and awareness of limitations
Business relevance and reusability	15	7	How SIXT could use the approach and clear next steps
Code quality and reproducibility	10	4 2/3	Readable code that runs from the instructions in `SUBMISSION.md`; no secrets or real data
Presentation and demo	10	4 2/3	A clear explanation, working demonstration and good answers
Total	**75**	**35**	

```
J = (35 / 75) × sum of the five raw criterion scores
```

Judge the working method and evidence, not slides alone. For example, raw scores `12 + 20 + 12 + 8 + 8 = 60` earn `J = 28` points. Judges score independently before discussion. The dataset component stays fixed when finalists present; the same five human criteria apply to their pitch and Q&A.

Small-model bonus: 15 points

The bonus is automatic once the organizers verify all the eligibility conditions below; it is not a subjective award for choosing a fashionable framework. For Problem 7, it replaces the event's general up-to-5-point bonus. The two bonuses do not stack.

- Every generative model used for challenge-specific method design, coding, analysis, answer generation or validation must have **at most 40 billion total parameters**. This includes planners, assistants, validators and fallback models.
- At least one qualifying model must perform a meaningful part of the analysis workflow. Merely reformatting answers already produced by a larger model does not qualify. A wholly manual or model-free solution receives no small-model bonus.
- For mixture-of-experts models, count **all parameters**, including inactive experts, not just the parameters activated per token. Quantization changes precision and memory use, not the parameter count. Each model in a multi-model workflow must meet the limit; their counts are not added together.
- Supply exact model names and versions, publisher/model-card evidence for total parameter counts, the framework and tool configuration, and concise usage/run evidence. Unknown or undisclosed model sizes cannot establish eligibility. A fine-tuned model must still meet the total parameter limit.
- Ordinary Python, SQL, spreadsheet calculations, retrieval and non-generative tools remain allowed. Local and hosted qualifying models are both acceptable, subject to the event's general tool policy.

Using a larger or unverifiable model does not remove your base-grade eligibility; it makes the workflow ineligible for the bonus. Disclose all model use honestly. The bonus has no minimum accuracy threshold and is awarded once for

the team's eligible workflow across both stages.

See the model declaration template and method report template. Remove credentials and secrets from submitted logs.

Total grade and example

```
Base grade = 0.65 × D + J                (0 to 100)
Bonus = 15 if verified eligible, else 0
Total grade = Base grade + Bonus         (0 to 115)
```

Example	Result
Public answers correct	160 / 200 = 80%
Final answers correct	180 / 200 = 90%
Dataset score	0.35 × 80 + 0.65 × 90 = 86.5
Dataset contribution	0.65 × 86.5 = 56.225 / 65
Other judging points	28 / 35
Base grade	84.225 / 100
Verified small-model bonus	+15
Total grade	**99.225 / 115**

A perfect base grade plus the bonus is **115 points**. Without the bonus, the example team earns **84.225 points**. Keep full precision for ranking; displayed scores may be rounded to two decimals. A displayed `99.22` is a rounded points total, not an accuracy percentage.

Ties on the exact total grade are resolved by higher dataset score, then jury discussion, following the event's Results-first tie policy. Dataset scores and human judging are recorded separately. Problem 7's 115-point maximum is an explicit project-specific exception to the general event rubric; organizers use this published policy for Problem 7 topic reviews and finalist judging.

Answer CSV format

Use exactly these headers, in this order:

```
question_id,answer
DEMO001,1
DEMO002,67.30
DEMO003,0
```

The example IDs above are teaching examples. In the competition, use the IDs supplied in each stage's blank template. Submit `public_answers.csv` for Stage 1 and `final_answers.csv` for Stage 2. Keep one row per question and put only the requested answer in the answer cell. Do not add explanations or extra columns.

Answer type	Recommended format and scoring rule
Number	Follow the question's units and rounding; absolute error at most 0.01 is accepted, with no relative tolerance
Count	Exact integral value

Answer type	Recommended format and scoring rule
Date	A valid `YYYY-MM-DD` date
Boolean	`true` or `false`
Text or ranking	Follow the supplied rule; case and whitespace are normalized, but ranking order matters
Undefined answer	`N/A` only when the correct result is undefined under the rules

An unknown, empty or duplicate ID, incorrect header, or malformed CSV row rejects the file. Missing answer rows and blank answers score zero. CSV row order does not affect accuracy. Use the supplied format checker and resolve errors before the deadline.

Setup before the event

Install **git and Python 3.11+** and create a virtual environment (`python -m venv .venv` or `uv venv`). Bring your own model access or local models; do not rely on SIXT providing LLM access. If claiming the bonus, your coding assistant must also meet the 40B rule. Create `requirements.txt` or `pyproject.toml` for your method and keep credentials in environment variables or a git-ignored `.env`.

Work inside `Project_7/` in your own team repository, not the organizers' source repository. Use the **Fork** button on the source repository, then clone your fork. Follow the main README to register your repository link and give the organizers access. Before arriving, check that you can run `python --version`, load the toy CSVs and push a commit to your own repository.

- Practise loading and joining CSV tables and exporting `question_id,answer` results.
- Choose your model and check its total parameter count if you plan to claim the bonus.
- Try a small workflow that reads a question, chooses relevant tables, runs a calculation and checks its result.
- Make your environment reproducible: record dependencies, model versions, settings and execution commands.
- Plan how to explain your method, division of work, checks, errors and limitations clearly.

Use METHOD_REPORT_TEMPLATE.md to prepare `SUBMISSION.md`. Cite the dataset using the citation supplied with the stage package, along with the package version, archive hash and access date. Only include a DOI if one has actually been assigned.

Submission checklist

- Valid `public_answers.csv` before the Stage 1 lock.
- Valid `final_answers.csv` before the final deadline.
- `Project_7/SUBMISSION.md`, using the method-report template.
- Your method code, dependencies/configuration and concise run evidence, with fresh-clone instructions sufficient to reproduce the workflow.
- **Either** `Project_7/submission/demo.mp4` (1-minute demo video, under 50 MB) **or** `Project_7/submission/slides.pdf` (at most 5 slides).
- Completed model declaration, including coding assistants and fallbacks; bonus evidence if claiming the small-model bonus.
- Dataset citation and any external code/model acknowledgements.

The registered team repository is the submission. Keep the answer files at `Project_7/public_answers.csv` and `Project_7/final_answers.csv`. By 16:45, push all final deliverables; no hacking is allowed during the 16:45-17:45 review period. Six finalists are selected across topics. If selected, give a maximum 3-minute pitch plus 2 minutes of Q&A during 17:45-18:20. Teams choosing a backup topic must name a primary topic and are scored under that primary topic's rubric.

Follow the event's data and integrity rules: use supplied synthetic/public data, never commit real SIXT/customer/personal data or secrets, and do not share the source repository outside the Hackathon. If a late or inaccessible repository prevents verification, the unverifiable dataset or code/reproducibility component receives no points under the event's late policy. Other misconduct follows the event's published disqualification rules.

Problem 7 uses the scoring policy on this page, including its replacement bonus. Older dataset documentation describing 35% public + 65% final as the “official score” refers to `D`, the dataset score only; it is not the full Hackathon grade.

Three toy examples

These miniature examples are invented for preparation. They are not live competition questions or private reference answers. All eligibility conditions not shown are assumed satisfied; the full competition rules remain authoritative for the released datasets.

DEMO001: Filter records without double-counting

Question: How many valid orders are there? For this example, a valid order must be completed or shipped and have at least one settled payment.

`orders.csv`:

order_id	status	payment_status
A	completed	paid
B	cancelled	paid
C	shipped	paid

`payments.csv`:

payment_id	order_id	status
p1	A	settled
p2	A	settled
p3	B	settled
p4	C	failed

Answer: `1`. Order A qualifies once despite having two settled payments. B is cancelled. C has no settled payment. Use the payments to establish eligibility, rather than counting joined payment rows as separate orders.

DEMO002: Apply discounts and the correct exchange rates

Question: What is net revenue in EUR for this valid single-line order?

Input	Value
Quantity	2
Unit price, USD	50
Total line discount, USD	10
Total order discount, USD	5
Order-month EUR per USD	0.90
Eligible approved refund, USD	10
Refund-month EUR per USD	0.92

Answer: `67.30`.

```
Discounted amount, USD = 2 × 50 - 10 - 5 = 85
Discounted amount, EUR = 85 × 0.90 = 76.50
Refund, EUR = 10 × 0.92 = 9.20
Net revenue, EUR = 76.50 - 9.20 = 67.30
```

The order has only one item line, so that line receives the entire order discount. Use the exchange rate for each event's month, and round only the final answer.

DEMO003: Respect a strict threshold

Question: How many replenishment units are suggested? Reorder only when end stock is strictly below the reorder point; if triggered, replenish to target stock.

Opening stock is 50. The reorder point is 40 and the target is 70.

Movement	Units	Status	Timing
Receipt	+20	posted	After stocktake, by reference time
Sale issue	-35	posted	After stocktake, by reference time
Return restock	+5	posted	After stocktake, by reference time
Adjustment	+100	draft	Before reference time
Receipt	+10	posted	After reference time

Answer: `0`. End stock is `50 + 20 - 35 + 5 = 40`. Exclude draft and future movements. Equality with the reorder point does not trigger an order. Do not add a receipt twice if it already appears in the movement ledger.

Example answer file

The complete file is demo_answers.csv:

```
question_id,answer
DEMO001,1
DEMO002,67.30
DEMO003,0
```

The teaching tables are also provided as CSV files. They are independent toy data with simplified schemas, not fragments of the live dataset.