PROJECT 5 / SIXT + TUM

From company data to trustworthy answers

Calculate answers from fictional company data, explain your method, and submit your answer CSVs.

1 Receive the data

STAGE 1 / PUBLIC

Released at the start

25 CSV files + 200 questions
Rules + column descriptions
10 practice examples (unscored)


STAGE 2 / FINAL

New data, released later

25 CSV files + 200 questions
Own rules + column descriptions

Use each dataset separately.
Orders, payments, stock, returns, support and other linked records.

2 Build your method



1. Read the business rules
2. Link, filter and calculate
3. Check and export answers

Repeat for both stages

Small models welcome!
Use a framework or your own code.
Document models, tools and checks.

3 Submit your work

One row per question

CSV **public_answers.csv**

question_id	answer
P001	...
P002	...

CSV **final_answers.csv**

question_id	answer
F001	...
F002	...

Methods + presentation
Explain how your system works and show evidence of your results.

4 Get evaluated

PRIVATE ANSWER KEY
Reference answers
Hidden from teams

Automatic CSV comparison
Correct = 1; wrong or missing = 0.
All 200 questions count per stage.

DATASET RESULTS
toward the base grade **65 points**

HUMAN JUDGING
Other rubric criteria **35 points**

YOUR TOTAL

65 dataset + 35 judging
Base grade: up to 100 points

+

15-POINT SMALL-MODEL BONUS
Qualifying models: at most 40B total parameters.
Eligibility is verified from your model evidence.

→

UP TO 115
points in total

Inside the dataset score: 35% public accuracy + 65% final accuracy. See the marking scheme for the full formula.

400 scored questions + 10 practice examples. CSV = a spreadsheet-style table saved as a text file.

Ioannis will announce the stage releases and deadlines. The real data and questions remain unreleased.

PROJECT 5 / SIXT + TUM

How your score is calculated

A 100-point base grade, plus 15 extra points for a verified small-model workflow. Maximum: 115.

DATASET RESULTS
65 points
Automatic comparison of your answer CSVs
400 scored questions across two separate stages

HUMAN JUDGING
35 points
Five criteria from the event judging rubric

1. Calculate the dataset component

PUBLIC ACCURACY P
100 x public correct / 200

FINAL ACCURACY F
100 x final correct / 200

Dataset score D = 0.35P + 0.65F

Dataset points = 0.65D

Public answers can earn 22.75 points; final answers can earn 42.25.

2. Add judging and any bonus

J = (35 / 75) x raw rubric points

Base grade = 0.65D + J

Final total = base grade + bonus

Bonus = 15 if eligible; otherwise 0.
An eligible team can score up to 115 points.

3. Qualify for the small-model bonus

Use qualifying models substantively in your challenge workflow.
Every generative model used for method/code, answers or validation must have at most 40 billion total parameters, including fallbacks.

Count all MoE experts. Quantization does not reduce parameter count.
Submit exact model IDs, parameter evidence and usage logs.
Larger or undisclosed-size models can still earn the 100 base points.

WORKED GRADING EXAMPLE

160/200 public + 180/200 final correct
P = 80; F = 90; D = 86.5
Dataset points = 56.225
Judging: 60 / 75 -> 28 points

Base: 84.225

With bonus: 99.225 points

Scores are ranked before display rounding.

The +15 replaces the event's general +5 bonus. Add it once; maximum total = 115 points (no cap at 100).

Imagine you are a data detective...

Imagine you are a detective helping a company. You get a box of spreadsheets and questions like: "How much did we sell?" and "What needs restocking?"

Your job is to teach a computer, with help from AI, to find the right files, follow the rules and calculate the answers. Hand in a CSV: a simple table with one question number and one answer on each row.

Later, you get a new box of data to see whether your method works again.

For now, try the three tiny solved examples. Ioannis will reveal the real data, questions and full instructions later.