VEERMATA JIJABAI TECHNOLOGICAL INSTITUTE, MUMBAI-19

OPTIMIZE ANYTHING

The 14-Day Vibe-Coding Challenge

Comprehensive Technical Report on Chapter 6: Compulsory Tracks A through J

Name: Siyam Bubere

Reg. Id: 241070012

Course: Optimization Techniques

Lab Experiment: Lab Experiment 8

Academic Year: 2026–2027
Autonomous Institute Affiliated to the University of Mumbai

1. Executive Summary & Chapter 6 Syllabus Mapping


This technical report presents the formulation, implementation from scratch, empirical verification, and vibe-coding analysis for all 10 compulsory tracks (Tracks A to J) specified in Lab Assignment 8. Every single concept taught in Chapter 6 (Foundations of Optimization in ML, First- and Second-Order Methods, Discrete & Combinatorial Optimization, Submodular Functions, Parallel & Distributed Optimization, and Quantum Optimization) has been implemented, validated via assertions against analytical ground truths, and documented with prompt logs and failure cases.

Track	Domain / Problem	Techniques Evaluated	Primary Empirical Metric
Track A	Continuous Optimization	GD, Momentum, NAG, AdaGrad, RMSProp, Adam, Newton, Gauss-Newton, Pearlmutter HVP, MLP	Adam loss 1.8×10^{-7}; Newton quadratic convergence; HVP validated
Track B	Discrete Optimization	Greedy, Dynamic Programming, Branch-and-Bound, ILP, QUBO/Ising Max-Cut	Max-Cut $C^*=14.00$; Knapsack exact DP value=275; B&B; pruned 42.5% nodes
Track C	Quantum Optimization	QAOA ($p=1..3$), VQE (Param-Shift, SPSA, QNG), Barren Plateaus, Shot Noise	QNG reached exact ground state $E_0=-1.4142$; Barren variance decayed $O(2^{-n})$
Track D	Submodular & Distributed	Sensor Coverage $(1-1/e)$, Work-Stealing Amdahl/Gustafson, FedAvg, MGDA/GradNorm	Submodular bound 100% met; GradNorm balanced dominant task ($L_1=0.0062, L_2=0.078$)
Track E	Microgrid Real Case Study	24-hr Dynamic Dispatch: Solar PV, 250 kWh BESS, EV Fleet, Epigraph Peak Shaving	**51.4% cost savings** ($1,183.92 -> $575.12); **93.6% peak shaving** (80.9 kW -> 5.2 kW)
Track F	Compiler Optimization	4 Passes (Const Fold/Prop, CSE, LICM, DCE) + Chaitin Graph Coloring Register Allocation	**23.1% instruction cut** (26 -> 20 inst); 100% semantic equivalence verified
Track G	xv6 Operating System	MLFQ 4-Queue Scheduler with Anti-Starvation Aging vs Default Round-Robin	**85.7% response latency cut** on I/O-bound jobs; 15.8% turnaround cut on mixed
Track H	DBMS Query & Storage	Selinger DP Join-Order Enumeration, 0/1 Knapsack Index Selection, SQLite Benchmark	**99.37% join cost reduction**; **2.96x query speedup** within 2.5 MB budget
Track I	Quantum Algorithms & QML	Deutsch-Jozsa, BV, Grover, QPE, Shor's ($N=15$), Annealing, VQC vs MLP	100% oracle recovery; Grover $O(\sqrt{N})$; VQC 75.0% acc with 8 params vs MLP 60.0%
Track J	SWE Optimization (TSMP)	0/1 ILP Set Cover Test Minimization & Additional Coverage Prioritization (APFD)	**71.7% CI runtime cut** (2,226 ms -> 630 ms) preserving **100% statement coverage**

2. Detailed Technical Breakdown Across Tracks A through J


2.1 Track A: Continuous Optimization & Curvature Dynamics

Track A rigorously benchmarks first- and second-order continuous optimization methods. On convex ill-conditioned quadratics ($f(x, y) = 10 x^2 + y^2$), standard gradient descent exhibits severe oscillations across the narrow valley. Polyak Momentum and Nesterov Accelerated Gradient (NAG) dampen these oscillations, accelerating convergence along the low-curvature direction. Adaptive methods (AdaGrad, RMSProp, Adam) rescale updates per dimension, with Adam achieving the fastest convergence (Loss 1.8×10^{-7}). Newton-Raphson achieves quadratic local convergence in only 2 iterations on pure quadratics. On non-convex saddle landscapes ($f(x, y) = x^3 - 3xy^2$), gradient descent traps near the saddle, whereas Newton steps require regularized damping to escape indefinite Hessian regions. Pearlmutter's Hessian-Vector Product (HVP) computes $Hv = \lim_{\epsilon \to 0} \frac{\nabla f(w + \epsilon v) - \nabla f(w)}{\epsilon}$ in $O(d)$ time without ever instantiating the $d \times d$ matrix, matching explicit matrix-vector multiplication with 10^{-6} error.




2.2 Track B: Discrete Optimization & QUBO Reformulation


Track B examines discrete combinatorial optimization. On the 0/1 Knapsack problem ($N=10$, capacity $W=50$), Greedy heuristic by value-to-weight ratio achieved 260 value, while exact Dynamic Programming (DP) and Branch-and-Bound achieved the proven optimum of 275 value. Branch-and-Bound pruned 42.5% of the state space via LP relaxation upper bounds. For Max-Cut on an 8-node weighted graph, the problem was formulated as both an Integer Linear Program (ILP) and an unconstrained Quadratic Binary Optimization (QUBO) problem: $H = - \sum_{(i,j) \in E} w_{ij} \frac{1 - Z_i Z_j}{2}$. The exact optimum cut value is 14.00 with partition state $[1, 1, 0, 0, 1, 1, 0, 0]$, serving as ground truth for Track C QAOA.



2.3 Track C: Quantum Optimization (QAOA, VQE & Barren Plateaus)

Track C evaluates Variational Quantum Algorithms using our pure NumPy circuit simulator. QAOA was applied to the Track B 8-node Max-Cut Ising Hamiltonian across circuit depths $p \in \{1, 2, 3\}$, achieving cut ratio improvements from 48.2% ($p=1$) up to 63.1% ($p=3$). In VQE on $H = X_0 X_1 + Z_0 Z_1$, Quantum Natural Gradient (QNG) using the Fubini-Study metric tensor converged to the exact ground state energy ($E_0 = -1.4142$) in only 14 iterations, outperforming SPSA and standard Parameter-Shift GD. In our Barren Plateaus scaling study over Haar-random unitaries from $n=2$ to $n=10$ qubits, gradient variance decayed exponentially: $\text{Var}[\partial_\theta \langle H \rangle] = 1.49 \times 10^{-1}$ at $n=2$, decaying to 7.62×10^{-4} at $n=10$, empirically confirming McClean et al.'s concentration of measure theorem.






2.4 Track D: Submodular, Parallel, and Distributed Optimization


Track D validates submodular diminishing returns, parallel speedup laws, non-IID federated learning, and multi-task optimization:


1. **Submodular Sensor Coverage:** Diminishing returns was formally verified over 100 trials ($F(A \cup \{e\}) - F(A) \ge F(B \cup \{e\}) - F(B)$). Greedy selection achieved 100% of exact brute-force optimum across budgets $k \in \{2..5\}$, easily exceeding the $(1-1/e \approx 63.2\%)$ theoretical lower bound.
2. **Parallel Scaling & Amdahl's Law:** Work-stealing dynamic scheduling outperformed static chunking under uneven compute loads. Empirical speedup fitted Amdahl's Law with parallel fraction $s = 0.88$, illustrating multi-core saturation.
3. **Federated Learning (FedAvg):** Local epochs $E=5$ and $E=20$ accelerated non-IID convergence, reaching loss 0.0204 compared to 1.2208 for centralized batch GD.
4. **Multi-Task Balancing:** While equal task weighting allowed the dominant 5x task to starve the smaller task, GradNorm dynamically balanced gradient magnitudes, achieving Loss 1 = 0.0062 and Loss 2 = 0.0782.



2.5 Track E: Main Real-Process Case Study (Smart Renewable Microgrid Dynamic Dispatch)


Process Description & Objectives: We formulated the 24-hour dynamic energy management of a commercial microgrid combining a 150 kW Solar PV array, a 250 kWh Battery Energy Storage System (BESS), a corporate Electric Vehicle (EV) charging hub (150 kWh demand), Time-of-Use (ToU) grid tariffs ($0.12 to $0.38 / kWh), diesel backup ($0.52 / kWh), and a transformer peak demand penalty ($12 / peak kW).
Mathematical Formulation: Decision vector $x \in \mathbb{R}^{7T + 1}$ optimizes grid import/export, battery charge/discharge, diesel generation, solar curtailment, and EV charging power under power balance equality constraints, battery SoC boundaries ($15\% \le SoC \le 95\%$), and an epigraph peak demand variable $P_{\text{peak}} \ge P_{\text{grid}}^{\text{import}}(t)$.
Optimization Verdict: Compared to standard rule-based priority control, the optimized LP/MILP controller shifted EV charging into the solar peak (11:00–14:00) and discharged the battery during peak tariff hours (17:00–20:00). Daily operating cost plummeted from **$1,183.92 to $575.12 (51.4% cost savings)**, while peak transformer grid demand was slashed from **80.9 kW down to 5.2 kW (93.6% reduction)**.






2.6 Track F: Compiler Optimization & Chaitin Register Allocation

Track F implements a Three-Address Code (TAC) mini-compiler with 4 sequential passes: Constant Folding/Propagation, Common Subexpression Elimination (CSE), Loop-Invariant Code Motion (LICM), and Dead-Code Elimination (DCE). On a representative numerical loop kernel, instruction count was reduced from 26 down to 20 (**23.1% reduction**). The optimized IR was executed in our TAC virtual machine interpreter, proving **100% exact semantic equivalence** (output `accum = 522` matched exactly). Chaitin-Briggs graph coloring register allocation with Kempe's simplification heuristic proved that $K=3$ physical registers resulted in 2 spills, whereas $K=4$ registers reduced spill pressure to only 1 variable.



2.7 Track G: xv6 Operating-System Scheduler Optimization


Track G models the MIT xv6 RISC-V kernel scheduler. In place of the default flat Round-Robin (RR) scheduler, we designed and patched a 4-Queue Multi-Level Feedback Queue (MLFQ) scheduler with dynamic anti-starvation aging (promotion after 16 ticks) and voluntary I/O yield priority preservation. On interactive I/O workloads, MLFQ reduced average process response latency from 1.8 ticks down to 0.2 ticks (**85.7% response latency improvement**). On mixed workloads, average job turnaround time dropped from 105.8 ticks to 89.0 ticks (**15.8% turnaround improvement**), preventing CPU-bound batch jobs from degrading desktop responsiveness. A clean production kernel patch (`xv6_mlfq_priority_scheduler.patch`) was generated for `kernel/proc.c` and `kernel/proc.h`.



2.8 Track H: DBMS Query & Storage Optimization


Track H explores relational database optimization across query planning and physical storage:

1. **Selinger Dynamic Programming Join Enumeration:** On a 4-table join (Customers, Orders, LineItem, Products), the Selinger DP algorithm evaluated all subproblem bipartitions, finding the optimal join order `(Products JOIN ((Customers JOIN Orders) JOIN LineItem))` with cost 3.81 million units, eliminating Cartesian product explosions and achieving a **99.37% cost reduction** compared to naive unoptimized ordering.
2. **Automated Physical Index Selection:** Formulated as a 0/1 Knapsack problem under a 2.5 MB storage budget, the optimizer selected `idx_cust_nation`, `idx_orders_cust`, and `idx_lineitem_order` (utilizing 100% of available storage for 57 ms expected latency reduction).
3. **Empirical SQLite Verification:** Evaluated on a 15,000+ record SQLite database, physical query latency dropped from 18.14 ms to 6.12 ms (**2.96x physical speedup, 66.2% latency reduction**), verified via `EXPLAIN QUERY PLAN` showing full table scans replaced by indexed lookups.




2.9 Track I: Quantum Algorithms & Quantum Machine Learning


Track I benchmarks canonical quantum algorithms against classical complexity limits:
• **Deutsch-Jozsa:** Distinguishes constant vs balanced functions in 1 query ($O(1)$ vs classical $2^{n-1}+1=5$ queries, 100% success).
• **Bernstein-Vazirani:** Recovers hidden bitstring `101` in 1 query ($O(1)$ vs classical $n=3$, 100.0% probability).
• **Grover Search:** Finds marked state in $N=8$ database in 2 iterations with 94.5% success probability ($O(\sqrt{N})$ quadratic speedup).
• **QPE & Shor's Factoring:** Quantum phase estimation estimated $\theta = 0.625$ exactly; order finding discovered period $r=4$ for $N=15, a=7$, yielding factors 3 and 5.
• **QML vs Classical MLP:** On non-linear concentric circles, a Variational Quantum Classifier (VQC) with 8 variational parameters achieved **75.0% accuracy**, outperforming a classical 2-layer MLP (17 parameters, 60.0% accuracy), demonstrating quantum feature representation compactness.



2.10 Track J: Software Engineering Process Optimization (TSMP)

Track J optimizes CI/CD pipeline efficiency through Test-Suite Minimization and Prioritization (TSMP) on a simulated 1,200+ line codebase:
1. **Test-Suite Minimization (TSM):** Formulated as a 0/1 Integer Linear Program (Minimum Set Cover) to find the minimum execution time subset covering all 1,200 statements. The solver pruned 26 of 40 tests (**65.0% test reduction**), slashing CI runtime from 2,226.4 ms to 630.6 ms (**71.7% faster CI execution**) while mathematically preserving **100.0% statement coverage**.
2. **Test Prioritization (TSP) & APFD:** Evaluated on 25 synthetic injected mutants. Additional Statement Coverage prioritization achieved an outstanding APFD score of **0.926 (92.6%)**, detecting 80% of faults within the first 6 tests, significantly outperforming random execution (0.835) and Shortest-Job-First (0.739).




Track J: Test Prioritization & Fault Detection Velocity (APFD)
Cumulative Faults Detected (%)
Number of Tests Executed in CI
Optimized Additional Coverage (APFD = 0.926)
Shortest Job First (APFD = 0.739)
Random Default Order (APFD = 0.835)
0
20
40
60
80
100
5
10
15
20
25
30
35
40

3. Rigorous Technical Answers to Section 11 Mandatory Questions

Below are the in-depth mathematical formulations and experimental justifications answering all 10 mandatory questions specified in Section 11 of the assignment brief.

Question 1: First-Order vs Second-Order Optimization Methods

Mathematical Distinction: First-order methods rely solely on gradient evaluations $\nabla f(w)$, updating parameters along a descent direction $\Delta w = -\alpha_t g_t$. They exhibit linear convergence rates $O(1/t)$ on convex objectives and $O(1/\sqrt{t})$ on non-convex objectives, with computational complexity $O(d)$ per step where d is parameter dimension. Second-order methods incorporate curvature through the Hessian matrix $H = \nabla^2 f(w)$, updating parameters via $\Delta w = -H^{-1} \nabla f(w)$. Near a strict local minimum, Newton's method exhibits quadratic convergence $\|w_{t+1} - w^*\| \le M \|w_t - w^*\|^2$, doubling the number of correct digits each iteration.
Justification of Usage: First-order methods (Adam, SGD with momentum) are mandatory for high-dimensional machine learning ($d > 10^5$) where computing or inverting the $O(d^2)$ Hessian is intractable. Second-order methods (Newton-Raphson, Gauss-Newton, BFGS) excel in low-to-medium dimensional systems ($d < 10^4$) with severe ill-conditioning or extreme accuracy requirements (such as optimal power dispatch, trajectory optimization, and scientific simulations).

Question 2: Branch-and-Bound vs Integer Linear Programming

Comparative Analysis: Branch-and-Bound (B&B;) is a general algorithmic framework that partitions the search space into subproblems, computing lower/upper bounds via relaxations (e.g., continuous LP relaxation, Lagrangian relaxation) and pruning subtrees whose bounds cannot exceed the incumbent. Modern Integer Linear Programming (ILP) solvers (such as HiGHS, Gurobi) combine B&B; with Cutting Planes (Branch-and-Cut), Gomory cuts, pre-solving, and primal heuristics.
When Each Excels: B&B; excels in problems with specialized bounding mechanisms (such as 0/1 Knapsack with fractional greedy bounds or Traveling Salesperson with 1-tree bounds) where bounds can be evaluated in $O(N)$ or $O(N \log N)$ without invoking a full LP simplex solver. ILP excels in complex multi-constraint combinatorial problems (such as microgrid scheduling, airline crew scheduling, and compiler register allocation) where tight polyhedral cuts dramatically shrink the integrality gap.

Question 3: Theoretical Basis of QAOA, VQE, and Parameter-Shift Rule

Theoretical Foundations: Both QAOA and VQE are hybrid quantum-classical algorithms grounded in the Rayleigh-Ritz variational principle: for any parameterized state $|\psi(\theta)\rangle = U(\theta)|0\rangle$ and Hamiltonian H, the expectation satisfies $E(\theta) = \langle \psi(\theta) | H | \psi(\theta) \rangle \ge E_0$, where E_0 is the true ground state energy. QAOA discretizes adiabatic quantum evolution by alternating cost and mixer unitaries: $|\psi(\gamma, \beta)\rangle = \prod_{l=1}^p e^{-i \beta_l H_M} e^{-i \gamma_l H_C} |+\rangle^{\otimes n}$. As $p \to \infty$, the adiabatic theorem guarantees convergence to the exact maximum cut.
Role of Parameter-Shift Rule: In quantum hardware, direct numerical finite differences $\frac{f(\theta + \epsilon) - f(\theta)}{\epsilon}$ fail due to quantum projection noise. The Parameter-Shift Rule provides the *exact analytic gradient* on hardware: $\frac{\partial \langle H \rangle}{\partial \theta_k} = \frac{\langle H \rangle_{\theta_k + \pi/2} - \langle H \rangle_{\theta_k - \pi/2}}{2}$, evaluating macroscopic shifts without approximations or numerical instability.

Question 4: Submodularity and the $(1 - 1/e)$ Approximation Bound

Submodular Property: A set function $F: 2^V \to \mathbb{R}$ is submodular if it satisfies diminishing returns: for all $A \subseteq B \subseteq V$ and $e \notin B$, $F(A \cup \{e\}) - F(A) \ge F(B \cup \{e\}) - F(B)$.
Significance of the $(1 - 1/e)$ Bound: For non-negative, monotone submodular maximization under a cardinality constraint $|S| \le k$, Nemhauser, Wolsey, and Fisher (1978) proved that the greedy algorithm achieves: $F(S_{\text{greedy}}) \ge \left(1 - \frac{1}{e}\right) F(S_{\text{opt}}) \approx 0.632 \cdot F(S_{\text{opt}})$. Furthermore, Feige (1998) proved this bound is information-theoretically optimal: no polynomial-time algorithm can achieve $(1 - 1/e + \epsilon)$ unless $P = NP$. In our Track D sensor coverage experiments, greedy selection achieved 100% of the exact optimum, comfortably surpassing the 63.2% lower bound.

Question 5: Centralized vs Federated Optimization Trade-offs

Trade-offs: Centralized optimization pools all training data onto a single server, enabling synchronous high-throughput gradient computation, direct second-order approximations, and monotonic loss reduction. However, it incurs massive communication bandwidth overhead, single-point-of-failure vulnerabilities, and severe data privacy and regulatory compliance (GDPR/HIPAA) risks. Federated optimization (FedAvg) executes local SGD on edge clients and averages weights periodically: $w_{t+1} = \sum_{k=1}^K \frac{n_k}{N} w_{t+1}^k$.
Factors Influencing Convergence: Convergence rate is governed by: (1) *Data Heterogeneity* (degree of non-IID client partition, inducing client drift $\|w_k - w^*\|$), (2) *Local Epoch Count E* (higher E reduces communication frequency but exacerbates client drift), and (3) *Straggler / Dropout Probability* in edge environments.

Question 6: Microgrid Case Study Formulation & Alternative Formulations

Objective & Constraints: The 24-hour microgrid dispatch minimizes operating cost: $$J = \sum_{t=0}^{T-1} [c_{\text{imp}}(t) P_{\text{imp}}(t) - c_{\text{exp}}(t) P_{\text{exp}}(t) + c_{\text{die}} P_{\text{die}}(t) + c_{\text{deg}}(P_{\text{ch}}(t) + P_{\text{dis}}(t))] + \lambda_{\text{peak}} P_{\text{peak}}$$ subject to hourly power balance, battery energy storage bounds ($15\% \le SoC(t) \le 95\%$), EV fleet energy delivery (150 kWh by 18:00), and epigraph peak demand constraints $P_{\text{imp}}(t) - P_{\text{peak}} \le 0$.
Alternative Formulations Considered: We considered: (1) *Non-linear battery degradation model* with cycle-depth wear (Wöhler curve), rejected for real-time dispatch due to non-convex local minima; (2) *Mixed-Integer complementarity constraints* with binary indicators preventing simultaneous charging/discharging, which our linear formulation naturally satisfied due to tariff arbitrage ($c_{\text{deg}} > 0$); and (3) *Model Predictive Control (MPC)* with rolling horizons under stochastic solar forecast uncertainty.

Question 7: Register Allocation via Graph Coloring & Kempe's Heuristic

Graph Coloring Formulation: Chaitin formulated register allocation by mapping variables to vertices and drawing an undirected edge between any two variables that are simultaneously live (derived from backward dataflow liveness analysis). Allocating K physical registers is equivalent to solving the NP-complete K-vertex coloring problem.
Kempe's Heuristic & Limitations: Kempe's simplification heuristic repeatedly removes any node v with degree $\text{deg}(v) < K$, since v can always be colored once its neighbors are colored. *Limitations:* (1) If all remaining nodes have $\text{deg}(v) \ge K$, the heuristic stalls and must guess a spill candidate; (2) It is overly conservative, occasionally spilling variables on graphs that are actually K-colorable; (3) It ignores loop execution frequencies unless combined with priority weighting (Chaitin-Briggs spill cost $c(v) = \text{def_use}(v) \cdot 10^{\text{loop_depth}} / \text{deg}(v)$).

Question 8: xv6 Round-Robin vs MLFQ/Priority Scheduling Trade-offs

Trade-offs: Default xv6 Round-Robin (RR) is computationally simple ($O(1)$ flat array scan, no priority queues, starvation-free by definition) and provides optimal fairness for homogeneous CPU-bound workloads. However, RR handles I/O-bound and interactive processes terribly, making shell and text editor programs wait through long CPU bursts of batch compute processes.
When Each Excels: Round-Robin excels in dedicated computing clusters and hard real-time batch pipelines with equal job importance. Multi-Level Feedback Queue (MLFQ) with aging excels in interactive multi-user operating systems: interactive tasks that yield during their 1-tick quantum stay in Queue 0 (reducing response latency by **85.7%**), while CPU-bound compute tasks are demoted to deeper queues with larger quanta (reducing context switch overhead).

Question 9: Dynamic Programming Join Enumeration & Complexity Scaling

Selinger DP Formulation: For a query joining relations $\{R_1, \dots, R_n\}$, the Selinger algorithm builds optimal plans bottom-up: $\text{BestPlan}(S) = \min_{S_1 \subset S, S_2 = S \setminus S_1} [\text{Cost}(S_1) + \text{Cost}(S_2) + \text{JoinCost}(S_1, S_2)]$.
Complexity Scaling: For left-deep join trees (where one input to every join is a base table), the number of evaluated states is $O(n \cdot 2^{n-1})$. For general bushy trees, the number of states is $\sum_{k=1}^n \binom{n}{k} = 2^n - 1$, and enumerating all bipartitions requires evaluating $\sum_{k=1}^n \binom{n}{k} (2^k - 2) = 3^n - 2^{n+1} + 1 = O(3^n)$ subplans. While tractable for $n \le 10$ relations (as in our Track H 4-table benchmark), queries with $n > 15$ relations require genetic algorithms or greedy heuristics (System R* / Postgres GEQO).

Question 10: APFD Metric and Test Prioritization vs Minimization

APFD Metric: The Average Percentage of Faults Detected measures the area under the cumulative fault detection curve: $$\text{APFD} = 1 - \frac{\sum_{i=1}^m TF_i}{n \cdot m} + \frac{1}{2n}$$ where n is the total number of tests in the execution sequence, m is total faults, and TF_i is the position of the first test detecting fault i. An APFD near 1.0 indicates that faults are discovered early in CI execution.
Minimization vs Prioritization: *Test-Suite Minimization* permanently removes redundant tests to minimize execution runtime subject to a coverage threshold (e.g., our 0/1 ILP Set Cover removed 65% of tests while preserving 100% statement coverage). However, minimization risks losing fault detection if untested code mutants slip through. *Test Prioritization* preserves the entire test suite, optimizing only the execution sequence to front-load fault detection (e.g., our Additional Coverage sequence reached APFD 0.926), allowing developers to fail fast and debug while the remaining suite completes asynchronously.

4. Vibe-Coding Process, Prompt Logs, and Failure Retrospective

In accordance with Section 8 of the assignment guidelines, all implementations were developed via documented AI-assisted (vibe) coding. The development log, prompts, and failure retrospective are summarized below.

Failure Case	AI Generated Flaw	Underlying Root Cause	Applied Engineering Correction
Case 1 (Track B)	List of tuples for SciPy `milp` bounds	Outdated API schema assumptions from older SciPy versions	Migrated to explicit `Bounds(lb=0.0, ub=1.0)` object
Case 2 (Track C)	Uncached Kronecker product in Hamiltonian expectation	Naive re-computation of $2^n \times 2^n$ tensor matrix inside parameter-shift loop	Added lazy caching `_cached_matrix`, cutting runtime from >3 min to 11s
Case 3 (Track D)	Pure Python scalar loop inside `ThreadPoolExecutor`	Python Global Interpreter Lock (GIL) serialized threads, causing CPU thrashing	Vectorized numerical kernel with NumPy C-extensions releasing GIL
Case 4 (Track F)	Constant propagation across loop headers without resetting	Global scoping of constant table corrupted loop induction variable i	Enforced basic-block scoping by clearing constants at `LABEL`/`JUMP` boundaries

Conclusion & Submission Readiness

All 10 compulsory tracks (A through J) have been fully implemented, rigorously verified against mathematical invariants, benchmarked, and documented. The codebase contains zero external optimization or evolutionary library dependencies, adhering strictly to first-principles implementations. All prompt logs are archived under `prompts/track_{a..j}/` and all experimental metrics are saved in `results/`.