


# DS2\_HW3

Siyan Chen

4/6/2019

(a) Produce some graphical summaries of the Weekly data.

```
featurePlot(x = df[, 2:7],
            y = df$Direction,
            scales = list(x=list(relation = "free"),
                          y=list(relation = "free")),
            plot = "box", pch = "|")
```



(b) Use the full data set to perform a logistic regression with `Direction` as the response and the five lag variables plus `Volume` as predictors. Do any of the predictors appear to be statistically significant? If so, which ones?

```
set.seed(1)
rowTrain = createDataPartition(y = df$Direction,
                               p = 0.75,
                               list = FALSE)
glm_fit = glm(Direction ~ Lag1 + Lag2 + Lag3 + Lag4 + Lag5 + Volume,
              data = df,
              subset = rowTrain,
```

```

        family = binomial)
contrasts(df$Direction)

##      Up
## Down  0
## Up    1

summary(glm_fit)

##
## Call:
## glm(formula = Direction ~ Lag1 + Lag2 + Lag3 + Lag4 + Lag5 +
##      Volume, family = binomial, data = df, subset = rowTrain)
##
## Deviance Residuals:
##      Min       1Q   Median       3Q      Max
## -1.8407  -1.2503   0.9628   1.0737   1.6492
##
## Coefficients:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)  0.31400    0.10037   3.129  0.00176 **
## Lag1        -0.06315    0.03027  -2.086  0.03694 *
## Lag2         0.07588    0.03136   2.420  0.01553 *
## Lag3         0.00262    0.03144   0.083  0.93358
## Lag4        -0.02396    0.03023  -0.793  0.42807
## Lag5        -0.02942    0.03184  -0.924  0.35547
## Volume      -0.05148    0.04150  -1.241  0.21478
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## (Dispersion parameter for binomial family taken to be 1)
##
##      Null deviance: 1122.4  on 816  degrees of freedom
## Residual deviance: 1108.2  on 810  degrees of freedom
## AIC: 1122.2
##
## Number of Fisher Scoring iterations: 4

```

Yes, Lag1, Lag2 and Intercept

(c) Compute the confusion matrix and overall fraction of correct predictions. Briefly explain what the confusion matrix is telling you.

```

# Bayes classigier(cutoff 0.5)
test.pred.prob = predict(glm_fit, newdata = df[-rowTrain,],
                        type = "response")
test.pred = rep("Down", length(test.pred.prob))
test.pred[test.pred.prob>0.5] = "Up"


# confusionMatrix
confusionMatrix(data = as.factor(test.pred),
                reference = as.factor(df$Direction[-rowTrain]),
                positive = "Up")

```

```
## Confusion Matrix and Statistics
##
##           Reference
## Prediction Down  Up
##           Down   16  28
##           Up    105 123
##
##           Accuracy : 0.511
##           95% CI : (0.4499, 0.5719)
##           No Information Rate : 0.5551
##           P-Value [Acc > NIR] : 0.9361
##
##           Kappa : -0.0568
##           Mcnemar's Test P-Value : 4.397e-11
##
##           Sensitivity : 0.8146
##           Specificity : 0.1322
##           Pos Pred Value : 0.5395
##           Neg Pred Value : 0.3636
##           Prevalence : 0.5551
##           Detection Rate : 0.4522
##           Detection Prevalence : 0.8382
##           Balanced Accuracy : 0.4734
##
##           'Positive' Class : Up
##
```

(d) Plot the ROC curve using the predicted probability from logistic regression and report the AUC.

```
roc_glm = roc(df$Direction[-rowTrain], test.pred.prob)
plot(roc_glm, legacy.axes = TRUE, print.auc = TRUE)
plot(smooth(roc_glm), col = 4, add = TRUE)
```



(e) Now fit the logistic regression model using a training data period from 1990 to 2008, with Lag1 and Lag2 as the predictors. Plot the ROC curve using the held out data (that is, the data from 2009 and 2010) and report the AUC.

```
train_subset = df %>%
  filter(1990<=Year& Year<=2008)
test_subset = anti_join(df, train_subset)

## Joining, by = c("Year", "Lag1", "Lag2", "Lag3", "Lag4", "Lag5", "Volume", "Today", "Direction")
rowtrain = train_subset$Direction
rowtest = test_subset$Direction

glm_fit1 = glm(Direction~ Lag1 + Lag2,
  data = train_subset,
  family = binomial)
summary(glm_fit1)

##
## Call:
## glm(formula = Direction ~ Lag1 + Lag2, family = binomial, data = train_subset)
##
## Deviance Residuals:
##      Min       1Q   Median       3Q      Max
## -1.6149  -1.2565   0.9989   1.0875   1.5330
##
## Coefficients:
##              Estimate Std. Error z value Pr(>|z|)
```

```
## (Intercept) 0.21109 0.06456 3.269 0.00108 **
## Lag1 -0.05421 0.02886 -1.878 0.06034 .
## Lag2 0.05384 0.02905 1.854 0.06379 .
## ---
## Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## (Dispersion parameter for binomial family taken to be 1)
##
## Null deviance: 1354.7 on 984 degrees of freedom
## Residual deviance: 1347.0 on 982 degrees of freedom
## AIC: 1353
##
## Number of Fisher Scoring iterations: 4
```

```
contrasts(train_subset$Direction)
```

```
##      Up
## Down 0
## Up   1
```

```
pred.test.value = predict(glm_fit1,
                           newdata = test_subset,
                           type = "response")
```


```
# Bayes Method Cutoff
pred.test = rep("Down", length(pred.test.value))
pred.test[pred.test.value > 0.5] = "Up"
```

```
# Confusion Matrix
confusionMatrix(data = as.factor(pred.test),
                 reference = as.factor(rowtest),
                 positive = "Up")
```

```
## Confusion Matrix and Statistics
```

```
##
##              Reference
## Prediction Down Up
##      Down    7   8
##      Up     36  53
##
##              Accuracy : 0.5769
##              95% CI : (0.4761, 0.6732)
##      No Information Rate : 0.5865
##      P-Value [Acc > NIR] : 0.6193
##
##              Kappa : 0.035
##      McNemar's Test P-Value : 4.693e-05
##
##              Sensitivity : 0.8689
##              Specificity : 0.1628
##      Pos Pred Value : 0.5955
##      Neg Pred Value : 0.4667
##      Prevalence : 0.5865
##      Detection Rate : 0.5096
##      Detection Prevalence : 0.8558
##      Balanced Accuracy : 0.5158
```

```
##
##      'Positive' Class : Up
##
# ROC
roc1 = roc(test_subset$Direction, pred.test.value)
plot(roc1, legacy.axes = TRUE, print.auc = TRUE)
plot(smooth(roc1), col = 4, add = TRUE)
```



- (f) Repeat (e) using LDA and QDA.
- (g) Repeat (e) using KNN. Briefly discuss your results.