

FORTYGUARD

Heat Intelligence Report

Heatmap Metadata

Location:	33.7778609994793, -112.158778
Date and Time:	2024-08-15 12:00
Temperature:	4.44°C (40.0°F)



Table of Contents

Table of Contents	2
Map	6
Environmental Factors Analysis	7
1. Air Quality & Atmospheric Opacity	7
Typical AQI Range and EPA Classification	7
Primary Pollutants and Sources	7
Air Quality Influence on Local Temperature	7
Seasonal and Industrial Drivers	7
Heat–Air Quality Feedback Loop	7
2. Climate Classification & Historical Weather	7
Köppen Climate Classification	8
Historical Climate Normals for August 15	8
Extreme Temperature Records	8
Long-Term Climate Profile and Urban Heat Behavior	8
3. Climate Trends & Projections	8
Observed Temperature and Heat Trends	8
Humidity and Dew Point Trends	8
Urban Expansion and Land-Use Change	9
Climate Change Projections (2030s and 2050s)	9
Cooling Degree Days (CDD) Trend	9
4. Soil Moisture & Permeability	9
Typical Soil Types and Permeability	9
Expected Soil Moisture Conditions (August)	9
Heat Absorption and Evaporative Cooling	10
Urbanization and Soil Sealing	10
Groundwater Table and Surface Moisture	10
5. Heat Retention Capacity of Surfaces	10
Dominant Surface Materials	10
Comparative Heat Retention and Surface Temperature Differentials	10
Thermal Admittance and Albedo Effects	11
Contribution to Urban Heat Island Intensity	11
Cooling Infrastructure	11
6. Humidity Levels	11
Typical Relative Humidity Range	11
Dew Point Temperature	11
Heat Index and Perceived Temperature	12
Seasonal Humidity Patterns	12
Humidity-Driven Phenomena and Heat Stress Thresholds	12
7. Solar Radiation Intensity	12
Global Horizontal Irradiance (GHI) on August 15 at 12:00 hours	12
Solar Elevation Angle and Radiation Intensity	13
Peak Sunlight Hours and Thermal Lag	13
Terrain, Urban Structures, and Cloud Cover Effects	13



Differential Heat Absorption by Surface Materials	13
8. Nighttime Cooling Rates	13
Diurnal Temperature Range (DTR)	13
Surface Thermal Mass and Urban Geometry Effects on Nocturnal Cooling	14
Strength of Nighttime Cooling and Heat Stress Implications	14
Factors Suppressing Cooling	14
Urban vs. Rural Nighttime Temperature Differential	14
9. Thermal Comfort Index	14
Most Applicable Thermal Comfort Metric	14
Components of WBGT and Index Calculation	15
Thermal Comfort Classification	15
Heat Stress Risks for Vulnerable Populations	15
Local Mitigation Measures	15
10. Seasonal Variability of Urban Heat Islands	16
UHI Intensity by Season	16
Driving Factors for Seasonal Variability	16
Known Urban-Rural Temperature Differentials Across Seasons	16
Seasonal Adaptation Measures	16
Season of Greatest Compound Heat Risk	16
Critical Note on Input Data	17
Geographic Analysis	17
1. General Location	17
2. Terrain & Elevation	18
3. Proximity to Water Bodies	18
4. Green Spaces & Vegetation	19
5. Land Cover Type	19
6. Building Density & Height	20
7. Shadow Coverage	20
8. Urban Geometry & Street Canyon Effects	21
Urban Factors Analysis	22
1. Urban Land Use Characteristics	22
Dominant Land Use & Composition	22
Impervious Surface Fraction	22
Heat Differential Patterns	22
Zoning & Planning Strategy	22
Land Use Fragmentation & Thermal Equity	22
2. Anthropogenic Heat Sources	23
Major Economic Activity & Waste Heat	23
Energy-Intensive Sectors	23
Vehicle Density & Transportation Heat	23
HVAC Rejection Heat	23
Impervious Commercial Surfaces	23
Sustainability Initiatives	23
Notable Heat-Contributing Zones	24
3. Green Infrastructure & Urban Cooling Systems	24



Urban Vegetation Strategy	24
Cooling Mechanisms & Effectiveness	24
Corporate & Public Greening Initiatives	24
Engineered Cooling Infrastructure	24
Seasonal Variability & Adequacy	25
Cooling Equity	25
Notable Cooling Infrastructure	25
4. Building Material Thermal Properties	25
Dominant Building Materials	25
Albedo Values & Thermal Characteristics	25
Thermal Mass & Heat Retention	25
Glass Curtain Wall Effects	26
Heat Mitigation Techniques	26
Building Stock Age & Thermal Performance	26
5. Urban Expansion & Development Trends	26
Population Growth & Urban Density	26
Construction & Development Trends	26
Net Change in Impervious Surface	27
Climate-Adaptive Urban Design & Policy	27
Projected Heat Profile Changes (5–10 Year Horizon)	27
6. Pedestrian Infrastructure & Outdoor Thermal Comfort	27
Walkability & Pedestrian Accessibility	27
Shading Infrastructure	27
Mean Radiant Temperature (MRT) & Pedestrian Thermal Load	28
Heat Exposure Risk & Thermal Comfort	28
Cooling Interventions & Comfort Design	28
Cycling Infrastructure & Heat Exposure	28
Notable Pedestrian Comfort Zones & Deficits	28
Events Analysis	29
Extreme Weather Events & Heat Event History	29
Heat-Related Events	29
Other Extreme Weather With Heat Relevance	29
Heatwave Frequency & Intensity	30
Public Health Impacts & Heat Vulnerability	31
Anthropogenic Factors Analysis	33
1. Heat Emissions from Vehicles & Industry	33
Transportation Heat Footprint	33
Industrial and Commercial Waste Heat	34
Spatial Heat Concentration Zones	34
Temporal Patterns	34
Emission-Reduction Measures in Effect or Planned	34
Waste Heat Recovery Opportunities	35
2. Cooling Infrastructure & Waste Heat Feedback Loop	35
Cooling Infrastructure Prevalence	35
The AC Feedback Loop & Ambient Warming Effect	35



Balance-Point Temperature & Cooling Activation	35
Cooling Inequality & Disparities	36
District Cooling Systems	36
Innovative & Passive Cooling Strategies	36
Cooling Demand Classification at Provided Temperature	36
3. Energy System Load & Grid Stress	37
Energy Demand Profile	37
Temperature-Demand Sensitivity	37
Grid Stability & Heat-Related Risk	37
Grid Heat Vulnerability	37
Load Shedding & Demand Response	38
Energy Resilience Measures	38
Energy System Demand Curve Assessment at Provided Temperature	38
4. Traffic Behavior & Vehicular Heat Contribution	38
Traffic Pattern Characterization	38
Waste Heat Concentration Zones	39
Pavement Heat Interaction	39
Public Transit Role	39
Heat-Induced Behavioral Shifts	39
Mitigation Measures	40
Traffic Assessment at Given Datetime	40
5. Seasonal Population Dynamics & Heat Demand	40
Population Variability	40
Demand Translation: Population to Heat Load	41
Current Season Assessment: August 15, 2024	41
Weekend/Weekday & Time-of-Day Demand Variation	41
Infrastructure & Policy Adjustments for Seasonal Demand Management	41
Alternative Demand Drivers: Weather-Driven Behavioral Changes & Holiday Patterns	
Summary & Key Findings	4242
At Provided Temperature (40.0°F):	42
At Realistic August 15, 12:00 Hours Conditions (~100–105°F):	42
Key Anthropogenic Heat Drivers in Phoenix Metro:	43
Mitigation Opportunities:	43



Map




Figure 1: Overview Area




Figure 2: Tile Area



Environmental Factors Analysis

1. Air Quality & Atmospheric Opacity

Typical AQI Range and EPA Classification

- Phoenix metropolitan area (33.77°N, 112.15°W) in mid-August typically experiences Moderate to Unhealthy for Sensitive Groups (USG) air quality conditions
- Estimated typical AQI range: 80–120 for this date and season, placing conditions in the Moderate to USG category
- August is a peak ozone season in the Southwest due to elevated temperatures and photochemical reactions

Primary Pollutants and Sources

- Ozone (O₃): Primary concern; formed from NO_x and volatile organic compounds (VOCs) under intense solar radiation. Sources include vehicle emissions, industrial facilities, and biogenic VOC emissions from desert vegetation
- PM_{2.5} and PM₁₀: Secondary concern; derived from dust storms (haboobs), construction, and combustion. Desert dust dominates PM₁₀; fine particles (PM_{2.5}) from urban combustion and secondary organic aerosol formation
- NO₂: Emitted from vehicle traffic and power generation; contributes to ozone formation
- CO: Urban traffic emissions; typically lower in August due to enhanced atmospheric mixing
- SO₂: Industrial and power plant emissions; generally low in Phoenix due to fuel regulations

Air Quality Influence on Local Temperature

- Particulate matter and ozone reduce solar transmittance (direct beam attenuation), lowering surface insolation by an estimated 5–15% under moderate to high AQI conditions
- Aerosols trap outgoing longwave radiation, creating a net warming effect in the lower atmosphere (positive radiative forcing), partially offsetting the cooling from reduced solar input
- Net effect: Atmospheric opacity typically suppresses peak daytime temperatures by 2–4°F but enhances nighttime warming, reducing diurnal temperature range

Seasonal and Industrial Drivers

- August peak ozone driven by: (1) maximum solar intensity and temperature, (2) stagnant high-pressure systems over the Southwest, (3) reduced wind ventilation
- Dust storms (haboobs) occur primarily May–September, episodically raising PM₁₀ to hazardous levels (AQI >300)
- Urban growth and vehicle emissions from the Phoenix metropolitan area (population ~4.9 million) are primary anthropogenic sources

Heat–Air Quality Feedback Loop

- Elevated temperatures accelerate ozone formation kinetics; each 1°C increase in temperature increases ozone production rate by ~3–5%
- Higher temperatures increase evaporative emissions of VOCs from vegetation and urban surfaces, fueling ozone precursors
- Ozone and particulates suppress atmospheric mixing, trapping heat near the surface and intensifying the urban heat island
- Result: Compound heat and air quality stress during extreme heat events

Sources:

- EPA AQI Standards and Breakpoints
- NOAA Southwest Regional Climate Center air quality climatology
- EPA Regional Haze and Visibility Studies
- Peer-reviewed aerosol radiative forcing literature (IPCC Assessment Reports)

2. Climate Classification & Historical Weather



Köppen Climate Classification

- Phoenix (33.77°N, 112.15°W) is classified as **BWh** (hot desert climate)
- Characteristics: Annual precipitation <10 inches, mean annual temperature >64°F, extremely hot summers with minimal moisture, cool but frost-free winters
- This classification reflects the dominance of clear skies, intense solar radiation, low humidity, and minimal precipitation—all drivers of extreme heat

Historical Climate Normals for August 15

- Typical high temperature: 104–106°F
- Typical low temperature: 78–80°F
- Typical mean temperature: 91–93°F
- Provided average temperature: 40.0°F — **significantly below normal** (approximately 50–53°F below the typical mean)
- This reading is inconsistent with Phoenix's August climate and likely represents a data anomaly or misclassification; actual August 15, 2024 conditions in Phoenix would have been substantially warmer

Extreme Temperature Records

- Phoenix all-time high: 122°F (June 26, 1990)
- August record high: 120°F (August 12, 1990)
- August mean high (1991–2020 normal): 104.8°F
- The 40°F reading is approximately 65°F below the August record high, placing it outside the realm of plausible Phoenix August conditions

Long-Term Climate Profile and Urban Heat Behavior

- The BWh classification ensures that Phoenix experiences minimal cloud cover (~85% sunshine annually), maximizing solar heating year-round
- Low atmospheric moisture limits evaporative cooling and nocturnal radiative loss, sustaining high nighttime temperatures
- Desert surface characteristics (low vegetation, high albedo in some areas, high thermal mass in urban zones) amplify surface heating
- This climate profile makes Phoenix highly susceptible to urban heat island intensification and heat stress during summer months

Sources:

- Köppen-Geiger Climate Classification System
- NOAA National Centers for Environmental Information (NCEI) Climate Normals 1991–2020
- National Weather Service Phoenix Office Historical Records
- NOAA Global Historical Climatology Network (GHCN)

3. Climate Trends & Projections

Observed Temperature and Heat Trends

- Phoenix has warmed at approximately **0.25–0.35°F per decade** over the past 50 years (1974–2024), consistent with Southwestern U.S. warming rates
- Nighttime minimum temperatures have increased faster than daytime maxima, reducing diurnal temperature range by ~0.5°F per decade
- Heatwave frequency has increased: the number of days ≥100°F in Phoenix has risen from ~90 days/year (1970s) to ~120 days/year (2010s–2020s)
- Duration and intensity of consecutive hot nights (Tmin >80°F) have increased, reducing recovery time for heat stress

Humidity and Dew Point Trends



- Summer relative humidity has declined slightly (~0.5% per decade), but absolute humidity (vapor pressure) has increased due to higher temperatures
- Dew point temperatures have risen ~0.1–0.2°F per decade, indicating increased atmospheric moisture content despite lower relative humidity

Urban Expansion and Land-Use Change

- Phoenix metropolitan area expanded from ~1.1 million residents (1990) to ~4.9 million (2020), with urban footprint increasing ~200% over 30 years
- Conversion of desert scrubland to asphalt, concrete, and buildings has increased surface albedo heterogeneity and thermal mass
- Loss of riparian vegetation and groundwater depletion have reduced evaporative cooling capacity
- Urban expansion has intensified the local heat island, with urban-rural temperature differentials increasing from ~2–3°F (1990s) to ~4–6°F (2020s)

Climate Change Projections (2030s and 2050s)

- **2030s (2020–2040):** Projected warming of +1.5–2.0°F above 1990–2020 baseline under moderate emissions scenarios (RCP 4.5)
- **2050s (2040–2060):** Projected warming of +3.0–4.0°F under moderate scenarios; +4.5–5.5°F under high emissions scenarios (RCP 8.5)
- August mean high temperature projected to reach 107–109°F by 2050 (from current ~105°F)
- Frequency of days ≥110°F projected to increase from ~10–15 days/year (current) to ~30–40 days/year by 2050
- Heatwave duration expected to extend by 2–4 weeks by mid-century

Cooling Degree Days (CDD) Trend

- Phoenix CDD (base 65°F) has increased from ~3,500 CDD/year (1970s) to ~4,200 CDD/year (2010s–2020s), representing a ~20% increase in cooling demand
- Projected to reach ~4,800–5,200 CDD/year by 2050, driving increased electricity consumption for air conditioning
- Peak electricity demand now occurs in summer (June–August) rather than winter, a reversal from historical patterns

Sources:

- NOAA National Centers for Environmental Information (NCEI) Long-Term Temperature Trends
- U.S. Geological Survey (USGS) Southwest Climate Change Assessment
- IPCC Fifth and Sixth Assessment Reports (AR5, AR6) — Regional Climate Projections for North America
- Scripps Institution of Oceanography Climate Projections (CMIP5/CMIP6 ensemble data)
- U.S. Census Bureau Decennial Census and Population Estimates

4. Soil Moisture & Permeability

Typical Soil Types and Permeability

- Phoenix area soils are predominantly **sandy loam to loamy sand** with significant gravel content, derived from alluvial fan and basin fill deposits
- Permeability: High to very high (>2 inches/hour), typical of desert soils with low clay content and minimal organic matter
- Soil structure: Weak, with minimal aggregation; prone to surface crusting and reduced water infiltration under intense rainfall
- Typical soil pH: 7.5–8.5 (alkaline), reflecting the arid climate and carbonate-rich parent material

Expected Soil Moisture Conditions (August)

- August is the driest month in Phoenix's pre-monsoon period; soil moisture is typically at or near wilting point (5–10% volumetric water content)
- Monsoon rains (July–September) can episodically raise soil moisture, but evaporative demand is so high that moisture is rapidly depleted



- Estimated: Soil moisture in the upper 12 inches is typically 5–15% of field capacity by mid-August in non-irrigated areas

Heat Absorption and Evaporative Cooling

- Dry soils have low thermal conductivity ($\sim 0.3\text{--}0.5\text{ W/m}\cdot\text{K}$) compared to moist soils ($\sim 1.5\text{--}2.0\text{ W/m}\cdot\text{K}$), reducing heat diffusion into deeper layers
- Surface temperatures of dry sandy soils can reach $140\text{--}160^\circ\text{F}$ under peak solar load, compared to $120\text{--}130^\circ\text{F}$ for moist soils
- Evaporative cooling potential is severely limited by low soil moisture; latent heat flux is minimal ($<20\text{ W/m}^2$ in dry conditions vs. $>150\text{ W/m}^2$ in irrigated areas)
- Result: Dry desert soils act as efficient heat accumulators and poor evaporative coolers, intensifying surface and near-surface air temperatures

Urbanization and Soil Sealing

- Urban development has sealed an estimated 15–25% of the Phoenix metropolitan area with impervious surfaces (asphalt, concrete, buildings)
- Sealed soils lose all permeability and evaporative cooling capacity; surface temperatures of asphalt can exceed $160\text{--}180^\circ\text{F}$
- Loss of soil permeability increases surface runoff, reduces groundwater recharge, and eliminates soil-based evaporative cooling
- Unsealed urban soils are often compacted and stripped of vegetation, further reducing moisture retention and evaporative potential

Groundwater Table and Surface Moisture

- Phoenix groundwater table is typically 300–500 feet below the surface in most urban areas, far below the capillary rise zone ($\sim 3\text{--}6$ feet)
- Groundwater is not available to support capillary-driven surface evaporative cooling in non-irrigated areas
- Irrigation (common in urban parks, golf courses, and landscaped areas) artificially raises soil moisture and evaporative cooling, creating localized cool islands
- Groundwater depletion (declining aquifer levels) has reduced available irrigation water, further limiting evaporative cooling in some areas

Sources:

- USDA Natural Resources Conservation Service (NRCS) Soil Survey Geographic (SSURGO) Database
- USGS Arizona Water Science Center Groundwater Studies
- Soil Science Society of America Soil Physics and Hydrology References
- NOAA Southwest Regional Climate Center Precipitation and Soil Moisture Data

5. Heat Retention Capacity of Surfaces

Dominant Surface Materials

- Urban Phoenix: Asphalt (roads, parking lots $\sim 40\%$ of urban area), concrete (buildings, sidewalks $\sim 25\%$), vegetation (parks, landscaping $\sim 15\%$), bare soil and gravel ($\sim 20\%$)
- Suburban and exurban areas: Bare soil, desert scrub vegetation, sparse landscaping, residential roofing (composition shingles, tile, metal)

Comparative Heat Retention and Surface Temperature Differentials

- **Asphalt:** Albedo $\sim 0.05\text{--}0.10$; thermal admittance $\sim 2,000\text{ J}/(\text{m}^2\cdot\text{K}\cdot\text{s}^{0.5})$; peak surface temperature $\sim 160\text{--}180^\circ\text{F}$ under full solar load
- **Concrete:** Albedo $\sim 0.25\text{--}0.35$; thermal admittance $\sim 2,500\text{ J}/(\text{m}^2\cdot\text{K}\cdot\text{s}^{0.5})$; peak surface temperature $\sim 130\text{--}150^\circ\text{F}$
- **Grass/vegetation:** Albedo $\sim 0.20\text{--}0.25$; thermal admittance $\sim 800\text{--}1,200\text{ J}/(\text{m}^2\cdot\text{K}\cdot\text{s}^{0.5})$; peak surface temperature $\sim 80\text{--}100^\circ\text{F}$ (evaporative cooling suppresses heating)



- **Bare desert soil:** Albedo ~0.25–0.40; thermal admittance ~1,500 J/(m²·K·s^{0.5}); peak surface temperature ~120–140°F
- **Temperature differential (asphalt vs. grass):** 60–100°F under peak solar conditions; this differential drives strong local convective heating and contributes significantly to the urban heat island

Thermal Admittance and Albedo Effects

- High thermal admittance (asphalt, concrete) means rapid heat absorption and release; these materials warm quickly in the morning and cool slowly at night
- Low albedo (asphalt) absorbs most incident solar radiation; high albedo (light concrete, reflective coatings) reflects more radiation and stays cooler
- Combination of low albedo and high thermal admittance makes asphalt the most heat-retentive common urban surface
- Vegetation has low thermal admittance and moderate albedo, but evaporative cooling (latent heat flux) is the dominant cooling mechanism, making vegetated surfaces much cooler than bare materials

Contribution to Urban Heat Island Intensity

- The replacement of low-albedo desert soil and sparse vegetation with high-albedo asphalt and concrete, combined with loss of evaporative cooling, contributes an estimated 3–5°F to the Phoenix urban heat island
- Street canyon geometry (building height-to-width ratio) traps radiation and reduces radiative cooling; this adds an estimated 1–2°F to the UHI
- Anthropogenic heat (air conditioning waste heat, vehicle emissions, industrial processes) contributes an estimated 1–2°F
- Total estimated UHI intensity: 4–9°F (urban vs. rural), with the largest differentials in dense downtown and commercial areas

Cooling Infrastructure

- **Cool pavements:** Reflective coatings and light-colored asphalt (albedo ~0.40–0.60) are being piloted in Phoenix; can reduce surface temperature by 20–40°F compared to conventional asphalt
- **Cool roofs:** White or reflective roofing (albedo ~0.60–0.80) reduces roof surface temperature by 30–50°F and building cooling load by 10–30%
- **Urban forestry:** Tree canopy cover in Phoenix is ~5–8% (target: 25%); expanding shade trees can reduce local air temperature by 2–4°F and surface temperatures by 20–40°F
- **Green infrastructure:** Green roofs, rain gardens, and permeable pavements are being implemented in select areas to increase evaporative cooling and reduce runoff

Sources:

- ASTM International Standards for Solar Absorptance and Thermal Emittance
- Lawrence Berkeley National Laboratory (LBNL) Cool Roofs and Cool Pavements Research
- EPA Heat Island Reduction Initiative and Technical Documentation
- Peer-reviewed urban heat island and surface energy balance literature

6. Humidity Levels

Typical Relative Humidity Range

- Phoenix August 15 at 12:00 hours (solar noon): Typical relative humidity ~20–30%
- Diurnal pattern: Morning RH ~40–50% (around sunrise), declining to 15–25% by mid-afternoon, rising to 30–45% by sunset
- August is the driest month before the monsoon; RH values are among the lowest of the year
- Provided average temperature of 40°F would imply saturation vapor pressure of ~0.25 kPa; if actual vapor pressure were typical for Phoenix in August (~1.5–2.0 kPa), the implied RH would exceed 100%, indicating condensation or frost—inconsistent with Phoenix's August climate

Dew Point Temperature



- Typical August 15 dew point in Phoenix: 35–45°F (morning) to 25–35°F (afternoon)
- Dew point is a more stable indicator of absolute humidity and moisture-driven discomfort than relative humidity
- A dew point of 35°F indicates very dry air; dew points >60°F are associated with humid conditions and elevated heat stress
- Phoenix's August dew points are typically 30–40°F, reflecting the desert's low absolute humidity despite occasional monsoon moisture intrusions

Heat Index and Perceived Temperature

- Heat Index = $f(T, RH)$; at 105°F and 20% RH, the Heat Index $\approx$ 105°F (low humidity suppresses the index)
- At 105°F and 50% RH, the Heat Index $\approx$ 120°F (humidity amplifies perceived temperature)
- Phoenix's low August humidity (20–30%) means the Heat Index is typically only 2–5°F above the actual air temperature, unlike humid climates where the index can exceed actual temperature by 15–25°F
- However, the low humidity also limits evaporative cooling of the human body, so absolute heat stress can still be severe despite a low Heat Index

Seasonal Humidity Patterns

- **Pre-monsoon (May–June):** RH 15–25%, very dry
- **Monsoon (July–September):** RH 20–40%, with episodic increases during thunderstorm activity; dew points can rise to 50–60°F during monsoon surges
- **Post-monsoon (October–November):** RH 20–35%, transitioning to winter
- **Winter (December–February):** RH 30–50%, higher due to cooler temperatures and occasional Pacific moisture
- Monsoon humidity increases can create compound heat stress (high temperature + elevated humidity), which is more dangerous than either condition alone

Humidity-Driven Phenomena and Heat Stress Thresholds

- **Nocturnal cooling suppression:** High nighttime RH (>60%) and dew point (>55°F) trap outgoing longwave radiation, reducing nighttime cooling rates from ~15–20°F/night (clear, dry conditions) to ~5–10°F/night (humid conditions)
- **Consecutive hot nights:** When T_{min} remains >80°F for multiple nights, the human body cannot recover from daytime heat stress; this is a major heat health risk
- **Dew point threshold for dangerous heat stress:** Dew point >75°F is associated with severe heat stress risk, even at moderate temperatures; dew point >80°F is extremely dangerous. Phoenix's August dew points (25–45°F) are well below this threshold, but monsoon surges can briefly exceed 60°F
- **Wet bulb temperature:** At 105°F and 30% RH, wet bulb $\approx$ 75°F (borderline heat stress); at 105°F and 50% RH, wet bulb $\approx$ 85°F (severe heat stress)

Sources:

- NOAA National Weather Service Heat Index Documentation
- EPA Excessive Heat Events Guidebook
- Wet Bulb Globe Temperature (WBGT) Standards (ISO 7243, ACGIH)
- NOAA Southwest Regional Climate Center Humidity Climatology

7. Solar Radiation Intensity

Global Horizontal Irradiance (GHI) on August 15 at 12:00 hours

- Phoenix latitude: 33.77°N; August 15 solar declination: ~13°N
- Solar elevation angle at solar noon: ~60–65° above the horizon
- Clear-sky GHI at sea level for this geometry: ~950–1,000 W/m²
- Actual GHI accounting for typical August atmospheric conditions (aerosols, ozone, water vapor): ~850–950 W/m² (10–15% reduction from clear-sky)
- If cloud cover is present (typical for monsoon season in July–August): GHI may be reduced to 600–800 W/m²
- Direct normal irradiance (DNI) at solar noon: ~850–900 W/m² (clear-sky); ~700–800 W/m² (typical atmospheric attenuation)



Solar Elevation Angle and Radiation Intensity

- At 12:00 hours (solar noon) on August 15, solar elevation $\approx 62^\circ$
- This high elevation angle means solar radiation is nearly perpendicular to horizontal surfaces, maximizing GHI
- Vertical surfaces (building walls) receive less radiation ($\sim 500\text{--}600\text{ W/m}^2$ on south-facing walls, $\sim 200\text{--}300\text{ W/m}^2$ on east/west walls)
- The high solar elevation in summer means that shadows are short, reducing shaded area and amplifying surface heating in urban canyons

Peak Sunlight Hours and Thermal Lag

- Phoenix receives ~ 14 hours of daylight on August 15; peak solar intensity occurs 12:00–15:00 hours (solar noon ± 3 hours)
- Peak air temperature typically occurs 14:00–16:00 hours (2–4 hours after solar noon), due to thermal lag in the atmosphere and surface
- Peak surface temperature occurs near solar noon (12:00–13:00 hours) for thin materials (asphalt, sand) but can lag until 15:00–16:00 hours for thick materials (concrete, buildings)
- This thermal lag means that the hottest air temperatures occur when solar intensity is declining, extending the period of high heat stress

Terrain, Urban Structures, and Cloud Cover Effects

- Phoenix is in a broad desert basin with minimal topographic shading; terrain has minimal effect on solar radiation at the city scale
- Urban structures (buildings, street canyons) create localized shadows that reduce GHI on street-level surfaces by 20–40% in dense downtown areas, but increase mean radiant temperature through radiation trapping
- Typical August cloud cover: 20–30% (pre-monsoon); 30–50% (monsoon season); clouds reduce GHI by 10–40% depending on cloud type and optical depth
- Dust and aerosols from Saharan dust outbreaks or local dust storms can reduce GHI by 20–50% episodically

Differential Heat Absorption by Surface Materials

- Asphalt (albedo 0.05–0.10): Absorbs $\sim 90\text{--}95\%$ of incident solar radiation; $1,000\text{ W/m}^2$ GHI $\rightarrow \sim 900\text{--}950\text{ W/m}^2$ absorbed
- Concrete (albedo 0.25–0.35): Absorbs $\sim 65\text{--}75\%$ of incident radiation; $1,000\text{ W/m}^2$ GHI $\rightarrow \sim 650\text{--}750\text{ W/m}^2$ absorbed
- Grass (albedo 0.20–0.25, with evaporative cooling): Absorbs $\sim 75\text{--}80\%$ but converts $\sim 50\text{--}70\%$ to latent heat; net sensible heat $\sim 100\text{--}300\text{ W/m}^2$
- Reflective coatings (albedo 0.60–0.80): Absorb $\sim 20\text{--}40\%$ of incident radiation; $1,000\text{ W/m}^2$ GHI $\rightarrow \sim 200\text{--}400\text{ W/m}^2$ absorbed
- The high solar intensity in Phoenix ($950+$ W/m^2) combined with low-albedo surfaces creates extreme surface temperatures and strong sensible heat fluxes

Sources:

- NREL Solar Radiation Data (NSRDB and TMY3 datasets)
- NOAA Solar Position Calculator
- NASA CERES (Clouds and the Earth's Radiant Energy System) Satellite Data
- ASTM G173 Standard Solar Spectral Irradiance

8. Nighttime Cooling Rates

Diurnal Temperature Range (DTR)

- Phoenix August typical DTR: $25\text{--}30^\circ\text{F}$ (high $\sim 105^\circ\text{F}$, low $\sim 75\text{--}80^\circ\text{F}$)
- This is a moderate DTR for a desert climate; clear, dry nights allow efficient radiative cooling, but the high nighttime minimum reflects the urban heat island and high thermal mass
- Rural areas surrounding Phoenix have DTR $\sim 30\text{--}35^\circ\text{F}$ (lower nighttime minimum $\sim 70\text{--}75^\circ\text{F}$), indicating that urban surfaces and structures suppress cooling by $\sim 5\text{--}10^\circ\text{F}$



Surface Thermal Mass and Urban Geometry Effects on Nocturnal Cooling

- High thermal mass surfaces (concrete, asphalt, buildings) absorb heat during the day and release it slowly at night, suppressing cooling rates
- Cooling rate for asphalt: ~5–8°F/hour in the first 2–3 hours after sunset, then ~2–3°F/hour as surface temperature approaches air temperature
- Cooling rate for grass/vegetation: ~10–15°F/hour initially (rapid evaporative cooling), then ~3–5°F/hour
- Street canyon geometry (tall buildings, narrow streets) reduces the view factor to the sky, trapping longwave radiation and reducing radiative cooling by ~10–20 W/m² compared to open areas
- Result: Urban areas cool 5–10°F slower than rural areas, creating persistent nighttime heat stress

Strength of Nighttime Cooling and Heat Stress Implications

- Phoenix exhibits **moderate nighttime cooling** for a desert climate; clear skies and low humidity allow significant radiative loss, but urban thermal mass limits the magnitude
- Typical nighttime cooling: 15–20°F from peak daytime temperature to minimum (e.g., 105°F → 80–85°F)
- This cooling is sufficient to provide some physiological recovery, but consecutive hot nights (T_{min} >80°F) occur 10–20 days/year in urban Phoenix, reducing recovery opportunity
- Heat stress risk increases dramatically when T_{min} remains >80°F for 3+ consecutive nights, as the human body cannot dissipate accumulated heat

Factors Suppressing Cooling

- **Cloud cover:** Clouds trap outgoing longwave radiation; overcast nights cool 5–10°F slower than clear nights
- **High humidity:** Dew point >55°F suppresses radiative cooling by ~5–10 W/m²; monsoon moisture can reduce nighttime cooling by 5–8°F
- **Thermal mass:** Buildings, pavement, and soil store daytime heat and release it at night, reducing the rate of air temperature decline
- **Street canyon geometry:** Buildings and structures reduce the view factor to the sky, trapping radiation and suppressing cooling by ~10–20%
- **Anthropogenic heat:** Air conditioning waste heat, vehicle traffic, and industrial processes add ~20–50 W/m² to the urban heat flux at night, suppressing cooling

Urban vs. Rural Nighttime Temperature Differential

- Phoenix urban-rural temperature differential at night (02:00–06:00 hours): ~5–8°F (urban warmer)
- This differential is largest in the hours immediately after sunset (20:00–24:00 hours), when urban thermal mass is still releasing stored heat
- By early morning (06:00 hours), the differential narrows to ~3–5°F as both urban and rural areas cool toward their minima
- The persistent nighttime urban heat island is a major contributor to heat-related mortality in Phoenix, as vulnerable populations (elderly, outdoor workers) have limited opportunity for nocturnal recovery

Sources:

- NOAA National Weather Service Diurnal Temperature Range Climatology
- Peer-reviewed urban heat island and surface energy balance studies
- EPA Urban Heat Island Mitigation Strategies Documentation
- Radiative Transfer and Atmospheric Physics References

9. Thermal Comfort Index

Most Applicable Thermal Comfort Metric

- **Selected metric: WBGT (Wet Bulb Globe Temperature)** for occupational and outdoor heat stress assessment
- **Justification:** WBGT integrates air temperature, humidity, solar radiation, and wind speed into a single index that predicts physiological heat strain and is widely used by occupational health agencies (OSHA, military, sports medicine). For Phoenix's dry, high-radiation environment, WBGT is more appropriate than Heat Index (which



overemphasizes humidity in dry climates) or PET (which is better suited to moderate climates)

- **Alternative metric: Heat Index** for general public communication; simpler but less physiologically grounded than WBGT

Components of WBGT and Index Calculation

- $WBGT = 0.7 \times Twb + 0.2 \times Tg + 0.1 \times Ta$ (outdoors with solar radiation)
- **Twb (wet bulb temperature):** Combines air temperature and humidity; represents evaporative cooling capacity. Typical August 15 at 12:00 hours: ~75–80°F
- **Tg (globe temperature):** Represents mean radiant temperature from solar radiation and surroundings. Typical for asphalt surface: ~140–160°F; for grass: ~100–110°F
- **Ta (air temperature):** Dry bulb temperature; typical August 15 at 12:00 hours: ~105°F
- **Estimated WBGT at solar noon on asphalt:** $0.7(77) + 0.2(150) + 0.1(105) \approx 54 + 30 + 10.5 \approx 94\text{--}96^\circ\text{F}$
- **Estimated WBGT on grass:** $0.7(77) + 0.2(105) + 0.1(105) \approx 54 + 21 + 10.5 \approx 85\text{--}87^\circ\text{F}$

Thermal Comfort Classification

- WBGT 82–90°F: **Moderate heat stress** — caution for continuous outdoor activity; increased risk for heat exhaustion and cramps
- WBGT 90–103°F: **Strong heat stress** — high risk of heat exhaustion and heat stroke; outdoor activity should be limited or discontinued
- WBGT >103°F: **Extreme heat stress** — dangerous for all populations; heat stroke risk is very high
- **Estimated classification for August 15, 2024 in Phoenix (solar noon):** Strong heat stress (WBGT ~94–96°F on asphalt, ~85–87°F on grass)
- The differential between asphalt and grass WBGT (~8–10°F) illustrates the critical importance of surface type and shade in heat stress mitigation

Heat Stress Risks for Vulnerable Populations

- **Elderly (>65 years):** Reduced thermoregulatory capacity, comorbidities (cardiovascular, renal), medications (diuretics, beta-blockers) that impair heat dissipation. Heat-related mortality peaks in this group during extreme heat events
- **Outdoor workers:** Construction, agriculture, landscaping workers experience prolonged exposure to high WBGT; risk of heat exhaustion, heat stroke, and exertional rhabdomyolysis
- **Children (<5 years):** Immature thermoregulation; higher metabolic rate; dependence on caregivers for hydration and shade
- **Low-income and homeless populations:** Limited access to air conditioning, cooling centers, and adequate hydration; higher heat-related mortality rates
- **Individuals with chronic conditions:** Diabetes, obesity, mental illness, and substance abuse increase heat vulnerability

Local Mitigation Measures

- **Shaded walkways and transit shelters:** Bus shelters with reflective roofing and shade structures reduce WBGT by ~5–10°F for waiting passengers
- **Misting stations:** Public fountains and misting systems in parks and downtown areas provide evaporative cooling; can reduce perceived temperature by ~10–15°F
- **Cooling centers:** Phoenix operates 17 public cooling centers during heat emergencies; air-conditioned libraries, community centers, and senior centers provide refuge
- **Urban forestry:** Tree planting programs aim to increase canopy cover from ~5–8% to 25% by 2050; shade trees reduce surface temperature by 20–40°F and air temperature by 2–4°F
- **Cool pavements and roofs:** Pilot programs in downtown Phoenix are testing reflective pavements and cool roofs to reduce surface temperatures and building cooling loads
- **Heat alert systems:** NOAA and National Weather Service issue heat advisories and excessive heat warnings; local media and emergency management coordinate public messaging
- **Occupational safety standards:** OSHA and Arizona Department of Industrial Safety enforce work-rest cycles and hydration requirements for outdoor workers during high WBGT conditions

Sources:



- ISO 7243 Standard for Wet Bulb Globe Temperature (WBGT) Assessment
- ACGIH (American Conference of Governmental Industrial Hygienists) Heat Stress Guidelines
- NOAA National Weather Service Heat Index and WBGT Documentation
- EPA Excessive Heat Events Guidebook
- CDC Heat-Related Illness and Death Epidemiology

10. Seasonal Variability of Urban Heat Islands

UHI Intensity by Season

- **Summer (June–August):** UHI intensity ~4–6°F (daytime), ~5–8°F (nighttime); maximum in late afternoon and early evening
- **Spring (March–May):** UHI intensity ~3–5°F (daytime), ~4–6°F (nighttime); increasing as temperatures rise and vegetation is sparse
- **Fall (September–November):** UHI intensity ~3–5°F (daytime), ~4–6°F (nighttime); decreasing as temperatures cool and vegetation begins dormancy
- **Winter (December–February):** UHI intensity ~2–4°F (daytime), ~2–4°F (nighttime); minimum, as lower temperatures reduce thermal mass heating and anthropogenic heat becomes more significant
- **Overall pattern:** UHI intensity is strongest in summer and weakest in winter, with a range of ~2–4°F between seasons

Driving Factors for Seasonal Variability

- **Foliage cycles:** Phoenix has minimal deciduous vegetation; most landscaping is evergreen or xerophytic. Seasonal foliage changes are minimal, so vegetation-driven UHI modulation is weak compared to humid climates
- **Snow and ice cover:** Phoenix rarely experiences snow; winter UHI is not suppressed by high-albedo snow cover
- **Monsoon effects:** July–September monsoon moisture increases humidity and cloud cover, reducing solar radiation and surface heating. However, monsoon rains are episodic and often brief; sustained moisture is rare. Monsoon-driven UHI reduction is modest (~1–2°F)
- **Seasonal HVAC load:** Peak air conditioning use occurs June–August, generating waste heat that contributes ~1–2°F to the UHI. Winter heating load is minimal, reducing anthropogenic heat
- **Solar angle and day length:** Summer has higher solar elevation angle and longer day length, maximizing surface heating. Winter has lower solar angle and shorter day length, reducing surface heating
- **Thermal mass release:** In summer, high thermal mass (buildings, pavement) stores significant heat and releases it at night, sustaining the nighttime UHI. In winter, lower daytime temperatures mean less heat storage and weaker nighttime UHI

Known Urban-Rural Temperature Differentials Across Seasons

- **Summer daytime:** Urban ~4–6°F warmer than rural (e.g., downtown Phoenix 110°F vs. rural 104–106°F)
- **Summer nighttime:** Urban ~5–8°F warmer than rural (e.g., downtown Phoenix 85°F vs. rural 77–80°F)
- **Winter daytime:** Urban ~2–3°F warmer than rural (e.g., downtown Phoenix 68°F vs. rural 65–66°F)
- **Winter nighttime:** Urban ~2–4°F warmer than rural (e.g., downtown Phoenix 50°F vs. rural 46–48°F)
- **Monsoon season (July–September):** UHI intensity reduced by ~1–2°F due to increased cloud cover and moisture; nighttime differential may narrow to ~3–5°F

Seasonal Adaptation Measures

- **Summer cooling strategies:** Increased misting station operation, extended cooling center hours, tree planting and shade structure installation, cool pavement and roof pilot programs
- **Monsoon preparedness:** Stormwater management and flood mitigation; however, monsoon rains provide minimal UHI relief due to episodic nature and high evaporative demand
- **Winter heating:** Minimal adaptation needed; UHI is weak and heating demand is low
- **Year-round urban forestry:** Tree planting is most effective in spring and fall when establishment is easier; trees provide summer shade and winter wind protection

Season of Greatest Compound Heat Risk



- **Summer (June–August)** poses the greatest compound heat risk due to:
 - Maximum air temperature (~105°F) combined with maximum UHI intensity (~5–8°F), creating peak urban temperatures ~110–113°F
 - High solar radiation (GHI ~950+ W/m²) and high mean radiant temperature, elevating WBGT to strong-to-extreme heat stress levels
 - Extended day length and peak HVAC load, sustaining high temperatures for 14+ hours
 - Persistent nighttime heat (Tmin ~80–85°F in urban areas) limiting physiological recovery; consecutive hot nights occur 10–20 days/year
 - Peak ozone and air quality degradation, reducing visibility and respiratory function during heat stress
 - Highest heat-related mortality and morbidity; Phoenix averages ~300–400 heat-related deaths annually during extreme heat years
- **Secondary risk period:** Late monsoon season (August–September) when monsoon moisture combines with residual summer heat, creating high humidity + high temperature conditions (compound heat stress)

Sources:

- NOAA National Centers for Environmental Information (NCEI) Seasonal Climate Data
- EPA Urban Heat Island Mitigation Strategies and Seasonal Effectiveness
- Peer-reviewed urban heat island seasonal variability studies
- Arizona Department of Health Services Heat-Related Illness Surveillance Data
- Maricopa County Department of Public Health Heat Response Programs

Critical Note on Input Data

The provided average temperature of **40.0°F on August 15, 2024 at 12:00 hours** in Phoenix (33.77°N, 112.15°W) is **inconsistent with the location's climate and historical records**. Phoenix's August 15 climate normal is approximately **91–93°F (mean)**, with typical highs of **104–106°F**. A reading of 40°F would be: - **~50–53°F below the August mean** — unprecedented for this date and location - **Colder than Phoenix's winter average** — physically implausible for mid-August - **Indicative of a data error, sensor malfunction, or misclassification**. All analyses above are grounded in **realistic Phoenix August conditions** (105°F typical high, 80°F typical low, 20–30% RH, 950+ W/m² GHI). If the 40°F reading is accurate, it would represent an extraordinary atmospheric or measurement anomaly requiring investigation beyond the scope of this analysis.

Geographic Analysis

1. General Location

City & Region: Phoenix, Arizona, United States

Geographic Classification: Urban core within a sprawling metropolitan area (Phoenix-Mesa-Chandler metropolitan statistical area). The coordinates place the analysis in the central Phoenix basin, characterized as an inland, arid desert city.

Köppen Climate Zone: BWh (hot desert climate). Phoenix experiences extremely hot summers with minimal precipitation, low humidity during most of the year, and mild winters. Annual precipitation averages approximately 8 inches, concentrated in monsoon season (July–September) and winter months.

Historical Temperature Context: Phoenix regularly records some of the highest temperatures in the continental United States. Historical August averages range from 95–105°F for daytime highs and 75–80°F for nighttime lows. The provided reading of 40°F at 12:00 hours on August 15 is **anomalously cold** and inconsistent with typical August midday conditions in Phoenix. This reading likely represents either:

- A data collection error or sensor malfunction
- A reading from an unusual microclimate (deep shade, elevated location, or air-conditioned environment)
- A hypothetical scenario rather than an observed measurement

For context, a normal August 15 midday temperature in Phoenix would be 100–108°F. The provided 40°F reading is approximately 60–68°F below normal for this date and time.

Sources:



- NOAA National Centers for Environmental Information (NCEI) — Phoenix Sky Harbor International Airport climate normals
- Köppen-Geiger climate classification system
- U.S. National Weather Service — Phoenix office historical records

2. Terrain & Elevation

Elevation: Approximately 1,100 feet above mean sea level in central Phoenix.

Terrain Type: Basin floor. Phoenix sits within the Salt River Valley, a broad alluvial basin surrounded by low mountain ranges (South Mountain to the south, McDowell Mountains to the northeast, White Tank Mountains to the northwest). The terrain is predominantly flat to gently rolling within the urban core.

Heat Retention & Dissipation Dynamics:

- **Basin Effect:** The valley configuration can trap warm air masses, particularly during high-pressure systems common in summer. Nighttime radiative cooling is partially inhibited by surrounding terrain that reflects longwave radiation back toward the basin floor.
- **Thermal Inversion Potential:** During calm, clear nights (frequent in the desert), temperature inversions can form, trapping warm air near the surface and suppressing convective mixing. This exacerbates nighttime heat retention.
- **Katabatic Wind Limitation:** The gentle slopes surrounding Phoenix produce weak katabatic (downslope) winds. Unlike mountain valleys with steep terrain, Phoenix does not benefit significantly from strong nocturnal drainage flows that would enhance cooling.
- **Daytime Solar Exposure:** The flat terrain offers minimal natural shading and exposes the urban surface to direct solar radiation throughout the day. Elevation of 1,100 feet provides no significant altitude-based cooling advantage.

Sources:

- USGS Digital Elevation Model (DEM) for Arizona
- Arizona Geological Survey — basin and range physiography
- Atmospheric boundary layer research on desert basin thermal dynamics

3. Proximity to Water Bodies

Nearest Significant Water Bodies:

- **Salt River:** Approximately 5–10 miles south/southeast of central Phoenix. The river is intermittent in many sections and carries water primarily during monsoon runoff and winter flows. Its thermal moderating effect is limited.
- **Lake Pleasant:** Approximately 45 miles north; too distant to influence urban microclimate.
- **Tempe Town Lake (Salt River Project reservoir):** Approximately 10 miles east/southeast; an artificial impoundment with limited thermal influence on central Phoenix.
- **Arizona Canal & Central Avenue Canal:** Irrigation canals within the metropolitan area; too narrow and shallow to provide significant thermal buffering.

Thermal Moderating Effect: Phoenix is fundamentally a water-limited desert city. The absence of large, proximate water bodies means:

- No significant evaporative cooling from surface water
- No thermal mass buffering effect typical of coastal or lakeside cities
- Humidity remains low (typically 10–30% in summer afternoons), limiting evaporative cooling potential
- The Salt River's intermittent flow provides negligible heat mitigation

Prevailing Wind Direction: Summer monsoon winds (July–September) typically flow from the south and southeast, bringing moisture from the Gulf of Mexico. However, these winds are seasonal and often weak in the urban core due to surface friction. Winter winds are more variable. Neither season produces strong, consistent sea-breeze-like effects that would transport cooler air into the city.

Sources:

- USGS Water Resources — Arizona surface water inventory
- Salt River Project (SRP) — water body locations and characteristics
- NOAA — prevailing wind patterns and monsoon climatology for the Southwest



4. Green Spaces & Vegetation

Type and Extent: Phoenix's urban vegetation is limited and unevenly distributed. The metropolitan area includes:

- **Parks:** Phoenix Parks and Recreation maintains approximately 200+ parks, including larger regional parks (South Mountain Park, Desert Botanical Garden, Phoenix Zoo grounds). However, parks represent a small fraction of total urban area.
- **Urban Forest:** Street tree canopy coverage in central Phoenix is estimated at 5–10%, well below the 20–25% considered optimal for UHI mitigation. Many neighborhoods, particularly older commercial and industrial zones, have minimal tree coverage.
- **Native Vegetation:** Sonoran Desert scrub (creosote bush, palo verde, saguaro cactus) exists in undeveloped areas and some parks, but is largely absent from the dense urban core.

Vegetation Type & Seasonal Impact: Phoenix's vegetation is predominantly drought-adapted, evergreen desert species. Unlike deciduous trees in temperate climates, these plants provide consistent but modest shading year-round. Evapotranspiration rates are lower than in humid regions due to water stress and low humidity. Landscaping in residential and commercial areas often relies on non-native turf grass (requiring irrigation) or hardscape (concrete, rock), which increases heat absorption rather than reducing it.

Urban Greening Initiatives: Phoenix's "Cool Corridors" program and similar municipal efforts have planted street trees in select neighborhoods, but coverage remains limited. The city has set goals to increase canopy coverage, but implementation is slow and unevenly distributed across socioeconomic zones.

Estimated Cooling Contribution: Well-maintained parks and tree-lined streets can reduce local temperatures by 2–5°F compared to adjacent built-up areas. However, the sparse overall canopy coverage (5–10%) means this benefit is localized and does not significantly moderate citywide temperatures. Estimated net cooling effect from green spaces on central Phoenix: **0.5–1.5°F** relative to a fully built-out scenario.

Sources:

- Phoenix Parks and Recreation — park inventory and acreage data
- USDA Forest Service — urban forest assessment for Phoenix metropolitan area
- Remote sensing studies on canopy coverage in Phoenix (Landsat, high-resolution imagery)
- Evapotranspiration research for Sonoran Desert vegetation

5. Land Cover Type

Dominant Surface Materials: Central Phoenix is characterized by high proportions of impervious surface:

- **Asphalt:** Roads, parking lots, and driveways comprise an estimated 25–35% of urban surface area.
- **Concrete:** Sidewalks, building foundations, and commercial hardscape comprise an estimated 15–25%.
- **Roofing:** Predominantly dark-colored asphalt shingles and tar-based materials on older structures; newer commercial buildings increasingly use reflective membranes. Estimated 20–30% of urban surface.
- **Bare Soil & Desert Scrub:** Undeveloped parcels and low-density residential areas with minimal landscaping; estimated 10–20%.
- **Vegetation:** As noted above, 5–10% canopy coverage plus scattered low desert shrubs.

Thermal Properties:

- **Asphalt Albedo:** 0.05–0.10 (very low reflectivity). Absorbs 90–95% of incident solar radiation. Surface temperatures can reach 140–160°F on clear summer days, re-radiating heat into the urban atmosphere.
- **Concrete Albedo:** 0.20–0.40 (moderate reflectivity). Absorbs 60–80% of solar radiation. Surface temperatures typically 120–140°F.
- **Dark Roofing Albedo:** 0.05–0.15. Contributes significantly to sensible heat release into the atmosphere, particularly in afternoon/evening hours.
- **Heat Retention:** Asphalt and concrete have high thermal mass and conductivity, storing daytime heat and releasing it slowly at night. This delays cooling and elevates nighttime temperatures.

Cool Surface Programs: Phoenix has implemented limited cool-roof and cool-pavement initiatives, primarily in municipal buildings and pilot neighborhoods. However, adoption remains low due to cost and aesthetic preferences. Estimated coverage of reflective surfaces: **<5%** of total urban area.

Sources:



- USGS Land Cover Classification — National Land Cover Database (NLCD) for Phoenix area
- Remote sensing studies on urban surface albedo and thermal properties
- Lawrence Berkeley National Laboratory — cool roof and cool pavement research
- Urban heat island studies documenting surface temperature measurements in Phoenix

6. Building Density & Height

Building Density Characterization: Phoenix exhibits a mixed urban form:

- **Central Business District (downtown Phoenix):** Mid- to high-rise commercial (10–40+ stories). Density: approximately 50–100 million square feet of built space per square mile.
- **Inner-Ring Neighborhoods:** Low- to mid-rise residential and mixed-use (1–6 stories). Density: approximately 15–40 million square feet per square mile.
- **Suburban Sprawl (majority of metro area):** Low-rise single-family residential (1–2 stories) with large lot sizes. Density: approximately 5–15 million square feet per square mile.

Typical Building Heights & UHI Contribution:

- Downtown Phoenix: 10–40 stories (100–400 feet). Tall buildings create deep street canyons and trap longwave radiation, elevating nighttime temperatures.
- Mid-rise commercial corridors: 4–10 stories (40–100 feet). Moderate canyon effects.
- Residential neighborhoods: 1–3 stories (15–40 feet). Minimal canyon effects but high lot coverage with dark roofing.

Roofing & Facade Materials: Older Phoenix buildings (pre-2000) predominantly feature dark asphalt shingles and stucco facades (low albedo, 0.10–0.20). Newer commercial construction increasingly uses reflective glass and light-colored materials (albedo 0.30–0.50), but represents a minority of total building stock. Estimated composition: 70% dark materials, 30% reflective/light materials.

Anthropogenic Heat Sources:

- **HVAC Exhaust:** Ubiquitous air conditioning in Phoenix (nearly 100% of commercial and residential buildings). Estimated waste heat release: 50–100 MW during peak summer afternoon hours, concentrated in urban core.
- **Vehicle Density:** High car dependency in sprawling Phoenix. Estimated 0.8–1.2 vehicles per capita. Combustion and idling contribute sensible heat, particularly on major corridors and during rush hours.
- **Industrial Activity:** Limited heavy industry in central Phoenix; light manufacturing and logistics distributed across metro area. Contribution to UHI: minor compared to HVAC and traffic.

Estimated Anthropogenic Heat Contribution: Approximately 10–20% of the urban heat island effect in Phoenix can be attributed to anthropogenic heat sources (HVAC, vehicles, metabolism). The dominant driver remains solar radiation absorption by dark surfaces.

Sources:

- U.S. Census Bureau — building density and housing unit data
- City of Phoenix Planning Department — zoning and building height regulations
- Remote sensing analysis of building footprints and heights (LiDAR, stereo imagery)
- HVAC energy consumption studies and waste heat quantification
- Urban heat island research documenting anthropogenic heat contributions

7. Shadow Coverage

Shadow Coverage Assessment: On August 15 at 12:00 hours (solar noon, approximately 1:00 PM local standard time), the sun is nearly at its highest annual elevation for Phoenix's latitude (33.77°N).

Solar Angle Calculation:

- **Solar Declination (Aug 15):** Approximately +14° (sun is 14° north of celestial equator)
- **Solar Altitude Angle at Solar Noon:** Approximately 79–81° above the horizon (very high, nearly vertical)
- **Implication:** At this high solar angle, shadows cast by buildings and trees are minimal (short shadows directly beneath structures). Shadow coverage from vertical structures is estimated at **5–10%** of ground surface area at solar noon.

Shadow Coverage by Source:



- **Buildings:** Estimated 5–8% of ground area shaded at solar noon (primarily north-south oriented street canyons and building overhangs). East-west oriented canyons provide minimal shade at midday.
- **Trees:** Estimated 1–3% of ground area shaded at solar noon, given the sparse canopy coverage (5–10% overall). Deciduous trees are absent; evergreen desert species provide modest shade.
- **Structures (awnings, pergolas):** Minimal coverage in Phoenix's urban core; estimated <1%.

Quantitative Impact on Temperature Reduction: Shaded surfaces (asphalt, concrete) can be 15–25°F cooler than unshaded surfaces at solar noon. However, due to the limited shadow coverage (5–10%), the net cooling effect on ambient air temperature is modest. Estimated reduction in mean radiant temperature from shading: **2–4°F** in well-shaded street canyons; negligible in open areas.

Permanent vs. Seasonal Shade: Phoenix's vegetation is predominantly evergreen (desert shrubs, palo verde trees), providing consistent year-round shading. Deciduous trees are rare and not well-adapted to the desert climate. Therefore, seasonal variation in shade coverage is minimal (unlike temperate cities where deciduous canopy provides summer shade and winter solar gain).

Sources:

- Solar geometry calculations using NOAA Solar Position Calculator
- Urban canyon radiation modeling studies
- Remote sensing analysis of shadow patterns in Phoenix
- Field measurements of surface and air temperatures in shaded vs. unshaded locations

8. Urban Geometry & Street Canyon Effects

Street Canyon Characteristics: Phoenix's urban form varies significantly by neighborhood:

Downtown Phoenix (Central Business District):

- **Height-to-Width Ratio (H/W):** Estimated 0.8–1.5 in major canyons (e.g., Central Avenue, Washington Street). Buildings are 100–400 feet tall; street widths are 60–120 feet.
- **Longwave Radiation Trapping:** High H/W ratios (≥ 1.0) trap outgoing longwave radiation, particularly at night. Estimated nighttime temperature elevation in deep canyons: **2–4°F** above surrounding areas.
- **Wind Corridor Effect:** Downtown canyons can channel winds, but Phoenix's weak prevailing winds limit convective cooling. Estimated wind speed reduction in canyons: 20–40% compared to open areas.

Mid-Rise Commercial Corridors (e.g., Camelback Road, Indian School Road):

- **Height-to-Width Ratio:** Estimated 0.4–0.8 (buildings 40–100 feet tall; streets 60–100 feet wide).
- **Longwave Radiation Trapping:** Moderate; estimated nighttime temperature elevation: **1–2°F**.

Residential Neighborhoods:

- **Height-to-Width Ratio:** Estimated 0.1–0.3 (buildings 15–40 feet tall; streets 40–80 feet wide). Minimal canyon effects.
- **Longwave Radiation Trapping:** Negligible.

Street Layout Pattern: Phoenix's street grid is predominantly orthogonal (north-south, east-west), particularly in older neighborhoods and downtown. This grid orientation means:

- **East-West Streets:** Experience maximum solar exposure in morning (east-facing facades) and afternoon (west-facing facades). At solar noon (high sun angle), minimal shading from buildings.
- **North-South Streets:** Experience more balanced solar exposure but stronger afternoon heating on west-facing facades.
- **Ventilation:** The grid layout does not inherently favor wind corridors. Weak prevailing winds (south/southeast in summer) may flow preferentially along certain corridors, but the effect is modest.

Sky View Factor (SVF) Estimation: SVF is the fraction of sky visible from a point on the ground, ranging from 0 (completely enclosed) to 1 (completely open).

- **Downtown Phoenix (high-rise canyons):** $SVF \approx 0.3\text{--}0.5$. Limited sky view reduces radiative cooling at night, elevating nighttime temperatures.
- **Mid-rise commercial:** $SVF \approx 0.5\text{--}0.7$.
- **Residential neighborhoods:** $SVF \approx 0.7\text{--}0.9$. Open sky view facilitates radiative cooling, but is partially offset by high surface albedo (dark roofing) and low vegetation coverage.



Nocturnal Cooling Rates: Lower SVF correlates with slower cooling rates at night. Downtown Phoenix, with $SVF \approx 0.3\text{--}0.5$, experiences slower nighttime cooling than suburban areas ($SVF \approx 0.8$). Estimated difference: **1–3°F** slower cooling in downtown canyons, contributing to elevated nighttime temperatures and reduced diurnal temperature range.

Sources:

- Urban canyon radiation modeling literature (Oke, Grimmond, and others)
- Remote sensing analysis of building heights and street widths in Phoenix
- Field measurements of wind speed and temperature in street canyons
- Sky View Factor calculations using LiDAR and building footprint data
- Nocturnal cooling studies in urban heat islands

Urban Factors Analysis

1. Urban Land Use Characteristics

Dominant Land Use & Composition

- Location (33.77°N, 112.15°E) is in the Phoenix metropolitan area, characterized by mixed residential-commercial sprawl typical of the Sunbelt.
- Estimated composition: residential ~50–60% (single-family and multi-family), commercial/retail ~20–25%, industrial/logistics ~10–15%, parks/open space ~5–10%.
- The region exhibits extensive horizontal sprawl with low-to-medium density residential neighborhoods interspersed with commercial corridors and strip retail centers.

Impervious Surface Fraction

- Estimated impervious surface ratio: 60–75% in developed zones, driven by extensive parking lots, roofing, and paved streets.
- Residential areas typically 40–50% impervious; commercial zones 75–85% impervious.
- Limited tree canopy and pervious landscaping in most suburban neighborhoods reduces evaporative cooling potential.

Heat Differential Patterns

- High-density commercial corridors and strip retail zones (with large parking lots) generate concentrated heat islands; these zones can be 5–10°F warmer than adjacent residential areas.
- Residential sprawl, while lower density, lacks sufficient vegetation to mitigate daytime solar absorption by roofing and pavement.
- Green corridors (riparian areas, parks) are fragmented and geographically segregated from dense commercial zones, limiting their cooling influence on heat-generating areas.

Zoning & Planning Strategy

- Phoenix has adopted a Heat Relief Strategy and Urban Heat Island Mitigation Plan, including cool roof ordinances and tree-planting programs.
- Recent zoning updates encourage infill and mixed-use development, but enforcement and uptake remain uneven across the metropolitan area.
- Typical for this area: suburban zoning still dominates, with limited integration of cooling-focused design standards in older neighborhoods.

Land Use Fragmentation & Thermal Equity

- Heat-generating commercial zones and industrial logistics hubs are concentrated along major arterials and highway corridors, while residential neighborhoods are dispersed.
- Lower-income residential areas often lack tree canopy and green space investment, concentrating heat exposure in socioeconomically disadvantaged zones.
- Consequence: unequal thermal burden, with vulnerable populations experiencing higher outdoor and indoor temperatures.



Sources:

- Phoenix Heat Relief Strategy and Urban Heat Island Mitigation Plan (City of Phoenix Planning Department)
- USGS Land Use/Land Cover Classification for Phoenix metropolitan area
- Typical Sunbelt suburban development patterns and zoning practices

2. Anthropogenic Heat Sources

Major Economic Activity & Waste Heat

- Phoenix economy is driven by retail, hospitality, healthcare, light manufacturing, and logistics.
- Estimated heat contribution from commercial HVAC systems: 10–15 W/m² in commercial zones during peak cooling demand (midday summer).
- Waste heat from air conditioning rejection is a primary anthropogenic heat source in the urban environment, particularly acute at the given average temperature of 40°F (which, if this is a winter scenario, is atypical for Phoenix in August; if this is a data error or edge case, thermal analysis assumes standard August conditions of 95–110°F).

Energy-Intensive Sectors

- Large commercial complexes (shopping centers, office parks) with significant HVAC loads; estimated thermal footprint: 5–8 MW per major retail center.
- Data centers and server farms: present in suburban industrial zones; high continuous cooling demand (~2–5 MW per facility).
- Transportation hubs: Phoenix Sky Harbor International Airport (~10 mi south of the coordinates) and associated ground transportation generate significant waste heat from aircraft, vehicles, and terminal HVAC systems.
- Typical for this area: light manufacturing and assembly plants with moderate cooling loads.

Vehicle Density & Transportation Heat

- Phoenix metropolitan area has high vehicle ownership (~0.8 vehicles per capita) and automobile-dependent sprawl.
- Estimated traffic volume on major arterials near the coordinates: 20,000–40,000 vehicles per day on primary corridors.
- Highway proximity (I-10 and I-17 within ~5–10 mi) contributes continuous exhaust heat and sensible heat from vehicle operation.
- Exhaust heat contribution: ~2–4 W/m² in zones with heavy traffic; cumulative effect on local air temperature: 1–3°F elevation in high-traffic corridors.

HVAC Rejection Heat

- In Phoenix's hot climate, air conditioning is ubiquitous; rejection heat from outdoor condensers and cooling towers is a dominant anthropogenic source.
- Estimated HVAC heat rejection: 15–25 W/m² in dense commercial zones during peak cooling (typically 2–6 PM in summer).
- This heat is directly released into outdoor air, raising ambient temperatures and creating positive feedback (higher outdoor temps → higher cooling demand → more rejection heat).
- At the given average temperature of 40°F, HVAC systems would be in heating mode (if accurate), significantly reducing this heat source; however, standard Phoenix summer conditions would show peak HVAC rejection in the 15–25 W/m² range.

Impervious Commercial Surfaces

- Parking lots (asphalt, albedo ~0.05–0.10) cover ~5–8% of total urban area; they absorb 85–95% of incident solar radiation and re-radiate as sensible heat.
- Daytime surface temperatures on asphalt: 140–160°F in summer, contributing 20–40 W/m² of radiant heat to the surrounding air.
- Logistics hubs and big-box retail zones (with minimal vegetation) concentrate this effect, creating localized heat islands 5–8°F above surrounding areas.

Sustainability Initiatives



- LEED adoption in Phoenix is moderate; estimated ~5–10% of commercial buildings meet LEED standards.
- Solar installations: Phoenix has one of the highest residential solar adoption rates in the US (~15–20% of homes have rooftop PV); this reduces daytime cooling demand and associated waste heat.
- Cool roof mandates: Phoenix Building Code requires cool roofing on new commercial buildings (minimum albedo 0.65); retrofits are voluntary and incomplete.
- District cooling systems: limited deployment; most buildings rely on individual HVAC units.

Notable Heat-Contributing Zones

- Central Phoenix commercial corridor (downtown and surrounding office parks): concentrated HVAC rejection and traffic heat; estimated 2–4°F elevation above suburban baseline.
- Sky Harbor International Airport vicinity (~10 mi south): aircraft operations, ground support equipment, and terminal HVAC; localized heat island of 3–5°F.
- Interstate 10 and I-17 corridors: continuous traffic and exhaust; 1–3°F elevation in adjacent areas.
- Suburban shopping centers and strip retail zones within ~2–5 mi of coordinates: large parking lots and commercial HVAC; 2–3°F local elevation.

Sources:

- Phoenix Building Code and Cool Roof Ordinance
- USGS Urban Heat Island research and Phoenix metropolitan area studies
- Typical HVAC thermal load estimates for hot-arid climates
- Vehicle emissions and traffic heat contribution literature

3. Green Infrastructure & Urban Cooling Systems

Urban Vegetation Strategy

- Phoenix's tree canopy coverage is estimated at 5–8% citywide, well below the 25–30% target for urban heat mitigation.
- City of Phoenix Million Tree Initiative aims to increase canopy to 25% by 2050; current progress is ~10–15% of target.
- Tree species adapted to hot-arid climate: palo verde, mesquite, desert willow, and acacia; these provide shade but have lower evapotranspiration than temperate species.
- Park system includes Sky Island parks and linear riparian corridors, but coverage is uneven; parks are concentrated in specific neighborhoods, leaving many residential areas underserved.

Cooling Mechanisms & Effectiveness

- Evapotranspiration from urban vegetation: estimated 0.5–1.5 W/m² in well-vegetated zones, compared to 0–0.2 W/m² in bare pavement.
- Tree shading reduces surface temperatures by 20–30°F and air temperatures by 2–5°F within the canopy footprint.
- Estimated temperature reduction from mature tree canopy vs. bare pavement: 3–6°F at pedestrian level within shade.
- At the given average temperature of 40°F, cooling from vegetation is less critical; however, in typical Phoenix summer conditions (95–110°F), green infrastructure provides essential relief.

Corporate & Public Greening Initiatives

- Rooftop gardens and green roofs: adoption is limited (~2–5% of commercial buildings); those present reduce building cooling load by 20–30% and lower roof surface temperature by 30–50°F.
- Vertical greening (living walls): minimal deployment; primarily in downtown and newer mixed-use developments.
- Public tree-planting programs: ongoing but underfunded; estimated 5,000–10,000 trees planted annually vs. ~50,000 needed to meet canopy targets.

Engineered Cooling Infrastructure

- Artificial water features (fountains, splash pads) are present in parks and public plazas; cooling radius: ~100–200 feet; evaporative cooling effect: 1–2°F in immediate vicinity.
- Cooling ponds and retention basins: limited; primarily in industrial and commercial zones for stormwater management;



minimal thermal impact on surrounding air.

- District cooling networks: not established in Phoenix; individual building HVAC systems dominate.

Seasonal Variability & Adequacy

- Phoenix's desert vegetation is deciduous or semi-deciduous; leaf-out occurs April–May; leaf-off occurs October–November.
- During peak heat season (June–September), canopy is at maximum; cooling effectiveness is highest.
- Water availability is limited; irrigation is necessary to maintain vegetation; drought conditions reduce evapotranspiration effectiveness.
- At the given average temperature of 40°F (winter scenario), cooling infrastructure is not the primary concern; in summer, current green infrastructure is inadequate to offset anthropogenic heat and solar gain across the urban area.

Cooling Equity

- Tree canopy and park access are unevenly distributed; lower-income neighborhoods in South Phoenix and West Phoenix have 2–4% canopy vs. 10–15% in affluent North Phoenix areas.
- Consequence: lower-income residents experience 3–5°F higher ambient temperatures and reduced access to shaded public spaces.

Notable Cooling Infrastructure

- Phoenix Parks system includes large regional parks (e.g., South Mountain Park, Papago Park) at ~5–15 mi distance from the coordinates; these provide localized cooling but limited influence on surrounding urban zones.
- Salt River (riparian corridor) runs south and west of downtown; vegetation along the river provides linear cooling corridor with ~1–2°F influence on adjacent areas.
- Urban lakes and reservoirs (e.g., Tempe Town Lake, ~5 mi south): water surface provides evaporative cooling and reduced surface temperatures; influence radius ~0.5–1 mi.

Sources:

- City of Phoenix Million Tree Initiative and Heat Relief Strategy
- USGS Urban Heat Island and Vegetation studies
- Evapotranspiration and tree canopy effectiveness literature for hot-arid climates
- Urban park and green space equity research

4. Building Material Thermal Properties

Dominant Building Materials

- Residential construction: concrete block (cinder block) with stucco finish, asphalt shingle roofing, and minimal insulation in older stock.
- Commercial construction: concrete and steel frame with glass curtain walls, flat roofs with tar/gravel or single-ply membrane roofing, aluminum frames.
- Parking structures and arterial pavement: asphalt concrete with low albedo.

Albedo Values & Thermal Characteristics

- Fresh asphalt pavement: albedo 0.04–0.05; aged asphalt: albedo 0.08–0.12.
- Concrete (aged, weathered): albedo 0.20–0.35.
- Concrete block/cinder block (typical stucco finish): albedo 0.25–0.40.
- Asphalt shingle roofing: albedo 0.10–0.20.
- Glass curtain walls: albedo 0.15–0.25 (reflective); transmittance 0.60–0.80.
- Cool roof coatings (white or light-colored): albedo 0.60–0.75.
- Typical Phoenix commercial roofing (tar/gravel): albedo 0.10–0.15.

Thermal Mass & Heat Retention



- Concrete and masonry have high thermal mass (specific heat capacity $\sim 0.9\text{--}1.0$ kJ/kg-K); they absorb solar radiation during the day and re-radiate heat at night.
- Daytime surface temperatures: concrete 130–150°F, asphalt 140–160°F; nighttime re-radiation lag extends cooling demand into evening hours.
- Older residential buildings (pre-1990) have poor insulation (R-value $\sim 5\text{--}10$); newer construction (post-2000) typically R-15–R-20, reducing cooling load by 20–30%.
- Consequence: older building stock contributes to prolonged nighttime heat release and higher HVAC loads.

Glass Curtain Wall Effects

- Reflective glass in commercial buildings (albedo 0.15–0.25) reflects solar radiation onto adjacent streets and buildings, creating localized heating of 2–5°F in nearby pedestrian zones.
- Greenhouse effect: interior glass surfaces trap solar radiation; without adequate shading or reflective coatings, interior temperatures rise, increasing cooling demand and waste heat rejection.
- Typical for this area: older commercial buildings have single-pane or low-performance glazing; newer buildings increasingly use high-performance, low-emissivity (low-E) glass.

Heat Mitigation Techniques

- Cool roof ordinance: Phoenix requires albedo ≥ 0.65 for new commercial roofing; compliance is $\sim 70\text{--}80\%$ for new construction, but retrofit rate is low ($\sim 10\text{--}15\%$).
- Permeable pavements: limited deployment; typically in parking lots and pedestrian plazas; estimated $\sim 5\text{--}10\%$ of new construction includes permeable surfaces.
- High-albedo coatings: adoption increasing in commercial sector; estimated 15–25% of commercial buildings have cool roof retrofits.
- Heat-resistant construction standards: newer building codes incorporate passive cooling strategies (thermal mass, natural ventilation, shading); older buildings lack these features.

Building Stock Age & Thermal Performance

- Phoenix's building stock is relatively young; $\sim 60\%$ of buildings were constructed post-1980.
- Pre-1980 buildings: poor insulation, single-pane windows, inefficient HVAC; cooling load 30–50% higher than modern equivalents.
- Post-2000 buildings: improved insulation (R-15–R-20), low-E glazing, efficient HVAC; cooling load 20–30% lower than 1980s stock.
- Consequence: mixed thermal performance across the urban area; older neighborhoods have higher cooling demand and waste heat rejection.

Sources:

- Phoenix Building Code and Cool Roof Ordinance
- ASHRAE (American Society of Heating, Refrigerating and Air-Conditioning Engineers) thermal property standards
- Material science literature on albedo, thermal mass, and building envelope performance
- USGS and EPA studies on urban surface temperatures and material properties

5. Urban Expansion & Development Trends

Population Growth & Urban Density

- Phoenix metropolitan area population growth: $\sim 2.0\text{--}2.5\%$ annually over the past decade; projected to reach ~ 5.5 million by 2050 (from ~ 4.9 million in 2020).
- Urban density: average $\sim 1,500\text{--}2,500$ people per square mile in developed areas; suburban sprawl dominates, with densities as low as 500–1,000 per square mile in outer rings.
- Consequence: continued horizontal expansion increases impervious surface and heat-generating area.

Construction & Development Trends

- Vertical expansion: downtown Phoenix and central corridors show increasing high-rise development (10–30+ stories);



estimated 5–10% of new construction is vertical infill.

- Horizontal sprawl: majority of new development (~70–80%) is suburban single-family residential in outer rings (Chandler, Gilbert, Scottsdale, Peoria).
- Infill development: increasing in central Phoenix and established neighborhoods; estimated 10–15% of new construction is infill on vacant or underutilized sites.
- Brownfield redevelopment: limited; Phoenix has ~50–100 identified brownfield sites; redevelopment rate is ~5–10 sites per year.

Net Change in Impervious Surface

- Estimated annual increase in impervious surface: 2–3% per year across the metropolitan area.
- Net effect: urban heat island effect is intensifying; average urban-rural temperature differential is increasing from ~3–5°F (2000s) to ~5–8°F (2020s).
- Trend: without significant green infrastructure investment, impervious surface fraction will continue to increase, exacerbating heat accumulation.

Climate-Adaptive Urban Design & Policy

- Phoenix Heat Relief Strategy (adopted 2018): includes cool roof ordinances, tree-planting targets, and heat action plans.
- Updated building codes: 2021 Phoenix Building Code incorporates passive cooling and cool roof requirements for new commercial construction.
- Master plans: Phoenix's General Plan 2040 includes heat resilience and green infrastructure goals, but implementation funding is limited.
- Heat action plans: City of Phoenix has a Heat Relief Task Force and publishes annual heat mitigation reports; however, enforcement and uptake remain inconsistent.

Projected Heat Profile Changes (5–10 Year Horizon)

- If current trends continue: impervious surface increases 10–15% over next 5–10 years; urban-rural temperature differential expands to 6–10°F.
- If cool roof and tree-planting initiatives accelerate: potential to offset 20–30% of projected heat increase; net result: 2–4°F increase instead of 5–8°F.
- High-density infill development in central Phoenix may reduce per-capita sprawl but will concentrate anthropogenic heat in smaller areas, creating localized heat islands of 8–12°F above suburban baseline.

Sources:

- U.S. Census Bureau population projections for Phoenix metropolitan area
- City of Phoenix General Plan 2040 and Heat Relief Strategy
- Arizona Department of Housing analysis of development trends
- USGS and EPA urban expansion monitoring

6. Pedestrian Infrastructure & Outdoor Thermal Comfort

Walkability & Pedestrian Accessibility

- Phoenix's walkability is moderate-to-low; suburban sprawl and automobile-oriented design dominate.
- Downtown Phoenix and central corridors (within ~2 mi of coordinates) have improved walkability (Walk Score ~60–75); suburban areas score 30–50.
- Sidewalk coverage: ~70–80% in established neighborhoods; newer suburban areas ~50–60%; many areas lack continuous sidewalks or have poor maintenance.
- Pedestrian crossing infrastructure: limited; many arterials lack safe crossing facilities, discouraging walking during peak heat hours.

Shading Infrastructure

- Covered walkways and arcades: limited to downtown and a few mixed-use districts; estimated <5% of total pedestrian network.



- Street tree canopy along pedestrian routes: sparse; estimated 10–20% of sidewalks have mature tree shade; many streets have no trees.
- Awnings and pergolas: present in commercial districts but absent in most residential areas.
- Consequence: most pedestrian routes lack shade; exposure to direct solar radiation is high during peak heat hours (10 AM–4 PM).

Mean Radiant Temperature (MRT) & Pedestrian Thermal Load

- MRT is the effective temperature experienced by a pedestrian, accounting for direct solar radiation, reflected radiation from surfaces, and air temperature.
- In unshaded urban areas with high-albedo surfaces (concrete, light-colored buildings), MRT can be 10–20°F higher than air temperature.
- In shaded areas (under trees or covered structures), MRT is typically 5–10°F lower than air temperature.
- At the given average temperature of 40°F, MRT effects are minimal; in typical Phoenix summer (95–110°F), MRT in unshaded areas reaches 115–130°F, creating severe thermal stress.
- Sky view factor (SVF): in wide streets with low buildings, SVF is high (~0.7–0.9), increasing radiant heat exposure; in narrow streets or under tree canopy, SVF is low (~0.3–0.5), reducing exposure.

Heat Exposure Risk & Thermal Comfort

- Pedestrian-level heat stress: high in unshaded commercial zones, parking lots, and wide arterials; estimated 5–8°F elevation above air temperature due to radiant heat.
- Shade deficit: ~70–80% of pedestrian routes lack adequate shade; vulnerable populations (elderly, children, outdoor workers) face significant heat exposure risk.
- Limited airflow: narrow streets with tall buildings can trap heat; wider streets with sparse vegetation experience higher wind speeds but also higher solar exposure.
- Thermal comfort threshold: at air temperature >95°F, pedestrians require shade and cooling to avoid heat-related illness; current infrastructure is inadequate.

Cooling Interventions & Comfort Design

- Misting systems: present in a few public plazas and parks; effectiveness: 2–5°F reduction in localized area; limited citywide deployment.
- Pergolas and shade structures: increasing in newer parks and public spaces; estimated 10–15% of public outdoor areas have permanent shade structures.
- Heat-reflective pavements: limited adoption; estimated <5% of pedestrian pavements use light-colored or permeable materials.
- Passive cooling corridors: riparian areas and parks provide natural cooling; however, access is limited for many residents.
- Shaded transit stops: increasing in newer bus rapid transit (BRT) corridors; estimated 30–50% of transit stops have shade structures.

Cycling Infrastructure & Heat Exposure

- Bike lane coverage: ~5–10% of arterials have dedicated bike lanes; most are unshaded and on high-albedo asphalt.
- Pavement materials: standard asphalt (albedo 0.05–0.10) dominates; permeable or light-colored pavements are rare.
- Heat exposure for cyclists: high; surface temperatures on bike lanes reach 140–160°F in summer; radiant heat and air temperature create severe thermal stress.
- Consequence: cycling is discouraged during peak heat hours; bike usage drops significantly in summer months.

Notable Pedestrian Comfort Zones & Deficits

- Downtown Phoenix (central business district, ~2–3 mi from coordinates): improved walkability, increasing shade structures, and cooling plazas; thermal comfort is moderate.
- Central Avenue and Roosevelt Row (arts district, ~1–2 mi): mixed-use development with some shade and public cooling features; pedestrian comfort is moderate-to-good.
- Suburban arterials (Indian School Road, McDowell Road, Van Buren Street): wide, unshaded streets with minimal tree canopy; high heat exposure and poor pedestrian comfort.



- Parking lots and big-box retail zones: severe heat exposure; surface temperatures 140–160°F; minimal shade; pedestrian thermal stress is extreme.
- Parks and riparian corridors (Salt River, local parks): shaded areas with water features; pedestrian comfort is good; however, access is limited for many residents.

Sources:

- Walk Score and pedestrian accessibility studies for Phoenix
- Mean Radiant Temperature (MRT) and outdoor thermal comfort literature (ASHRAE, ISO standards)
- Urban heat island and pedestrian-level thermal stress research
- City of Phoenix Parks and Recreation and Transportation Planning departments
- Cycling infrastructure and heat exposure studies

Events Analysis

Extreme Weather Events & Heat Event History

Heat-Related Events

- Phoenix, Arizona (the location indicated by coordinates 33.77°N, 112.15°W) experiences some of the most intense and prolonged heatwaves in North America, with a documented history of extreme heat events
- June–September is the primary heat season in Phoenix; August 15 falls within the peak intensity period when daytime highs routinely exceed 110°F and nighttime lows remain above 85°F
- Typical synoptic drivers of Phoenix extreme heat include:
 - Persistent thermal high-pressure ridges anchored over the Southwest, blocking mid-latitude storm systems
 - Clear skies and low humidity enabling intense solar heating by day and rapid radiative loss at night (though urban heat island effects limit nighttime cooling)
 - Antecedent drought conditions reducing soil moisture and evapotranspiration, further amplifying surface temperatures
 - Occasional downslope (föhn-like) wind patterns from elevated terrain to the east, compressing and warming air masses
- August 2023 heat event: Phoenix experienced an exceptionally severe heatwave with a streak of 31 consecutive days above 110°F (the longest on record at that time), with peak temperatures reaching 122°F. This event drove widespread power demand strain, heat-related emergency room visits, and multiple heat-related fatalities across Maricopa County
- June 2017 heatwave: Phoenix recorded 19 consecutive days above 110°F with a peak of 120°F, causing significant strain on the electrical grid and documented increases in heat illness presentations
- Government and institutional responses to past heat events:
 - Salt River Project (SRP) and Arizona Public Service (APS) have issued emergency conservation alerts and demand-response programs during extreme heat, with documented instances of rolling blackouts or demand curtailment
 - Maricopa County and City of Phoenix activate cooling centers and issue heat health alerts through the National Weather Service
 - Arizona Department of Health Services and local public health agencies coordinate heat-illness surveillance and public messaging campaigns
- Compound events: Phoenix heat frequently co-occurs with:
 - Severe drought conditions (ongoing megadrought in the Colorado River Basin since 2000), which depletes soil moisture and reduces evaporative cooling capacity, intensifying surface temperature anomalies
 - Wildfire smoke from regional fires (particularly from July–September monsoon-season fire activity), which reduces solar transmittance during the day but can trap heat at night, elevating heat index and air quality hazards simultaneously
 - Power outages during peak demand periods, removing air-conditioning access during the most dangerous hours

Other Extreme Weather With Heat Relevance

- **Droughts:** The Southwest has been in a prolonged megadrought since approximately 2000, with particular intensification since 2020. This drought directly amplifies Phoenix heat through:



- Depletion of soil moisture, reducing evapotranspiration and allowing more solar energy to go into sensible heating rather than latent cooling
- Reduced vegetation cover and groundwater availability in the surrounding region, eliminating natural cooling mechanisms
- Feedback mechanism: heat stress increases evaporative demand, further depleting soil moisture and groundwater, creating a self-reinforcing cycle of intensifying heat anomalies
- **Wildfires:** Regional wildfire activity (particularly in Arizona and New Mexico during late summer) contributes to heat risk through:
 - Smoke plumes that reduce direct solar radiation during daytime hours but trap outgoing longwave radiation at night, elevating nighttime temperatures and preventing physiological recovery
 - Combined thermal and air quality stress, forcing vulnerable populations (elderly, respiratory disease sufferers) to remain indoors with increased heat exposure
 - Estimated: Historically typical fire season (June–October) overlaps with peak heat season, creating compound hazard windows
- **North American Monsoon (July–September):** While monsoon moisture occasionally brings temporary cooling and precipitation, the pre-monsoon period (June–early July) and gaps between monsoon pulses maintain extreme heat with low humidity, maximizing evaporative stress. Post-monsoon conditions (late August–September) return to hot, dry patterns

Sources:

- National Weather Service Phoenix office historical records and heat event documentation
- Maricopa County Department of Public Health heat surveillance data
- U.S. Drought Monitor and NOAA Southwest Climate Outlook
- Salt River Project and Arizona Public Service utility demand and outage records

Heatwave Frequency & Intensity

- **Heatwave Definition:** The National Weather Service defines an Excessive Heat Warning for Phoenix as:
 - Daytime high temperatures $\geq 110^{\circ}\text{F}$ for 3+ consecutive days, OR
 - Daytime high $\geq 115^{\circ}\text{F}$ for any duration, OR
 - Heat Index $\geq 125^{\circ}\text{F}$
 - These thresholds reflect the temperature at which heat illness risk becomes severe and widespread across the general population
- **Frequency Trend:** Phoenix has experienced a dramatic increase in heatwave frequency and duration over recent decades:
 - 1960s–1980s: Heatwaves ($\geq 110^{\circ}\text{F}$ for 3+ days) occurred roughly 1–2 times per summer season
 - 1990s–2010s: Frequency increased to 2–4 events per season, with longer durations
 - 2010s–present: Multiple overlapping heatwaves per season are now typical; the 2023 event with 31 consecutive days above 110°F represents an extreme but increasingly plausible outcome
 - Estimated trend: Approximately 2–3 additional days per decade above 110°F in Phoenix since 1980, with acceleration in recent years
- **Intensity Metrics:**
 - Typical peak temperatures during major heatwaves: $115\text{--}120^{\circ}\text{F}$
 - Record peak: 122°F (June 2017); tied or approached in August 2023
 - Typical duration of major events: 7–14 consecutive days above 110°F ; the 2023 event (31 days) is exceptional but no longer unprecedented
 - **Nighttime Behavior (Critical for Health):** Phoenix's urban heat island effect prevents adequate nighttime cooling. During heatwaves:
 - Nighttime lows typically remain $85\text{--}95^{\circ}\text{F}$, well above the physiological recovery threshold of $\sim 75^{\circ}\text{F}$
 - Consecutive nights above 80°F prevent core body temperature recovery, compounding heat stress and mortality risk
 - In the 2023 event, many nights remained above 90°F , creating dangerous conditions for unacclimatized populations and those without air conditioning
- **Record-Breaking Events:**
 - August 2023: 31 consecutive days $\geq 110^{\circ}\text{F}$ (longest streak on record for Phoenix), peak 122°F , documented heat-related deaths in Maricopa County
 - June 2017: 19 consecutive days $\geq 110^{\circ}\text{F}$, peak 120°F , significant grid strain and emergency response activation



- July 1990: Extended heatwave with multiple days $\geq 122^{\circ}\text{F}$, one of the earliest documented extreme events in modern Phoenix records
- **Trend Context:** Heatwaves in Phoenix are increasing in frequency, duration, and intensity. Attribution factors include:
 - Regional warming from greenhouse gas forcing, with the Southwest warming faster than the global average
 - Weakening of the jet stream and more persistent high-pressure systems, increasing the likelihood of blocking patterns that sustain heat domes
 - Urban heat island effect: Phoenix's built environment (low albedo surfaces, reduced vegetation, waste heat from air conditioning) elevates temperatures $5\text{--}10^{\circ}\text{F}$ above surrounding rural areas
- **Temperature Classification for August 15, 2024 at 12:00 hours:**
 - Provided average temperature: 40.0°F — this value is implausible for Phoenix in August and likely represents a data error or misalignment
 - Climatological normal for Phoenix on August 15: High $\sim 107^{\circ}\text{F}$, Low $\sim 85^{\circ}\text{F}$ (based on 1991–2020 normals)
 - **Assumption for analysis:** If the provided 40.0°F is a transcription error and the actual temperature is in the range of $100\text{--}115^{\circ}\text{F}$ (typical for Phoenix on August 15), the conditions would be:
 - $100\text{--}107^{\circ}\text{F}$: Normal to slightly above normal for this date; no heatwave threshold exceeded
 - $107\text{--}110^{\circ}\text{F}$: Above normal; approaching or at the lower threshold for heat advisory consideration
 - $110\text{--}115^{\circ}\text{F}$: Exceeding heatwave thresholds; Excessive Heat Warning criteria met
 - $\geq 115^{\circ}\text{F}$: Extreme heat; severe health risk
 - August 15 falls within the peak heat season (June–September), with August typically the second-hottest month after July in Phoenix
 - Heat dome and blocking pattern susceptibility: Phoenix's geography (low elevation, surrounded by mountains that channel and compress air masses, interior basin location) makes it highly susceptible to persistent high-pressure ridges and heat domes. The region experiences blocking patterns in roughly 30–50% of summers, with frequency increasing in recent decades

Sources:

- National Weather Service Phoenix Forecast Office climate normals and heatwave documentation
- NOAA National Centers for Environmental Information (NCEI) temperature records for Phoenix Sky Harbor International Airport
- Maricopa County Department of Public Health heat event summaries
- Climate change attribution studies for the Southwest (IPCC AR6, regional downscaling analyses)

Public Health Impacts & Heat Vulnerability

- **Heat-Related Health Burden:** Phoenix experiences significant heat-related morbidity and mortality, particularly during multi-day heatwaves:
 - Heat exhaustion and heatstroke presentations increase dramatically when temperatures exceed 110°F ; emergency department visits for heat-related illness can increase 2–5 fold during Excessive Heat Warnings
 - Cardiovascular and respiratory exacerbations: Heat stress increases demand on the cardiovascular system and can trigger acute coronary syndromes, arrhythmias, and respiratory decompensation in vulnerable individuals
 - August 2023 event: Maricopa County documented multiple heat-related deaths (estimated: 10–20+ deaths directly or substantially attributed to heat during the 31-day streak, though final counts vary by attribution methodology)
 - Historical pattern: Phoenix typically experiences 10–30 heat-related deaths per year during normal summers; major heatwaves can double or triple this count
- **Vulnerable Populations:**
 - Elderly (65+ years): Reduced thermoregulatory capacity, multiple comorbidities, medications that impair heat dissipation (diuretics, anticholinergics), and social isolation increase risk. This group accounts for 50–70% of heat-related deaths in Phoenix
 - Outdoor workers: Construction, landscaping, agricultural, and delivery workers face prolonged heat exposure without adequate shade or cooling. Occupational heat illness is common; OSHA heat guidelines are advisory rather than mandatory in Arizona
 - Low-income households: Limited access to air conditioning, inability to afford electricity costs during peak demand periods, and residence in heat-vulnerable neighborhoods (often with less tree canopy and more impervious surfaces) concentrate risk
 - Unhoused populations: Lack of shelter, inability to access cooling centers, and higher prevalence of chronic disease and substance use disorders create extreme vulnerability
 - Children: While less common than elderly mortality, heat illness in children occurs, particularly in outdoor



settings and vehicles

- Populations with chronic disease: Diabetes, cardiovascular disease, respiratory disease, and mental health conditions increase susceptibility to heat stress
- Geographic concentration: South Phoenix and West Phoenix neighborhoods (historically lower-income, predominantly Hispanic and African American communities) have documented higher heat vulnerability due to lower tree canopy coverage, higher concentrations of impervious surfaces, and lower air-conditioning prevalence
- **Heat-Mortality Relationship:**
 - Threshold for excess mortality in Phoenix: Excess deaths begin to increase noticeably when daytime highs exceed 105–110°F and nighttime lows remain above 80°F for multiple consecutive days
 - The relationship is non-linear: mortality risk increases sharply above 110°F, particularly when nighttime cooling is inadequate (lows above 85°F)
 - Acclimatization: Phoenix residents are more heat-adapted than populations in cooler climates, so the mortality threshold is higher than in regions unaccustomed to extreme heat; however, even in Phoenix, temperatures above 115°F overwhelm physiological capacity
- **Consecutive Hot Night Risk:**
 - Nighttime lows above 75°F prevent adequate core body temperature recovery; above 80°F, recovery is severely compromised
 - Consecutive nights above 85°F create cumulative physiological stress, particularly in elderly and chronically ill populations
 - During the 2023 event, Phoenix experienced multiple consecutive nights with lows above 90°F, creating dangerous conditions where indoor temperatures in non-air-conditioned homes remained elevated throughout the night
 - The combination of daytime highs $\geq 110^\circ\text{F}$ and nighttime lows $\geq 85^\circ\text{F}$ for 3+ consecutive days is a strong predictor of excess mortality in Phoenix
- **Heat Advisory and Warning Systems:**
 - National Weather Service Phoenix issues Heat Advisories when heat index or temperature reaches criteria that pose moderate risk (typically daytime highs 105–109°F or heat index 105–109°F for 2+ days)
 - Excessive Heat Warnings are issued when criteria for severe risk are met (daytime highs $\geq 110^\circ\text{F}$ for 3+ days, or $\geq 115^\circ\text{F}$ for any duration)
 - Tiered response protocols:
 - Heat Advisory: Public awareness campaigns, recommendations for vulnerable populations to check on elderly neighbors, cooling center information disseminated
 - Excessive Heat Warning: Enhanced public messaging, activation of cooling centers, coordination with emergency services for increased heat-illness response, utility companies implement demand-response programs
- **Cooling Infrastructure and Public Health Interventions:**
 - Cooling centers: City of Phoenix and Maricopa County operate cooling centers during heat events, though utilization is often lower than needed due to transportation barriers, stigma, and awareness gaps
 - Public awareness campaigns: NWS, county health department, and local media issue regular heat safety messaging during the heat season
 - Employer heat-safety regulations: Arizona does not have a state-level occupational heat standard; OSHA guidelines are federal recommendations but not enforceable in Arizona. Some large employers (utilities, government) have internal heat protocols
 - Utility shutoff moratoriums: Arizona utilities typically implement summer moratoriums on disconnections for non-payment, though these are not always comprehensive
 - Air conditioning access programs: Limited utility assistance programs exist (e.g., LIHEAP), but funding is insufficient to meet demand among low-income households
- **Heat Vulnerability Mapping:**
 - The City of Phoenix and Maricopa County have developed heat vulnerability indices and maps identifying neighborhoods at highest risk based on temperature, tree canopy, income, age demographics, and air-conditioning prevalence
 - South Phoenix (particularly areas south of downtown and west of the city center) and West Phoenix neighborhoods consistently rank as highest vulnerability
 - The coordinates provided (33.77°N, 112.15°W) fall in central Phoenix; specific vulnerability classification would require detailed mapping, but central Phoenix generally has moderate-to-high vulnerability due to mixed urban density, variable tree canopy, and diverse socioeconomic conditions
- **Health-System Preparedness:**



- Phoenix-area hospitals (Banner Health, HonorHealth, Mayo Clinic Arizona) have surge protocols for heat-related illness, though major heatwaves can strain emergency departments
- EMS response: Phoenix Fire Department and private ambulance services report increased call volumes during heat events, with response times potentially delayed during peak demand periods
- During the 2023 event, some hospitals reported elevated emergency department census and increased admissions for heat-related and exacerbated chronic conditions
- **Equity Dimension:**
 - Heat health burden is disproportionately concentrated in South and West Phoenix neighborhoods, which are predominantly low-income, Hispanic, and African American communities
 - These neighborhoods have documented lower tree canopy coverage (often 5–15% vs. 20–30% in wealthier North Phoenix), higher concentrations of impervious surfaces, and lower rates of air-conditioning access
 - Historical redlining and discriminatory zoning practices have concentrated poverty and environmental hazards in these areas, creating compounding heat vulnerability
 - Language and cultural barriers may limit access to heat health information and cooling resources for non-English-speaking populations

Sources:

- Maricopa County Department of Public Health heat-related illness and mortality surveillance
- National Weather Service Phoenix heat health impact assessments
- Arizona Department of Health Services environmental health and epidemiology data
- City of Phoenix Office of Heat Response and Mitigation (established 2022)
- Published heat vulnerability indices and mapping projects for Phoenix (local public health and urban planning sources)
- OSHA heat illness guidance and occupational health literature

Anthropogenic Factors Analysis

Location: Phoenix, Arizona metropolitan area (33.77°N, 112.15°W) | **Date/Time:** August 15, 2024, 12:00 hours | **Reference Temperature:** 40.0°F (4.4°C)

Critical Note on Input Temperature: The provided average temperature of 40.0°F is anomalously low for Phoenix in mid-August and does not align with historical climate data for this location (typical August highs: 110–115°F; lows: 80–85°F). This analysis proceeds using the provided 40.0°F as a calibration reference while noting that actual anthropogenic heat contributions at this location in August would occur under significantly hotter baseline conditions. The 40.0°F value may represent a data error or a hypothetical scenario; real-world cooling demand and grid stress assessments for Phoenix in August would be substantially more severe.

1. Heat Emissions from Vehicles & Industry

Transportation Heat Footprint

- Phoenix is a highly car-dependent metropolitan area with minimal public transit mode share (estimated 1–2% of commute trips); private vehicle use dominates transportation energy consumption and waste heat generation.
- Dominant transport modes: single-occupant vehicles on extensive freeway network (I-10, I-17, Loop 101, Loop 202); significant truck freight movement due to regional distribution hub role and proximity to Mexico border.
- Traffic volume characterization: At 12:00 hours on August 15 (a Thursday in summer), traffic would be at moderate levels post-morning rush (peak 7–9 AM) but before afternoon peak (4–6 PM). Midday traffic is lighter than peak periods but sustained by commercial delivery, service vehicles, and airport traffic.
- Vehicular waste heat mechanisms:
 - Engine exhaust: internal combustion engines reject ~65–70% of fuel energy as waste heat; typical vehicle produces 40–60 kW of thermal output while operating.
 - Tire-road friction and brake heat: continuous low-level heat generation even at steady speeds; braking events produce concentrated thermal pulses.
 - Cumulative effect: Phoenix metro area with ~2.1 million residents and car-dependent sprawl generates sustained vehicular waste heat across extensive road network, particularly on major corridors.
- At 12:00 hours on a summer Thursday, waste heat from vehicles is elevated but not at peak intensity; afternoon rush-hour peak (4–6 PM) would generate higher concentrations.



Industrial and Commercial Waste Heat

- Power generation: Arizona Public Service (APS) and Salt River Project (SRP) operate natural gas-fired and coal plants in the region; Palo Verde Nuclear Generating Station (largest nuclear plant in U.S. by capacity) is located ~40 miles west of Phoenix. These facilities reject enormous quantities of waste heat via cooling towers and condenser systems.
- Data centers: Phoenix has emerged as a significant data center hub due to low land costs, available power, and cooling water access (though water scarcity is a constraint). Major hyperscale facilities operated by cloud providers generate sustained waste heat; estimated: several hundred megawatts of continuous thermal load across metro area.
- Refineries and chemical manufacturing: limited heavy refining in immediate Phoenix area; however, significant industrial operations in surrounding regions (Avondale, Goodyear) contribute to broader metro heat load.
- Commercial HVAC and refrigeration: extensive retail, hospitality, and food service sectors (major tourism and convention center activity) operate large cooling and refrigeration systems that exhaust heat to outdoor air.
- Thermal output profile: Industrial and power generation waste heat is continuous (24/7 baseline) with peaks during high-demand periods (afternoon/evening). Data centers operate at relatively constant load. Commercial HVAC peaks during business hours and evening dining/entertainment periods.
- At 12:00 hours on August 15, industrial waste heat is at moderate-to-elevated levels; afternoon peak would intensify further.

Spatial Heat Concentration Zones

- Interstate corridors (I-10, I-17, Loop 101, Loop 202): sustained traffic generates measurable heat plumes; highway corridors in hot climates typically run 2–4°F warmer than surrounding areas during peak traffic periods due to cumulative vehicle waste heat, pavement absorption, and reduced vegetation.
- Sky Harbor International Airport (PHX): major hub with continuous aircraft operations, ground support equipment, and vehicle traffic. Aircraft engines and auxiliary power units generate concentrated waste heat; apron areas and taxiways show elevated surface temperatures.
- Downtown Phoenix and central business district: high building density, concentrated commercial HVAC exhaust, vehicle congestion, and reduced vegetation create urban heat island effect amplified by industrial waste heat.
- Tempe and Scottsdale commercial corridors: retail, hospitality, and office parks with extensive parking and HVAC systems contribute localized heat concentrations.
- Data center clusters: specific industrial parks hosting hyperscale facilities generate localized thermal plumes; cooling tower exhaust is visible and measurable.
- Quantified differential: Estimated 3–6°F warming in dense traffic corridors and commercial zones relative to surrounding suburban/rural areas during peak activity periods, with contribution from vehicle and industrial waste heat accounting for roughly 1–2°F of this differential (remainder from urban materials and reduced vegetation).

Temporal Patterns

- Morning rush hour (6:30–9:00 AM): peak vehicle waste heat generation; industrial facilities ramping to full output; commercial HVAC systems activating.
- Midday (11:00 AM–2:00 PM): moderate traffic, sustained industrial output, peak commercial activity. At 12:00 hours on August 15, waste heat is elevated but not at absolute peak.
- Afternoon peak (4:00–6:30 PM): second rush-hour surge, maximum combined traffic and commercial cooling demand; industrial facilities at sustained high load.
- Evening (6:30 PM–11:00 PM): declining traffic, sustained commercial activity (dining, entertainment), industrial output steady.
- Nighttime (11:00 PM–6:00 AM): minimal traffic, reduced commercial activity, industrial baseline continues; freight operations increase (less congestion for trucks).
- Weekend pattern (Saturday–Sunday): reduced commute traffic, sustained commercial activity (retail, hospitality), lower industrial demand. August 15, 2024 is a Thursday, so weekday pattern applies.

Emission-Reduction Measures in Effect or Planned

- EV adoption: Arizona has moderate EV adoption (~3–4% of registered vehicles as of 2023); Phoenix metro has growing charging infrastructure but remains car-dependent on internal combustion engines.
- Fleet electrification: APS and SRP have committed to renewable energy targets (50% by 2030 for APS); however, grid decarbonization does not directly reduce waste heat from vehicles or industrial cooling systems in the near term.
- Industrial heat recovery: Some data centers employ waste heat recovery for district heating or other productive use,



but this is not systematic across Phoenix metro. Power plants operate standard cooling towers without significant heat recovery.

- Emission control policies: Arizona has adopted California emission standards for light-duty vehicles; however, no specific low-emission zones or congestion pricing in Phoenix metro (as of 2024).
- Public transit expansion: Valley Metro bus system and planned light rail extensions (Phoenix Light Rail Phase 2, Mesa extension) aim to reduce vehicle mode share, but current penetration remains very low.

Waste Heat Recovery Opportunities

- Limited current deployment: Phoenix has minimal district heating infrastructure (not needed in hot climate); waste heat recovery from power plants and data centers is not systematically captured for productive use.
- Potential opportunities: Data center waste heat could theoretically be used for desalination, industrial process heat, or district cooling in adjacent facilities, but this is not currently implemented at scale in Phoenix.
- Barrier: Low natural gas prices and abundant air-cooled condenser capacity have historically made waste heat recovery economically unattractive; water scarcity may incentivize future innovation in this area.

Sources:

- Arizona Public Service (APS) and Salt River Project (SRP) utility data and sustainability reports
 - U.S. Energy Information Administration (EIA) state and utility-level energy consumption data
 - Federal Highway Administration (FHWA) traffic volume and vehicle emissions data
 - U.S. Census Bureau American Community Survey (ACS) commute mode and transportation data
 - General knowledge of automotive thermal efficiency and waste heat generation
 - Urban heat island literature and traffic-related warming studies
-

2. Cooling Infrastructure & Waste Heat Feedback Loop

Cooling Infrastructure Prevalence

- Air conditioning penetration: Phoenix has among the highest AC penetration rates in the United States; estimated 90–95% of residential units have air conditioning (far above national average of ~87%), and nearly 100% of commercial and institutional buildings are air-conditioned.
- Justification: Phoenix's extreme summer heat (regularly exceeding 110°F) makes AC essential for habitability and public health; cooling is not optional but baseline infrastructure.
- Housing stock composition: Mix of older (pre-1980) housing with window units and newer construction with central AC; newer suburban developments predominantly have central systems.
- Commercial and institutional: All major office buildings, retail centers, hospitals, schools, and government facilities operate mechanical cooling systems.

The AC Feedback Loop & Ambient Warming Effect

- Mechanism: Air conditioning systems reject heat from indoor spaces to outdoor air via condenser units (rooftop units, ground-level compressors, cooling towers). This displaced heat directly warms the outdoor environment.
- Quantified effect: Studies of urban heat islands in hot climates suggest AC waste heat contributes 1–2°F to nighttime urban temperatures in dense areas; in Phoenix's sprawling, lower-density development, the effect is more distributed but still measurable.
- Temporal pattern: AC waste heat peaks during afternoon and evening hours (2:00 PM–10:00 PM) when cooling demand is highest and outdoor temperatures are elevated. At 12:00 hours on August 15, cooling demand is ramping up but not yet at peak.
- Density effect: Downtown Phoenix and dense commercial zones experience greater AC waste heat concentration; suburban and exurban areas have lower density but still significant cumulative effect due to sprawl.
- Nighttime persistence: AC waste heat contributes to elevated nighttime temperatures, reducing radiative cooling and extending the thermal stress period for outdoor workers and vulnerable populations.
- Feedback amplification: Higher ambient temperatures drive increased AC demand, which generates more waste heat, which further elevates ambient temperatures—a self-reinforcing cycle.

Balance-Point Temperature & Cooling Activation



- Balance-point temperature for Phoenix: approximately 65–70°F. Below this threshold, heating is required; above it, cooling is required.
- Provided temperature (40.0°F) is 25–30°F below the balance point, indicating a scenario where no cooling would be required. This is inconsistent with August 15 conditions in Phoenix.
- Realistic August 15 conditions: Typical daytime high ~112°F, nighttime low ~82°F. At 12:00 hours, ambient temperature would be ~100–105°F, well above balance point and deep into peak cooling demand territory.
- Under realistic conditions: Cooling systems would be operating at near-maximum capacity at 12:00 hours on August 15, generating substantial waste heat feedback.

Cooling Inequality & Disparities

- Documented disparities: Older housing stock in central Phoenix and lower-income neighborhoods has lower AC penetration and efficiency; some units rely on window AC units or lack adequate cooling.
- Rental housing: Some rental properties lack cooling requirements in lease agreements; tenants may be unable to afford AC operation costs.
- Homeless and outdoor populations: Extremely vulnerable to heat stress; limited access to cooling infrastructure.
- Equity implications: Heat vulnerability is correlated with socioeconomic status and housing security; cooling infrastructure disparities exacerbate health inequities during extreme heat events.
- Policy response: City of Phoenix has implemented cooling center networks and emergency cooling assistance programs during extreme heat events.

District Cooling Systems

- Current deployment: Phoenix has minimal district cooling infrastructure. Most cooling is provided by distributed, building-level air conditioning systems.
- Potential: District cooling could improve efficiency and reduce waste heat per unit of cooling delivered, but high capital costs and existing distributed infrastructure make retrofit challenging.
- Relevance: Not a significant current factor in Phoenix's cooling landscape.

Innovative & Passive Cooling Strategies

- Evaporative cooling (swamp coolers): Historically common in Arizona; less effective than AC but lower energy consumption. Declining use as AC becomes standard and humidity increases.
- Passive design: Some newer buildings incorporate passive cooling (natural ventilation, thermal mass, shading) but mechanical AC remains primary cooling method.
- Cool roofs and pavements: City of Phoenix has promoted cool roof coatings and reflective pavement to reduce solar absorption; effectiveness is modest compared to AC waste heat feedback.
- Nighttime ventilation flushing: Possible in spring/fall when nighttime temperatures drop below indoor setpoints; limited utility in summer when nighttime lows remain 80°F+.
- Green infrastructure: Vegetation and urban forestry provide localized cooling but are limited by water scarcity constraints in Phoenix.
- Smart thermostats and demand response: Growing adoption; enables load shifting and reduces peak demand, indirectly reducing waste heat concentration during peak hours.

Cooling Demand Classification at Provided Temperature

- At 40.0°F: **Baseline** (no cooling required; heating might be needed in early morning or winter conditions).
- At realistic August 15, 12:00 hours conditions (~100–105°F): **Peak** cooling demand. Cooling systems operating at maximum or near-maximum capacity; grid stress and waste heat feedback at high levels.

Sources:

- U.S. Census Bureau American Housing Survey (AHS) and American Community Survey (ACS) data on AC prevalence
- Arizona Department of Housing and U.S. Department of Housing and Urban Development (HUD) housing stock data
- City of Phoenix Office of Heat Response and Mitigation reports
- Urban heat island and AC waste heat feedback literature
- ASHRAE (American Society of Heating, Refrigerating and Air-Conditioning Engineers) standards and thermal balance data



3. Energy System Load & Grid Stress

Energy Demand Profile

- Residential consumption: Approximately 35–40% of total electricity demand; dominated by air conditioning (summer peak) and water heating.
- Commercial consumption: Approximately 40–45% of total electricity demand; includes office buildings, retail, hospitality, data centers, and food service. Peak during business hours and evening.
- Industrial consumption: Approximately 15–20% of total electricity demand; includes manufacturing, mining, and agricultural operations. More stable than residential/commercial but subject to demand fluctuations.
- Energy source mix (APS and SRP combined):
 - Natural gas: ~40–45% of generation (primary peaking fuel)
 - Nuclear: ~25–30% (Palo Verde baseload)
 - Coal: ~15–20% (declining; retirement of some units planned)
 - Renewables (solar, wind): ~15–20% and growing (APS target: 50% by 2030)
 - Hydro: ~5–10% (limited by water availability)
- Summer peak demand: Phoenix metro area experiences extreme summer peaks (July–August) driven by air conditioning load; winter demand is relatively low.

Temperature-Demand Sensitivity

- Cooling degree days (CDD) baseline: 65°F for Phoenix region (standard reference temperature).
- Temperature-demand relationship: Estimated 2–3% increase in electricity demand per 1°F increase above 65°F in summer months (based on typical hot-climate utility data). This sensitivity is high due to AC load dominance.
- Realistic August 15 scenario: At typical 12:00 hours temperature of ~100–105°F, demand would be ~70–105 CDD above baseline, corresponding to peak or near-peak summer demand levels.
- Peak demand record: APS and SRP have experienced all-time peak demand records during extreme heat events (e.g., June 2023 heat wave); demand can exceed 30 GW across the region during afternoon peaks.
- At provided 40.0°F: Demand would be well below baseline (heating-mode demand), which is not applicable to August 15 scenario.

Grid Stability & Heat-Related Risk

- Documented heat-related strain: Arizona utilities have experienced multiple grid stress events during extreme heat:
 - June 2023 heat wave: Record-breaking temperatures (120°F+) drove peak demand; utilities implemented voluntary conservation measures and load management.
 - August 2022: Extreme heat and renewable curtailment (solar declining in evening peak hours) created supply-demand mismatch; rolling blackout risk was elevated.
 - Historical pattern: Most grid stress events occur in late afternoon/early evening (4:00–8:00 PM) when cooling demand peaks and solar generation declines.
- Specific incidents: APS and SRP have issued conservation appeals during extreme heat events; no widespread rolling blackouts in recent years, but close calls have occurred.
- At 12:00 hours on August 15: Grid would be approaching peak demand but not yet at absolute maximum (peak typically 4:00–8:00 PM). Stress level would be elevated but manageable if weather is typical for date.

Grid Heat Vulnerability

- Transmission and distribution infrastructure: High-voltage transmission lines and distribution transformers experience capacity derating at elevated temperatures (typically ~0.5–1% capacity loss per 1°C above rated temperature).
- Exposure: Arizona's transmission system is exposed to extreme heat; lines and transformers in desert regions operate near thermal limits during summer peaks.
- Cooling water constraints: Palo Verde Nuclear Station and some thermal plants depend on cooling water; drought conditions and water scarcity create vulnerability to generation curtailment during extreme heat (when cooling water is most needed).
- Documented incidents: During 2023 heat wave, some transmission constraints were reported; however, no major generation outages due to cooling water limitations occurred.



Load Shedding & Demand Response

- Load shedding history: Arizona utilities have not implemented widespread rolling blackouts in recent years, but the risk is real during extreme heat events. Grid is generally reliable but approaching stress limits during peak summer conditions.
- Demand response programs: APS and SRP operate demand response programs (voluntary conservation appeals, automated load control for large commercial/industrial customers, time-of-use rates) to manage peak demand.
- Relevance: Load shedding is a potential risk during extreme heat but not a routine occurrence. Demand response is actively used to manage peaks.

Energy Resilience Measures

- Smart grid deployment: Both APS and SRP have invested in smart grid technologies, including advanced metering infrastructure (AMI), distribution automation, and real-time monitoring.
- Renewable penetration: Solar generation is growing rapidly in Arizona (abundant solar resource); however, solar output declines in evening peak hours, creating supply-demand mismatch. Battery storage deployment is increasing to address this gap.
- Battery storage: APS and SRP have deployed or planned battery storage systems (utility-scale and distributed); capacity is growing but still modest relative to peak demand.
- Demand response: Automated and voluntary programs help manage peak demand; effectiveness increases with customer participation and technology deployment.
- Microgrid capacity: Limited current deployment; some facilities (military bases, universities, industrial parks) have microgrids or backup generation, but this is not systematic across the grid.
- Renewable targets: APS committed to 50% renewable energy by 2030 and 100% clean energy by 2050; SRP has similar targets. Progress is on track but dependent on continued investment and technology deployment.

Energy System Demand Curve Assessment at Provided Temperature

- At 40.0°F: Demand would be at winter baseline or below (heating-mode); not applicable to August 15 scenario.
- At realistic August 15, 12:00 hours (~100–105°F): Energy system would be operating in upper-middle to peak demand range, approaching historically documented stress points. Grid would be stressed but not at emergency levels (peak stress typically occurs 4:00–8:00 PM). Renewable solar generation would be at high levels (mitigating some demand), but evening peak would create supply-demand tension.

Sources:

- Arizona Public Service (APS) and Salt River Project (SRP) annual reports, sustainability reports, and integrated resource plans
- U.S. Energy Information Administration (EIA) state-level electricity generation and consumption data
- Federal Energy Regulatory Commission (FERC) and Southwest Power Pool (SPP) grid operations data
- NERC (North American Electric Reliability Corporation) reliability assessments
- Arizona Corporation Commission (ACC) utility filings and proceedings
- General knowledge of temperature-demand sensitivity in hot climates and grid thermal constraints

4. Traffic Behavior & Vehicular Heat Contribution

Traffic Pattern Characterization

- Congestion levels: Phoenix metro area experiences moderate-to-heavy congestion on major corridors during peak hours (7–9 AM, 4–6 PM); midday and off-peak traffic is lighter but still sustained.
- Peak hours: Morning rush (6:30–9:00 AM), midday (11:00 AM–2:00 PM), afternoon rush (4:00–6:30 PM), evening (6:30–10:00 PM).
- At 12:00 hours on August 15 (Thursday): Traffic is in midday period, post-morning rush but before afternoon peak. Congestion is moderate; traffic volume is sustained but not at peak intensity.
- Dominant commute patterns: Car-dependent sprawl; single-occupant vehicles dominate (estimated 85–90% of commute trips). Public transit mode share is very low (~1–2%).
- Commute distances: Phoenix metro is large and sprawling; average commute distance is 10–15 miles; many commuters travel 20+ miles.



Waste Heat Concentration Zones

- Interstate corridors:
 - I-10 (east-west spine): Highest traffic volume; sustained congestion during peaks; major waste heat concentration.
 - I-17 (north-south): Secondary major corridor; significant truck traffic to/from northern Arizona.
 - Loop 101 and Loop 202 (outer loops): Circumferential routes; moderate-to-heavy traffic; distributed heat load.
- Major intersections and on-ramps: I-10/I-17 interchange (downtown), I-10/Loop 101 interchanges, Sky Harbor Airport access roads—all experience concentrated vehicular waste heat during peak periods.
- Freight corridors: I-10 between Phoenix and Tucson (south), I-10 toward California (west), I-17 toward Flagstaff (north); sustained truck traffic generates continuous waste heat.
- Sky Harbor International Airport: Major hub with continuous aircraft operations, ground support equipment, rental car facilities, and access road traffic. Apron and taxiway areas show elevated surface temperatures; vehicle traffic to/from airport adds to waste heat.
- Delivery zones and commercial corridors: Downtown Phoenix, Tempe, Scottsdale, and suburban commercial areas experience concentrated delivery vehicle traffic during business hours.
- Transit terminals: Limited public transit; however, Park-and-Ride facilities and bus transit centers experience vehicle congestion.
- Drive-through clusters: Fast food, coffee, and retail drive-throughs concentrated in suburban areas; vehicles idle and operate at low speeds, generating elevated waste heat per unit distance traveled.
- Parking structures: Large surface and multi-level parking lots in downtown, commercial, and airport areas; vehicles circulating and idling generate localized heat.
- Quantified differential: Highway corridors during peak traffic periods run 2–4°F warmer than surrounding areas due to cumulative vehicle waste heat, pavement absorption, and reduced vegetation. At 12:00 hours on August 15, differential would be lower than peak periods but still measurable (estimated 1–2°F above surrounding areas).

Pavement Heat Interaction

- Tire-road friction: Vehicle tires generate heat through friction with pavement; this heat is absorbed by the road surface and surrounding air.
- Exhaust heat: Engine exhaust at 400–600°F is directed near pavement level, heating the road surface and air immediately above it.
- Shade obstruction: Vehicle traffic prevents pavement cooling by blocking solar radiation during day and reducing radiative cooling at night (vehicles parked on pavement).
- Pavement material: Asphalt and concrete absorb and retain heat; dark asphalt is particularly effective at heat absorption. Pavement temperatures in Phoenix can exceed 160–180°F on summer days, contributing to ground-level air warming.
- Cumulative effect: Vehicle traffic prevents pavement cooling and adds direct waste heat, compounding surface heat retention and creating elevated ground-level temperatures in traffic corridors.

Public Transit Role

- Current mode share: Public transit accounts for ~1–2% of commute trips in Phoenix metro; very low compared to national average (~5%) or major transit-oriented cities (10–30%).
- Transit system: Valley Metro operates bus system with ~400 routes; Phoenix Light Rail (opened 2008) serves downtown and limited corridors (~20 miles of track). Ridership is modest relative to metro area population.
- Capacity constraints: Limited transit capacity means most commuters cannot shift to transit even if desired; car dependency is structural.
- Heat vulnerability of transit: Bus stops and light rail stations often lack shade or cooling; waiting passengers experience extreme heat stress in summer. This reduces transit appeal during extreme heat, potentially increasing vehicle use (negative feedback).
- Efficiency comparison: Bus transit produces ~1/10 the waste heat per passenger-mile compared to single-occupant vehicles; light rail is even more efficient. However, low mode share means transit's heat mitigation impact is limited.
- Planned expansion: Phoenix Light Rail Phase 2 and Mesa extension aim to increase transit capacity and mode share, potentially reducing vehicle waste heat in the long term.

Heat-Induced Behavioral Shifts



- Increased driving to avoid walking/cycling: Extreme heat (110°F+) makes walking and cycling dangerous; residents shift to air-conditioned vehicles, increasing vehicle traffic and waste heat.
- Reduced transit use: Exposed bus stops and light rail platforms without adequate shade/cooling become unbearable during extreme heat; some transit riders switch to vehicles.
- Shifted peak hours: Some commercial activity (outdoor dining, shopping) shifts to evening/night hours to avoid daytime heat; this can shift traffic peaks and waste heat generation patterns.
- Increased air conditioning demand in vehicles: Drivers run AC at maximum to cool vehicles quickly; this increases fuel consumption and waste heat per vehicle.
- At 12:00 hours on August 15: Behavioral shifts would be moderate; afternoon peak (4–6 PM) would show stronger effects as heat intensifies.

Mitigation Measures

- Congestion pricing: Not currently implemented in Phoenix metro; potential future measure to reduce vehicle traffic during peak hours.
- Low-emission zones: Not currently implemented in Phoenix; Arizona has adopted California emission standards but no specific geographic restrictions.
- Car-free zones: Limited implementation; downtown Phoenix has some pedestrian areas but car-free zones are not extensive.
- Electric bus deployment: Valley Metro has deployed some electric buses; expansion planned but current penetration is modest (~5–10% of fleet).
- Freight routing restrictions: Some restrictions on truck traffic during peak hours in downtown Phoenix; not comprehensive.
- Smart traffic management: APS and city of Phoenix have deployed smart traffic signal systems to optimize flow and reduce congestion; effectiveness is modest.
- Shaded transit stops: City of Phoenix has installed shade structures at some bus stops; expansion is ongoing but coverage is incomplete.
- Cool pavements: City has promoted cool pavement coatings; limited deployment to date.
- EV charging infrastructure: Growing network of public and private charging stations; supports EV adoption but current EV penetration remains low (~3–4% of vehicles).

Traffic Assessment at Given Datetime

- Date/Time: Thursday, August 15, 2024, 12:00 hours (midday, weekday).
- Traffic pattern: Moderate traffic; post-morning rush (peak 7–9 AM) but before afternoon rush (peak 4–6 PM). Vehicular waste heat load is elevated but not at peak intensity.
- Waste heat contribution: Estimated 40–60% of peak traffic-related waste heat at this time; afternoon rush would generate 100% (peak).

Sources:

- Federal Highway Administration (FHWA) traffic volume and vehicle emissions data
- U.S. Census Bureau American Community Survey (ACS) commute mode and transportation data
- Valley Metro bus and light rail ridership and operational data
- Arizona Department of Transportation (ADOT) traffic monitoring and incident data
- City of Phoenix transportation and sustainability reports
- General knowledge of vehicular waste heat, traffic patterns, and urban transportation dynamics

5. Seasonal Population Dynamics & Heat Demand

Population Variability

- Seasonal patterns: Phoenix experiences significant seasonal population fluctuations:
 - Winter (November–March): Influx of snowbirds (seasonal residents from northern states); population increases by estimated 10–15% during peak winter months (January–February).
 - Summer (June–August): Exodus of some residents to cooler climates; population decreases slightly, but many residents remain. Tourism declines significantly due to extreme heat.



- Spring (March–May) and Fall (September–October): Shoulder seasons with moderate population levels and tourism.
- Tourism: Phoenix is a major tourism destination, but summer tourism is minimal due to extreme heat; winter and spring are peak tourism seasons.
- University cycles: Arizona State University (ASU) and other universities have academic calendars; student population varies seasonally (lower during summer break).
- Seasonal labor: Agricultural and construction labor fluctuates seasonally; summer construction activity is reduced due to heat constraints.

Demand Translation: Population to Heat Load

- Winter (snowbird season): Increased population drives higher residential energy consumption (heating, hot water), increased traffic, increased commercial activity (retail, hospitality, dining). However, heating demand is modest in Phoenix winter (65–70°F typical daytime highs).
- Summer (peak heat season): Reduced population (some residents leave) but extreme heat drives peak cooling demand among remaining residents. Per-capita energy consumption is highest in summer due to AC load.
- Quantified effect: Estimated 10–15% increase in summer electricity demand during snowbird season (winter); estimated 5–10% decrease in summer electricity demand during summer exodus. However, summer peak demand is driven by extreme heat, not population increase.
- Traffic and waste heat: Snowbird season increases vehicle traffic and waste heat; summer exodus reduces traffic but extreme heat increases per-vehicle AC waste heat.

Current Season Assessment: August 15, 2024

- Season: Peak summer heat season (June–August); post-monsoon period (monsoon typically July–September in Arizona).
- Population status: Low-population season; many residents have left for cooler climates; snowbirds are absent. Resident population is reduced by estimated 5–10% from peak winter levels.
- Anthropogenic heat load implications: Reduced population would normally decrease energy demand and waste heat generation. However, this is overwhelmed by extreme heat driving peak cooling demand among remaining residents. Per-capita energy consumption is at annual maximum.
- Net effect: Total anthropogenic heat load (absolute) may be slightly lower than winter due to reduced population, but per-capita heat generation is at annual maximum due to extreme cooling demand.
- Grid stress: Peak summer demand is driven by extreme heat and cooling demand, not by population increase. August is typically one of the highest-demand months for electricity in Phoenix.

Weekend/Weekday & Time-of-Day Demand Variation

- Weekday pattern (Monday–Friday):
 - Morning (6:00–9:00 AM): Residential heating/cooling and appliance use; commute traffic; commercial buildings opening and HVAC activation.
 - Midday (9:00 AM–5:00 PM): Commercial energy consumption peaks; office buildings, retail, food service at full load; traffic moderate-to-heavy.
 - Evening (5:00–10:00 PM): Residential energy consumption peaks (cooking, cooling, appliances); commute traffic peaks (4–6 PM); commercial activity sustained.
 - Night (10:00 PM–6:00 AM): Reduced residential and commercial demand; baseline industrial load continues.
- Weekend pattern (Saturday–Sunday):
 - Morning/Midday: Residential demand elevated (people at home); retail and hospitality activity high; traffic lighter than weekday.
 - Evening: Residential and commercial demand sustained; entertainment and dining activity high; traffic moderate.
 - Night: Similar to weekday.
- Thursday, August 15, 2024, 12:00 hours: Weekday midday pattern applies. Commercial energy consumption is elevated; traffic is moderate; residential demand is baseline (occupants at work/school). Overall energy demand is elevated but not at peak (peak typically 4–8 PM).

Infrastructure & Policy Adjustments for Seasonal Demand Management



- Temporary cooling infrastructure: City of Phoenix operates cooling centers during extreme heat events; capacity is expanded as needed. Not a routine seasonal adjustment but an emergency response measure.
- Modified transit schedules: Valley Metro may adjust bus schedules seasonally to match demand; however, no major seasonal changes documented.
- Tourism-zone heat mitigation: Downtown Phoenix and tourist areas have some enhanced cooling infrastructure (fountains, shade structures, misting stations) but this is not systematically adjusted seasonally.
- Seasonal energy pricing: APS and SRP offer time-of-use (TOU) rates that vary seasonally; summer rates are higher to reflect peak demand, incentivizing conservation during summer.
- Demand response programs: Utilities activate demand response programs during extreme heat events; participation is voluntary but incentivized.
- Water management: Seasonal adjustments to irrigation and water use (reduced in summer due to scarcity and heat) indirectly affect cooling demand (less evaporative cooling from landscaping).

Alternative Demand Drivers: Weather-Driven Behavioral Changes & Holiday Patterns

- Weather-driven behavioral changes: Extreme heat (110°F+) drives behavioral shifts (increased AC use, reduced outdoor activity, shifted activity hours) that increase energy demand and waste heat generation independent of population changes.
- Holiday patterns: Winter holidays (November–December) increase retail activity and residential energy consumption; summer holidays (July 4th, Labor Day) have modest effects in Phoenix.
- School calendar: ASU and K–12 schools have summer breaks (June–August); reduced campus activity lowers energy demand on university and school campuses but increases residential demand (students at home).
- Monsoon season (July–September): Afternoon thunderstorms can reduce solar radiation and cooling demand temporarily; however, humidity increases, which can increase AC load (lower efficiency).

Sources:

- U.S. Census Bureau American Community Survey (ACS) and Decennial Census data on seasonal population changes
- Arizona tourism and hospitality industry data
- Arizona State University (ASU) enrollment and campus operations data
- Arizona Public Service (APS) and Salt River Project (SRP) seasonal demand data and reports
- City of Phoenix Office of Heat Response and Mitigation reports
- U.S. National Weather Service (NWS) climate and seasonal data for Phoenix
- General knowledge of seasonal population dynamics and energy demand patterns in hot climates

Summary & Key Findings

Critical Data Caveat: The provided reference temperature of 40.0°F is anomalously low for Phoenix in mid-August and does not reflect realistic conditions. Actual anthropogenic heat contributions at this location in August occur under significantly hotter baseline conditions (typical August 15 daytime high: ~112°F). The following summary addresses both the provided 40.0°F scenario and realistic August 15 conditions.

At Provided Temperature (40.0°F):

- Cooling demand: Baseline (no AC required).
- Energy system load: Winter-mode baseline or below; minimal grid stress.
- Traffic and vehicular waste heat: Moderate (midday Thursday pattern); waste heat load is elevated but not at peak.
- Industrial waste heat: Continuous baseline; no peak demand.
- Overall anthropogenic heat contribution: Low to moderate; not representative of August 15 conditions.

At Realistic August 15, 12:00 Hours Conditions (~100–105°F):

- Cooling demand: Peak (AC systems operating at maximum or near-maximum capacity).
- Energy system load: Upper-middle to peak demand range; grid approaching historically documented stress points. Peak stress would occur 4–8 PM.
- Traffic and vehicular waste heat: Moderate-to-elevated (midday Thursday pattern); afternoon rush (4–6 PM) would



generate peak waste heat.

- Industrial waste heat: Elevated and sustained; power generation, data centers, and commercial HVAC at high load.
- AC waste heat feedback loop: Significant contributor to ambient warming; estimated 1–2°F of nighttime urban warming attributable to AC waste heat in dense areas.
- Overall anthropogenic heat contribution: Very high; human-generated waste heat is a major factor in urban temperature elevation and grid stress during peak summer conditions.
- Vulnerable populations: Outdoor workers, homeless populations, and those without adequate cooling face severe heat stress; cooling infrastructure disparities exacerbate health inequities.

Key Anthropogenic Heat Drivers in Phoenix Metro:

- Air conditioning waste heat (largest single contributor during summer peak).
- Vehicular waste heat from car-dependent transportation system.
- Industrial and power generation waste heat (continuous baseline with peaks during high-demand periods).
- Commercial HVAC and refrigeration systems (retail, hospitality, food service).
- Data center waste heat (growing contributor).

Mitigation Opportunities:

- Increased EV adoption and fleet electrification (reduces vehicular waste heat).
- Transit-oriented development and increased public transit mode share (reduces vehicle traffic and waste heat).
- Building efficiency improvements and passive cooling strategies (reduces AC demand and waste heat).
- Waste heat recovery from data centers and industrial facilities (productive use of waste heat).
- Renewable energy expansion and battery storage (reduces thermal generation and grid stress).
- Urban forestry and green infrastructure (provides localized cooling; limited by water scarcity).
- Cooling infrastructure equity and emergency response (protects vulnerable populations during extreme heat).

All respondents consented to the use of their data as outlined in our "Privacy Policy" at the point of collection. [Privacy Policy](#)