

## 3.1\_100R

November 26, 2024

```
[ ]: import numpy as np
```

```
[8]: def pbc(x, y, L):  
    """  
    Function to enforce periodic boundary conditions on the positions.  
  
    Parameters  
    =====  
    x, y : Position.  
    L : Side of the squared arena.  
    """  
  
    outside_left = np.where(x < - L / 2)[0]  
    x[outside_left] = x[outside_left] + L  
  
    outside_right = np.where(x > L / 2)[0]  
    x[outside_right] = x[outside_right] - L  
  
    outside_up = np.where(y > L / 2)[0]  
    y[outside_up] = y[outside_up] - L  
  
    outside_down = np.where(y < - L / 2)[0]  
    y[outside_down] = y[outside_down] + L  
  
    return x, y
```

```
[9]: def replicas(x, y, L):  
    """  
    Function to generate replicas of a single particle.  
  
    Parameters  
    =====  
    x, y : Position.  
    L : Side of the squared arena.  
    """  
  
    xr = np.zeros(9)  
    yr = np.zeros(9)
```

```

for i in range(3):
    for j in range(3):
        xr[3 * i + j] = x + (j - 1) * L
        yr[3 * i + j] = y + (i - 1) * L

return xr, yr

```

```

[3]: def remove_overlap(x, y, R, L, dl, N_max_iter):
    """
    Function to remove the overlap between particles.
    Use the volume exclusion methods.
    If N_max_iter iterations are reached, then it stops.

    Parameters
    =====
    x, y : Positions.
    R : Particle radius.
    L : Dimension of the squared arena.
    dl : Tolerance on the overlap. Must be much smaller than R.
    N_max_iter : stops if the number of iterations is larger than this.
    """

    N_part = np.size(x)
    step = 0
    running = True

    while running:

        n_overlaps = 0

        for i in np.arange(N_part):
            for j in np.arange(i + 1, N_part):
                # Check overlap.
                dx = x[j] - x[i]
                dy = y[j] - y[i]
                dist = np.sqrt(dx ** 2 + dy ** 2)

                if dist < 2 * R - dl:
                    n_overlaps += 1 # Increment overlap counter.
                    # Remove overlap.
                    xm = 0.5 * (x[j] + x[i])
                    ym = 0.5 * (y[j] + y[i])
                    x[i] = xm - dx / dist * R
                    y[i] = ym - dy / dist * R
                    x[j] = xm + dx / dist * R
                    y[j] = ym + dy / dist * R

```

```

    step += 1

    if (step >= N_max_iter) or (n_overlaps == 0):
        running = False

    x, y = pbc(x, y, L) # Apply periodic boundary conditions.

    return x, y

```

```

[4]: from functools import reduce

def phoretic_velocity(x, y, R, v0, r_c, L):
    """
    Function to calculate the phoretic velocity.

    Parameters
    =====
    x, y : Positions.
    R : Particle radius.
    v0 : Phoretic reference velocity.
    r_c : Cut-off radius.
    L : Dimension of the squared arena.
    """

    N = np.size(x)

    vx = np.zeros(N) # Phoretic velocity (x component).
    vy = np.zeros(N) # Phoretic velocity (y component).

    # Preselect what particles are closer than r_c to the boundaries.
    replicas_needed = reduce(
        np.union1d, (
            np.where(y + r_c > L / 2)[0],
            np.where(y - r_c < - L / 2)[0],
            np.where(x + r_c > L / 2)[0],
            np.where(x - r_c > - L / 2)[0]
        )
    )

    for j in range(N - 1):

        # Check if replicas are needed to find the interacting neighbours.
        if np.size(np.where(replicas_needed == j)[0]):
            # Use replicas.
            xr, yr = replicas(x[j], y[j], L)
            for nr in range(9):
                dist2 = (x[j + 1:] - xr[nr]) ** 2 + (y[j + 1:] - yr[nr]) ** 2

```

```

nn = np.where(dist2 <= r_c ** 2)[0] + j + 1

# The list of nearest neighbours is set.
# Contains only the particles with index > j

if np.size(nn) > 0:
    nn = nn.astype(int)

    # Find interaction
    dx = x[nn] - xr[nr]
    dy = y[nn] - yr[nr]
    dist = np.sqrt(dx ** 2 + dy ** 2)
    v_p = v0 * R ** 2 / dist ** 2
    dvx = dx / dist * v_p
    dvy = dy / dist * v_p

    # Contribution for particle j.
    vx[j] += np.sum(dvx)
    vy[j] += np.sum(dvy)

    # Contribution for nn of particle j nr replica.
    vx[nn] -= dvx
    vy[nn] -= dvy

else:
    dist2 = (x[j + 1:] - x[j]) ** 2 + (y[j + 1:] - y[j]) ** 2
    nn = np.where(dist2 <= r_c ** 2)[0] + j + 1

    # The list of nearest neighbours is set.
    # Contains only the particles with index > j

    if np.size(nn) > 0:
        nn = nn.astype(int)

        # Find interaction
        dx = x[nn] - x[j]
        dy = y[nn] - y[j]
        dist = np.sqrt(dx ** 2 + dy ** 2)
        v_p = v0 * R ** 2 / dist ** 2
        dvx = dx / dist * v_p
        dvy = dy / dist * v_p

        # Contribution for particle j.
        vx[j] += np.sum(dvx)
        vy[j] += np.sum(dvy)

        # Contribution for nn of particle j.

```

```

        vx[nn] -= dvx
        vy[nn] -= dvy

    return vx, vy

```

## 0.1 L = 100 R

```

[ ]: N_part = 200 # Number of active Brownian particles.

R = 1e-6 # Radius of the Brownian particle [m].
eta = 1e-3 # Viscosity of the medium.
gamma = 6 * np.pi * R * eta # Drag coefficient.
gammaR = 8 * np.pi * R ** 3 * eta # Rotational drag coefficient.
kBT = 4.11e-21 # kB*T at room temperature [J].
D = kBT / gamma # Diffusion constant [m^2 / s].
DR = kBT / gammaR # Rotational diffusion constant [1 / s].
t_r = 1 / DR # Orientation relaxation time.
dt = 1e-2 # Time step [s].

v = 5e-6 # Self-propulsion speed [m/s].

v0 = 20e-6 # Phoretic reference speed [m/s].
r_c = 10 * R # Cut-off radius [m].

L = 100 * R # Side of the arena.

# Initialization.

# Random position.
x = (np.random.rand(N_part) - 0.5) * L # in [-L/2, L/2]
y = (np.random.rand(N_part) - 0.5) * L # in [-L/2, L/2]

# Random orientation.
phi = 2 * (np.random.rand(N_part) - 0.5) * np.pi # in [-pi, pi]

# Coefficients for the finite difference solution.
c_noise_x = np.sqrt(2 * D * dt)
c_noise_y = np.sqrt(2 * D * dt)
c_noise_phi = np.sqrt(2 * DR * dt)

```

The Kernel crashed while executing code in the current cell or a previous cell.

Please review the code in the cell(s) to identify a possible cause of the failure.

Click [here](\"https://aka.ms/vscodeJupyterKernelCrash\") for more info.

View Jupyter [log](\"command:jupyter.viewOutput\") for further details.

```
[ ]: import time
from scipy.constants import Boltzmann as kB
from tkinter import *
import os
import matplotlib.pyplot as plt

window_size = 600
vp = 2 * R # Length of the arrow indicating the velocity direction.
line_width = 1 # Width of the arrow line.
N_skip = 1

# Plot
diameter_pixel = 2 * R / L * window_size
s_mpl = (diameter_pixel / 2) ** 2

tk = Tk()
tk.geometry(f'{window_size + 20}x{window_size + 20}')
tk.configure(background='#000000')

canvas = Canvas(tk, background='#ECECEC') # Generate animation window
tk.attributes('-topmost', 0)
canvas.place(x=10, y=10, height=window_size, width=window_size)

particles = []
for j in range(N_part):
    particles.append(
        canvas.create_oval(
            (x[j] - R) / L * window_size + window_size / 2,
            (y[j] - R) / L * window_size + window_size / 2,
            (x[j] + R) / L * window_size + window_size / 2,
            (y[j] + R) / L * window_size + window_size / 2,
            outline='#808080',
            fill='#808080',
        )
    )

velocities = []
for j in range(N_part):
    velocities.append(
        canvas.create_line(
```

```

        x[j] / L * window_size + window_size / 2,
        y[j] / L * window_size + window_size / 2,
        (x[j] + vp * np.cos(phi[j])) / L * window_size + window_size / 2,
        (y[j] + vp * np.cos(phi[j])) / L * window_size + window_size / 2,
        width=line_width
    )
)

step = 0
target_time = [0, 5, 10, 20, 50]
N_steps = [int(t / dt) for t in target_time]

def stop_loop(event):
    global running
    running = False
tk.bind("<Escape>", stop_loop) # Bind the Escape key to stop the loop.
running = True # Flag to control the loop.
while running:

    # Calculate phoretic velocity.
    vp_x, vp_y = phoretic_velocity(x, y, R, v0, r_c, L)

    # Calculate new positions and orientations.
    nx = x + (v * np.cos(phi) + vp_x) * dt + c_noise_x * np.random.normal(0, 1, N_part)
    ny = y + (v * np.sin(phi) + vp_y) * dt + c_noise_y * np.random.normal(0, 1, N_part)
    nphi = phi + c_noise_phi * np.random.normal(0, 1, N_part)

    # Apply pbc.
    nx, ny = pbc(nx, ny, L)

    # Remove overlap.
    nx, ny = remove_overlap(nx, ny, R, L, dl=1e-8, N_max_iter=20)

    # Reflecting boundary conditions.
    nx, ny = pbc(nx, ny, L)

    # Update animation frame.
    if step % N_skip == 0:
        for j, particle in enumerate(particles):
            canvas.coords(
                particle,
                (nx[j] - R) / L * window_size + window_size / 2,
                (ny[j] - R) / L * window_size + window_size / 2,
                (nx[j] + R) / L * window_size + window_size / 2,
                (ny[j] + R) / L * window_size + window_size / 2,

```

```

    )

    for j, velocity in enumerate(velocities):
        canvas.coords(
            velocity,
            nx[j] / L * window_size + window_size / 2,
            ny[j] / L * window_size + window_size / 2,
            (nx[j] + vp * np.cos(nphi[j])) / L * window_size + window_size /
↪ 2,
            (ny[j] + vp * np.sin(nphi[j])) / L * window_size + window_size /
↪ 2,
        )

    tk.title(f'Time {step * dt:.1f} - Iteration {step}')
    #print(f'TK: step={step}, nx[1]={nx[1]}')
    tk.update_idletasks()
    tk.update()
    time.sleep(.001) # Increase to slow down the simulation.

    if step in N_steps:
        #print(f'Mt: step={step}, nx[1]={nx[1]}')
        print(f'step = {step}, image saved.')
        plt.figure(figsize=(window_size / 100, window_size / 100))
        plt.scatter(nx, ny, c="gray", s=s_mpl, alpha=0.8, label="Particles")
        plt.quiver(
            nx, ny, #
            vp * np.cos(nphi), vp * np.sin(nphi), #
            angles="xy", scale_units="xy", scale=0.9, #
            color="red", alpha=0.8
        )
        plt.title(f"Step: {step}, Time: {step * dt:.2f}")
        plt.xlim(-L / 2, L / 2)
        plt.ylim(-L / 2, L / 2)
        plt.gca().set_aspect("equal", adjustable="box")
        plt.savefig(f"frame_{step}.png")
        plt.close()
        step += 1
        x[:] = nx[:]
        y[:] = ny[:]
        phi[:] = nphi[:]

    #
    if step >= (max(N_steps)+1) :
        running = False

tk.update_idletasks()

```



```
tk.update()
tk.mainloop() # Release animation handle (close window to finish).
```

```
step = 0, image saved.
step = 500, image saved.
step = 1000, image saved.
step = 2000, image saved.
```

```
2024-11-24 21:05:53.913 Python[6531:400168] +[IMKClient subclass]: chose
IMKClient_Legacy
```

```
2024-11-24 21:05:53.913 Python[6531:400168] +[IMKInputSession subclass]: chose
IMKInputSession_Legacy
```

```
step = 5000, image saved.
```