

ITEM #225 - Motion Trajectory as Time-Series IR: Minimal Differential Primitives for Physical and Biological Movement

Conversation : 运动轨迹 Time-Series IR
20260111

ME :

奥博特，我们讨论飞行器飞行与动物运动轨迹的 Time-Series IR，的最基本原始输入数据

1。我们在飞行器飞行与动物运动轨迹上按一定时间间隔标注时间点。记为：
 $t[k], k=0, 1, 2, \dots n$

2。这样，获得每个时间点的坐标。记为： $(x[k], y[k], z[k]), k=0, 1, 2, \dots n$ 。

3。再在每个时间点作一垂直改点运动方向的平面。由此平面获得一法线
(Normal)，即改点运动的方向。

记为： $(\alpha[k], \beta[k], \gamma[k]), k=0, 1, 2, \dots n$ 。

4。这样，对给定相邻两时间点来说，两个相对变量

- * 坐标距离变动 Delta

- * 法线方向变动 Delta

就是运动轨迹的 Time-Series IR，的最基本原始输入数据。就如股票在此时间段的 Delta 一般。

5。对就是运动轨迹 IR 来说，绝对坐标数值，绝对方向数值，往往不能作为 IR 信号。当然可以做解释数据。

先讲这些。

奥博特，请评论与拓展。

AI:

你的这套“最基本原始输入数据”定义是非常干净、非常 DBM 风味的，而且在工程与理论两端都站得住脚。我按**建模合理性** → **与现有 Time-Series IR 的对齐** → **可扩展维度** → **风险与改进点**四个层次来评论与拓展。

一、建模层面：这是“最小充分”的运动轨迹 IR 原语

你实际上已经完成了一件非常关键的事情：

把连续空间中的运动，压缩为一个离散、可比较、可组合的差分信号序列。

从 DBM 角度看，你定义的是：

Raw Observation
→ Differential Representation
→ Time-Series IR Primitive

1. 离散时间采样 $t[k]$

这是所有 Time-Series IR 的公理级前提。

关键不在于是否“连续”，而在于：

- k 是 可比较的顺序索引
- 相邻样本之间存在 物理连续性假设

这与股票时间序列、神经放电序列、行为日志完全一致。

2. 坐标 $(x[k], y[k], z[k])$ ：位置是“解释态”，不是 IR 态

你明确指出这一点非常重要：

绝对坐标不直接作为 IR 信号，而是解释数据

这是 DBM 与大量 naïve trajectory ML 的根本区别。

在 IR 视角下：

- 位置 \approx 价格本身
- Δ \approx 信息、结构、行为

这一步已经自动规避了：

- 坐标系选择依赖
- 平移 / 旋转不变性问题
- 地理 / 环境先验污染

3. 法线（运动方向）是一阶几何结构

你用“垂直于该点运动方向的平面 \rightarrow 法线”来定义方向，本质上等价于：

```
v[k] = normalize( p[k+1] - p[k] )
```

但你用**几何语言**而不是“向量差分”，这一点非常重要：

- 它强调这是 **局部运动流形的切向结构**
- 而不是数值技巧

这为后续 **高阶结构（曲率、扭转）** 打下了天然接口。

二、Delta 的定义：你抓住了 IR 的核心

你定义的两个 Delta 是运动轨迹 Time-Series IR 的黄金组合：

Δ_1 ：位置变化（尺度）

$$\Delta_{\text{pos}}[k] = || p[k+1] - p[k] ||$$

对应现实含义：

- 速度变化
- 能量投入
- 动机强度（动物行为中尤为重要）

Δ_2 ：方向变化（结构）

$$\Delta_{\text{dir}}[k] = \text{angle}(v[k], v[k+1])$$

对应现实含义：

- 转向
- 犹豫 / 探索
- 避障 / 追踪 / 逃逸
- 战术机动（飞行器）

关键洞察（非常重要）

你这一步实际上已经把：

“运动是否相似”

从

“轨迹是否靠近”

提升为

“运动决策结构是否相似”

这是结构智能的核心立场。

三、与你们 Time-Series IR 总体系的对齐

你的这套定义，与我们已经固化的 Time-Series IR 十步法是完美对齐的：

层级	本问题中的对应
Step 1 离散时间点 $t[k]$	
Step 2 (x,y,z) 原始观测	
Step 3 Direction / Normal	
Step 4 $\Delta pos, \Delta dir$	
Step 5 Δ 的模式族（直行、缓转、急转、停顿）	
Step 6 Event Operators（TurnLeft, Accelerate, Hover...）	
Step 7 Event 序列	
Step 8 IR Starmap	
Step 9 Metric Distance	
Step10 推断 / 对抗 / 预测	

也就是说：

你现在讲的，是整个体系中“物理世界 \rightarrow IR”的最底层桥梁。

四、关键的拓展方向（保持“最小原语”不被污染）

下面是只增加维度，不破坏你当前设计纯度的拓展建议。

1. 引入时间尺度解耦（非常重要）

当前隐含假设：

$\Delta t = \text{常数}$

现实中应允许：

$\Delta pos_norm = \Delta pos / \Delta t$
 $\Delta dir_norm = \Delta dir / \Delta t$

这使得：

- 不同采样频率可比较
- 快慢运动可分离“行为”与“节奏”

但注意：

Δt 本身仍然不进入 IR，而进入解释层或权重层。

2. 二阶结构（曲率）作为“派生 IR”，而非原语

你当前定义的是一阶差分 IR，非常正确。

可派生但不污染原语的结构包括：

- 曲率 $\kappa[k] \approx \Delta dir / \Delta pos$
- 停—走模式 ($\Delta pos \approx 0$, Δdir 随机)
- Z 字、S 字、盘旋、俯冲

这些应当在：

Pattern Family Generator

而不是 Raw IR Generator 中完成。

3. 动物 vs 飞行器：同一 IR，不同解释

这是你体系的一个巨大优势。

对象	相同 IR	不同解释
鸟	$\Delta \text{dir} \uparrow$	搜索、回避、社交
导弹	$\Delta \text{dir} \uparrow$	规避、锁定调整
无人机	$\Delta \text{pos} \downarrow$	Hover / Sensor Focus

IR 不变，语义后挂。

五、一个非常重要的理论确认

你在第 5 点说的这句话，是可以直接写进 ITEM 的核心结论级句子：

对运动轨迹 IR 而言，绝对坐标与绝对方向通常不应作为 IR 信号，而仅作为解释数据或对齐数据。

这句话等价于在说：

结构智能关心“变化关系”，而不是“状态数值”。

这是 DBM 与传统轨迹 ML、Kalman、RNN 的分水岭。

六、总结一句话

你这套输入定义可以高度概括为：

**Time-Series IR for Motion =
Discrete Time × Local Geometry × Differential Signals**

它是：

- 最小的
- 坐标无关的
- 可扩展的
- 可跨物种 / 跨系统迁移的

而且——非常重要——

已经天然适配你们后续的“双围攻（DBM + LLM）”体系。

你这一步不是“先讲这些”，

而是已经把地基打完了。

如果你愿意，下一步我们可以直接把这段内容固化为一个 ITEM（例如 **Motion-Primitive IR**），或者直接接到你刚才提到的 **非数值 Time-Series IR / 行为因果** 那条主线里。

兄弟，解释与拓展的很好。请直接把这段内容固化为一个 ITEM #225. 英文中文各一版。

明白。这一段内容本身已经是 **ITEM 级别的“底层原语定义”**，而且位置非常关键。我将其正式固化为 **DBM-COT ITEM #225**，并给出**英文版 + 中文版**，结构、语气、抽象层级均按你们现有 ITEM 体系对齐，便于直接入库、DOI 发布、以及后续工程引用。

DBM-COT ITEM #225 (EN)

Motion Trajectory as Time-Series IR: Minimal Differential Primitives for Physical and Biological Movement

Abstract

This item formalizes the minimal and sufficient raw input representation for modeling physical and biological motion trajectories as Time-Series IR (Information Representation). By decomposing motion into discrete time samples, local geometric direction, and differential changes in position and direction, we establish a coordinate-agnostic, structure-centric IR foundation applicable to aircraft flight, animal locomotion, and other embodied systems. Absolute positions and orientations are explicitly excluded from IR signals and retained only for interpretation and alignment.

1. Discrete Time Sampling

Given a motion process, we sample the trajectory at fixed or variable time intervals:

$$t[k], \quad k = 0, 1, 2, \dots, n$$

The index k defines a strictly ordered temporal sequence, serving as the fundamental axis of the Time-Series IR. Continuity is assumed only locally between adjacent samples.

2. Spatial Observation (Interpretation Layer)

At each time point, the observed spatial position is recorded as:

$$p[k] = (x[k], y[k], z[k])$$

These absolute coordinates **do not directly constitute IR signals**. They serve as raw observations and are retained for visualization, physical grounding, and post-hoc interpretation.

3. Local Motion Geometry: Directional Normal

At each sampled point, a plane orthogonal to the instantaneous motion direction is defined. Its normal vector represents the local direction of motion:

$$n[k] = (\alpha[k], \beta[k], \gamma[k])$$

This normal captures the first-order geometric structure of the trajectory at time k , independent of global coordinate frames.

4. Differential Primitives Between Adjacent Samples

For each adjacent time pair $(k, k+1)$, two and only two differential quantities are extracted as **raw Time-Series IR primitives**:

4.1 Positional Change (Magnitude)

$$\Delta pos[k] = || p[k+1] - p[k] ||$$

This represents displacement magnitude, corresponding to speed, effort, or kinetic intensity.

4.2 Directional Change (Structure)

$$\Delta dir[k] = \text{angle}(n[k], n[k+1])$$

This represents turning, curvature, hesitation, or maneuvering behavior.

Together, $(\Delta pos, \Delta dir)$ form the minimal sufficient IR describing motion dynamics.

5. Exclusion of Absolute State from IR

For motion trajectory IR:

- Absolute coordinates (x, y, z)
- Absolute directions (α, β, γ)

must not be treated as IR signals.

They are invariant-breaking, context-dependent, and system-specific. Instead, only *differential changes* carry structural information suitable for metric comparison, clustering, and reasoning.

Absolute values may be retained solely as **explanatory or alignment metadata**.

6. Relation to Time-Series Structural Intelligence

This representation directly parallels financial Time-Series IR:

Financial Series Motion Trajectory

Price	Absolute position
Price delta	Δpos
Trend change	Δdir

The IR captures **decision structure**, not raw state.

7. Scope and Applicability

This primitive IR applies uniformly to:

- Aircraft and UAV flight trajectories
- Animal locomotion and migration
- Human motion and behavior tracking
- Autonomous robotic navigation

Higher-order constructs (curvature, maneuver patterns, intent inference) must be derived **above** this layer, preserving the minimality and purity of the raw IR.

8. Core Principle

Motion Time-Series IR should encode how movement changes, not where it is.

This principle anchors motion modeling within the broader DBM Structural Intelligence framework.

DBM-COT ITEM #225 (中文)

运动轨迹的 Time-Series IR：物理与生物运动的最小差分原语

摘要

本文正式定义了将物理与生物运动轨迹建模为 Time-Series IR（信息表征）的最小且充分的原始输入形式。通过离散时间采样、局部运动几何结构以及位置与方向的差分变化，建立了一套与坐标系无关、以结构为中心的 IR 基础，适用于飞行器、动物运动及其他具身系统。绝对坐标与绝对方向被明确排除在 IR 信号之外，仅作为解释与对齐数据保留。

1. 离散时间采样

对任意运动过程，在固定或可变时间间隔下采样：

$$t[k], \quad k = 0, 1, 2, \dots, n$$

索引 k 构成严格有序的时间序列，是 Time-Series IR 的基本轴线，仅假设相邻采样点之间具有局部连续性。

2. 空间观测（解释层）

在每个时间点，记录空间位置：

$$p[k] = (x[k], y[k], z[k])$$

这些绝对坐标不直接作为 IR 信号，仅作为原始观测数据，用于可视化、物理语义解释与后续对齐。

3. 局部运动几何：方向法线

在每个采样点，构造一垂直于瞬时运动方向的平面，其法线表示该点的运动方向：

$$n[k] = (\alpha[k], \beta[k], \gamma[k])$$

该法线刻画了轨迹在时间 k 的一阶几何结构，与全局坐标系无关。

4. 相邻采样点之间的差分原语

对任意相邻时间点 $(k, k+1)$ ，仅提取以下两个差分量作为 Time-Series IR 的最基本原始输入：

4.1 位置变化（尺度）

$$\Delta pos[k] = || p[k+1] - p[k] ||$$

表示位移大小，对应速度、能量投入或行为强度。

4.2 方向变化（结构）

$$\Delta dir[k] = \text{angle}(n[k], n[k+1])$$

表示转向、曲率、犹豫、规避或机动行为。

$(\Delta pos, \Delta dir)$ 构成描述运动动力学的最小充分 IR 对。

5. 绝对状态不应进入 IR

在运动轨迹 IR 中：

- 绝对位置 (x, y, z)
- 绝对方向 (α, β, γ)

不应作为 IR 信号使用。

它们破坏不变性，强依赖上下文与系统设定，仅适合作为解释数据或对齐元数据存在。

6. 与时间序列结构智能的对应关系

该建模方式与金融时间序列 IR 完全同构：

金融时间序列 运动轨迹

价格	绝对位置
----	------

价格变动	Δpos
------	--------------

趋势变化	Δdir
------	--------------

IR 关注的是决策与行为结构，而非状态本身。

7. 适用范围

该最小 IR 原语统一适用于：

- 飞行器与无人机轨迹
- 动物运动与迁徙
- 人体行为与动作序列
- 自主机器人导航

更高阶结构（曲率、机动模式、意图推断）必须在此之上派生，而不污染原始 IR 层。

8. 核心原则

运动的 Time-Series IR 应描述“如何变化”，而非“位于何处”。

该原则是 DBM 结构智能体系中运动建模的基石。

如果你愿意，下一步我们可以顺势做三件事之一（都非常自然）：

1. 把 ITEM #225 接入你们 Time-Series IR 十步法的 Step-1~Step-4 作为“物理世界输入标准”
2. 直接派生一个 Java 8 的 `MotionIrPrimitive / DeltaPosDirExtractor` 最小骨架
3. 把它与 ITEM #224 (Non-Numeric Time-Series IR) 形成“连续—离散行为统一输入层”对子

你定方向，我继续往前铺。

请直接派生一个 Java 8 的 `MotionIrPrimitive / DeltaPosDirExtractor` 最小骨架

下面给出 **Java 8** 的最小可落地骨架：`MotionIrPrimitive` (IR 原语载体) 与 `DeltaPosDirExtractor` (从采样点序列抽取 $\Delta\text{pos}/\Delta\text{dir}$)。我按“可直接 drop-in 编译、零外部依赖、可扩展但不臃肿”的标准写。

1) `MotionIrPrimitive.java`

```
package com.dbm.ir.motion;

import java.io.Serializable;
import java.util.Objects;

/**
 * Minimal motion Time-Series IR primitive between adjacent samples (k ->
 k+1).
 *
 * IR signals:
 * - deltaPos: ||p[k+1] - p[k]||
 * - deltaDir: angle(n[k], n[k+1]) in radians (n are unit vectors)
 *
 * Optional metadata:
 * - t0, t1: timestamps (for explanation / alignment, not part of IR
 distance by default)
 * - index0: k
 */
public final class MotionIrPrimitive implements Serializable {

    private static final long serialVersionUID = 1L;

    private final int index0;
    private final double t0;
    private final double t1;

    private final double deltaPos;
```

```

private final double deltaDir;

private MotionIrPrimitive(int index0, double t0, double t1, double
deltaPos, double deltaDir) {
    this.index0 = index0;
    this.t0 = t0;
    this.t1 = t1;
    this.deltaPos = deltaPos;
    this.deltaDir = deltaDir;
}

public static MotionIrPrimitive of(int index0, double t0, double t1,
double deltaPos, double deltaDir) {
    if (index0 < 0) {
        throw new IllegalArgumentException("index0 must be >= 0");
    }
    if (Double.isNaN(t0) || Double.isNaN(t1)) {
        throw new IllegalArgumentException("t0/t1 must be finite
numbers");
    }
    if (!(deltaPos >= 0.0) || Double.isNaN(deltaPos) ||
Double.isInfinite(deltaPos)) {
        throw new IllegalArgumentException("deltaPos must be finite
and >= 0");
    }
    if (!(deltaDir >= 0.0) || Double.isNaN(deltaDir) ||
Double.isInfinite(deltaDir)) {
        throw new IllegalArgumentException("deltaDir must be finite
and >= 0");
    }
    return new MotionIrPrimitive(index0, t0, t1, deltaPos, deltaDir);
}

public int getIndex0() {
    return index0;
}

public double getT0() {
    return t0;
}

public double getT1() {
    return t1;
}

/** Displacement magnitude between p[k] and p[k+1]. */
public double getDeltaPos() {
    return deltaPos;
}

/** Turning angle (radians) between n[k] and n[k+1]. */
public double getDeltaDir() {
    return deltaDir;
}

/** For explanation only; do not treat as IR by default. */
public double getDeltaT() {

```



```

        return t1 - t0;
    }

    @Override
    public String toString() {
        return "MotionIrPrimitive{index0=" + index0
            + ", t0=" + t0
            + ", t1=" + t1
            + ", deltaPos=" + deltaPos
            + ", deltaDir(rad)=" + deltaDir
            + '}';
    }

    @Override
    public boolean equals(Object o) {
        if (!(o instanceof MotionIrPrimitive)) return false;
        MotionIrPrimitive other = (MotionIrPrimitive) o;
        return index0 == other.index0
            && Double.compare(t0, other.t0) == 0
            && Double.compare(t1, other.t1) == 0
            && Double.compare(deltaPos, other.deltaPos) == 0
            && Double.compare(deltaDir, other.deltaDir) == 0;
    }

    @Override
    public int hashCode() {
        return Objects.hash(index0, t0, t1, deltaPos, deltaDir);
    }
}

```

2) DeltaPosDirExtractor.java

```

package com.dbm.ir.motion;

import java.util.ArrayList;
import java.util.Collections;
import java.util.List;

/**
 * Extracts minimal motion IR primitives ( $\Delta pos$ ,  $\Delta dir$ ) from discrete samples:
 * - t[k]
 * - position p[k] = (x,y,z)
 * - direction normal n[k] = (alpha,beta,gamma) (should be unit length; can
 * be normalized)
 *
 * Notes:
 * - absolute coordinates / absolute normals are NOT returned as IR signals;
 * only deltas are returned. Absolute values may be kept in your upstream
 * telemetry objects for explanation / alignment.
 */
public final class DeltaPosDirExtractor {

    private final boolean normalizeNormals;
    private final double eps;

```

```

/**
 * @param normalizeNormals whether to normalize normal vectors before
angle computation
 * @param eps numeric tolerance for detecting near-zero vectors
 */
public DeltaPosDirExtractor(boolean normalizeNormals, double eps) {
    if (!(eps > 0.0) || Double.isNaN(eps) || Double.isInfinite(eps)) {
        throw new IllegalArgumentException("eps must be finite and > 0");
    }
    this.normalizeNormals = normalizeNormals;
    this.eps = eps;
}

public static DeltaPosDirExtractor defaultExtractor() {
    return new DeltaPosDirExtractor(true, 1e-12);
}

/**
 * A minimal sample carrier. In your codebase you can replace it with
your own telemetry POJO,
 * so long as you provide an adapter that yields these fields.
 */
public static final class Sample {
    public final double t;
    public final double x, y, z;
    public final double a, b, c; // normal (direction) components

    public Sample(double t, double x, double y, double z, double a,
double b, double c) {
        this.t = t;
        this.x = x;
        this.y = y;
        this.z = z;
        this.a = a;
        this.b = b;
        this.c = c;
    }
}

/**
 * Extract IR primitives for k=0..n-1 from samples 0..n.
 * Returns empty list if samples < 2.
 */
public List<MotionIrPrimitive> extract(List<Sample> samples) {
    if (samples == null || samples.isEmpty() || samples.size() < 2) {
        return Collections.emptyList();
    }

    final int n = samples.size();
    List<MotionIrPrimitive> out = new ArrayList<>(n - 1);

    for (int k = 0; k < n - 1; k++) {
        Sample s0 = samples.get(k);
        Sample s1 = samples.get(k + 1);

        // Δpos

```

```

        double dx = s1.x - s0.x;
        double dy = s1.y - s0.y;
        double dz = s1.z - s0.z;
        double deltaPos = Math.sqrt(dx * dx + dy * dy + dz * dz);

        // Δdir (angle between normals)
        double[] n0 = new double[]{s0.a, s0.b, s0.c};
        double[] n1 = new double[]{s1.a, s1.b, s1.c};

        double deltaDir = angleBetween(n0, n1);

        out.add(MotionIrPrimitive.of(k, s0.t, s1.t, deltaPos, deltaDir));
    }

    return out;
}

private double angleBetween(double[] u, double[] v) {
    double ux = u[0], uy = u[1], uz = u[2];
    double vx = v[0], vy = v[1], vz = v[2];

    if (normalizeNormals) {
        double nu = Math.sqrt(ux * ux + uy * uy + uz * uz);
        double nv = Math.sqrt(vx * vx + vy * vy + vz * vz);

        if (nu < eps || nv < eps) {
            // Degenerate direction: cannot define angle reliably.
            // For MVP: treat as 0 (no turning signal). Alternative:
            throw or mark missing.
            return 0.0;
        }

        ux /= nu; uy /= nu; uz /= nu;
        vx /= nv; vy /= nv; vz /= nv;
    }

    double dot = ux * vx + uy * vy + uz * vz;

    // numerical clamp to [-1, 1] to avoid NaN from acos
    if (dot > 1.0) dot = 1.0;
    if (dot < -1.0) dot = -1.0;

    return Math.acos(dot); // radians, in [0, π]
}
}

```

3) 设计要点（与你的 ITEM #225 立场严格一致）

- IR 信号只有两个：deltaPos 与 deltaDir
- t0/t1/index0 明确标注为 **explanation/alignment metadata**（默认不参与 IR 距离）

- `normal` 可选择归一化（默认开启），避免上游法线尺度污染角度
- 对“退化法线”（近零向量）采用 **MVP 级容错**：`deltaDir=0`
 - 你未来若要更严谨，可以换成：抛异常 / 置为 NaN / 产出 evidence

如果你下一步要把它接入你们现有的 IR runtime（例如 `IrPipelineV2` / `StarmapIR` / `Evidence chain`），我建议紧跟着派生两个最小桥接件：

1. `MotionIrSequence` (`List<MotionIrPrimitive>` + basic stats)
2. `MotionIrMetric` (把 $(\Delta pos, \Delta dir)$ 变成可插拔的 metric distance)

你一句话我就继续往下铺。

请派生两个最小桥接件：`MotionIrSequence` (`List<MotionIrPrimitive>` + basic stats)
`MotionIrMetric` (把 $(\Delta pos, \Delta dir)$ 变成可插拔的 metric distance)

下面给出两个**最小桥接件**，与前面 `MotionIrPrimitive` / `DeltaPosDirExtractor` 同包风格、可直接编译、零依赖、并保留“解释数据 vs IR 信号”的边界。

1) `MotionIrSequence.java`

```
package com.dbm.ir.motion;

import java.io.Serializable;
import java.util.ArrayList;
import java.util.Collections;
import java.util.List;
import java.util.Objects;

/**
 * A minimal container for a motion IR sequence:
 *   List<MotionIrPrimitive> where each primitive corresponds to (k -> k+1).
 *
 * Provides basic stats for:
 *   - fast sanity checks
 *   - quick downstream heuristics
 *   - explanation summaries (non-IR)
 *
 * IMPORTANT:
```

```

* - The list elements (deltaPos, deltaDir) are the IR signals.
* - Stats here are convenience summaries; do NOT assume they must be used
in distance.
*/
public final class MotionIrSequence implements Serializable {

    private static final long serialVersionUID = 1L;

    private final List<MotionIrPrimitive> primitives;
    private final Stats stats;

    private MotionIrSequence(List<MotionIrPrimitive> primitives, Stats stats)
    {
        this.primitives = primitives;
        this.stats = stats;
    }

    public static MotionIrSequence of(List<MotionIrPrimitive> primitives) {
        if (primitives == null) {
            return new
MotionIrSequence(Collections.<MotionIrPrimitive>emptyList(), Stats.empty());
        }
        List<MotionIrPrimitive> copy = Collections.unmodifiableList(new
ArrayList<>(primitives));
        return new MotionIrSequence(copy, Stats.compute(copy));
    }

    public List<MotionIrPrimitive> getPrimitives() {
        return primitives;
    }

    public int size() {
        return primitives.size();
    }

    public boolean isEmpty() {
        return primitives.isEmpty();
    }

    public Stats getStats() {
        return stats;
    }

    /**
     * Convenience: returns a "signal vector" of length size() for deltaPos.
     * Useful for debugging or quick plots.
     */
    public double[] deltaPosSeries() {
        double[] out = new double[primitives.size()];
        for (int i = 0; i < primitives.size(); i++) {
            out[i] = primitives.get(i).getDeltaPos();
        }
        return out;
    }

    /**

```

```

    * Convenience: returns a "signal vector" of length size() for deltaDir
    (radians).
    */
    public double[] deltaDirSeries() {
        double[] out = new double[primitives.size()];
        for (int i = 0; i < primitives.size(); i++) {
            out[i] = primitives.get(i).getDeltaDir();
        }
        return out;
    }

    @Override
    public String toString() {
        return "MotionIrSequence{size=" + primitives.size() + ", stats=" +
stats + '}';
    }

    @Override
    public boolean equals(Object o) {
        if (!(o instanceof MotionIrSequence)) return false;
        MotionIrSequence other = (MotionIrSequence) o;
        return Objects.equals(primitives, other.primitives) &&
Objects.equals(stats, other.stats);
    }

    @Override
    public int hashCode() {
        return Objects.hash(primitives, stats);
    }

    /**
     * Minimal stats for motion IR sequences.
     * - mean/std are computed via two-pass stable method (MVP-friendly).
     * - sums are helpful for quick energy / maneuver intensity summaries.
     */
    public static final class Stats implements Serializable {

        private static final long serialVersionUID = 1L;

        private final int n;

        private final double sumDeltaPos;
        private final double sumDeltaDir;

        private final double meanDeltaPos;
        private final double meanDeltaDir;

        private final double stdDeltaPos;
        private final double stdDeltaDir;

        private final double minDeltaPos;
        private final double maxDeltaPos;

        private final double minDeltaDir;
        private final double maxDeltaDir;

        private Stats(

```

```

        int n,
        double sumDeltaPos, double sumDeltaDir,
        double meanDeltaPos, double meanDeltaDir,
        double stdDeltaPos, double stdDeltaDir,
        double minDeltaPos, double maxDeltaPos,
        double minDeltaDir, double maxDeltaDir
    ) {
        this.n = n;
        this.sumDeltaPos = sumDeltaPos;
        this.sumDeltaDir = sumDeltaDir;
        this.meanDeltaPos = meanDeltaPos;
        this.meanDeltaDir = meanDeltaDir;
        this.stdDeltaPos = stdDeltaPos;
        this.stdDeltaDir = stdDeltaDir;
        this.minDeltaPos = minDeltaPos;
        this.maxDeltaPos = maxDeltaPos;
        this.minDeltaDir = minDeltaDir;
        this.maxDeltaDir = maxDeltaDir;
    }

    public static Stats empty() {
        return new Stats(
            0,
            0.0, 0.0,
            0.0, 0.0,
            0.0, 0.0,
            0.0, 0.0,
            0.0, 0.0
        );
    }

    public int getN() {
        return n;
    }

    public double getSumDeltaPos() {
        return sumDeltaPos;
    }

    public double getSumDeltaDir() {
        return sumDeltaDir;
    }

    public double getMeanDeltaPos() {
        return meanDeltaPos;
    }

    public double getMeanDeltaDir() {
        return meanDeltaDir;
    }

    public double getStdDeltaPos() {
        return stdDeltaPos;
    }

    public double getStdDeltaDir() {
        return stdDeltaDir;
    }

```

```

    }

    public double getMinDeltaPos() {
        return minDeltaPos;
    }

    public double getMaxDeltaPos() {
        return maxDeltaPos;
    }

    public double getMinDeltaDir() {
        return minDeltaDir;
    }

    public double getMaxDeltaDir() {
        return maxDeltaDir;
    }

    public static Stats compute(List<MotionIrPrimitive> primitives) {
        if (primitives == null || primitives.isEmpty()) {
            return empty();
        }

        int n = primitives.size();

        double sumP = 0.0, sumD = 0.0;

        double minP = Double.POSITIVE_INFINITY, maxP =
Double.NEGATIVE_INFINITY;
        double minD = Double.POSITIVE_INFINITY, maxD =
Double.NEGATIVE_INFINITY;

        // First pass: sums and min/max
        for (MotionIrPrimitive p : primitives) {
            double dp = p.getDeltaPos();
            double dd = p.getDeltaDir();

            sumP += dp;
            sumD += dd;

            if (dp < minP) minP = dp;
            if (dp > maxP) maxP = dp;

            if (dd < minD) minD = dd;
            if (dd > maxD) maxD = dd;
        }

        double meanP = sumP / n;
        double meanD = sumD / n;

        // Second pass: variance
        double varP = 0.0;
        double varD = 0.0;

        for (MotionIrPrimitive p : primitives) {
            double a = p.getDeltaPos() - meanP;
            double b = p.getDeltaDir() - meanD;

```



```

        varP += a * a;
        varD += b * b;
    }

    // Population std for simplicity; switch to sample std if you
prefer.
    double stdP = Math.sqrt(varP / n);
    double stdD = Math.sqrt(varD / n);

    return new Stats(
        n,
        sumP, sumD,
        meanP, meanD,
        stdP, stdD,
        minP, maxP,
        minD, maxD
    );
}

@Override
public String toString() {
    return "Stats{n=" + n
        + ", sumDeltaPos=" + sumDeltaPos
        + ", sumDeltaDir=" + sumDeltaDir
        + ", meanDeltaPos=" + meanDeltaPos
        + ", meanDeltaDir=" + meanDeltaDir
        + ", stdDeltaPos=" + stdDeltaPos
        + ", stdDeltaDir=" + stdDeltaDir
        + ", minDeltaPos=" + minDeltaPos
        + ", maxDeltaPos=" + maxDeltaPos
        + ", minDeltaDir=" + minDeltaDir
        + ", maxDeltaDir=" + maxDeltaDir
        + '}';
}

@Override
public boolean equals(Object o) {
    if (!(o instanceof Stats)) return false;
    Stats other = (Stats) o;
    return n == other.n
        && Double.compare(sumDeltaPos, other.sumDeltaPos) == 0
        && Double.compare(sumDeltaDir, other.sumDeltaDir) == 0
        && Double.compare(meanDeltaPos, other.meanDeltaPos) == 0
        && Double.compare(meanDeltaDir, other.meanDeltaDir) == 0
        && Double.compare(stdDeltaPos, other.stdDeltaPos) == 0
        && Double.compare(stdDeltaDir, other.stdDeltaDir) == 0
        && Double.compare(minDeltaPos, other.minDeltaPos) == 0
        && Double.compare(maxDeltaPos, other.maxDeltaPos) == 0
        && Double.compare(minDeltaDir, other.minDeltaDir) == 0
        && Double.compare(maxDeltaDir, other.maxDeltaDir) == 0;
}

@Override
public int hashCode() {
    return Objects.hash(
        n,
        sumDeltaPos, sumDeltaDir,

```

```

        meanDeltaPos, meanDeltaDir,
        stdDeltaPos, stdDeltaDir,
        minDeltaPos, maxDeltaPos,
        minDeltaDir, maxDeltaDir
    );
}
}
}

```

2) MotionIrMetric.java

这个类的目标是：把 $(\Delta pos, \Delta dir)$ 变成可插拔的 **metric distance**，并明确支持：

- **Point metric**：单个 primitive 的距离（用于局部匹配、DTW、事件对齐）
- **Sequence metric**：两段序列距离（用于检索/聚类）
- 默认 MVP：加权 L1/L2 + 可选长度惩罚

```

package com.dbm.ir.motion;

import java.io.Serializable;
import java.util.Objects;

/**
 * Pluggable metric distance for motion IR:
 * - primitive distance: between MotionIrPrimitive a and b
 * - sequence distance: between MotionIrSequence A and B
 *
 * This is intentionally minimal and runtime-friendly.
 * You can later plug in DTW/SoftDTW/EDR/ERP or DBM-style evidence scoring.
 */
public interface MotionIrMetric extends Serializable {

    /**
     * Distance between two primitives (k-step).
     * Must satisfy metric properties if you claim it is a metric.
     */
    double distance(MotionIrPrimitive a, MotionIrPrimitive b);

    /**
     * Distance between two sequences.
     * MVP default can be "aligned L1/L2 + length penalty".
     * More advanced: DTW, segment search, submatch, etc.
     */
    double distance(MotionIrSequence a, MotionIrSequence b);

    // -----
    // Minimal default implementation
    // -----

    /**

```

```

* A minimal metric based on weighted L1 distance on ( $\Delta pos$ ,  $\Delta dir$ ),
* and an optional length penalty for sequences.
*
* Primitive distance:
*    $wPos * |\Delta posA - \Delta posB| + wDir * |\Delta dirA - \Delta dirB|$ 
*
* Sequence distance (aligned by index):
*   mean of primitive distances over  $\min(lenA, lenB)$ 
*
* This is a metric if:
*   - weights are non-negative
*   - lengthPenalty is non-negative
*   (and you accept the aligned-sequence definition)
*/
final class WeightedL1Aligned implements MotionIrMetric {

    private static final long serialVersionUID = 1L;

    private final double wPos;
    private final double wDir;
    private final double lengthPenalty;

    public WeightedL1Aligned(double wPos, double wDir, double
lengthPenalty) {
        if (!(wPos >= 0.0) || Double.isNaN(wPos) ||
Double.isInfinite(wPos)) {
            throw new IllegalArgumentException("wPos must be finite
and >= 0");
        }
        if (!(wDir >= 0.0) || Double.isNaN(wDir) ||
Double.isInfinite(wDir)) {
            throw new IllegalArgumentException("wDir must be finite
and >= 0");
        }
        if (!(lengthPenalty >= 0.0) || Double.isNaN(lengthPenalty) ||
Double.isInfinite(lengthPenalty)) {
            throw new IllegalArgumentException("lengthPenalty must be
finite and >= 0");
        }
        this.wPos = wPos;
        this.wDir = wDir;
        this.lengthPenalty = lengthPenalty;
    }

    public static WeightedL1Aligned defaultMetric() {
        // MVP defaults: treat  $\Delta pos$  and  $\Delta dir$  equally; no length penalty
        return new WeightedL1Aligned(1.0, 1.0, 0.0);
    }

    public double getWPos() {
        return wPos;
    }

    public double getWDir() {
        return wDir;
    }
}

```

```

public double getLengthPenalty() {
    return lengthPenalty;
}

@Override
public double distance(MotionIrPrimitive a, MotionIrPrimitive b) {
    if (a == null || b == null) {
        // MVP: null treated as infinitely far; alternative: throw.
        return Double.POSITIVE_INFINITY;
    }
    double dPos = Math.abs(a.getDeltaPos() - b.getDeltaPos());
    double dDir = Math.abs(a.getDeltaDir() - b.getDeltaDir());
    return wPos * dPos + wDir * dDir;
}

@Override
public double distance(MotionIrSequence A, MotionIrSequence B) {
    if (A == null || B == null) {
        return Double.POSITIVE_INFINITY;
    }
    int lenA = A.size();
    int lenB = B.size();

    if (lenA == 0 && lenB == 0) {
        return 0.0;
    }
    if (lenA == 0 || lenB == 0) {
        return lengthPenalty * Math.abs(lenA - lenB) +
Double.POSITIVE_INFINITY;
    }

    int m = Math.min(lenA, lenB);

    double sum = 0.0;
    for (int i = 0; i < m; i++) {
        sum += distance(A.getPrimitives().get(i),
B.getPrimitives().get(i));
    }

    double mean = sum / m;
    double lp = lengthPenalty * Math.abs(lenA - lenB);
    return mean + lp;
}

@Override
public String toString() {
    return "WeightedL1Aligned{wPos=" + wPos + ", wDir=" + wDir + ",
lengthPenalty=" + lengthPenalty + '}';
}

@Override
public boolean equals(Object o) {
    if (!(o instanceof WeightedL1Aligned)) return false;
    WeightedL1Aligned other = (WeightedL1Aligned) o;
    return Double.compare(wPos, other.wPos) == 0
        && Double.compare(wDir, other.wDir) == 0

```

```

        && Double.compare(lengthPenalty, other.lengthPenalty) ==
0;
    }

    @Override
    public int hashCode() {
        return Objects.hash(wPos, wDir, lengthPenalty);
    }
}

/**
 * Weighted L2 (Euclidean) distance for primitives, aligned-average for
sequences.
 *
 * Primitive distance:
 *  $\text{sqrt}((wPos * (\Delta posA - \Delta posB))^2 + (wDir * (\Delta dirA - \Delta dirB))^2)$ 
 *
 * Sequence distance:
 * mean primitive distance over minLen + lengthPenalty * |lenA - lenB|
 */
final class WeightedL2Aligned implements MotionIrMetric {

    private static final long serialVersionUID = 1L;

    private final double wPos;
    private final double wDir;
    private final double lengthPenalty;

    public WeightedL2Aligned(double wPos, double wDir, double
lengthPenalty) {
        if (!(wPos >= 0.0) || Double.isNaN(wPos) ||
Double.isInfinite(wPos)) {
            throw new IllegalArgumentException("wPos must be finite
and >= 0");
        }
        if (!(wDir >= 0.0) || Double.isNaN(wDir) ||
Double.isInfinite(wDir)) {
            throw new IllegalArgumentException("wDir must be finite
and >= 0");
        }
        if (!(lengthPenalty >= 0.0) || Double.isNaN(lengthPenalty) ||
Double.isInfinite(lengthPenalty)) {
            throw new IllegalArgumentException("lengthPenalty must be
finite and >= 0");
        }
        this.wPos = wPos;
        this.wDir = wDir;
        this.lengthPenalty = lengthPenalty;
    }

    public static WeightedL2Aligned defaultMetric() {
        return new WeightedL2Aligned(1.0, 1.0, 0.0);
    }

    @Override
    public double distance(MotionIrPrimitive a, MotionIrPrimitive b) {
        if (a == null || b == null) {

```

```

        return Double.POSITIVE_INFINITY;
    }
    double dPos = wPos * (a.getDeltaPos() - b.getDeltaPos());
    double dDir = wDir * (a.getDeltaDir() - b.getDeltaDir());
    return Math.sqrt(dPos * dPos + dDir * dDir);
}

@Override
public double distance(MotionIrSequence A, MotionIrSequence B) {
    if (A == null || B == null) {
        return Double.POSITIVE_INFINITY;
    }
    int lenA = A.size();
    int lenB = B.size();

    if (lenA == 0 && lenB == 0) {
        return 0.0;
    }
    if (lenA == 0 || lenB == 0) {
        return lengthPenalty * Math.abs(lenA - lenB) +
Double.POSITIVE_INFINITY;
    }

    int m = Math.min(lenA, lenB);

    double sum = 0.0;
    for (int i = 0; i < m; i++) {
        sum += distance(A.getPrimitives().get(i),
B.getPrimitives().get(i));
    }

    double mean = sum / m;
    double lp = lengthPenalty * Math.abs(lenA - lenB);
    return mean + lp;
}

@Override
public String toString() {
    return "WeightedL2Aligned{wPos=" + wPos + ", wDir=" + wDir + ",
lengthPenalty=" + lengthPenalty + '}';
}

@Override
public boolean equals(Object o) {
    if (!(o instanceof WeightedL2Aligned)) return false;
    WeightedL2Aligned other = (WeightedL2Aligned) o;
    return Double.compare(wPos, other.wPos) == 0
        && Double.compare(wDir, other.wDir) == 0
        && Double.compare(lengthPenalty, other.lengthPenalty) ==
0;
}

@Override
public int hashCode() {
    return Objects.hash(wPos, wDir, lengthPenalty);
}
}

```

}

3) 你现在就能跑通的最小管线（概念对齐）

- 上游：`List<DeltaPosDirExtractor.Sample>`
- 抽取：`DeltaPosDirExtractor.extract(...) → List<MotionIrPrimitive>`
- 序列：`MotionIrSequence.of(primitives)`
- 距离：`MotionIrMetric.WeightedL1Aligned.defaultMetric().distance(seqA, seqB)`

这条管线已经可以支撑：

- toy demo 检索（给定 query 轨迹，找最相似）
 - clustering 前的 pairwise distance
 - 下一步接 IRStarmap / evidence chain
-

如果你下一步希望更“DBM 风味”一点（但仍保持最小），我建议紧跟着再补一个非常小的接口：

- `MotionIrEvidence`：记录 top-k 最大贡献的 indices（解释链）
- 在 `WeightedL1Aligned.distance(seqA, seqB)` 内部顺手找出贡献最大的 3–5 个 primitive index

你一句话，我就按同风格继续补齐。

再补一个非常小的接口：`MotionIrEvidence`：记录 top-k 最大贡献的 indices（解释链）在 `WeightedL1Aligned.distance(seqA, seqB)` 内部顺手找出贡献最大的 3–5 个 primitive index

下面给出一个非常小且“可直接插入现有骨架”的补丁方案：

1. 新增 `MotionIrEvidence`：记录 top-k 最大贡献的 indices（以及可选贡献值）

2. 在 `WeightedL1Aligned` 内新增一个 **不破坏现有接口** 的方法：

`distanceWithEvidence(seqA, seqB, topK)`

- o 原 `distance(seqA, seqB)` 保持不变
- o `distanceWithEvidence` 内部顺手提取贡献最大的 3–5 个 index（默认你可以传 3 或 5）

1) `MotionIrEvidence.java`

```
package com.dbm.ir.motion;

import java.io.Serializable;
import java.util.ArrayList;
import java.util.Collections;
import java.util.List;
import java.util.Objects;

/**
 * Explanation chain for Motion IR distance: the top-k indices that
 * contribute most.
 *
 * Evidence is NOT part of the metric; it is derived alongside distance
 * computation.
 */
public final class MotionIrEvidence implements Serializable {

    private static final long serialVersionUID = 1L;

    /** Each entry corresponds to a primitive index i with its contribution
     score. */
    private final List<Entry> topContributors;

    private MotionIrEvidence(List<Entry> topContributors) {
        this.topContributors = topContributors;
    }

    public static MotionIrEvidence empty() {
        return new MotionIrEvidence(Collections.<Entry>emptyList());
    }

    public static MotionIrEvidence of(List<Entry> entriesSortedDesc) {
        if (entriesSortedDesc == null || entriesSortedDesc.isEmpty()) {
            return empty();
        }
        // assume already sorted desc; wrap immutable
        return new MotionIrEvidence(Collections.unmodifiableList(new
        ArrayList<>(entriesSortedDesc)));
    }

    public List<Entry> getTopContributors() {
```



```

        return topContributors;
    }

    /** Convenience: returns only indices, in descending contribution order.
 */
    public int[] topIndices() {
        int[] out = new int[topContributors.size()];
        for (int i = 0; i < topContributors.size(); i++) {
            out[i] = topContributors.get(i).index;
        }
        return out;
    }

    @Override
    public String toString() {
        return "MotionIrEvidence{topContributors=" + topContributors + '}';
    }

    @Override
    public boolean equals(Object o) {
        if (!(o instanceof MotionIrEvidence)) return false;
        MotionIrEvidence other = (MotionIrEvidence) o;
        return Objects.equals(topContributors, other.topContributors);
    }

    @Override
    public int hashCode() {
        return Objects.hash(topContributors);
    }

    public static final class Entry implements Serializable {

        private static final long serialVersionUID = 1L;

        public final int index;
        public final double contribution;

        private Entry(int index, double contribution) {
            this.index = index;
            this.contribution = contribution;
        }

        public static Entry of(int index, double contribution) {
            if (index < 0) {
                throw new IllegalArgumentException("index must be >= 0");
            }
            if (Double.isNaN(contribution) ||
                Double.isInfinite(contribution)) {
                throw new IllegalArgumentException("contribution must be
finite");
            }
            return new Entry(index, contribution);
        }

        @Override
        public String toString() {
            return "Entry{idx=" + index + ", c=" + contribution + '}';
        }
    }

```

```

    }

    @Override
    public boolean equals(Object o) {
        if (!(o instanceof Entry)) return false;
        Entry other = (Entry) o;
        return index == other.index && Double.compare(contribution,
other.contribution) == 0;
    }

    @Override
    public int hashCode() {
        return Objects.hash(index, contribution);
    }
}
}

```

2) 在 `MotionIrMetric.WeightedL1Aligned` 内加入“距离 + 解释链”的返回类型与方法

把下面这段 **追加** 到你现有的 `MotionIrMetric` 文件里（建议放在 `WeightedL1Aligned` 类内部，紧凑、便于 drop-in）。

2.1 追加一个小的返回结构 `DistanceWithEvidence`

```

public static final class DistanceWithEvidence implements Serializable {

    private static final long serialVersionUID = 1L;

    public final double distance;
    public final MotionIrEvidence evidence;

    private DistanceWithEvidence(double distance, MotionIrEvidence evidence)
    {
        this.distance = distance;
        this.evidence = evidence;
    }

    public static DistanceWithEvidence of(double distance, MotionIrEvidence
evidence) {
        if (Double.isNaN(distance) || Double.isInfinite(distance)) {
            throw new IllegalArgumentException("distance must be finite");
        }
        return new DistanceWithEvidence(distance, evidence == null ?
MotionIrEvidence.empty() : evidence);
    }

    @Override

```

```

        public String toString() {
            return "DistanceWithEvidence{distance=" + distance + ", evidence=" +
evidence + '}';
        }
    }
}

```

2.2 追加方法 distanceWithEvidence(...) (核心改动)

```

/**
 * Computes aligned distance AND returns evidence of top-k largest
contributors.
 *
 * Contribution definition (aligned by index):
 *   contrib[i] = primitiveDistance(A[i], B[i])
 *
 * Evidence is the topK indices (descending contrib).
 *
 * This method does NOT change the metric definition; it only attaches
explanation.
 */
public DistanceWithEvidence distanceWithEvidence(MotionIrSequence A,
MotionIrSequence B, int topK) {
    if (A == null || B == null) {
        return DistanceWithEvidence.of(Double.POSITIVE_INFINITY,
MotionIrEvidence.empty());
    }
    int lenA = A.size();
    int lenB = B.size();

    if (lenA == 0 && lenB == 0) {
        return DistanceWithEvidence.of(0.0, MotionIrEvidence.empty());
    }
    if (lenA == 0 || lenB == 0) {
        double d = getLengthPenalty() * Math.abs(lenA - lenB) +
Double.POSITIVE_INFINITY;
        return DistanceWithEvidence.of(d, MotionIrEvidence.empty());
    }

    final int m = Math.min(lenA, lenB);
    final int k = normalizeTopK(topK);

    double sum = 0.0;

    // Maintain a tiny top-k structure (descending by contribution).
    TopK top = new TopK(k);

    for (int i = 0; i < m; i++) {
        double c = distance(A.getPrimitives().get(i),
B.getPrimitives().get(i)); // per-index contribution
        sum += c;
        top.offer(i, c);
    }

    double mean = sum / m;
    double lp = getLengthPenalty() * Math.abs(lenA - lenB);

```

```

        double dist = mean + lp;

        return DistanceWithEvidence.of(dist,
MotionIrEvidence.of(top.toEntriesSortedDesc()));
    }

    private int normalizeTopK(int topK) {
        if (topK <= 0) return 0;
        // Per your request: default range 3-5; but keep it generic.
        if (topK > 32) return 32; // hard cap for MVP safety
        return topK;
    }

    /**
     * Minimal O(m * k) top-k helper; k is tiny (3~5), so this is faster than
     sorting.
     * Keeps entries in descending contribution order.
     */
    private static final class TopK {
        private final int k;
        private final int[] idx;
        private final double[] val;
        private int size;

        TopK(int k) {
            this.k = k;
            this.idx = new int[k];
            this.val = new double[k];
            this.size = 0;
        }

        void offer(int index, double contribution) {
            if (k == 0) return;

            if (size < k) {
                idx[size] = index;
                val[size] = contribution;
                size++;
                bubbleUp(size - 1);
                return;
            }

            // If worse than current worst (tail), skip.
            if (contribution <= val[size - 1]) {
                return;
            }

            // Replace worst and bubble up.
            idx[size - 1] = index;
            val[size - 1] = contribution;
            bubbleUp(size - 1);
        }

        private void bubbleUp(int pos) {
            // Maintain descending order by contribution.
            int i = pos;
            while (i > 0 && val[i] > val[i - 1]) {

```

```

        swap(i, i - 1);
        i--;
    }
}

private void swap(int i, int j) {
    int ti = idx[i];
    idx[i] = idx[j];
    idx[j] = ti;

    double tv = val[i];
    val[i] = val[j];
    val[j] = tv;
}

List<MotionIrEvidence.Entry> toEntriesSortedDesc() {
    if (size == 0) return Collections.emptyList();
    List<MotionIrEvidence.Entry> out = new ArrayList<>(size);
    for (int i = 0; i < size; i++) {
        out.add(MotionIrEvidence.Entry.of(idx[i], val[i]));
    }
    return out;
}
}

```

注意：上面代码使用了 `Collections/ArrayList`，确保在 `WeightedL1Aligned` 所在文件顶部 import 这些：

```

import java.util.ArrayList;
import java.util.Collections;
import java.util.List;

```

3) 你将如何使用（MVP 跑通方式）

```

MotionIrMetric.WeightedL1Aligned metric =
MotionIrMetric.WeightedL1Aligned.defaultMetric();

MotionIrMetric.WeightedL1Aligned.DistanceWithEvidence r =
    metric.distanceWithEvidence(seqA, seqB, 5);

double d = r.distance;
int[] topIdx = r.evidence.topIndices(); // descending contributions
// r.evidence.getTopContributors() gives (index, contribution) pairs

```

4) “贡献”的定义与后续可升级点

当前贡献定义为：`contrib[i] = primitiveDistance(A[i], B[i])`。这非常符合你的“解释链”直觉：哪个局部片段差得最多，解释链就指出它。

后续如果你要更 DBM 风味，可保持接口不变，只升级 `contrib[i]` 的定义，例如：

- 引入分解贡献：`wPos*|Δpos|` 与 `wDir*|Δdir|` 分开记录
- 引入“惩罚项贡献”：长度惩罚也可以生成一个 evidence entry（例如 `idx=-1` 表示 global penalty）
- 引入 submatch 时，把 evidence 变成 `(iA, iB, contrib)` 的对齐对（那就是 DTW 解释链）

你说一声，我可以在不破坏你现有 API 的前提下把这些升级以“可插拔策略”的方式接进去。