Hitotsubashi University

Autumn–Winter Term 2026

Topics in Econometrics B

Lecturer: Masayuki Sawada

Can an AI Agent Replace a Sales Rep Who Already Uses AI?

A Proposal for a Multi-Firm Field Experiment in B2B Outbound Sales

Final Report (Research Proposal)

Simon Jensen

Student ID: 2226237U

6 November 2026

Can an AI Agent Replace a Sales Rep Who Already Uses AI?

1. Motivation

My bachelor thesis starts from a simple premise: what keeps a start-up small is staff. Growth needs people, and people are slow to hire and expensive to keep. AI agents promise to loosen this constraint, and the entry-level sales role is where they make that claim first. A business development associate (BDA) researches prospects, contacts them by phone, e-mail and LinkedIn, follows up and books meetings; an autonomous agent can now do the same by e-mail. Whether it does them as well decides whether a start-up still needs to hire for this role. This proposal asks:

"How much does replacing an AI-assisted BDA with an autonomous AI agent change the share of prospect accounts that book a meeting, and at what cost per account?"

2. Related Work and Contribution

Most field evidence on generative AI at work answers a neighboring question. An AI assistant raised the issues resolved per hour in customer support by 15% (Brynjolfsson et al., 2025), and ChatGPT made professional writing faster and better (Noy & Zhang, 2023). Both treat AI as a tool in a human's hand. They measure augmentation, not replacement.

The closest study compares human and automated sales agents directly. In a randomized field experiment (n = 325) and an online experiment (n = 408), Adam et al. (2023) find that customers are more willing to show initial interest to a human sales agent, but more willing to leave their contact details with an automated one. As far as its abstract reports, it never compares the automated agent with a human who does the whole job with AI. Both decisions it studies come before a meeting. Who makes the contact also matters in its own right: in outbound sales calls, disclosing that the caller was a chatbot cut purchase rates by 79.7% (Luo et al., 2019).

To my knowledge, no randomized study compares an autonomous agent with a human who already uses AI, on booked meetings, across more than one start-up. This proposal fills that gap, with Adam et al. (2023) as its benchmark.

3. Data: Where and How

Such a comparison needs data from more than one start-up. The experiment would run at Finto and three further B2B start-ups, each contributing one BDA for a two-week pilot and a twelve-week main phase. In return, each start-up uses the agent free of charge and receives its own results. Finto, a Munich-based AI start-up where I worked over the summer, sets the baseline: of the roughly 1,000 firms I contacted there, about 100 a week, two to three in every 100 booked a meeting. Because the pool of prospects is finite, each start-up's target profile, drawn from its CRM and a commercial prospect database, must yield up to 4,800 accounts (up to 1,200 for the BDA and 3,600 for the agent), de-duplicated across start-ups.

All outcomes come from systems the start-ups already run: the sending tool, the dialer and the CRM record every contact, reply and meeting, the BDA logs hours and the agent its API spend.

Covariates (industry, firm size, country, lead source) come from the CRM and the prospect database. Each start-up exports pseudonymized account-level records under a data-sharing agreement; the BDAs consent, outreach follows the rules on unsolicited messages, and the study needs ethics approval.

4. Design and Parameter of Interest

So what should the agent be compared with? The obvious control group is a human without AI. It would be the easier comparison and would show the larger effect. It is also the wrong one. A start-up that replaces its BDA today replaces one who already drafts e-mails with ChatGPT. The control arm is therefore a BDA who works as usual, by e-mail, phone and LinkedIn, and may use any general-purpose AI tool but not the agent; the tools used are logged. The comparison thus bundles author and channel, which is exactly what a replacement changes.

Field experiments with sales and call-center staff usually randomize the workers (Bloom et al., 2015; Sandvik et al., 2020). Here the agent does not change how the BDA works but takes the BDA's place, so the unit of randomization is the prospect firm (the account), not the contact person; two colleagues at the same prospect then never hear from both arms (Sawada, 2026, Lecture 2). Each week, a new batch of accounts is assigned within strata of start-up × week (Bruhn & McKenzie, 2009). Because only the human arm is capacity-bound, three accounts go to the agent for every account the BDA handles (List et al., 2011). Each arm keeps its accounts and sends from its own domains, which limits interference between the arms. The agent writes only e-mails and states in each that it is an AI assistant.

The two arms hit different limits. The median sales development representative (SDR, the common US title for a BDA) logs 112 activities a day, 44 of them calls and 41 e-mails (Bertuzzi, 2025). These are touches across sequences: at an assumed eight to ten touches per account, 560 touches a week reach only 56 to 70 new accounts, so my 100 a week at Finto is optimistic and the design plans with 85 to 100. The pilot therefore measures each BDA's pace, which then fixes the size of all twelve weekly batches; a researcher draws each batch from the pool and randomizes it before the BDA sees it. The agent is limited by deliverability, not time: new mailboxes need weeks of warm-up and then send 14 to 42 cold e-mails a day (Smartlead, n.d.; Google, n.d.), so each mailbox is capped at an assumed 40 (Appendix C). The agent wins on volume, the BDA perhaps on quality, so the meeting rate per account is the estimand and meetings per week are reported descriptively.

The parameter of interest is the intention-to-treat effect $\tau = \mathbb{E}[Y_i(1) - Y_i(0)]$ on the accounts of the participating start-ups, where Y_i equals one if account i books a meeting within 45 days of its batch date, a window fixed at assignment and long enough for both arms' sequences. τ is the net policy effect of deploying an e-mail-only, disclosed agent rather than an AI-assisted, multichannel BDA, and the booked meeting is the single primary outcome. Cost, the second quantity the question names, accrues per week, so cost per account is measured for each start-up, week and arm: API spend, mailboxes and supervision time for the agent, logged hours times the loaded wage for the BDA. With a median SDR pay of USD 55,000 to 80,000 (Bertuzzi, 2025) and wages at 70.3% of employer costs (U.S. Bureau of Labor Statistics, 2025), a BDA costs about USD 15 to 26 per account at 85 to 100 accounts a week and USD 22 to 39 at 56 to 70.

The cost difference between the arms, τ_C, gives the net value of a meeting worth v as $v\tau - \tau_C$, reported over a range of v so that no estimate close to zero ever sits in a denominator.

5. Estimation and Power

The meeting effect is estimated by

$$Y_i = \tau A_i + \gamma_{s(i)} + (X_i - \bar{X})'\beta + A_i(X_i - \bar{X})'\delta + \varepsilon_i,$$

where A_i is assignment to the agent, $\gamma_{s(i)}$ are stratum fixed effects and X_i are the centered pre-assignment covariates, interacted with A_i as in Lin (2013). The covariates add precision, not identification. Assignment varies at the account level, and the four start-ups are not a random sample of start-ups, so heteroskedasticity-robust standard errors fit the estimand (Abadie et al., 2023). τ_C is estimated across the 48 start-up-weeks.

Secondary outcomes (any reply, positive reply, bounce, unsubscribe) are corrected for multiple testing with the Romano-Wolf step-down procedure (Romano & Wolf, 2005; Sawada, 2026, Lecture 2, Part 2). Under ITT, every account stays in its assigned arm, including accounts the BDA never works and prospects who answer the BDA after the agent's e-mails. Whether a meeting is held is defined only for accounts that book, so the target is the effect on accounts that would book with either arm, bounded under monotonicity (Frangakis & Rubin, 2002; Lee, 2009; Sawada, 2026, Lecture 10).

At $p_0 = 2.5\%$ and 85 to 100 accounts a week, four BDAs over twelve weeks give 4,080 to 4,800 human accounts, and with three times as many agent accounts the design detects a rise of 30 to 33% or a fall of 28 to 30%. At 150 accounts a week the bounds narrow to +25% and −23%; at 50 they widen to +43% and −39% (Appendix, Tables A2 and A3). A Monte Carlo check under independent accounts comes close: 93 to 95% coverage, 6.2% false rejections and 76 to 78% power at +30% (Appendix, Table B1). A null result therefore means that, at the planned pace, changes of about 30% would probably have been found, not that the arms perform equally. The experiment runs into the very constraint it is meant to test: the number of people.

6. Threats to Validity

The agent learns, so the treatment changes while it is being measured, which breaks the "no hidden treatments" part of SUTVA (Sawada, 2026, Lecture 2). Updates are therefore allowed only between weekly batches and are logged, so the pooled τ averages over the agent versions used. A John Henry effect, BDAs working harder because they know the comparison, would understate τ; activity and hours are logged. Because the agent only writes, a positive result shows that e-mail alone can do the BDA's multichannel job, not that an agent could also call. Finally, four start-ups chosen by access are not all start-ups; the estimate holds for them and their four BDAs, and start-up-specific estimates are reported alongside.

The experiment returns to the opening premise with a number. If the agent's net value per account is positive across plausible meeting values, staff stops being the constraint at the first stage of sales. If it is negative, a start-up still needs people to grow.

References

Abadie, A., Athey, S., Imbens, G. W., & Wooldridge, J. M. (2023). When should you adjust standard errors for clustering? *The Quarterly Journal of Economics, 138*(1), 1–35. https://doi.org/10.1093/qje/qjac038

Adam, M., Roethke, K., & Benlian, A. (2023). Human vs. automated sales agents: How and why customer responses shift across sales stages. *Information Systems Research, 34*(3), 1148–1168. https://doi.org/10.1287/isre.2022.1171

Bertuzzi, M. (2025). *2025 SDR models & metrics report*. The Bridge Group. https://www.bridgegroupinc.com/research/2025-sdr-models-metrics-report-the-bridge-group

Bloom, N., Liang, J., Roberts, J., & Ying, Z. J. (2015). Does working from home work? Evidence from a Chinese experiment. *The Quarterly Journal of Economics, 130*(1), 165–218. https://doi.org/10.1093/qje/qju032

Bruhn, M., & McKenzie, D. (2009). In pursuit of balance: Randomization in practice in development field experiments. *American Economic Journal: Applied Economics, 1*(4), 200–232. https://doi.org/10.1257/app.1.4.200

Brynjolfsson, E., Li, D., & Raymond, L. (2025). Generative AI at work. *The Quarterly Journal of Economics, 140*(2), 889–942. https://doi.org/10.1093/qje/qjae044

Frangakis, C. E., & Rubin, D. B. (2002). Principal stratification in causal inference. *Biometrics, 58*(1), 21–29. https://doi.org/10.1111/j.0006-341X.2002.00021.x

Google. (n.d.). *Email sender guidelines FAQ*. Gmail Help. Retrieved November 4, 2026, from https://support.google.com/a/answer/14229414

Ibragimov, R., & Müller, U. K. (2010). t-Statistic based correlation and heterogeneity robust inference. *Journal of Business & Economic Statistics, 28*(4), 453–468. https://doi.org/10.1198/jbes.2009.08046

Jensen, S. (2026). *ai-sales-agent-proposal: Power calculation and Monte Carlo check for a research proposal* [Computer software]. GitHub. https://github.com/sj-johnsen/ai-sales-agent-proposal

Lee, D. S. (2009). Training, wages, and sample selection: Estimating sharp bounds on treatment effects. *The Review of Economic Studies, 76*(3), 1071–1102. https://doi.org/10.1111/j.1467-937X.2009.00536.x

Lin, W. (2013). Agnostic notes on regression adjustments to experimental data: Reexamining Freedman's critique. *The Annals of Applied Statistics, 7*(1), 295–318. https://doi.org/10.1214/12-AOAS583

List, J. A., Sadoff, S., & Wagner, M. (2011). So you want to run an experiment, now what? Some simple rules of thumb for optimal experimental design. *Experimental Economics, 14*(4), 439–457. https://doi.org/10.1007/s10683-011-9275-7

Luo, X., Tong, S., Fang, Z., & Qu, Z. (2019). Frontiers: Machines vs. humans: The impact of artificial intelligence chatbot disclosure on customer purchases. *Marketing Science, 38*(6), 937–947. https://doi.org/10.1287/mksc.2019.1192

Noy, S., & Zhang, W. (2023). Experimental evidence on the productivity effects of generative artificial intelligence. *Science, 381*(6654), 187–192. https://doi.org/10.1126/science.adh2586

Romano, J. P., & Wolf, M. (2005). Stepwise multiple testing as formalized data snooping. *Econometrica, 73*(4), 1237–1282. https://doi.org/10.1111/j.1468-0262.2005.00615.x

Sandvik, J. J., Saouma, R. E., Seegert, N. T., & Stanton, C. T. (2020). Workplace knowledge flows. *The Quarterly Journal of Economics, 135*(3), 1635–1680. https://doi.org/10.1093/qj

e/qjaa013

Sawada, M. (2026). *Topics in Econometrics B: Lectures 2 and 10* [Lecture slides]. Hitotsubashi University.

Smartlead. (n.d.). *How long should you warm up an email domain before a campaign?* Retrieved November 4, 2026, from https://www.smartlead.ai/benchmarks/how-long-to-warm-up-email-before-cold-outreach

U.S. Bureau of Labor Statistics. (2025). *Employer costs for employee compensation, March 2025* (News Release USDL-25–0958). https://www.bls.gov/news.release/archives/ecec_06132025.htm

Appendix

The power calculation (Tables A1 to A3) and the simulation (Table B1) were run in Python; code and results are public (Jensen, 2026). The simulation contains no estimates of the agent's effect. It only checks that the planned estimator behaves as the power calculation promises, under independent accounts.

A. Power calculation

Two-sided test of two proportions at $\alpha = 0.05$ and power 0.80, normal approximation with unpooled variance. The regression of Section 5 can only be more precise, so the calculation is conservative. The control rate $p_0 = 2.5\%$ comes from Finto. With n_0 human and n_1 agent accounts, the smallest detectable rise $p_1 > p_0$ solves

$$\frac{p_1 - p_0}{\sqrt{p_0(1-p_0)/n_0 + p_1(1-p_1)/n_1}} = z_{0.975} + z_{0.80},$$

and the largest detectable fall is found the same way for $p_1 < p_0$.

Table A1. Accounts needed per arm in a 1:1 design.

p_0	**+25%**	**+50%**	**+100%**
2.0%	13,806	3,822	1,138
2.5%	10,981	3,038	903
3.0%	9,097	2,514	746

Table A2. Detectable rise / fall by number of start-ups (one BDA each, 100 accounts per week, 12 weeks, 1:3 allocation). The main design is the row with four start-ups.

Start-ups	**Human accounts**	**Agent accounts**	$p_0 = 2.0\%$	$p_0 = 2.5\%$	$p_0 = 3.0\%$
1	1,200	3,600	+71% / −60%	+63% / −54%	+57% / −50%
2	2,400	7,200	+49% / −44%	+43% / −39%	+39% / −36%
3	3,600	10,800	+40% / −36%	+35% / −32%	+32% / −30%
4	**4,800**	**14,400**	**+34% / −31%**	**+30% / −28%**	**+27% / −26%**
6	7,200	21,600	+28% / −26%	+25% / −23%	+22% / −21%
8	9,600	28,800	+24% / −22%	+21% / −20%	+19% / −18%

Giving the agent more accounts helps less than it seems, because the variance of the smaller human arm dominates. At $p_0 = 2.5\%$, raising the ratio from 1:3 to 1:5 (9,600 more agent accounts) lowers the detectable rise only from +30% to +28%; one more start-up (4,800 accounts) lowers it to +27%.

B. Monte Carlo check of the design

Each replication draws four start-ups with baselines that differ on the logit scale (standard deviation 0.3, population mean of p_0 calibrated to 2.5%) and accounts with three covariates standing in for those of Section 3. Outcomes are independent across accounts given these

Table A3. Detectable rise / fall by the BDAs' pace (four start-ups, 12 weeks, 1:3, $p_0 = 2.5\%$). The pace is measured in the pilot and sets the size of the weekly batches; the design plans with 85 to 100 (bold).

New accounts per BDA and week	Human accounts	Agent accounts	Detectable rise / fall
50	2,400	7,200	+43% / −39%
75	3,600	10,800	+35% / −32%
85	**4,080**	**12,240**	**+33% / −30%**
100	**4,800**	**14,400**	**+30% / −28%**
150	7,200	21,600	+25% / −23%
200	9,600	28,800	+21% / −20%

baselines; week-level shocks, non-compliance and cost are not simulated. Assignment is 1:3 within start-up × week. The agent multiplies each account's baseline probability by $(1 + r_f)$; in the heterogeneous scenarios r_f varies across start-ups with standard deviation 0.10. The true effect is computed from the simulated probabilities, so coverage is measured against the effect the estimator targets.

Two tests are checked. The **main test** is the Lin (2013) regression of Section 5 with stratum fixed effects and robust standard errors; its target is the effect on the participating start-ups. The **start-up test** averages one Lin estimate per start-up and uses a t-test with three degrees of freedom (Ibragimov & Müller, 2010); its target is the average effect across start-ups like these.

Table B1. Rejection rates and coverage of 95% intervals, 1,000 replications each.

Scenario	Main test: rejects	Main test: coverage
No effect, same relative effect in every start-up	6.2%	93.8%
No average effect, varies across start-ups	8.8%	94.9%
Effect at the detectable size (+30%), same relative effect in every start-up	77.9%	93.4%
Effect at the detectable size, varies across start-ups	76.2%	94.8%

Under no effect, the main test rejects in 6.2% and the start-up test in 4.5% of replications; with 1,000 replications the Monte Carlo standard error is about 0.7 points, so the main test is slightly liberal. In the second row, the main test rejects more often because the effect on the four participating start-ups is not exactly zero when effects vary across start-ups; its coverage of that effect stays at 95%. At the detectable effect, the main test comes close to the planned power (76 to 78% against 80%), while the start-up test, which answers a broader question with four units, reaches only 34 to 42%. The headline estimand is the effect on the participating start-ups because they are not a random sample (Section 5); the lower power of the start-up test is a second reason, not the first.

C. Timeline and pre-specification

Table C1. Timeline of the experiment.

Weeks	Phase	Content
before 1	Warm-up	Agent and BDA mailboxes are warmed up on separate domains, capped at an assumed 40 cold e-mails a day each; at an assumed four e-mails per account, the agent's 300 new accounts a week need six mailboxes per start-up and the BDA's 100 need two. Authentication (SPF, DKIM, DMARC) is set up.
1–2	Pilot	Normal BDA pace at 1:3 in each start-up to test logging and deliverability and measure the BDA's pace, which then fixes the batch size, and see how much cost per account varies across weeks. Analysis code registered before the main phase. Pilot data are not used in the main analysis.
3–14	Main experiment	12 weekly batches per start-up, drawn and randomized by a researcher at the pace measured in the pilot (100 BDA and 300 agent accounts at the planned pace). Agent updates only between batches, logged.
15–18	Outcome closure	30-day booking windows of the last batch close; meetings held are verified.
19–20	Analysis	Pre-specified estimators of Section 5 and the start-up test of Appendix B.