Certifying Safe Operating Regions under Monotone Failure Modes

Anonymous authors

Abstract

Many systems are configured by a few continuous knobs, and each setting can fail in more than one way: a language model sampled at low temperature degenerates into repetition and at high temperature into incoherence; a laser powder bed fusion process at low energy leaves unmelted powder and at high energy drills keyhole pores. Practitioners need the *safe operating region*, the settings where every failure mode is rare. Each failure rate can only be estimated from trials at that very setting, so evaluating a grid of configurations costs in proportion to its area. We study *certifying a safe region with a family-wise guarantee when every configuration needs its own trials*, using the one piece of structure these systems share: each failure mode is monotone in known directions. We give (i) the *cone rule*, a closed-testing procedure with betting e-processes that is valid at any stopping time and under any adaptive choice of trials, and under monotonicity reduces to two cumulative sums; (ii) a *search algorithm* for the fixed-confidence problem that stops on its own once the target region is certified; (iii) lower bounds showing that with the ordering the cost is governed by the region's *edge* and without it by its *area*, and an upper bound for the search within logarithmic and multiple-testing factors of the ordered lower bound. On sampling settings of a language model [TBD: LM numbers], on additive manufacturing process windows and on a drug-combination screen, the method needs 1.3–9$\times$ fewer trials than adaptive testing without the ordering and, on 48×48 grids, 19–26$\times$ fewer than a full grid with Learn-then-Test fixed-sequence testing, with no unsafe setting certified in any run, while a Gaussian-process level-set baseline certifies unsafe settings in 7.5–100% of runs unless it certifies almost nothing.

1 Introduction

A team deploying a language model must choose sampling settings (temperature, top-p). Too low, and outputs repeat themselves; too high, and they stop making sense. They want a region of settings where, with 95% confidence, both failure rates are below 10%, so that any setting in it is safe to ship. A setting's failure rates can only be estimated by generating outputs at that setting and judging them, which is expensive at scale. The same pattern appears in process qualification for additive manufacturing (laser power $\times$ scan speed; lack of fusion vs. keyholing), in dose finding for drug combinations (toxicity vs. lack of response), and in operating envelopes of controllers.

What we ask for. A certified region C such that, with probability at least $1 - \alpha$, every setting in C has every failure rate below its tolerance. The guarantee must hold when the experimenter looks at results after every batch and stops whenever they like, and however the next trials are chosen, including by an imperfect simulator or model.

Why existing tools fall short. *Risk control for configurations* (Learn-then-Test [Angelopoulos et al., 2025]; Pareto Testing [Laufer-Goldshtein et al., 2023]; Conformal Language Modeling [Quach et al., 2024]; MultiRisk [Joshi et al., 2025]) evaluates every candidate configuration on a shared calibration set. When evaluating a configuration means fresh trials at it, that costs the full grid; we compare against Learn-then-Test's fixed-sequence testing, which uses monotonicity along one axis, and find it needs 19–26$\times$ more trials than our method at 48×48. *Adaptive multiple testing with bandits* [Jamieson and Jain, 2018, Xu et al., 2021] samples adaptively but treats configurations as unrelated. *Monotone thresholding bandits* [Garivier et al., 2017, Cheshire et al., 2020] use order in one dimension, for one constraint, without anytime validity. *Safe Bayesian optimization and GP level-set estimation* [Sui et al., 2015, Gotovos et al., 2013, Losalka and Scarlett, 2023, 2024] rely on the GP model being right; their certificates fail when it is not (Section 6).

Structure. In all these systems each failure mode is monotone in known directions (repetition falls with temperature, incoherence rises with it). The null hypotheses "setting x is unsafe for mode m" are therefore logically related: if x is unsafe, so is everything riskier than x.

Contributions.

1. *Problem.* Certification of a safe region under per-mode partial orders when each configuration needs its own trials, in a fixed-budget and a fixed-confidence version (Section 2).
2. *Testing.* The cone rule: closed testing with weighted e-values, which under monotonicity is a cumulative sum; valid at every time under arbitrary adaptive sampling (Section 3).
3. *Allocation.* For a fixed budget, trials at the riskiest uncertified settings of a slightly shrunken target (the lower bound's binding constraints). For fixed confidence, a galloping/bisection search along the ordering with a two-sided probe that never stalls near a threshold (Section 4).

4. *Theory.* Lower bounds with and without the ordering (edge vs. area); upper bounds by Wald's identity; the search is within $O(\log n)$ and multiple-testing factors of the ordered lower bound (Section 5).

5. *Experiments.* Sampling settings of a language model, additive manufacturing (a Rosenthal melt-pool model and a synthetic window), and a drug-combination screen (Section 6).

2 Problem

Configurations form a grid $\mathcal{X} = [n_1] \times [n_2]$, $N = n_1 n_2$. There are M failure modes. A trial at x yields $Y \in \{0,1\}^M$, i.i.d. given x (modes may be dependent). The failure rate is $p_m(x) = \mathbb{E}Y_m$; x is *safe* if $p_m(x) < \varepsilon_m$ for all m, and the safe region is W.

Assumption A (monotone failure modes)**.** *For each m there is a known product order $\preceq_m$ on $\mathcal{X}$ such that $x \preceq_m y$ implies $p_m(y) \le p_m(x)$ ("y is at least as safe as x for mode m").*

Protocol. Trials are requested in batches; each batch is chosen from all data so far and any side information (a simulator, a cheaper model, a pilot study) before its outcomes are seen.

Fixed budget. Output certified sets C_t with $\mathbb{P}(C_t \subseteq W\ \forall t) \ge 1-\alpha$, and make C_t large.

Fixed confidence. For a slack $q < 1$ and target $T = \{x : p_m(x) \le q\varepsilon_m\ \forall m\}$, stop at a time τ with a certified set C.

Definition 1. *A procedure is* (α,β)-correct *if for every instance satisfying Assumption A: (validity)* $\mathbb{P}(C \not\subseteq W) \le \alpha$*, and (completeness)* $\mathbb{P}(\tau < \infty,\ T \subseteq C) \ge 1-\beta$.

Settings with rates between $q\varepsilon$ and ε may be certified or not.

3 Testing: the cone rule

Per-configuration evidence. For each (m,x), a betting e-process $K_{m,x}(t) = \prod_{s \le t:\, x_s = x}\big(1 + \lambda_s(\varepsilon_m - Y_{s,m})\big)$, with $\lambda_s \in [0, c/(1-\varepsilon_m)]$, $c < 1$, chosen before trial s. Under $H_{m,x} : p_m(x) \ge \varepsilon_m$ it is a nonnegative supermartingale for the filtration generated by all trials and side information (Lemma 1). We bet with a hedge: half a plug-in bet seeded by side information [Waudby-Smith and Ramdas, 2024], half a mixture of eight fixed bets.

The rule. Fix weights $w_{m,x} \ge 0$ with $\sum w \le 1$ before the trials. Let $\mathcal{C}_m(x) = \{y : y \preceq_m x\}$ be the riskier cone of x (including x). Certify x for mode m once

$$S_m(x,t) = \sum_{y \in \mathcal{C}_m(x)} w_{m,y} K_{m,y}(t) \ \ge\ 1/\alpha, \qquad (1)$$

and certify x once it is certified for every mode. For a product order on a grid, S_m for all x is two cumulative sums.

Theorem 1 (validity)**.** *Under Assumption A, for any allocation and stopping time,*

$$\mathbb{P}\big(\exists\, t, (m,x) :\ p_m(x) \ge \varepsilon_m,\ x \text{ certified for } m \text{ by } t\big) \le \alpha.$$

Proof sketch. The unsafe pairs D are closed toward risk, so a false certification of x gives

$$1/\alpha \le S_m(x,t) \le E(t) := \textstyle\sum_{(m,y)\in D} w_{m,y} K_{m,y}(t),$$

a nonnegative supermartingale starting at most 1; apply Ville's inequality. Full proof in Appendix A.2. □

This is closed testing [Marcus et al., 1976] with the weighted e-value intersection test [Vovk and Wang, 2021]: monotonicity makes the smallest true intersection containing (m,x) a cone, so the closure is a cumulative sum. A certificate at x automatically covers every safer setting, and evidence from riskier settings is pooled.

Weights. Certifying x with weight w takes about $\ln(1/(\alpha w))$ divided by $\mathrm{KL}(p\|\varepsilon)$ trials, so weights should sit on likely edge points. We use the frequency with which a setting is an edge point of the target under perturbed side information (logit shifts), mixed 50/50 with uniform weights.

4 Allocation

Fixed budget: the edge rule. Estimate the target with slack (all estimated rates below 0.7ε); for each mode, run trials at the riskiest uncertified settings of that estimate, several per batch, cheapest first; then re-check uncertified settings whose lower confidence bound still admits membership. These are the binding constraints of the lower bound (Theorem 2a).

Fixed confidence: search (Algorithm 1). For each mode and each row (a chain of the order), run a *two-sided probe* at one setting at a time: certify it by the cone rule, or reject "$p_m(x) \le q\varepsilon_m$" with a failure-betting e-process at level $\beta/(MN)$. A certificate spreads to safer settings, a rejection to riskier ones. Start at the edge found in an adjacent row (or the side information's predicted edge), gallop until the edge is bracketed, then bisect. Stop when every row is decided for every mode. Because $q < 1$, at every rate at least one side of the probe has positive drift, so no probe stalls.

Algorithm 1 (search, fixed confidence)

Input: grid, modes and orders, ε, q, α, β, side information.

Probe(m, x): run trials at x until $S_m(x) \geq 1/\alpha$ (certify x and everything safer for m) or $R_{m,x} \geq MN/\beta$ (reject x and everything riskier for m).

For each mode m and row j, riskiest rows first:

$s \leftarrow$ edge found in an adjacent row, else predicted edge;

gallop: probe s, then $s \pm 1, s \pm 2, s \pm 4, \ldots$ toward the side the outcome points to, until the outcome flips;

bisect the undecided positions of the bracket until every position is certified or rejected.

Stop when every (mode, setting) is certified, rejected, or excluded (rejected for another mode); output the certified settings.

5 Theory

Let $K_1 = \mathrm{kl}(1-\beta, \alpha)$, and for $\pi \in [0,1]$ let $f(\pi) = \mathrm{kl}(\pi, 1-\beta)$ for $\pi < 1-\beta$ (else 0) and $g(\pi) = \mathrm{kl}(\pi, \alpha)$ for $\pi > \alpha$ (else 0). Write $\mathrm{KL}_m(y) = \mathrm{KL}(p_m(y) \| \varepsilon_m)$ when $p_m(y) < \varepsilon_m$ and 0 otherwise.

Theorem 2 (lower bound)**.** *Any (α, β)-correct procedure has $\mathbb{E}[\tau] \geq \mathrm{OPT}$, the value of the convex program: minimize $\sum_y n_y$ over $n \geq 0$ subject to*

(i) for each m and each riskiest point t of T (for $\preceq_m$): $\sum_{y \preceq_m t} n_y \mathrm{KL}_m(y) \geq K_1$;

(ii) for each m and each boundary point *z ($z \notin T$ only because of mode m, and every setting strictly safer than z for m is in T for m): $(A_z, B_z) \in R$, where*

$$R = \{(A, B) : \exists \pi \;\; A \geq f(\pi),\; B \geq g(\pi)\},$$

$$A_z = n_z \mathrm{KL}(p_m(z) \| q\varepsilon_m) \text{ and } B_z = \textstyle\sum_{y \preceq_m z} n_y \mathrm{KL}_m(y).$$

Without the ordering, every setting must be resolved on its own and the bound is a sum of per-setting terms over all of $\mathcal{X}$.

The binding points of (i) form an antichain (at most $\min(n_1, n_2)$ per mode), and so do those of (ii): with the ordering the bound involves at most $2M \min(n_1, n_2)$ settings, without it all N.

Theorem 3 (oracle upper bound)**.** *Running trials only at a cover of T costs at most $\sum_{cover}(\ln(16/(\alpha w)) + b)/g(p)$ in expectation, where $g(p)$ is the best growth rate of the fixed bets; $\mathrm{KL}(p\|\varepsilon)/g(p) \in [1.00, 1.05]$ for $p \in [0.5\%, 4\%]$ at $\varepsilon = 5\%$.*

Theorem 4 (search)**.** *The search is (α, β)-correct. If each mode's evidence at x uses only the trials of that mode's probes, its expected cost is at most*

$$(C^* + B)\Big(\textstyle\sum_{m,j} P_{m,j} + (\alpha + \beta)MN\Big),$$

where $P_{m,j} = 2\lceil \log_2 d_{m,j} \rceil + 2$, $d_{m,j}$ is the distance from the first probe in row j to the far end of mode m's slack band (rates between $q\varepsilon_m$ and ε_m), B is the batch size, and $C^* = \max_p \min(T_c(p), T_r(p)) < \infty$ is the largest expected two-sided probe length.

Corollary 1 (edge vs. area)**.** *On an $n \times n$ grid the ordered bound involves $O(Mn)$ settings and the unordered bound $O(n^2)$; the search is within $O(\log n)$, the ratio $C^*/C(p_{boundary})$, and the multiple-testing factor $\ln(16MN/(\alpha w))/K_1$ of the ordered lower bound.*

Whether the $\ln N$ in the multiple-testing factor is necessary for a family-wise guarantee is open; in unstructured pure exploration such terms are necessary in moderate-confidence regimes [Simchowitz et al., 2017].

Proofs are in Appendix A.

6 Experiments

Applications. *Language model sampling.* SmolLM2-135M [Allal et al., 2025]; 12 temperatures (0.2–2.0) $\times$ 12 top-p values (0.5–1.0) [Holtzman et al., 2020]; prompts from WikiText-2 [Merity et al., 2017]; *degenerate* = more than 20% of 4-grams repeated [Welleck et al., 2020], *incoherent* = mean token NLL under the unmodified model above 3.5 nats; $\varepsilon = 10\%$ for both. Ground truth from 160 generations per setting (monotone fit); side information is a pilot of 16 separate generations per setting, counted in the budget. *Additive manufacturing.* A Rosenthal melt-pool model [Rosenthal, 1946] of 316L with lack-of-fusion [Tang et al., 2017], keyhole [King et al., 2014] and balling criteria, and a synthetic window with controllable simulator error. *Drug combinations.* Toxicity and non-response surfaces with a synergy term; Bliss independence [Bliss, 1939] as side information.

Baselines. *No ordering*: the same e-processes, weights and allocation, without the cone (each setting on its own). *Full grid, Bonferroni*: equal trials everywhere, exact binomial bounds at level $\alpha/(MN)$. *Full grid, fixed sequence*: equal trials everywhere, fixed-sequence testing along each row from the safest end at level $\alpha/(Mn)$, certificates spread to safer settings; this is how Learn-then-Test uses a monotone risk. *GP level set*: a GP classifier surrogate with a confidence-bound certificate.

Fixed budget. Table 1 and Figure 1. The gap to the unordered method grows with resolution (synthetic: 3.2$\times$ at 16^2, 9.1$\times$ at 48^2), as the edge-vs-area bounds predict. The full grids pay for the whole area; fixed-sequence testing helps them by only 20–40%. At 24×24, to certify 70% of the region, ours needs 5.0$\times$ fewer trials than no ordering on the synthetic window, 1.5–1.7$\times$ on Rosenthal 316L and 1.3$\times$ on the drug screen.




Figure 1: Trials to certify half of the safe region as the grid is refined (fixed budget, log–log). With the ordering the cost grows roughly like the region's edge (slope 1); without it, and for full grids, like its area (slope 2).

Table 1: Trials to certify 50% of the safe region (fixed budget, median of 5 runs; full grids: smallest budget reaching 50% on average).

	grid	ours	no order	grid FST	grid Bonf.
synthetic	16^2	7.6k	24.6k	58.1k	77.1k
	32^2	16.6k	116k	256k	339k
	48^2	29.6k	270k	576k	763k
Rosenthal	16^2	5.3k	7.7k	112k	135k
316L	32^2	19.5k	38.0k	493k	653k
	48^2	42.5k	93.5k	1.11M	1.77M
LM	12^2	[TBD:]	[TBD:]	[TBD:]	[TBD:]

Table 2: Fixed confidence on the synthetic window (good side information; median of 4 runs). LB: Theorem 2. The target was fully certified in 23 of 24 runs (the exception, at 32^2, hit a probe time-out, a heuristic outside Theorem 4).

	with the ordering			without	
grid	search	LB	ratio	per-setting	LB
8^2	14.2k	3.4k	4.2	21.9k	4.5k
16^2	50.3k	8.8k	5.7	100.0k	18.7k
32^2	165.6k	19.4k	8.5	457.7k	77.0k
48^2	334.6k	24.8k	13.5	—	174.4k
LM 12^2	[TBD:]	[TBD:]	[TBD:]	[TBD:]	[TBD:]

Fixed confidence. Table 2 and Figure 2. The ordered bound grows roughly linearly in n and the unordered one quadratically, as Theorem 2 predicts. Both methods pay a similar multiple-testing price over their own bound (per-setting: 4.8–5.9×; $\ln(16MN/(\alpha w))/K_1 \approx 5$ at 32^2); the search's extra growth with n is the $O(\log n)$ probe factor. With optimistic side information at 32^2 the search needs 215k trials against 458k without the ordering.

Validity. With every setting exactly at the tolerance (the worst case), the false-certification rate is 0–2.75% across configurations at $\alpha = 5\%$ (400 runs each); no unsafe setting was certified in any efficiency run.

Model-based baseline. The GP level-set certificate certifies an unsafe setting in 40–100% of runs at confidence parameter 2 and still 7.5–20% at 4, where it certifies at most 69% (drug screen) and typically under 25% of the region; ours: 0% and 54–84%. Language model: [TBD:].

Ablations. The ordering and the allocation rule matter most (no ordering +69 to +213%; greedy allocation +63 to +94%); weights, pooling and bet seeding give smaller gains; a fixed maximum bet fails when relevant rates are near the tolerance.

When monotonicity fails. A pocket of unsafe settings inside the region is certified by spreading in 75–92% of runs; an audit re-testing every certified setting (about 1.2× the budget) catches gross violations (96–100%) but rarely mild ones (4–9%).

7 Related work

Anytime-valid inference and e-values: Ville [1939], Shafer [2021], Ramdas et al. [2023], Vovk and Wang [2021], Wang and Ramdas [2022], Waudby-Smith and Ramdas [2024]. *Multiple testing with structure:* closed testing [Marcus et al., 1976], sequential rejection [Goeman and Solari, 2010], graphical procedures [Bretz et al., 2009], closure for monotone bi-factorial




Figure 2: Fixed confidence on the synthetic window: cost at the stopping time and the lower bounds of Theorem 2.

dose designs [Hellmich and Lehmacher, 2005]. *Adaptive testing and bandits:* Jamieson and Jain [2018], Xu et al. [2021]; thresholding bandits [Locatelli et al., 2016] and their monotone versions [Garivier et al., 2017, Cheshire et al., 2020, 2021]; lower bounds [Garivier and Kaufmann, 2016, Kaufmann et al., 2016, Garivier et al., 2019]; multi-fidelity best-arm identification [Poiani et al., 2022, 2024]. *Risk control for configurations and LLM evaluation:* Angelopoulos et al. [2025], Laufer-Goldshtein et al. [2023], Quach et al. [2024], Joshi et al. [2025]; anytime-valid evaluation of a single system [Zhou et al., 2026b,a]. *Predictions and simulators inside tests:* prediction-powered inference and e-values [Angelopoulos et al., 2023, Csillag et al., 2025], active inference [Zrnic and Candès, 2024], simulator-guided betting for one robot's mean performance [Chen et al., 2026, Chen and Weng, 2026]; we use side information only for allocation and weights, over a whole region. *Safe exploration and level sets:* Sui et al. [2015], Losalka and Scarlett [2023, 2024], Gotovos et al. [2013], Mason et al. [2022]. *Applications:* adaptive experimental design for AM process parameters [BEAM authors (Washington State University; incl. J. R. Doppa), 2026]; dose finding for combinations [Wages et al., 2011].

8 Limitations

Assumption A is load-bearing (Section 6); thin regions gain less at coarse resolution; the multiple-testing factor dominates the gap to the lower bound; the language-model study uses a small model and automatic judges; the manufacturing studies are simulated with placeholder calibrations.

References

Loubna Ben Allal et al. SmolLM2: when smol goes big – data-centric training of a small language model. *arXiv preprint arXiv:2502.02737*, 2025.

Anastasios N. Angelopoulos, Stephen Bates, Clara Fannjiang, Michael I. Jordan, and Tijana Zrnic. Prediction-powered inference. *Science*, 382(6671):669–674, 2023.

Anastasios N. Angelopoulos, Stephen Bates, Emmanuel J. Candès, Michael I. Jordan, and Lihua Lei. Learn then test: calibrating predictive algorithms to achieve risk control. *The Annals of Applied Statistics*, 19:1641–1662, 2025. arXiv:2110.01052.

BEAM authors (Washington State University; incl. J. R. Doppa). Discovery of feasible 3D printing configurations for metal alloys via AI-driven adaptive experimental design. *arXiv preprint arXiv:2601.17587*, 2026.

C. I. Bliss. The toxicity of poisons applied jointly. *Annals of Applied Biology*, 26(3):585–615, 1939.

Frank Bretz, Willi Maurer, Werner Brannath, and Martin Posch. A graphical approach to sequentially rejective multiple test procedures. *Statistics in Medicine*, 28(4):586–604, 2009.

Yujia Chen and Bowen Weng. Betting for sim-to-real performance certificates. *arXiv preprint arXiv:2608.21572*, 2026.

Yujia Chen, Zaid Mahboob, and Bowen Weng. Betting for sim-to-real performance evaluation. In *Robotics: Science and Systems*, 2026. arXiv:2604.24018.

James Cheshire, Pierre Ménard, and Alexandra Carpentier. The influence of shape constraints on the thresholding bandit problem. In *Conference on Learning Theory*, volume 125 of *PMLR*, pages 1228–1275, 2020.

James Cheshire, Pierre Ménard, and Alexandra Carpentier. Problem dependent view on structured thresholding bandit problems. In *International Conference on Machine Learning*, volume 139 of *PMLR*, 2021.

Daniel Csillag, Claudio José Struchiner, and Guilherme Tegoni Goedert. Prediction-powered e-values. In *International Conference on Machine Learning*, volume 267 of *PMLR*, 2025.

Aurélien Garivier and Emilie Kaufmann. Optimal best arm identification with fixed confidence. In *Conference on Learning Theory*, 2016.

Aurélien Garivier, Pierre Ménard, and Laurent Rossi. Thresholding bandit for dose-ranging: the impact of monotonicity. *arXiv preprint arXiv:1711.04454*, 2017.

Aurélien Garivier, Pierre Ménard, and Gilles Stoltz. Explore first, exploit next: the true shape of regret in bandit problems. *Mathematics of Operations Research*, 44(2):377–399, 2019.

Jelle J. Goeman and Aldo Solari. The sequential rejection principle of familywise error control. *The Annals of Statistics*, 38(6):3782–3810, 2010.

Alkis Gotovos, Nathalie Casati, Gregory Hitz, and Andreas Krause. Active learning for level set estimation. In *International Joint Conference on Artificial Intelligence*, 2013.

Martin Hellmich and Walter Lehmacher. Closure procedures for monotone bi-factorial dose-response designs. *Biometrics*, 61(1):269–276, 2005.

Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. The curious case of neural text degeneration. In *International Conference on Learning Representations*, 2020.

Kevin Jamieson and Lalit Jain. A bandit approach to sequential experimental design with false discovery control. In *Advances in Neural Information Processing Systems*, 2018.

Sunay Joshi, Yan Sun, Hamed Hassani, and Edgar Dobriban. MultiRisk: multiple risk control via iterative score thresholding. *arXiv preprint arXiv:2512.24587*, 2025.

Emilie Kaufmann, Olivier Cappé, and Aurélien Garivier. On the complexity of best-arm identification in multi-armed bandit models. *Journal of Machine Learning Research*, 17 (1):1–42, 2016.

Wayne E. King, Holly D. Barth, Victor M. Castillo, Gilbert F. Gallegos, John W. Gibbs, Douglas E. Hahn, Chandrika Kamath, and Alexander M. Rubenchik. Observation of keyhole-mode laser melting in laser powder-bed fusion additive manufacturing. *Journal of Materials Processing Technology*, 214(12):2915–2925, 2014.

Bracha Laufer-Goldshtein, Adam Fisch, Regina Barzilay, and Tommi Jaakkola. Efficiently controlling multiple risks with Pareto testing. In *International Conference on Learning Representations*, 2023.

Andrea Locatelli, Maurilio Gutzeit, and Alexandra Carpentier. An optimal algorithm for the thresholding bandit problem. In *International Conference on Machine Learning*, 2016.

Arpan Losalka and Jonathan Scarlett. Benefits of monotonicity in safe exploration with Gaussian processes. In *Conference on Uncertainty in Artificial Intelligence*, volume 216 of *PMLR*, 2023.

Arpan Losalka and Jonathan Scarlett. No-regret algorithms for safe Bayesian optimization with monotonicity constraints. In *International Conference on Artificial Intelligence and Statistics*, volume 238 of *PMLR*, pages 3232–3240, 2024.

Ruth Marcus, Eric Peritz, and K. Ruben Gabriel. On closed testing procedures with special reference to ordered analysis of variance. *Biometrika*, 63(3):655–660, 1976.

Blake Mason, Lalit Jain, Subhojyoti Mukherjee, Romain Camilleri, Kevin Jamieson, and Robert Nowak. Nearly optimal algorithms for level set estimation. In *International Conference on Artificial Intelligence and Statistics*, volume 151 of *PMLR*, pages 7625–7658, 2022.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. In *International Conference on Learning Representations*, 2017.

Riccardo Poiani, Alberto Maria Metelli, and Marcello Restelli. Multi-fidelity best-arm identification. In *Advances in Neural Information Processing Systems*, 2022.

Riccardo Poiani, Rémy Degenne, Emilie Kaufmann, Alberto Maria Metelli, and Marcello Restelli. Optimal multi-fidelity best-arm identification. In *Advances in Neural Information Processing Systems*, 2024.

Victor Quach, Adam Fisch, Tal Schuster, Adam Yala, Jae Ho Sohn, Tommi S. Jaakkola, and Regina Barzilay. Conformal language modeling. In *International Conference on Learning Representations*, 2024.

Aaditya Ramdas, Peter Grünwald, Vladimir Vovk, and Glenn Shafer. Game-theoretic statistics and safe anytime-valid inference. *Statistical Science*, 38(4):576–601, 2023.

Daniel Rosenthal. The theory of moving sources of heat and its application to metal treatments. *Transactions of the ASME*, 68:849–866, 1946.

Glenn Shafer. Testing by betting: a strategy for statistical and scientific communication. *Journal of the Royal Statistical Society: Series A*, 184(2):407–431, 2021.

Max Simchowitz, Kevin Jamieson, and Benjamin Recht. The simulator: understanding adaptive sampling in the moderate-confidence regime. In *Conference on Learning Theory*, 2017.

Yanan Sui, Alkis Gotovos, Joel Burdick, and Andreas Krause. Safe exploration for optimization with Gaussian processes. In *International Conference on Machine Learning*, 2015.

Ming Tang, P. Chris Pistorius, and Jack L. Beuth. Prediction of lack-of-fusion porosity for powder bed fusion. *Additive Manufacturing*, 14:39–48, 2017.

Jean Ville. *Étude critique de la notion de collectif*. Gauthier-Villars, Paris, 1939.

Vladimir Vovk and Ruodu Wang. E-values: calibration, combination and applications. *The Annals of Statistics*, 49(3): 1736–1754, 2021.

Nolan A. Wages, Mark R. Conaway, and John O'Quigley. Continual reassessment method for partial ordering. *Biometrics*, 67(4):1555–1563, 2011.

Ruodu Wang and Aaditya Ramdas. False discovery rate control with e-values. *Journal of the Royal Statistical Society: Series B*, 84(3):822–852, 2022.

Ian Waudby-Smith and Aaditya Ramdas. Estimating means of bounded random variables by betting. *Journal of the Royal Statistical Society: Series B*, 86(1):1–27, 2024.

Sean Welleck, Ilia Kulikov, Stephen Roller, Emily Dinan, Kyunghyun Cho, and Jason Weston. Neural text generation with unlikelihood training. In *International Conference on Learning Representations*, 2020.

Ziyu Xu, Ruodu Wang, and Aaditya Ramdas. A unified framework for bandit multiple testing. In *Advances in Neural Information Processing Systems*, 2021.

Siyu Zhou, Patrick Vossler, Venkatesh Sivaraman, Yifan Mai, and Jean Feng. Adaptive auditing of AI systems with anytime-valid guarantees. *arXiv preprint arXiv:2605.07002*, 2026a.

Zhijian Zhou, Zesheng Ye, Zhaorun Chen, Bo Li, and Feng Liu. CELEUS: certifiable and efficient LLM evaluation via e-processes. In *International Conference on Machine Learning*, 2026b. arXiv:2606.20820.

Tijana Zrnic and Emmanuel J. Candès. Active statistical inference. In *International Conference on Machine Learning*, 2024.

A Proofs

A.1 Setup

Trial $t = 1, 2, \ldots$ is run at x_t and yields $Y_t \in \{0,1\}^M$. Given the past and $x_t = x$, $Y_t \sim P_x$, independently of the past. Let $\mathcal{F}_t = \sigma(x_1, Y_1, \ldots, x_t, Y_t, U)$, where U is independent side information (simulator output, pilot data, internal randomization). The allocation x_t is $\mathcal{F}_{t-1}$-measurable: trials in a batch are chosen before any of them is observed, and processing them one at a time in a fixed order keeps this property.

Lemma 1. *If $p_m(x) \geq \varepsilon_m$ then $K_{m,x}$ is a nonnegative supermartingale with respect to $(\mathcal{F}_t)$. If $p_m(x) \leq q\varepsilon_m$, the rejection process $R_{m,x}(t) = \prod_{s \leq t : x_s = x}(1 + \mu_s(Y_{s,m} - q\varepsilon_m))$, $\mu_s \in [0, 1/(q\varepsilon_m))$ predictable, is a nonnegative supermartingale.*

Proof. Nonnegativity: $1+\lambda(\varepsilon-1) \geq 1-c > 0$. On $\{x_t = x\}$, $\mathbb{E}[K(t) \mid \mathcal{F}_{t-1}] = K(t-1)(1+\lambda_t(\varepsilon - p_m(x))) \leq K(t-1)$, since λ_t and x_t are $\mathcal{F}_{t-1}$-measurable and the conditional law of Y_t given $\mathcal{F}_{t-1}$ and $x_t = x$ is P_x. On $\{x_t \neq x\}$, $K(t) = K(t-1)$. The rejection process is identical with the roles of failures and successes exchanged. A fixed-weight average of such processes (our hedge) is again a nonnegative supermartingale. □

A.2 Validity of the cone rule

Proof of Theorem 1. Let $D = \{(m, y) : p_m(y) \geq \varepsilon_m\}$. Under Assumption A, if $(m, x) \in D$ and $y \preceq_m x$ then $p_m(y) \geq p_m(x) \geq \varepsilon_m$, so $\{m\} \times \mathcal{C}_m(x) \subseteq D$. Let $E(t) = \sum_{(m,y)\in D} w_{m,y} K_{m,y}(t)$, a nonnegative supermartingale by Lemma 1 with $E(0) \leq 1$. A false certification of $(m, x) \in D$ at t means $1/\alpha \leq S_m(x, t) \leq E(t)$. By Ville's inequality $\mathbb{P}(\sup_t E(t) \geq 1/\alpha) \leq \alpha$. □

Remarks: nothing about the allocation is used beyond predictability; certification is sticky, and the bound covers "ever certified"; with uniform weights $S_m(x) \geq \max_{y \in \mathcal{C}_m(x)} w K_y$, so the cone rule certifies everything Bonferroni with spreading certifies.

A.3 Correctness of the search

Proof of Theorem 4, correctness. Validity is Theorem 1. Completeness: let G be the event that no (m, x) with $p_m(x) \leq q\varepsilon_m$ is rejected directly. By Lemma 1, Ville and a union bound over MN pairs, $\mathbb{P}(G^c) \leq \beta$. On G no $x \in T$ is rejected or excluded: a spread rejection of x for m comes from a direct rejection at some y with $x \preceq_m y$, but then $p_m(y) \leq p_m(x) \leq q\varepsilon_m$, contradicting G; exclusion through another mode is the same argument for that mode. Termination: every probe ends almost surely (if $p < \varepsilon$ the certification statistic has positive expected log-growth under the hedge's best fixed bet; if $p > q\varepsilon$ the rejection process does; since $q < 1$ every p is covered), each probe decides at least one configuration, and $\mathcal{X}$ is finite. So on G, $\tau < \infty$ and $T \subseteq C$. □

A.4 Expected passage times

Lemma 2 (Wald)**.** *Let $Z_k = \sum_{i \leq k} \xi_i$ with ξ_i i.i.d., bounded, $\mathbb{E}\xi = g > 0$, and $\tau = \min\{k : Z_k \geq c\}$. Then $\mathbb{E}\tau \leq (c + b)/g$, $b = \operatorname{ess\,sup} \xi$.*

Proof. $\mathbb{E}\tau < \infty$ for positive drift with bounded increments; by Wald's identity $\mathbb{E}Z_\tau = g\mathbb{E}\tau$, and $Z_\tau \leq c + b$. □

Applied to the log-wealth of the best fixed bet in the hedge (held with weight $1/16$) and $S_m(x) \geq w_{m,x} K_{m,x}$: a setting with rate $p < \varepsilon$ sampled exclusively is certified within an expected $T_c(p) = (\ln(16/(\alpha w)) + \ln(1 + \lambda^*\varepsilon))/g_c(p)$ trials, where $g_c(p) = \max_j \mathbb{E}\ln(1 + \lambda_j(\varepsilon - Y))$. Likewise rejection at $p > q\varepsilon$ within $T_r(p) = (\ln(5MN/\beta) + b')/g_r(p)$. This gives Theorem 3 by summing over the cover (plus B per cover point when certification is checked once per batch).

Lemma 3 (probes per row)**.** *Fix m and a row ordered safest to riskiest for m; let a be the last position with $p_m \leq q\varepsilon_m$ and b the first with $p_m \geq \varepsilon_m$. On the event that no e-process misleads (probability at least $1 - \alpha - \beta$), a probe at i can certify only if $i < b$ and reject only if $i > a$, and if the first probe is at s the row is decided after at most $2\lceil \log_2 d \rceil + 2$ probes, $d = \max(b - s, s - a, 1)$.*

Proof. If the first probe certifies, galloping probes $s+1, s+2, s+4, \ldots$ and cannot certify at or beyond b, so it rejects within $\lceil \log_2(b-s) \rceil + 1$ probes, leaving at most $b-s$ undecided positions in the bracket. A probe at the median of the undecided positions certifies it and everything safer or rejects it and everything riskier, halving them. Positions decided elsewhere only shrink the bracket. The other case is symmetric. □

Proof of Theorem 4, cost. Number the probes in the order they start. When probe k starts at (m, x), its processes start fresh and the trials it will see at x are i.i.d. and independent of the past; since $S_m(x) \geq w_{m,x} K_{m,x}$, it ends no later than the first of the two passage times of Lemma 2, so its conditional expected length is at most $\min(T_c, T_r) + B \leq C^* + B$ (B for checking once per batch). Whether probe k happens is known when it starts, so the expected total is at most $(C^* + B)$ times the expected number of probes. By Lemma 3 that number is at most $\sum_{m,j} P_{m,j}$ on the good event, and at most MN otherwise. □

A.5 Lower bounds

We use the transportation lemma [Kaufmann et al., 2016, Lemma 1]: for instances ν, ν', a stopping time τ and $E \in \mathcal{F}_\tau$, $\sum_x \mathbb{E}_\nu[N_x(\tau)] \mathrm{KL}(\nu_x, \nu'_x) \geq \mathrm{kl}(\mathbb{P}_\nu(E), \mathbb{P}_{\nu'}(E))$. It needs only $\mathbb{E}_\nu[\tau] < \infty$ (otherwise there is nothing to prove): then $\tau < \infty$ ν-a.s., the restriction of $\mathbb{P}_\nu$ to $\mathcal{F}_\tau$ is absolutely continuous with respect to that of $\mathbb{P}_{\nu'}$ with density the likelihood ratio at τ, Wald's identity gives the left side as the expected log-likelihood ratio, and the data-processing inequality gives the right side; τ may be infinite under ν'. If $\mathbb{P}_{\nu'}(E) \leq \alpha$ the right side is at least $g(\mathbb{P}_\nu(E))$, and if $\mathbb{P}_{\nu'}(E) \geq 1-\beta$ it is at least $f(\mathbb{P}_\nu(E))$. We restrict to instances with independent modes (a lower bound on a subclass is a lower bound), so KL adds over modes, and a trial at y counts once in every constraint that involves y.

Proof of Theorem 2. (i) For m and t, let ν' set $p'_m(y) = \max(p_m(y), \varepsilon_m + \eta)$ for $y \preceq_m t$ and leave everything else unchanged. ν' satisfies Assumption A: the riskier cone of t is closed toward risk, and raising a monotone function to at least a constant on such a set keeps it monotone (check the three cases of a comparable pair). In ν', t is unsafe, so $\mathbb{P}_{\nu'}(T \subseteq C) \leq \alpha$, while $\mathbb{P}_\nu(\tau < \infty, T \subseteq C) \geq 1-\beta$; apply the lemma and let $\eta \to 0$.

(ii) Lowering alternative: $p''_m(z) = q\varepsilon_m$, everything else unchanged. This keeps Assumption A because every setting strictly safer than z has $p_m \leq q\varepsilon_m$ and every riskier one has $p_m \geq p_m(z) > q\varepsilon_m$. In ν'', $z \in T$, so $\mathbb{P}_{\nu''}(z \in C) \geq 1-\beta$, giving $A_z \geq f(\pi)$ with $\pi = \mathbb{P}_\nu(z \in C)$. Raising alternative: as in (i) with t replaced by z; z is unsafe there, giving $B_z \geq g(\pi)$ for the same π.

R is convex: its lower-left boundary is $B = g(f^{-1}(A))$ on the range of f, an increasing convex function composed with a decreasing convex one. Replacing R by finitely many supporting half-planes $wA + (1-w)B \geq \min_\pi [wf(\pi) + (1-w)g(\pi)]$ gives a linear program with a smaller value, which is what we report.

Without the ordering, alternatives may change a single setting x, so the constraints decouple: for $x \in T$, $n_x \geq K_1 / \min_m \mathrm{KL}(p_m(x) \| \varepsilon_m)$ for safe $x \notin T$, $n_x \geq \min_\pi \max(f(\pi)/R_x, g(\pi)/C_x)$ with $R_x = \sum_{m: p_m(x) > q\varepsilon_m} \mathrm{KL}(p_m(x) \| q\varepsilon_m)$ and $C_x = \min_m \mathrm{KL}(p_m(x) \| \varepsilon_m)$; for unsafe x, $n_x \geq \mathrm{kl}(\alpha, 1-\beta)/R_x$. □

Points to check. (1) Lemma 1 with batched allocation; (2) the closed-testing interpretation of the cone rule; (3) that no target configuration is rejected by spreading or exclusion on G; (4) the transportation lemma when τ may be infinite under the alternative; (5) that the alternatives keep Assumption A, and the sharing of trials across modes; (6) convexity of R; (7) Lemma 3 with spreading from other rows.