Development of a Machine Learning Model for Enhancing the Security of the Internet of Things (IoT) System

Kamalakar Raminenei[1](✉), Vratika Gupta[2], Thirupathi Durgam[3], and Dhiraj Kapila[4]

[1] School of Computer Science and Artificial Intelligence, SR University, Warangal, Telangana, India
[2] Research Scholar, College of Computing Science & Information Technology, Teerthanker Mahaveer University, Moradabad, India
[3] ECE, St. Martin's Engineering College Secunderabad, Secunderabad, Telangana, India
[4] Department of Computer Science & Engineering, Lovely Professional University, Phagwara, Punjab, India
dhiraj.23509@lpu.co.in

Abstract. In the previous decade, Internet of Things (IoT) systems have grown into a worldwide behemoth that has encompassed every element of everyday existence by enhancing human existence with uncountable intelligent assistance. Due to the ease of usage and increasing need for smart gadgets and networks, IoT is experiencing more security concerns today than ever before. As a result, a powerful constantly improved and current security solution is necessary for contemporary IoT systems. A significant technological improvement in Machine Learning (ML) has been observed, opening up several potential study avenues for tackling existing and prospective IoT concerns. The fundamental goal of this study is to implement an ML-based model for IoT security enhancement. In the initial phase of this study approach, feature scaled has been performed on the UNSW-NB15 database utilizing the Minimum-maximum idea of normalizing to reduce data leaks on the experimental statistics. Principal Components Assessment (PCA) has been utilized to reduce dimensions in the following phase. Finally, for the investigation, 6 suggested ML solutions have been applied. The outcomes from experiments have been assessed using a validating database. The outcomes have been compared to previous research, and the outcomes have been compatible with an accuracy of 99.99 percent and an MCC-Mathew correlation coefficient of 99.97 percent.

Keywords: Internet of things · Security · Machine learning · Anomaly detection · and Intrusion prevention

1 Introduction

As the Internet of Things (IoT) increases rapidly, it generates a vast amount of data. There are numerous detectors, including those that assess air standards, temperature, a global positioning system, stresses, and movement. Substantial amounts of statistics can

© The Author(s), under exclusive license to Springer Nature Singapore Pte Ltd. 2025
A. Kumar et al. (Eds.): ICDSMLA 2023, LNEE 1273, pp. 1086–1093, 2025.
https://doi.org/10.1007/978-981-97-8031-0_114

be saved on several gadgets. Due to the massive number of statistics, data assessment systems that function in real-time were needed. At each phase, IoT-generated facts overwhelm present big data systems [1].

The IoT links electronic gadgets to a system and transmits data without the need for human involvement [2]. Customers may utilize their gadgets distantly from anywhere, exposing them to various threats. IoT networks have more and more linked devices every day. For example, in contrast to 8.4 billion linked objects in 2020, there are going to be approximately 20.4 billion linked items worldwide in 2022 [3]. Our daily activities are significantly impacted by the IoT in several manners, particularly in the societal, business, and financial realms. The IoT sector is anticipated to increase its earnings from 892 billion in 2018 to 4 trillion by 2025 as part of the expansion of the electronic economy [4].

With a growing number of electronic appliances currently the security of IoT systems is a major worry, as the gadgets transport confidential and important data of consumers. Smart residences and smartwatches, for instance, save details about the customer's whereabouts, name and address, medical history, and so on, all of which must be kept private and concealed. As numerous IoT gadgets have restricted assets (such as energy, bandwidth, storage, and computing), extremely flexible and complicated algorithm-oriented security approaches are inapplicable [5].

The most fundamental requirement for IoT networking is the protection of each of the interconnected equipment, applications, and gadgets. The enormous size of IoT systems creates significant difficulties in several regions, such as gadget administration, handling information, computation, security, and confidentiality. As the IoT expands, several security issues are being brought up as potential hazards [6]. The new IoT uses, like the ones stated previously, are not going to be capable of satisfying the demands of individuals or the requirements of the community as a whole without a trustworthy structure, and they risk losing each of their strengths. IoT gadgets typically function on several layers, notably the application, the middleware or supporting the networks and information transmission, and the perceptual or detecting layer [7].In IoT uses, every one of these tiers has a specific collection of responsibilities and pertinent innovations to carry out, and everyone introduces a fresh collection of problems and security hazards. The most frequent IoT threats are, for instance, denial of service assaults, spoofing attempts, blocking, eavesdropping, manipulation of data, person-in-the-middle assaults, malevolence, etc. Therefore, prospective IoT security methods like authentication, access management, danger and risk assessment, malware assessment, anomalous or intrusion identification, and avoidance, etc., based on the character of the security challenges, might be helpful. The traditional ways of handling them are no more efficient because of the increased development in security dangers and assaults and the complicated nature of cybersecurity events.

Machine learning (ML) and deep learning (DL) oriented solutions are a possible substitute for IoT network cybersecurity [8]. One of the most sophisticated artificial intelligence methods is ML, which may surpass other solutions in dynamic systems without explicitly coding. A computerized system can be taught to recognize distinct assaults and deliver the appropriate defense strategy using ML techniques. In this situation, assaults can be quickly identified [9]. Additionally, ML approaches seem to hold promise for smartly identifying novel assaults employing learning capabilities.

Hence this research aims to develop an ML model for enhancing the security of IoT systems.

2 Literature Review

The research [10] and [11] are two groundbreaking investigations in cyber security identification and avoidance. For the application level, new intrusion detection has been suggested [12]. The majority of the investigations that the researchers analyzed had a network intrusion identification and prevention platform as their primary objective. There have been many different uses for ML approaches.

For example, [13] uses a Support Vector Machine (SVM) classifier on the extremely popular KDD'99 cup database to categorize several assaults, including DoS, Probe or Scan, U2R, R2L, and ordinary traffic.

A logistic regression framework has been used in multiple investigations [14] to categorize invasions and harmful traffic. Another popular ML technique is the k-nearest neighbors (KNN), which uses an instance-oriented learning technique to classify data points depending on their KNN.

The study [15] employs the decision trees (DT) classification approach to develop intrusion detection structures in their investigations.

In their binary categorization approach, [16] uses random forest learning composed of several DTs to identify abnormalities and mitigate IoT cybersecurity concerns in smart cities.

The research [17] reviewed numerous IoT security vulnerabilities and highlighted ML-based issues and study gaps employing 78 papers published up till 2017. [18] discussed various IoT assault types, including spoofing, denial of service, blocking, and spying assaults, and proposed potential cybersecurity measures based on IoT authorization, control of access, virus, and safe unloading ML solutions. Overall, thirty publications have been mentioned, and those papers provide 4 distinct potential ML-based IoT cybersecurity solutions.

Overall, thirty publications have been mentioned, and those papers provide 4 distinct potential ML-based IoT cybersecurity solutions [19].

A comprehensive study on ML-based cybersecurity of IoT was also released shortly by a different study team [20], with the researchers concentrating primarily on detecting intrusions and different ML-related applications to the IoT network.

3 Materials and Method

3.1 The Suggested ML Model

This part outlines the suggested ML modelfor enhancing the security of IoT systems. The data collected by a mobile device and its detectors is transferred to the cloud. Data on the cloud is not secure since it is susceptible to breaching. The breach can be carried out straight on the cloud or through transfer. The UNSW-NB15 database was used in this study. This database, which was just set free, comprises current assault variants. In the initial phase of this study approach, feature scaled has been performed

on the UNSWNB15 database utilizing the min-max notion of normalized to reduce data leaks on the experimental statistics. PCA has been used to reduce size in the following phase. Following the gathering and uploading of a database, the initial assessment is data preprocessing. Data preparation is critical since it aids in the removal of outliers and unnecessary characteristics. For data preprocessing, a normalizing approach using the Min-max methodology was utilized. The maximum-minimum data is passed into the PCA feature selection method. From the 49 characteristics in the sample, the PCA chose ten significant elements. The XG-Boost, Cat-Boost, KNN, SVM, QDA, & NB classification algorithms are then developed on the smaller database. Figure 1 depicts the design of the suggested ML model.

3.2 Data Preprocessing

It is an important task in the ML area since it serves to remove faults in the database. It represents the initial level of the approach that has been suggested. It is planned to convert unprocessed system IoT assault data into a successful format for future research.

3.3 Normalization

It is a scaling of features strategy that aims to possess every feature number of the same size. There have been several approaches for normalizing, such as standardized period, z-value, and min-max. In this research, we applied the min-max normalizing method.

3.4 Feature Selection

It is a procedure of selecting features that are known, and it adds the finest ones to the predictive factor while reducing training duration and preventing computing complications. The feature-selecting methodology is a dimensional elimination method that may be employed to eliminate unimportant characteristics from highly dimensional databases like IDS statistics. The features include data about the targets; the greater the number of characteristics, the greater the data and discriminatory authority. Nevertheless, possessing greater characteristics does occasionally imply having higher classification authority.

3.5 Principal Component Assessment (PCA)

The PCA is an unsupervised methodology for selecting widely employed features and the earliest methodology in multidimensional quantitative assessment. The purpose of using PCA is to minimize dimensionality by retaining important characteristic data within the database. It decreases the number of variables by employing orthogonal linear combos with substantial variation. PCA additionally chooses the most significant subgroups of the database features for categorization. We employ PCA for reducing the area of characteristics in this research, with ten elements chosen to reduce the dimensions of the UNSW-NB15 database.



Fig. 1: The suggested ML models.

4 Result and Discussion

The framework's performance has been assessed in terms of accuracy, precision, AUC, recall, F1-value, kappa, and MCC. Tables 1, Table 2, Fig. 2, and Fig. 3 display the empirical outcomes of the studies for the offered frameworks.

Table 1: Performance assessment of the frameworks accuracy, precision, AUC, and F1-value.

Solutions	Accuracy	Precision	AUC	F1-value
NB	97.14	96.72	99.77	97.94
QDA	99.97	99.99	1	99.98
SVM	99.98	1	0	99.99
KNN	99.98	1	1	99.99
Cat Boost	99.99	1	1	99.99
Xg-boost	99.99	1	1	1

The performance of the suggested technique XgBoost was higher than that of every other suggested technique, as shown in Tables 1 and 2, in terms of accuracy, precision, F1, and MCC. The Cat Boost likewise beat other suggested approaches, with an accuracy of 99.9, precision of 1, F1 of 99.9, and MCC of 99.9. It is also noted that the KNN provided an accuracy of 99.9, precision of 1, F1 of 99.9, and MCC of 99.9. The suggested SVM had an accuracy of 99.9, precision of 0, F1 of 1, and MCC of 99.9. The suggested QDA



Fig. 2: Performance assessment of the frameworks accuracy, precision, AUC, and F1-value.

Table 2: Performance assessment of the frameworks recall, kappa, MCC, and training duration

Solution	Recall	Kappa	MCC	Training duration
NB	99.2	93.28	93.41	0.01
QDA	99.97	99.94	99.94	0.114
SVM	99.98	99.96	99.96	0.032
KNN	99.98	99.96	99.96	0.091
Cat Boost	99.99	99.97	99.97	18.09
Xg-boost	99.99	99.97	99.97	0.709

had an accuracy of 99.9, precision of 99.9, F1 of 99.9, and MCC of 99.9. Finally, the suggested NB achieved 97.1 accuracy, 96.7 precision, 97.9 F1 and 93.4 MCC.

5 Conclusion

This research examined an ML-based model for IoT security enhancement. To achieve this, this studyskillfully combined feature dimensional compression and ML solutions to create a smart IDS that can recognize suspicious activity on IoT cybersecurity. We examined the effectiveness of the proposed framework employing the UNSW-NB15 database to find the optimal solution for the ML-oriented IDS solution. The IoT's growth has hit a severe snag due to cybersecurity issues. ML-based IDS might be utilized to address cybersecurity detection duties. To choose 10 parts, the scale has been reduced using the PCA method. The framework has been validated using the new database UNSW-NB15, which backs contemporary threats and is optimal for IoT uses. Additionally, the suggested framework reduces interaction overhead and does not need an external key, as



Fig. 3: Performance assessment of the frameworks Recall, Kappa, MCC, and Training Duration

is necessary for IoT security encryption solutions. The findings show that the proposed technique accomplishes greater F1 values, suggesting a better total detection efficiency. This research can conclude from the empirical findings of system simulators and laboratory setups that applying ML solutions for effective anomaly identification in the context of IoT is both achievable and possible. The suggested PCA-basedXg-Boost, Cat Boost, KNN, SVM, QDA, & NB algorithms outperform previous research in terms of accuracy and can handle the challenge of labeled information in IoT systems. The results of our study outperformed the latest developments in terms of validating database, precision, F1-value, MCC, & accuracy of the 2 suggested frameworks, reaching 99.9 percent. The framework may be structured as a component that identifies assaults in IoT contexts with smart towns, residences, and medical care equipment. The next step is to use an ensemble framework with a new database appropriate for the IoT context. Furthermore, this method can be improved in the years to come by using DL frameworks. The BoT-IoT database, in particular, will be used for empirical research and contrasted to the UNSWNB-15 employing a DL algorithm for system traffic categorization.

References

1. Raghuvanshi, A., Singh, U.K.: WITHDRAWN: Internet of Things for smart cities-security issues and challenges (2020)
2. Sarker, I.H., Abushark, Y.B., Alsolami, F., Khan, A.I.: Intrudtree: a machine learning-based cyber security intrusion detection model. Symmetry **12**(5), 754 (2020)
3. Lokhande, M.P., Patil, D.D., Patil, L.V., Shabaz, M.: Machine-to-machine communication for device identification and classification in secure telerobotics surgery. Secur. Commun. Netw. **2021**, 1–16 (2021)
4. Hemamalini, V., et al.: Food quality inspection and grading using efficient image segmentation and machine learning-based system. J. Food Qual. **2022**, 1–6 (2022)

5. Gera, T., Singh, J., Mehbodniya, A., Webber, J.L., Shabaz, M., Thakur, D.: Dominant feature selection and machine learning-based hybrid approach to analyze Android ransomware. Secur. Commun. Netw. **2021**, 1–22 (2021)
6. Sharma, S., Krishna, C.R., Kumar, R.: RansomDroid: Forensic analysis and detection of Android Ransomware using unsupervised machine learning technique. Forensic Sci. Int.: Digit. Investig. **37**, 301168 (2021)
7. Raghuvanshi, A., Singh, U.K., Joshi, C.: A review of various security and privacy innovations for IoT applications in healthcare. Advanced Healthcare Systems: Empowering Physicians with IoT-Enabled Technologies, pp. 43–58 (2022)
8. Gaur, V., Kumar, R.: Analysis of machine learning classifiers for early detection of DDoS attacks on IoT devices. Arab. J. Sci. Eng. **47**(2), 1353–1374 (2022)
9. Chopra, A., Behal, S., Sharma, V.: Evaluating machine learning algorithms to detect and classify DDoS attacks in IoT. In 2021 8th international conference on computing for sustainable global development (INDIACom), pp. 517–521. IEEE (2021)
10. Hamid, Y., Sugumaran, M., Journaux, L.: Machine learning techniques for intrusion detection: a comparative analysis. In Proceedings of the international conference on informatics and analytics, pp. 1–6 (2016)
11. Wu, M., Zhu, Z., Xia, Y., Yan, Z., Zhu, X., Ye, N.: A Q-learning-based two-layer cooperative intrusion detection for internet of drones system. Drones **7**(8), 502 (2023)
12. Kotpalliwar, M.V., Wajgi, R.: Classification of attacks using support vector machine (SVM) on kddcup'99 ids database. In 2015 fifth international conference on communication systems and network technologies, pp. 987–990. IEEE (2015)
13. Bapat, R., Mandya, A., Liu, X., Abraham, B., Brown, D.E., Kang, H., Veeraraghavan, M.: Identifying malicious botnet traffic using logistic regression. In 2018 Systems and information engineering design symposium (SIEDS), pp. 266–271. IEEE (2018)
14. Zhang, C., Jia, D., Wang, L., Wang, W., Liu, F., Yang, A.: Comparative research on network intrusion detection methods based on machine learning. Comput. & Secur., 102861 (2022)
15. Alrashdi, I., Alqazzaz, A., Aloufi, E., Alharthi, R., Zohdy, M., Ming, H.: Ad-iot: anomaly detection of IoT cyberattacks in smart city using machine learning. In 2019 IEEE 9th annual computing and communication workshop and conference (CCWC), pp. 0305–0310. IEEE (2019)
16. Ashraf, J., et al.: IoTBoT-IDS: A novel statistical learning-enabled botnet detection framework for protecting networks of smart cities. Sustain. Cities Soc. **72**, 103041 (2021)
17. Cui, L., Yang, S., Chen, F., Ming, Z., Lu, N., Qin, J.: A survey on the application of machine learning for the internet of things. Int. J. Mach. Learn. Cybern. **9**, 1399–1417 (2018)
18. Xiao, L., Wan, X., Lu, X., Zhang, Y., Wu, D.: IoT security techniques based on machine learning: How do IoT devices use AI to enhance security? IEEE Signal Process. Mag. **35**(5), 41–49 (2018)
19. Chaabouni, N., Mosbah, M., Zemmari, A., Sauvignac, C., Faruki, P.: Network intrusion detection for IoT security based on learning techniques. IEEE Commun. Surv. & Tutor. **21**(3), 2671–2701 (2019)
20. Alaa, M., Zaidan, A.A., Zaidan, B.B., Talal, M., Kiah, M.L.M.: A review of smart home applications based on the Internet of Things. J. Netw. Comput. Appl. **97**, 48–65 (2017)