



Accelerating configuration of Reconfigurable Intelligent Surfaces through a hardware-enhanced deep learning approach

Rubén Padial-Allué ^{a,*,}, Alberto Martín-Martín ^{a,b,}, Antonio García ^{a,c,},
Encarnación Castillo ^{a,c,}, José David Fernández-Rodríguez ^{d,e,},
Marcos Baena-Molina ^{f,}, Luis Parrilla ^{a,c,}

^a Department Electronics and Computer Technology, University of Granada, Campus Universitario Fuentenueva, Granada, 18071, Spain

^b Safran Electronics & Defense, Granada, 18014, Spain

^c CITIC-UGR, University of Granada, Granada, 18071, Spain

^d ITIS Software, University of Málaga, c/Arquitecto Francisco Peñalosa 18, Málaga, 29010, Spain

^e Biomedic Research Institute of Málaga (IBIMA), c/Doctor Miguel Díaz Recio, 28, Málaga, 29010, Spain

^f Department Signal Theory, Telematics and Communications, CITIC-UGR, University of Granada, Granada, 18071, Spain

ARTICLE INFO

Keywords:

6G
Reconfigurable Intelligent Surfaces
Intelligent reflecting surfaces
Artificial intelligence
Neural networks
Field-Programmable Gate Arrays (FPGA)

ABSTRACT

The dawn of Reconfigurable Intelligent Surfaces (RIS) promises to revolutionize wireless communication by enabling dynamic control of the propagation of electromagnetic waves. However, the practical implementation of RIS demands sophisticated configuration strategies to unlock their full potential. This paper presents a hardware implementation of a Deep Learning (DL) approach to the configuration of RIS, addressing both the complexity and efficiency of the configuration process. A deep learning-based algorithm, designed to optimize the phase shifts of RIS elements and shown to enhance signal quality and system performance, is implemented on two dedicated hardware platforms based on Field-Programmable Gate Arrays (FPGA), which leads to real-time processing and adaptability. This approach leverages the inherent parallelism of FPGAs to accelerate the computationally intensive tasks associated with deep learning inference. As a matter of fact, it is possible to achieve more than 18.000 configurations per second, thus ensuring rapid and efficient RIS configuration with a novel approach within this field.

1. Introduction

The rapid advancement of wireless communication technology necessitates innovative solutions to meet the ever-increasing demands for higher data rates, improved coverage, and energy efficiency. On June 2018, after years of research and development, the initial commercial roll-out of the 5th generation (5G) mobile communication standard was successfully completed. The new generation is already delivering speeds 10 times faster than its predecessor, with up to 20-Gbps peak data rates [1]. According to the Global System for Mobile Communications Association (GSMA), a non-profit organization representing the interest of mobile networks worldwide, 5G is on track to account for 15% of the global mobile industry by 2025 [2].

However, it has become clear during the standardization process of 5G wireless networks that no single enabling technology can meet all the application requirements of 5G [3]. Consequently, researchers have already begun exploring technologies beyond 5G

* Corresponding author.

E-mail address: rubenpadial@ugr.es (R. Padial-Allué).

<https://doi.org/10.1016/j.compeleceng.2026.111101>

Received 26 November 2025; Received in revised form 2 February 2026; Accepted 4 March 2026

Available online 6 March 2026

0045-7906/© 2026 The Authors. Published by Elsevier Ltd. This is an open access article under the CC BY license (<http://creativecommons.org/licenses/by/4.0/>).