LEXIGRID

Uninstallation and Data Retention

Version 5.54.15 | Reviewed 2026-11-11

Shahryar Jahangir, Aniza Inc.

Procedures, examples, verification and operational limits. Complete commissioning on your deployment before serving customer traffic. Sample values are fictional; original keys and data must be preserved.

Contents

Uninstallation and data retention **3**

- Choose the correct procedure . . . 3
- Prepare recovery evidence . . . 3
- Root wrapper removal . . . 3
- Destructive flag . . . 3
- Native manager distinction . . . 3
- Verify and retain . . . 3

Uninstallation and data retention

Choose the correct procedure

Uninstall is a deliberate operator action, not a fix for a failed migration, bad key or inaccurate import. Identify the actual installed directory, deployment mode and external database/volume dependencies before proceeding. An extracted download directory may redirect the CLI to another verified installation; it is not necessarily the installed service directory.

Prepare recovery evidence

1. Take a consistent database backup and verify restoration to an isolated target.
2. Retain original evidence, MFA, mail, audit and anchor keys through approved storage.
3. Record VERSION/schema, runtime identities, source documents, provider dependencies and log retention obligations.
4. Stop/verify the intended native instance or Compose services and finish outstanding work before the final snapshot.
5. Confirm the preservation destination has protected access and sufficient capacity.

Root wrapper removal

Run ./uninstall.sh from the verified installation. The normal wrapper requests the explicit UNINSTALL confirmation, preserves local configuration/logs/data to a sibling LexiGrid-preserved-TIMESTAMP directory and removes the application directory. ./uninstall.sh --yes skips the interactive confirmation but retains default preservation.

Preservation is a filesystem copy, not proof of database consistency. External PostgreSQL and Docker volumes require separate administrator decisions; normal application cleanup does not silently delete them. Historical stage artifacts inside the actual installation may be removed with the directory, while a separate extracted download remains separate.

Destructive flag

The root wrapper's --delete-data option removes local application data without its normal preservation copy. Use it only under explicit approved data-retention/deletion scope after independently verified backups. It does not authorize deletion of external PostgreSQL or Docker volumes. Do not include this flag in a routine upgrade/reinstall recipe.

Native manager distinction

Direct scripts/native/manager.py uninstall removes the virtual environment while retaining configuration/logs/database. Its database deletion is deliberately not automated. This differs from the root wrapper's whole-installation cleanup. Read the exact tool's help rather than treating the commands as interchangeable.

Verify and retain

Confirm the intended service is stopped, the removed installation is absent where expected and preserved artifacts/keys are accessible only to authorized operators. Record the archive/manifest and recovery test, not the secrets themselves. Confirm any external database/volumes remain as intended before separate decommissioning. Windows and customer-specific retention requirements need target-environment validation.