

# Crystal Oscillator

## CXO Series

### Features

- Wide frequency range
- Tri-State Function
- TTL/HCMOS
- RoHS Compliant / Pb Free



### Specifications

Holder Type	Half size (Dip 08)	
Frequency	1.000Mhz ~	
Operating Temperature Range	-10°C to +60°C	
Storage Temperature Range	- 40°C to +85°C	
Frequency	±10ppm ~ ±	
Supply Voltage	5.0V or 3.3V ±	
Current Consumption	5.0V	3.3V
	25mA (1.000 ~ 35.999Mhz)	20mA (1.000 ~ 35.999Mhz)
	60mA (36.00 ~ 69.999Mhz)	40mA (36.00 ~ 69.999Mhz)
	80mA (70.00 ~ 150.00Mhz)	60mA (70.00 ~ 150.00Mhz)
Output Waveform	TTL/HCMOS	
Output Load	10TTL or 15pF	
Symmetry	40/60% or	
Rise/Fall Time	10nS	
Output Voltage "1" VoH "0" VoL	TTL: 2.4V Min.	HCMOS: 90%V Min.
	TTL: 0.4V Max.	HCMOS: 10%V Max.
Start-Up Time	10mS Max.	
Pin 1 Tri-State Function	T: Enable / N: Disable	
Aging (at 25°C)	±5ppm/ year	

### How to order

CXO08	24M	5	3	1	3
Series No Holder Type	Frequency	Input Voltage	Output Code	Operating Temperature	Frequency Stability
CXO08	20=20 Mhz	5 = 5.0V	T = TTL	1=- 10°C to +60°C	1=10ppm
CXO14	24=24 Mhz	3 = 3.3V	H = HCMOS	2=- 20°C to +70°C	2=20ppm
	40=40 Mhz			3=- 40°C to +85°C	3=30ppm
					5=50ppm
					0=100ppm

**MSC**

# Crystal Oscillator

## CXO Series

### Dimensions (mm)

