Newtonian gravitation for C++ programmers

S. Halayka*

Thursday 28th November, 2024 11:25

Abstract

...

1 Numerical: integer field line count

Where r is the receiver radius, R is the distance from the centre of the emitter, β is the get intersecting line count function, and n is the field line count, the gradient is:

$$\alpha = \frac{\beta(R + \epsilon) - \beta(R)}{\epsilon}. \tag{1}$$

The gradient strength is:

$$g = \frac{-\alpha}{r^2}. \tag{2}$$

```cpp
long long unsigned int get_intersecting_line_count(
        const vector<vector_3>& unit_vectors,
        const vector_3 sphere_location,
        const real_type sphere_radius)
{
        long long unsigned int count = 0;

        vector_3 cross_section_edge_dir(sphere_location.x, sphere_radius, 0);
        cross_section_edge_dir.normalize();

        vector_3 receiver_dir(sphere_location.x, 0, 0);
        receiver_dir.normalize();

        const real_type min_dot = cross_section_edge_dir.dot(receiver_dir);

        for (size_t i = 0; i < unit_vectors.size(); i++)
                if (unit_vectors[i].dot(receiver_dir) >= min_dot)
                        count++;

        return count;
}
```

---

*sjhalayka@gmail.com

```cpp
int main(int argc, char** argv)
{
        // Field line count
        const size_t n = 1000000000;

        cout << "Allocating memory for field lines" << endl;
        vector<vector_3> unit_vectors(n);

        for (size_t i = 0; i < n; i++)
        {
                unit_vectors[i] = RandomUnitVector();

                static const size_t output_mod = 10000;

                if (i % output_mod == 0)
                        cout << "Getting pseudorandom locations: "
                        << static_cast<float>(i) / n << endl;
        }

        string filename = "newton.txt";
        ofstream out_file(filename.c_str());
        out_file << setprecision(30);

        const real_type start_distance = 10.0;
        const real_type end_distance = 100.0;
        const size_t distance_res = 1000;

        const real_type distance_step_size =
                (end_distance - start_distance)
                / (distance_res - 1);

        for (size_t step_index = 0; step_index < distance_res; step_index++)
        {
                const real_type r =
                        start_distance +
                        step_index * distance_step_size;

                const vector_3 receiver_pos(r, 0, 0);
                const real_type receiver_radius = 1.0;

                const real_type epsilon = 1.0;

                vector_3 receiver_pos_plus = receiver_pos;
                receiver_pos_plus.x += epsilon;

                const long long signed int collision_count_plus =
                        get_intersecting_line_count(
                                unit_vectors,
                                receiver_pos_plus,
                                receiver_radius);

                const long long signed int collision_count =
                        get_intersecting_line_count(
                                unit_vectors,
```

```
                          receiver_pos ,
                          receiver_radius );

            const real_type gradient =
                    static_cast<real_type>
                    ( collision_count_plus − collision_count )
                    / epsilon ;

            const real_type gradient_strength =
                    −gradient
                    / ( receiver_radius ∗ receiver_radius );

            cout << "r: " << r << " gradient strength: "
            << gradient_strength << endl ;

            out_file << r << " " << gradient_strength << endl ;
    }

    out_file . close ();

    return 0;
}
```

2   Analytical: real field line count

Where r is the receiver radius, R is the distance from the centre of the emitter, β is the get intersecting line count function, and n is the field line count, the gradient is:

$$\alpha = \frac{\beta(R + \epsilon) - \beta(R)}{\epsilon}. \tag{3}$$

Here we assume that the maximum number of field lines is given by the holographic principle:

$$n = \frac{c^3 A}{4G\hbar \log 2}. \tag{4}$$

The gradient strengths are:

$$g = \frac{-\alpha}{r^2} \approx \frac{n}{2R^3}, \tag{5}$$

$$g_N = \frac{nc\hbar \log 2}{4\pi MR^2} = \frac{c^4 A}{16\pi GMR^2} = \frac{GM}{R^2}. \tag{6}$$

```
real_type get_intersecting_line_count (
        const real_type n,
        const vector_3 sphere_location ,
        const real_type sphere_radius )
{
        const real_type big_area =
                4 ∗ pi ∗ sphere_location . x ∗ sphere_location . x ;

        const real_type small_area =
```

```cpp
                     pi * sphere_radius * sphere_radius;

        const real_type ratio =
                small_area / big_area;

        return n * ratio;
}


int main(int argc, char** argv)
{
        const real_type emitter_radius = 1.0;

        const real_type emitter_area =
                4.0 * pi * emitter_radius * emitter_radius;

        // Field line count
        // re: holographic principle:
        const real_type n =
                (c3 * emitter_area)
                / (log(2.0) * 4.0 * G * hbar);

        const real_type emitter_mass = c2 * emitter_radius / (2.0 * G);

        // 1.73502e+70 is the 't Hooft-Susskind constant:
        // the number of field lines for a black hole of
        // unit Schwarzschild radius
        //
        //const real_type G_ =
        //       (c3 * pi)
        //       / (log(2.0) * hbar * 1.73502e+70);

        const string filename = "newton.txt";
        ofstream out_file(filename.c_str());
        out_file << setprecision(30);

        const real_type start_distance = 10.0;
        const real_type end_distance = 100.0;
        const size_t distance_res = 1000;

        const real_type distance_step_size =
                (end_distance - start_distance)
                / (distance_res - 1);

        for (size_t step_index = 0; step_index < distance_res; step_index++)
        {
                const real_type r =
                        start_distance + step_index * distance_step_size;

                const vector_3 receiver_pos(r, 0, 0);
                const real_type receiver_radius = 1.0;

                const real_type epsilon = 1.0;

                vector_3 receiver_pos_plus = receiver_pos;
```

```cpp
                receiver_pos_plus.x += epsilon;

                // https://en.wikipedia.org/wiki/Directional_derivative
                const real_type collision_count_plus =
                        get_intersecting_line_count(
                                n,
                                receiver_pos_plus,
                                receiver_radius);

                const real_type collision_count =
                        get_intersecting_line_count(
                                n,
                                receiver_pos,
                                receiver_radius);

                const real_type gradient =
                        (collision_count_plus - collision_count)
                        / epsilon;

                real_type gradient_strength =
                        -gradient
                        / (receiver_radius * receiver_radius);

                const real_type gradient_strength_ =
                        n / (2.0 * pow(receiver_pos.x, 3.0));

                const real_type newton_strength =
                        n * c * hbar * log(2.0)
                        /
                        (pow(receiver_pos.x, 2.0)
                                * emitter_mass * 4.0 * pi);

                const real_type newton_strength_ =
                        c4 * emitter_area
                        / (16.0 * pi * G
                                * pow(receiver_pos.x, 2.0) * emitter_mass);

                const real_type newton_strength__ =
                        G * emitter_mass / pow(receiver_pos.x, 2.0);

                //cout << newton_strength__ / newton_strength << endl;

                cout << "r: " << r << " gradient strength: "
                        << gradient_strength << endl;

                out_file << r << " " << gradient_strength << endl;
        }

        out_file.close();

        return 0;
}
```

3   Newtonian gravitational integration

```
vector_3 Newtonian_acceleration(
        const real_type emitter_mass,
        const vector_3& pos, // Receiver pos
        const real_type G)
{
        vector_3 grav_dir = vector_3(0, 0, 0) − pos;
        const real_type distance = grav_dir.length();
        grav_dir.normalize();

        vector_3 accel = grav_dir * G * emitter_mass / pow(distance, 2.0);

        return accel;
}
```

```
void proceed_Euler(
        vector_3& pos,
        vector_3& vel,
        const real_type G,
        const real_type dt)
{
        vector_3 accel =
                Newtonian_acceleration(
                        emitter_mass,
                        pos,
                        G);

        vel += accel * dt;
        pos += vel * dt;
}
```

```
void idle_func(void)
{
        proceed_Euler(receiver_pos, receiver_vel, G, dt);
}
```

```
void proceed_symplectic4(
        vector_3& pos,
        vector_3& vel,
        real_type G,
        real_type dt)
{
        static real_type const cr2 =
                pow(2.0, 1.0 / 3.0);

        static const real_type c[4] =
        {
                1.0 / (2.0 * (2.0 − cr2)),
                (1.0 − cr2) / (2.0 * (2.0 − cr2)),
                (1.0 − cr2) / (2.0 * (2.0 − cr2)),
                1.0 / (2.0 * (2.0 − cr2))
        };
```

```
        static const real_type d[4] =
        {
                1.0 / (2.0 − cr2),
                −cr2 / (2.0 − cr2),
                1.0 / (2.0 − cr2),
                0.0
        };

        pos += vel * c[0] * dt;
        vel += Newtonian_acceleration(
                        emitter_mass,
                        pos,
                        G) * d[0] * dt;

        pos += vel * c[1] * dt;
        vel += Newtonian_acceleration(
                        emitter_mass,
                        pos,
                        G) * d[1] * dt;

        pos += vel * c[2] * dt;
        vel += Newtonian_acceleration(
                        emitter_mass,
                        pos,
                        G) * d[2] * dt;

        pos += vel * c[3] * dt;
        // last element d[3] is always 0
}
```