Newtonian gravitation for C++ programmers

S. Halayka*

Thursday 28th November, 2024 14:07

Abstract

...

1 Typedefs

2 Constants

```
const real_type dt = 10000; // 2.77777 hours

const real_type pi = 4.0 * atan(1.0);

const real_type G = 6.67430e-11;
const real_type c = 299792458;
const real_type c2 = c * c;
const real_type c3 = c * c * c;
```

^{*}sjhalayka@gmail.com

```
const real_type c4 = c * c * c * c;
const real_type h = 6.62607015e-34;
const real_type hbar = h / (2.0 * pi);
```

3 Numerical: integer field line count

Where r is the receiver radius, R is the distance from the centre of the emitter, β is the get intersecting line count function, and n is the field line count, the gradient is:

$$\alpha = \frac{\beta(R+\epsilon) - \beta(R)}{\epsilon}.$$
 (1)

The gradient strength is:

$$g = \frac{-\alpha}{r^2}. (2)$$

```
int main(int argc, char** argv)
{
    // Field line count
    const size_t n = 10000000000;

    cout << "Allocating memory for field lines" << endl;
    vector<vector_3> unit_vectors(n);

for (size_t i = 0; i < n; i++)
{
    unit_vectors[i] = RandomUnitVector();
    static const size_t output_mod = 10000;
}</pre>
```

```
if (i \% output_mod = 0)
                 cout << "Getting pseudorandom locations: "</pre>
                << static_cast<float>(i) / n << endl;</pre>
}
string filename = "newton.txt";
ofstream out_file (filename.c_str());
out_file << setprecision(30);
const real_type start_distance = 10.0;
const real_type end_distance = 100.0;
const size_t distance_res = 1000;
const real_type distance_step_size =
        (end_distance - start_distance)
        / (distance_res - 1);
for (size_t step_index = 0; step_index < distance_res; step_index++)
        const real_type r =
                 start_distance +
                 step_index * distance_step_size;
        const vector_3 receiver_pos(r, 0, 0);
        const real_type receiver_radius = 1.0;
        const real_type epsilon = 1.0;
        vector_3 receiver_pos_plus = receiver_pos;
        receiver_pos_plus.x += epsilon;
        const long long signed int collision_count_plus =
                 get_intersecting_line_count(
                         unit_vectors,
                         receiver_pos_plus,
                         receiver_radius);
        const long long signed int collision_count =
                 get_intersecting_line_count(
                         unit_vectors,
                         receiver_pos,
                         receiver_radius);
        const real_type gradient =
                 static_cast < real_type >
                 (collision_count_plus - collision_count)
                 / epsilon;
        const real_type gradient_strength =
                -gradient
                / (receiver_radius * receiver_radius);
        \operatorname{cout} << "r: " << r << " \operatorname{gradient} strength: "
        << gradient_strength << endl;</pre>
```

```
out_file << r << " " << gradient_strength << endl;
}
out_file.close();
return 0;
}</pre>
```

4 Analytical: real field line count

Where r is the receiver radius, R is the distance from the centre of the emitter, β is the get intersecting line count function, and n is the field line count, the gradient is:

$$\alpha = \frac{\beta(R+\epsilon) - \beta(R)}{\epsilon}.$$
 (3)

Here we assume that the maximum number of field lines is given by the holographic principle:

$$n = \frac{c^3 A}{4G\hbar \log 2}. (4)$$

The gradient strengths are:

$$g = \frac{-\alpha}{r^2} \approx \frac{n}{2R^3},\tag{5}$$

$$g_N = \frac{nc\hbar \log 2}{4\pi M R^2} = \frac{c^4 A}{16\pi G M R^2} = \frac{GM}{R^2}.$$
 (6)

```
// Field line count
// re: holographic principle:
const real_type n =
        (c3 * emitter\_area)
        / (\log (2.0) * 4.0 * G * hbar);
const real_type emitter_mass = c2 * emitter_radius / (2.0 * G);
// 1.73502e+70 is the 't Hooft-Susskind constant:
// the number of field lines for a black hole of
// unit Schwarzschild radius
//const\ real\_type\ G_{-}=
        (c3 * pi)
        / (log(2.0) * hbar * 1.73502e+70);
const string filename = "newton.txt";
ofstream out_file(filename.c_str());
out_file << setprecision(30);
const real_type start_distance = 10.0;
const real_type end_distance = 100.0;
const size_t distance_res = 1000;
const real_type distance_step_size =
        (end_distance - start_distance)
        / (distance_res - 1);
for (size_t step_index = 0; step_index < distance_res; step_index++)
        const real_type r =
                start_distance + step_index * distance_step_size;
        const vector_3 receiver_pos(r, 0, 0);
        const real_type receiver_radius = 1.0;
        const real_type epsilon = 1.0;
        vector_3 receiver_pos_plus = receiver_pos;
        receiver_pos_plus.x += epsilon;
        // https://en.wikipedia.org/wiki/Directional_derivative
        const real_type collision_count_plus =
                get_intersecting_line_count(
                        receiver_pos_plus,
                        receiver_radius);
        const real_type collision_count =
                get_intersecting_line_count(
                        receiver_pos,
                        receiver_radius);
```

```
const real_type gradient =
                (collision_count_plus - collision_count)
                / epsilon;
        real_type gradient_strength =
                -gradient
                / (receiver_radius * receiver_radius);
        const real_type gradient_strength_ =
                n / (2.0 * pow(receiver_pos.x, 3.0));
        const real_type newton_strength =
                n * c * hbar * log(2.0)
                (pow(receiver_pos.x, 2.0)
                        *  emitter_mass *  4.0 *  pi);
        const real_type newton_strength_ =
                c4 * emitter\_area
                / (16.0 * pi * G)
                         * pow(receiver_pos.x, 2.0) * emitter_mass);
        const real_type newton_strength__ =
                G * emitter_mass / pow(receiver_pos.x, 2.0);
        //cout \ll newton\_strength\_ / newton\_strength \ll endl;
        cout << "r: " << r << " gradient strength: "
                << gradient_strength << endl;</pre>
        out_file << r << " " << gradient_strength << endl;
out_file.close();
return 0;
```

5 Modeling Mercury's orbit via numerical integration

```
vector_3 Newtonian_acceleration(
    const real_type emitter_mass,
    const vector_3& pos, // Receiver pos
    const real_type G)
{
    vector_3 grav_dir = vector_3(0, 0, 0) - pos;
    const real_type distance = grav_dir.length();
    grav_dir.normalize();

    vector_3 accel = grav_dir * G * emitter_mass / pow(distance, 2.0);
```

```
return accel;
void proceed_Euler(
        vector_3& pos,
        vector_3& vel,
        const real_type G,
        const real_type dt)
        vector_3 accel =
                Newtonian_acceleration (
                        emitter_mass,
                        pos,
                        G);
        vel += accel * dt;
        pos += vel * dt;
void idle_func(void)
        proceed_Euler(receiver_pos, receiver_vel, G, dt);
void proceed_symplectic_order_4(
        vector_3& pos,
        vector_3& vel,
        real_type G,
        real_type dt)
        static real_type const cr2 =
                pow(2.0, 1.0 / 3.0);
        static const real_type c[4] =
                1.0 / (2.0 * (2.0 - cr2)),
                (1.0 - cr2) / (2.0 * (2.0 - cr2)),
                (1.0 - cr2) / (2.0 * (2.0 - cr2)),
                1.0 / (2.0 * (2.0 - cr2))
        };
        static const real_type d[4] =
                1.0 / (2.0 - cr2),
                -cr2/(2.0 - cr2),
                1.0 / (2.0 - cr2),
                0.0
        };
        pos += vel * c[0] * dt;
        vel += Newtonian_acceleration(
                         emitter_mass,
                        pos,
                        G) * d[0] * dt;
```

A final code, which models the orbit of Mercury, is at: https://github.com/sjhalayka/mercury_orbit_glut