

# Learning and Evaluation of STRIPS Action Models with Classical Planning

Diego Aineto<sup>a</sup>, Sergio Jiménez Celorrio<sup>a</sup>, Eva Onaindia<sup>a</sup>

<sup>a</sup>*Department of Computer Systems and Computation, Universitat Politècnica de València, Spain*

---

## Abstract

This paper presents a novel approach for learning STRIPS action models from observations of plan executions that compiles this learning task into classical planning. The compilation approach is flexible to various amount and kind of available input knowledge; learning examples can range from plans (with their corresponding initial state) to sequences of state observations or even just a set of initial and final states (where no intermediate action or state is known). The compilation accepts also partially specified action models and can be used to validate whether the observation of a plan execution follows a given STRIPS action model, even if this model is not fully specified. On the other hand, the compilation is extensible to assess how well a given STRIPS action model matches the observation of a plan execution. This extension allows us to evaluate the quality of the learned models with respect to the actual models but also, with respect to a *test set* of observations of plan executions. The performance of our compilation approach is evaluated learning action models, for a wide range of classical planning domains from the International Planning Competition (IPC), and following these two evaluation approaches.

**Keywords:** Classical planning, Learning action models, Generalized planning

---

## 1. Introduction

Besides *plan synthesis* [1], planning action models are also useful for *plan/goal recognition* [2]. At both planning tasks, automated planners reason about action models that correctly and completely capture the possible world transitions [3]. Unfortunately, modeling planning actions is complex, even for planning experts, and this knowledge acquisition task is a bottleneck that limits the potential of AI planning [4].

Machine Learning (ML) has shown to be able to compute a wide range of different kinds of models from examples [5]. The application of inductive ML to the learning of STRIPS action models, the vanilla action model for automated planning [6], is not straightforward though:

- The *input* to ML algorithms (the *learning/training* data) usually are finite vectors encoding the value of fixed features in a given set of objects. The input for learning planning action models are observations of plan executions (where each observed plan possibly has a different number of steps and involves a different number of objects).
- The *output* of ML algorithms usually is a scalar value (an integer, in the case of *classification* tasks, or a real value, in the case of *regression* tasks). When learning STRIPS action models the output is, for each action, the sets of *preconditions*, *negative* and *positive effects* that define the possible state transitions.

Motivated by recent advances on the synthesis of different kinds of generative models with classical planning [7, 8, 9, 10], this paper introduces an innovative approach for learning STRIPS action models that can be defined as

a classical planning compilation. A solution to the classical planning task that results from our compilation is a sequence of actions that determines the preconditions and effects of a STRIPS model such that this model satisfies the plan executions given as input.

The compilation approach is appealing by itself because it leverages off-the-shelf planners and because its practicality allow us to report learning results over a wide range of domains from the *International Planning Competition* (IPC). Moreover, it opens up a way towards *bootstrapping* planning action models, enabling a planner to gradually learn/update its action model. Apart from these, our compilation exhibits the following contributions:

1. **Input flexibility.** Our classical planning compilation is flexible to various amount and kind of available input knowledge. The action model to learn can be partially specified and the learning examples can range from a set of plans (with their corresponding initial state) or state observations, to just a set of initial and final states where no intermediate action or state is observed.
2. **Model validation.** The compilation poses a novel framework to assess the validation of a STRIPS model with respect a plan execution. This validation capacity goes beyond the functionality of VAL [11] since it does require neither a full action model nor a fully observed plan to determine validation.
3. **Model evaluation.** The compilation can assess how well a given STRIPS action model matches a plan execution, which allows us to assess learning performance without having the actual action model. The idea is to assess the amount of edition that is required by the input action model to induce the given observation of the plan execution.

A first description of the compilation previously appeared in our conference paper [12]. Compared to that conference paper, this work includes the following novel material:

- A unified formulation for learning and evaluating STRIPS action models from observed executions of plans. Further, these executions can only comprise state observations.
- A redefinition of the ML metrics *precision* and *recall* to evaluate STRIPS action models with respect to observations of plan executions.
- A complete empirical evaluation of the compilation approach. Our evaluation analyses how the amount of input knowledge affects to the performance of the compilation approach when learning and evaluating STRIPS action models.

Section 2 introduces classical planning and reviews related work on learning planning action models. Section ?? introduces the classical planning model and the STRIPS action model (the target of our learning and evaluation tasks). Section ?? formalizes the learning of STRIPS action models with regard to different amount and kind of available input knowledge. Sections ?? and ?? describe our compilation approach for addressing the formalized learning tasks its extension to evaluate and recognize STRIPS action models. Section ?? reports the data collected in a two-fold empirical evaluation of our learning approach: First, the learned STRIPS action models are tested with observations of plan executions and second, the learned models are compared to the actual models. Finally, Section ?? discusses the strengths and weaknesses of the compilation approach and proposes several opportunities for future research.

## 2. Background

This section serves two purposes: First we introduce the basic planning concepts as well as the classical planning model that we will use throughout the rest of the paper. Second, we summarize the existing approaches to learn action models in classical planning and highlight our contributions via the related work.

### 2.1. Basic planning concepts

We use  $F$  to denote the set of *fluents* (propositional variables) describing a state. A *literal*  $l$  is a valuation of a fluent  $f \in F$ , i.e. either  $l = f$  or  $l = \neg f$ . A set of literals  $L$  represents a partial assignment of values to fluents (without loss of generality, we will assume that  $L$  does not assign conflicting values to any fluent). We use  $\mathcal{L}(F)$  to denote the set of all literal sets on  $F$ , i.e. all partial assignments of values to fluents.

A *state*  $s$  is a full assignment of values to fluents, i.e.  $|s| = |F|$ , so the size of the state space is  $2^{|F|}$ . Explicitly including negative literals  $\neg f$  in states simplifies subsequent definitions but often, we will abuse notation by defining a state  $s$  only in terms of the fluents that are true in  $s$ , as is common in STRIPS planning.

A *classical planning frame* is a tuple  $\Phi = \langle F, A \rangle$ , where  $F$  is a set of fluents and  $A$  is a set of actions. An action  $a \in A$  is defined with:

- $\text{pre}(a) \in \mathcal{L}(F)$ , the *preconditions* of  $a$ , is the set of literals that must hold for the action  $a \in A$  to be applicable.
- $\text{eff}^+(a) \in \mathcal{L}(F)$ , the *positive effects* of  $a$ , is the set of literals that true after the application of the action  $a \in A$ .
- $\text{eff}^-(a) \in \mathcal{L}(F)$ , the *negative effects* of  $a$ , is the set of literals that are false after the application of the action.

We say that an action  $a \in A$  is *applicable* in a state  $s$  iff  $\text{pre}(a) \subseteq s$ . The result of applying  $a$  in  $s$  is the *successor state* denoted by  $\theta(s, a) = \{s \setminus \text{eff}^-(a)\} \cup \text{eff}^+(a)$ .

A *classical planning problem* is a tuple  $P = \langle F, A, I, G \rangle$ , where  $I$  is an initial state and  $G \in \mathcal{L}(F)$  is a goal condition. A *plan* for  $P$  is an action sequence  $\pi = \langle a_1, \dots, a_n \rangle$  that induces the *state trajectory*  $s = \langle s_0, s_1, \dots, s_n \rangle$  such that  $s_0 = I$  and, for each  $1 \leq i \leq n$ ,  $a_i$  is applicable in  $s_{i-1}$  and generates the successor state  $s_i = \theta(s_{i-1}, a_i)$ . The *plan length* is denoted with  $|\pi| = n$ . A plan  $\pi$  *solves*  $P$  iff  $G \subseteq s_n$ , i.e. if the goal condition is satisfied at the last state reached after following the application of the plan  $\pi$  in the initial state  $I$ . A solution plan is *optimal* if it has minimum length.

In this work, we will use the term *plan trace* to refer to the observation of a plan execution that starts on a given initial state. *Plan traces* are the input knowledge of the learning tasks that are addressed in this paper. A *plan trace* is a combination of a state and an action sequence  $\tau = \langle s_0, a_1, s_1, a_2, s_2, \dots, a_n, s_n \rangle$ . This sequence is obtained watching the execution of a plan  $\pi = \langle a_1, \dots, a_n \rangle$  such that, for each  $1 \leq i \leq n$ ,  $a_i$  is applied in state  $s_{i-1}$  and generates the successor state  $s_i$ . We name different classes of *plan traces* according to the kind of knowledge that is observed:

- FO** We say that a plan trace  $\mathcal{T} = \langle s_0, s_1, \dots, s_n \rangle$  is a *fully-observable (FO) state trajectory* if every state  $s_i$ ,  $1 \leq i \leq n$ , is a full assignment of values to fluents and the transition from states  $s_i$  to states  $s_{i+1}$  is caused by the execution of a single action  $a_i$  that is unobserved; that is,  $\theta(s_i, \langle a_i \rangle) = s_{i+1}$ .
- PO** A plan trace  $\mathcal{T}$  is a *partially-observable (PO) state trajectory*, meaning that at least one  $s_i \in \mathcal{T}$  is a partial assignment of values to fluents in which one or more literals are missing, formally there exists a state  $s_i$ ,  $1 < i$  such that  $|s_i| < |F|$ .
- PO\*** *Plan traces* with some missing intermediate states is regarded as a particular case of partial observability (that we name PO\*).
- NO** A state trajectory  $\mathcal{T}$  where every intermediate state  $s_i \in \mathcal{T}$ ,  $1 < i$ , holds that  $|s_i| = 0$  is a *non-observable (NO) state trajectory*.

Regarding to the action sequence,  $\langle a_1, \dots, a_n \rangle$ , it is called a FO action sequence if it contains all the necessary actions  $a_i$  to transit every state  $s_i$  to the corresponding sucesor state  $s_{i+1}$ , for each  $1 \leq i \leq n$ . We say that an action sequence is PO if at least one of these necessary  $a_i$  actions is missing in the sequence and NO, in case that the action sequence is empty.

## 2.2. Related work

Here we summarize the most recent and relevant approaches to learning action models that is found in the AI planning literature. These approaches will be examined according to the following parameters: the *input knowledge* that is accepted by the approach (i.e. the information observed in the given plan traces), the *expressiveness* of the learned action models and, the principal *technique* that is used for learning the action models (Table 1). In addition, we examine the characteristics of the *evaluation* methods that are used to assess the quality of the learned models (Table 2).

The first column of Table 1 shows that all the approaches analyzed in this work accept partial observations of intermediate states, and that some approaches also allow the sequence of intermediate states to be empty. Although not explicitly stated in the corresponding published works, it seems reasonable to assume that handling NO state

sequences subsumes PO\* trajectories and that a PO\* plan trace can be regarded as composed of several NO sub-traces. Exceptionally, a NO state sequence in LOCM is a fully-empty trajectory, with neither initial or final state.

Most approaches assume that a set of predicates and a set of action headers are provided alongside the input traces. Others do not explicitly say so but the fact is that the predicates and the actions headers are easily extractable from the state sequence and action sequence of the given plan traces, respectively. A requirement, however, for these two sets to be representative is that the set of input plan traces comprises a grounded sample of all predicates and operator schemas of the domain model.

The expressiveness of the learned action models varies across approaches (second column of Table 1). All the presented systems are able to learn action models in a STRIPS representation [6] and some propose algorithms to learn more expressive action models that include *quantifiers*, *logical implications* or the *type hierarchy* of the domain.

Table 2 summarizes the main characteristics of the evaluation of the learned action models based on the type of evaluation method (first column of Table 2 – almost all approaches rely on a syntactic comparison between the learned model and a ground-truth model), the metrics used in the comparison (second column of Table 2) and the number of tested domains alongside the size of the training dataset (third column of Table 2).

In the following, we present a comprehensive insight of the particularities of the seven systems presented in Table 1 and Table 2. This exposition will help us to highlight in section 3 the value of our contribution FAMA.

The Action-Relation Modelling System (**ARMS**) [13] is one of the first learning algorithms able to learn from plan traces with partial or null observations of intermediate states. ARMS uncovers a number of constraints from the plan traces in the training data that must hold for the plans to be correct. These constraints are then used to build and solve a weighted propositional satisfiability problem with a MAX-SAT solver. Three types of constraints are considered: 1) constraints imposed by general syntactic axioms of correct STRIPS actions, 2) constraints extracted from the distribution of actions in the plan traces and 3) constraints obtained from the PO states, if available. Frequent subsets of actions in which to apply the two latter types of constraints are found by means of frequent set mining.

ARMS defines an error metric and a redundancy metric to measure the correctness and conciseness of an action model over the test set of input plan traces using a cross-validation evaluation. Learning is posed as an optimization task that returns the model that best explains the input traces by minimizing the error and redundancy functions. This yields a model that is approximately correct (100% correctness is not required so as to ensure generality and avoid overfitting), approximately concise (low redundancy rates), and that can explain as many examples as possible. Hence, there is no guarantee that the learned model of ARMS explains all observed plans, not even that it correctly explains any of the plan traces of the test set.

The ARMS system became a benchmark in action-model learning, showing empirically that it is feasible to learn a model in a reasonably efficient way using a weighted MAX-SAT even with NO state trajectories. Nevertheless, we argue that using the home-made error and redundancy metrics to evaluate the model correctness is questionable since models that exhibit a wrong preconditions or effects in any of its actions could still be eligible as the minimal-error output model.

Simultaneous Learning and Filtering (**SLAF**) [14] is a tractable and exact method for learning action models in partially observable domains. SLAF alongside ARMS can be considered another of the precursors of the modern algorithms for action-model learning, able to learn from plan traces with PO and non-null intermediate states. Given a formula representing the initial belief state, a sequence of executed actions and the corresponding partially observed states, SLAF builds a complete explanation of observations by models of actions through a CNF formula. The learning algorithm updates the formula of the belief state with every action and observation in the sequence such that the new transition belief formula represents all possible transition relations consistent with the actions and observations at every time step.

SLAF extracts all satisfying models of the learned formula with a SAT solver. For doing so, the training data set for each domain is composed of randomly generated action-observation sequences (1,000 randomly selected actions and 10 fluents uniformly selected at random per observation). Additional processing in the form of replacement procedures or extra axioms are run into the SAT solver when finding the satisfying models. The experimentally tested SLAF version is an algorithm that learns only effects for actions that have no conditional effects and assumes that actions in the sequences are all executed successfully (without failures). This algorithm cannot effectively learn the unknown preconditions of the actions and in the resulting models ‘one can see that the learned preconditions are often inaccurate’ [14]. On the other hand, it does not report any statistical evaluation of measurement error other than

	Input plan traces	Learned action model	Technique
ARMS	PO and NO states FO actions	STRIPS	MAX-SAT
SLAF	PO states FO actions	universal quantifiers in eff	logical inference SAT solver
LAMP	PO and PO * states FO actions	quantifiers logical implications	Markov logic networks
AMAN	NO states noisy actions	STRIPS	graphical model estimation
NOISTA	PO and noisy states FO actions	STRIPS	classification STRIPS rules derivation
CAMA	PO and PO * states FO actions	STRIPS	crowdsourcing annotation MAX-SAT
LOCM2	NO states FO actions	predicates and types	Finite State Machines
FAMA	PO, PO * and NO states PO and NO actions	STRIPS	compilation to planning

Table 1: Characteristics of action-model learning approaches

a manually comparison of the learned models with a ground-truth model.

The Learning Action Models from Plan Traces (**LAMP**) [15] algorithm extends the expressiveness of ARMS to learning models with *universal* and *existential* quantifiers as well as *logical implications*. The input to LAMP is a set of plan traces with intermediate states, which are encoded by the algorithm into propositional formulas. LAMP then uses the action headers and predicates to build a set of candidate formulas that are validated against the input set using a Markov Logic Network and effectively weighting each formula. The formulas with weights larger than a certain threshold are chosen to represent preconditions and effects of the learned action models.

LAMP allows PO\* state observations up to a minimum percentage of 1/5 of the observed states as well as PO state trajectories with different degrees of observability in the number of propositions in each state. It uses an error metric based on counting the differences in the number of precondition and effects between the ground-truth model and the learned model. In general, the results show that the accuracy of the learned models is fairly sensitive to the threshold chosen to learn the weights of the candidate formulas, and that domains that feature more conditional effects are harder to learn.

The Action Model Acquisition from Noisy plan traces (**AMAN**) [16] introduces an algorithm able to learn action models from plan traces with NO state sequences where actions have a probability of being observed incorrectly (noisy actions). The first step of the AMAN algorithm is to build the set of candidate domain models that are compliant with the action headers and predicates. AMAN then builds a graphical model to capture the domain physics; i.e., the relations between states, correct actions, observed actions and domain models. After that, the parameters of the graphical model are learned, computing at the same time the probability distribution of each candidate domain model. Finally AMAN returns the model that maximizes a reward function defined in terms of the percentage of actions successfully executed and the percentage of goal propositions achieved after the last successfully executed action.

AMAN uses the same metric as LAMP, namely counting the number of preconditions and effects that appear in the learned model and not in the ground-truth model (extra fluents) and viceversa (missing fluents). In a comparison between AMAN and ARMS on noiseless inputs, the results show that the accuracies of both AMAN and ARMS are very close to each other and neither dominates the other. On the other hand, a test comparing plan traces with and without noisy actions reveals that the accuracy in the case *with noise* becomes more and more close to *without noise* as the number of iterations of AMAN algorithm increases because the distribution of noise in the plan becomes gradually closer to the real distribution.

Another interesting approach that deals with noisy and incomplete observations of states is presented in [17]. We will refer to this approach as **NOISTA** henceforth. In NOISTA, actions are correctly observed but they can obviously be unsuccessfully executed in the possibly noisy application state. The basis of this approach consists of two parts: a) the application of a voted Perceptron classification method to predict the effects of the actions in vectorized state

	Evaluation method	Metrics	#tested domains/ training data size
ARMS	cross-validation with a test set of plan traces	error counting of #pre satisfaction and redundancy	6 1,600-4,320 actions (160 plan traces)
SLAF	manual checking wrt GTM	—	4 1,000 actions
LAMP	checking wrt GTM	error counting of extra and missing #pre and #eff	4 1,300-6,100 actions (100-200 plan traces)
AMAN	checking wrt GTM	error counting of extra and missing #pre and #eff	3 40-200 plan traces
NOISTA	checking wrt GTM	error counting of extra and missing #pre and #eff	5 5,000-20,000 actions
CAMA	checking wrt GTM	error counting of extra and missing #pre and #eff	3 15-75 plan traces
LOCM2	manual checking wrt GTM	—	—
FAMA	checking wrt GTM	precision and recall of #pre and #eff	15 25 actions

Table 2: Evaluation of action models (GTM: ground-truth model)

descriptions and b) the derivation of explicit STRIPS action rules to predict each fluent in isolation. Experimentally, the error rates in NOISTA fall below 0.1 after 5,000 training samples for the five tested domains under a maximum of 5% noise and a minimum of 10% of observed fluents.

The Crowdsourced Action-Model Acquisition (**CAMA**) [18] explores knowledge from both crowdsourcing (human annotators) and plan traces to learn action models for planning. **CAMA** relies on the assumption that obtaining enough training samples is often difficult and costly because there is usually a limited number of plan traces available. In order to overcome this limitation, **CAMA** builds on a set of soft constraints based on labels `true` or `false` given by the crowd and a set of soft constraints based on the input plan traces. Then it solves the constraint-based problem using a MAX-SAT solver and converts the solution to action models. An experimental comparison reveals that a manual crowdsourcing of **CAMA** outperforms **ARMS** and that as expectedly the difference becomes smaller as the number of plan traces becomes larger. The accuracy of **CAMA** for a small number of plan traces (e.g., 30) is not less than 80%, which means that exploiting the knowledge of the crowd can help learning action models.

The Learning Object-Centred Models (**LOCM**) is an approach that only requires the FO action sequence as input knowledge, without need for providing any information about the predicates or the state trajectory, not even the initial or final state citecrewell2013acquiring. The lack of available information is overcome by exploiting assumptions about the structure of the actions. Particularly, it assumes that objects found in the same position in the header of actions are grouped as a collection of objects (sorts) whose defined set of states is captured by a parameterized Finite State Machine (FSM). The intuitive assumptions of **LOCM**, like the continuity of object transitions or the association of parameters between consecutive actions in the training dataset, yield a learning model heavily reliant on the kind of domain structure. A later work, **LOCM2**, extends the applicability of the **LOCM** algorithm to a wider range of domains by introducing a richer representation that allows using multiple FSMs to represent the state of a sort [19].

**LOCM2** is not experimentally evaluated and only the outcome of running the **LOCM2** algorithm on several benchmark domains wrt to the reference model is reported. It is worth noting the last contribution of **LOCM**, called **LOP** (**LOCM** with Optimized Plans), addresses the problem of inducing static predicates [20]. **LOP** applies a post-processing step after the **LOCM** analysis and it requires additional input information, particularly a set of optimal plans besides the suboptimal FO action sequences.

### 3. Motivation

The main novelty of FAMA with respect to other approaches lies in that our system is capable of handling input plan traces whose length is a priori unbound. This brings one essential difference:

- The transition between two given observed states may now involve the execution of more than a single action. Formally  $\theta(s_i, \langle a_1, \dots, a_k \rangle) = s_{i+1}$ , where  $k \geq 1$  is unknown and unbound;

In this particular scenario the number of actual plan traces that can correspond with the given input observations is also unbound and grows exponentially with the actual length of the plan trace (that is now unknown). Otherwise, the learning task is SAT compilable, which is known to be a NP-complete task [21]. This is the reason that SAT solving is a common technique in the approaches presented in section 2.

Under this new assumption, the learning of STRIPS action models that satisfy a set of observations of plan executions becomes PSPACE-complete instead of NP-complete, which motivates planning as a more suitable approach for the learning of STRIPS action models. The length a plan trace, that represent the observation of a plan execution, is a priori unbound because of the conjunction of the following two causes:

1. There may be an unbound number of missing intermediate states in the trace because of partial state observability. The assumption of having FO state trajectory means that the sensors are able to capture every state change at every instant which typically is unrealistic. Normally the process of getting state feedback from sensors (or the processing of the sensor readings) is associated with a given sampling frequency that misses intermediate data between two sensor readings.
2. There may be an unbound number of missing intermediate actions in the trace because of partial observability. The common assumption of having FO action sequences in a learning task is rather unrealistic in many domains because it implies the existence of human observers that annotate the observed action sequences. In some real-world applications, the observed and collected data are sensory data (e.g., home automation, robotics) or images (e.g. traffic) and one cannot rely on human intervention for labeling actions. Actually, learning the executed actions can also be part of the action-model learning task. Learning from unstructured data involves some prior processing to transform the sensor or image information into a predicate-like format before applying the action-model learning approach [22], and it also requires the ability of identifying action symbols. In this sense, this work represents a step ahead towards learning action models without assuming observed actions.

The Table 3 precisely characterizes the scenarios where the length of the input plan traces cannot longer be assumed to be unbound.

action observability	state observability			
	FO	PO	PO*	NO
FO	NP-complete	NP-complete	NP-complete	NP-complete
PO	NP-complete	PSPACE-complete	PSPACE-complete	PSPACE-complete
NO	NP-complete	PSPACE-complete	PSPACE-complete	PSPACE-complete

Table 3: Complexity of learning tasks according to the kind of the input plan traces.

Regarding the metric to evaluate the learned action models, we can observe in Table 2 that most of the approaches use a similar metric that consists in counting the missing and extra fluents that appear in the learned model wrt the GTM and normalizing by the total number of all the possible preconditions and effects of an action model. This is an *optimistic* metric since it returns error rates that are not normalized with respect to the size of the actual models. For instance these metrics could output a rate below 100% for a totally wrong learned model that only includes a subset of all possible preconditions and effects of an action model.

To overcome this limitation, we propose to use two standard ML metrics, *precision* and *recall*. These two metrics are frequently used in *pattern recognition*, *information retrieval* and *binary classification* and are more informative than simply counting the number of errors in the learned model or computing the *symmetric difference* between the learned and the reference model [23].

A striking figure of Table 2 that emphasizes a relevant feature of FAMA is the small size of the training dataset it requires in comparison to other approaches. Unlike extensive-data ML approaches, our work explores an alternative research direction to learn sound models from small amounts of plan traces. This is an important advantage, particularly in domains in which it is costly or impossible to obtain a significant number of training samples. Unlike CAMA, our approach does not require human intervention to label samples as it is able to learn from very small datasets.

Finally, we would also like to point out that, as shown in section 7, FAMA is exhaustively evaluated over a wide range of domains (15 domains compared to the scarce number of tested domains of the rest of the approaches in Table 2) and uses exclusively an *off-the-shelf* classical planner.

## 4. Learning task

### 4.1. STRIPS action schemas

This work addresses the learning and evaluation of PDDL action schemas that follow the STRIPS requirement [24, 25]. Figure 1 shows the *stack* action schema, coded in PDDL, from a four-operator *blocksworld* [26].

```
(:action stack
:parameters (?v1 ?v2 - object)
:precondition (and (holding ?v1) (clear ?v2))
:effect (and (not (holding ?v1)) (not (clear ?v2)) (handempty) (clear ?v1) (on ?v1 ?v2)))
```

Figure 1: STRIPS operator schema coding, in PDDL, the *stack* action from a four-operator *blocksworld*.

To formalize the target of the learning and evaluation tasks, we assume that fluents  $F$  are instantiated from a set of predicates  $\Psi$ , as in PDDL. Each predicate  $p \in \Psi$  has an argument list of arity  $ar(p)$ . Given a set of objects  $\Omega$ , the set of fluents  $F$  is induced by assigning objects in  $\Omega$  to the arguments of predicates in  $\Psi$ , i.e.  $F = \{p(\omega) : p \in \Psi, \omega \in \Omega^{ar(p)}\}$  s.t.  $\Omega^k$  is the  $k$ -th Cartesian power of  $\Omega$ .

Let  $\Omega_v = \{v_i\}_{i=1}^{\max_{a \in A} ar(a)}$  be a new set of objects ( $\Omega \cap \Omega_v = \emptyset$ ), denoted as *variable names*, and that is bound by the maximum arity of an action in a given planning frame. For instance, in a three-block *blocksworld*  $\Omega = \{block_1, block_2, block_3\}$  while  $\Omega_v = \{v_1, v_2\}$  because the operators with the maximum arity, *stack* and *unstack*, have arity two.

We define  $F_v$ , a new set of fluents s.t.  $F \cap F_v = \emptyset$ , produced instantiating  $\Psi$  using only *variable names*, and that defines the elements that can appear in the action schemes. In *blocksworld* this set contains 11 elements,  $F_v = \{\text{handempty}, \text{holding}(v_1), \text{holding}(v_2), \text{clear}(v_1), \text{clear}(v_2), \text{ontable}(v_1), \text{ontable}(v_2), \text{on}(v_1, v_1), \text{on}(v_1, v_2), \text{on}(v_2, v_1), \text{on}(v_2, v_2)\}$ .

In more detail, for a given operator schema  $\xi$ , we define  $F_v(\xi) \subseteq F_v$  as the subset of elements that can appear in that action schema. For instance, for the *stack* action schema  $F_v(\text{stack}) = F_v$  while  $F_v(\text{pickup}) = \{\text{handempty}, \text{holding}(v_1), \text{clear}(v_1), \text{ontable}(v_1), \text{on}(v_1, v_1)\}$  excludes the elements from  $F_v$  that involve  $v_2$  because *pickup*( $v_1$ ) has arity one.

We assume also that actions  $a \in A$  are instantiated from STRIPS operator schemas  $\xi = \langle \text{head}(\xi), \text{pre}(\xi), \text{add}(\xi), \text{del}(\xi) \rangle$  where:

- $\text{head}(\xi) = \langle \text{name}(\xi), \text{pars}(\xi) \rangle$ , is the operator *header* defined by its name and the corresponding *variable names*,  $\text{pars}(\xi) = \{v_i\}_{i=1}^{ar(\xi)}$ . The headers of a four-operator *blocksworld* are *pickup*( $v_1$ ), *putdown*( $v_1$ ), *stack*( $v_1, v_2$ ) and *unstack*( $v_1, v_2$ ).
- The preconditions  $\text{pre}(\xi) \subseteq F_v$ , the negative effects  $\text{del}(\xi) \subseteq F_v$ , and the positive effects  $\text{add}(\xi) \subseteq F_v$  such that,  $\text{del}(\xi) \subseteq \text{pre}(\xi)$ ,  $\text{del}(\xi) \cap \text{add}(\xi) = \emptyset$  and  $\text{pre}(\xi) \cap \text{add}(\xi) = \emptyset$ .

Given the set of predicates  $\Psi$  and the header of the operator schema  $\xi$ ,  $2^{|F_v(\xi)|}$  defines the size of the space of possible STRIPS models for that operator. Note that the previous constraints require that negative effects appear as preconditions and that they cannot be positive effects and also, that a positive effect cannot appear as a precondition. For the *blocksworld*,  $2^{|F_v(\text{stack})|} = 4194304$  while for the *pickup* operator this number is only 1024.



We say that two STRIPS operator schemes  $\xi$  and  $\xi'$  are *comparable* if both schemas have the same parameters so they share the same space of possible STRIPS models (formally, iff  $\text{pars}(\xi) = \text{pars}(\xi')$ ). For instance, we can claim that blocksworld operators `stack` and `unstack` are *comparable* while `stack` and `pickup` are not. Last but not least, two STRIPS action models  $\mathcal{M}$  and  $\mathcal{M}'$  are *comparable* iff there exists a bijective function  $\mathcal{M} \mapsto \mathcal{M}^*$  that maps every  $\xi \in \mathcal{M}$  to a comparable action schema  $\xi' \in \mathcal{M}'$  and vice versa.

#### 4.2. Learning STRIPS action schemas from plan executions

The *learning task* addressed in this paper corresponds to learning an action model by observing an agent(s) acting in the world. This learning task is formalized as a tuple  $\Lambda = \langle \mathcal{M}, \Psi, \mathcal{T} \rangle$ :

- $\mathcal{M}$  is the set of *initial* operator schemas (*empty* or *partially specified* if some preconditions or effects are known) that define the actions of a given planning frame.
- $\Psi$  is the set of predicates that define the abstract state space of that planning frame.
- $\mathcal{T} = \langle s_0, a_{s_1}, s_1, \dots, a_n, s_n \rangle$  is a plan trace that contains the sequence of *state observations* obtained watching the execution of a plan  $\pi = \langle a_1, \dots, a_n \rangle$  such that, for each  $1 \leq i \leq n$ ,  $a_i$  is applied in state  $s_{i-1}$  and generates the successor state  $s_i$ .

A *solution* to a  $\Lambda = \langle \mathcal{M}, \Psi, \mathcal{T} \rangle$  learning task is a set of operator schema  $\mathcal{M}'$  that is compliant with the input model  $\mathcal{M}$ , the predicates  $\Psi$ , and the observed plan trace  $\mathcal{T}$ . Note that  $\mathcal{M}$  can be inferred from  $\mathcal{T}$  provided that the actions in  $\mathcal{T}$  are *diverse* enough. Meaning that  $\mathcal{T}$  contains at least one instantiation of every action scheme in  $\mathcal{M}$ . Likewise  $\Psi$  can be inferred from  $\mathcal{T}$  when at least the observation of a state  $s \in \mathcal{T}$  is a full state, that is  $|s| = |F|$ .

When all the elements in  $\mathcal{T}$  are fully observed, i.e. learning from plans where the *pre-* and *post-states* of every action are available, solving the  $\Lambda = \langle \mathcal{M}, \Psi, \mathcal{T} \rangle$  learning task is straightforward [27]:

- *Preconditions* are derived lifting the minimal set of literals that appears in all the pre-states of the corresponding action, that is any action that belongs to the same operator scheme.
- *Effects* are derived lifting the literals that change between the pre and post-state of the corresponding action executions.

In this paper we address the  $\Lambda = \langle \mathcal{M}, \Psi, \mathcal{T} \rangle$  learning task with the following assumptions:

1. Each input action scheme  $\xi \in \mathcal{M}$  is at least composed of its *head*( $\xi$ ),
2. The initial state  $s_0 \in \mathcal{T}$  is *fully observable*.
3. Intermediate actions  $a_i \in \mathcal{T}$  and states  $s_i \in \mathcal{T}$  s.t.  $1 \leq i \leq n$ , can be *partially observable* (some fluents in  $s_i$  are missing because it is unknown whether their value is either positive or negative). In the extreme, all actions  $a_i$ ,  $1 \leq i \leq n$ , can be missing (unobserved) provided that the final state  $s_n$  is at least, partially observed. Likewise, all states  $s_i$ ,  $1 \leq i \leq n$ , can be missing (unobserved) provided that at least actions  $a_i$ ,  $1 \leq i \leq n$ , are partially observed.
4. Observations in  $\mathcal{T}$  are *noiseless*, meaning that if a fluent or an action is observed it is the correct value.

Figure 2 shows an example of a learning task  $\Lambda = \langle \mathcal{M}, \Psi, \mathcal{T} \rangle$ , that corresponds to observing the execution of a four-action plan  $\pi = \langle (\text{unstack B A}), (\text{putdown B}), (\text{pickup A}), (\text{stack A B}) \rangle$  for inverting a two-block tower. In this example  $\mathcal{T} = \langle s_0, (\text{unstack B A}), (\text{putdown B}), (\text{pickup A}), (\text{stack A B}), s_4 \rangle$  which means that only the first and last states are observed and the three intermediate states  $s_1$ ,  $s_2$  and  $s_3$  are fully unknown.

The definition of the  $\Lambda = \langle \mathcal{M}, \Psi, \mathcal{T} \rangle$  learning task is also extensible to the more general case where the execution of  $\tau$  plans is observed. In this case,  $\mathcal{T} = \{t_1, \dots, t_\tau\}$  where each  $t \in \mathcal{T}$  is a plan trace  $t = \langle s_0^t, a_1^t, s_1^t, \dots, a_n^t, s_n^t \rangle$  such that, for each  $1 \leq i \leq n^t$ ,  $a_i^t$  is applied in  $s_{i-1}^t$  and generates the successor state  $s_i^t$ .

```

;;;;;;;; Action headers in  $\mathcal{M}$ 

(pickup ?v1) (putdown ?v1) (stack ?v1 ?v2) (unstack ?v1 ?v2)

;;;;;;;; Predicates  $\Psi$ 

(handempty) (holding ?v1) (clear ?v1) (ontable ?v1) (on ?v1 ?v2)

;;;;;;;; Plan trace  $\mathcal{T}$ 

;;; state observation #0
(clear B) (on B A) (ontable A) (handempty)

;;; Plan  $\pi$ 

0: (unstack B A)
1: (putdown B)
2: (pickup A)
3: (stack A B)

;;; state observation #4
(clear A) (on A B) (ontable B) (handempty)

```

Figure 2: Task  $\Lambda = \langle \mathcal{M}, \Psi, \mathcal{T} \rangle$  for learning a *blocksworld* STRIPS action model from a four-action plan and two state observations.

## 5. Compilation scheme

Our approach for addressing a  $\Lambda$  learning task is compiling it into a classical planning task with conditional effects. The intuition behind the compilation is that a solution to the resulting classical planning task is a sequence of actions that:

1. **Programs the action model  $\mathcal{M}'$ .** A solution plan starts with a *prefix* that, for each  $\xi \in \mathcal{M}$ , determines which fluents  $f \in F_v(\xi)$  belong to its  $pre(\xi)$ ,  $del(\xi)$  and  $add(\xi)$  sets.
2. **Validates the action model  $\mathcal{M}'$ .** The solution plan continues with a *postfix* that reproduces the given input knowledge (the available observations of the plan executions) with the programmed action model  $\mathcal{M}'$ .

### 5.1. Classical planning with conditional effects

Conditional effects allow us to compactly define actions whose effects depend on the current state. Supporting conditional effects is now a requirement of the IPC [28] and many classical planners cope with conditional effects without compiling them away.

An action  $a \in A$  with conditional effects is defined as a set of *preconditions*  $pre(a) \in \mathcal{L}(F)$  and a set of *conditional effects*  $cond(a)$ . Each conditional effect  $C \triangleright E \in cond(a)$  is composed of two sets of literals  $C \in \mathcal{L}(F)$ , the *condition*, and  $E \in \mathcal{L}(F)$ , the *effect*. An action  $a \in A$  is *applicable* in a state  $s$  if and only if  $pre(a) \subseteq s$ , and the *triggered effects* resulting from the action application are the effects whose conditions hold in  $s$ :

$$triggered(s, a) = \bigcup_{C \triangleright E \in cond(a), C \subseteq s} E,$$

The result of applying action  $a$  in state  $s$  is the *successor* state  $\theta(s, a) = \{s \setminus eff_c^-(s, a)\} \cup eff_c^+(s, a)$  where  $eff_c^-(s, a) \subseteq triggered(s, a)$  and  $eff_c^+(s, a) \subseteq triggered(s, a)$  are, respectively, the triggered *negative* and *positive* effects.

### 5.2. Learning from from observations of plan executions

Here we formalize the compilation for learning STRIPS action models with classical planning. Given a learning task  $\Lambda = \langle \mathcal{M}, \Psi, \mathcal{T} \rangle$  the compilation outputs a classical planning task  $P_\Lambda = \langle F_\Lambda, A_\Lambda, I_\Lambda, G_\Lambda \rangle$ :

- $F_\Lambda$  contains:

- The set of fluents  $F$  built instantiating the predicates  $\Psi$  with the objects  $\Omega$  that appear in the plan trace given as input, i.e. the blocks A and B in the example of Figure 2. Formally,  $\Omega = \bigcup_{s \in \mathcal{T}} obj(s)$ , where  $obj$  is a function that returns the objects that appear in a given state.
- Fluents  $pre_f(\xi)$ ,  $del_f(\xi)$  and  $add_f(\xi)$ , for every  $f \in F_v(\xi)$ , that represent the programmed action model. If a fluent  $pre_f(\xi)/del_f(\xi)/add_f(\xi)$  holds, it means that  $f$  is a precondition/negative/positive effect in the schema  $\xi \in \mathcal{M}'$ . For instance, the preconditions of the *stack* schema (Figure 1) are represented by the pair of fluents `pre_holding_stack_v1` and `pre_clear_stack_v2` set to True.
- The fluents  $F_\pi = \{plan(name(a_i), \Omega^{ar(a_i)}, i)\}_{1 \leq i \leq n}$  to code the  $i^{th}$  action in  $\mathcal{T}$ . The static facts  $next_{i,i+1}$  and the fluents  $at_i$ ,  $1 \leq i < n$ , are also added to iterate through the  $n$  steps of  $\mathcal{T}$ .
- The fluents  $mode_{prog}$  and  $mode_{val}$  to indicate whether the operator schemas are programmed or validated, and the fluents  $\{test_i\}_{1 \leq i \leq n}$ , indicating the state observation  $s_i \in \mathcal{T}$  where the action model is validated.
- $I_\Lambda$  encodes the first state observation,  $s_0 \subseteq F$  and sets to true  $mode_{prog}$  as well as the fluents  $F_\pi$  plus fluents  $at_1$  and  $\{next_{i,i+1}\}$ ,  $1 \leq i < n$ , for tracking the plan step where the action model is validated. Our compilation assumes that initially, operator schemas are programmed with every possible precondition (the most specific learning hypothesis), no negative effect and no positive effect. Therefore fluents  $pre_f(\xi)$ , for every  $f \in F_v(\xi)$ , hold also at the initial state.
- $G_\Lambda = \bigcup_{1 \leq i \leq n} \{test_i\}$ , requires that the programmed action model is validated in the state observations  $s_i \in \mathcal{T}$ .
- $A_\Lambda$  comprises three kinds of actions:
  1. Actions for *programming* operator schema  $\xi \in \mathcal{M}$ :
    - Actions for **removing** a precondition  $f \in F_v(\xi)$  from the action schema  $\xi \in \mathcal{M}$ .

$$\begin{aligned} pre(programPre_{i,\xi}) &= \{\neg del_f(\xi), \neg add_f(\xi), mode_{prog}, pre_f(\xi)\}, \\ cond(programPre_{i,\xi}) &= \{\emptyset\} \triangleright \{\neg pre_f(\xi)\}. \end{aligned}$$

- Actions for **adding** a negative or positive effect  $f \in F_v(\xi)$  to the action schema  $\xi \in \mathcal{M}$ .

$$\begin{aligned} pre(programEff_{i,\xi}) &= \{\neg del_f(\xi), \neg add_f(\xi), mode_{prog}\}, \\ cond(programEff_{i,\xi}) &= \{pre_f(\xi)\} \triangleright \{del_f(\xi)\}, \{\neg pre_f(\xi)\} \triangleright \{add_f(\xi)\}. \end{aligned}$$

2. Actions for *applying* a programmed operator schema  $\xi \in \mathcal{M}$  bound with objects  $\omega \subseteq \Omega^{ar(\xi)}$ . Since operators headers are given as input, the variables  $pars(\xi)$  are bound to the objects in  $\omega$  that appear at the same position. Figure 3 shows the PDDL encoding of the action for applying a programmed operator *stack* from *blocksworld*.

$$\begin{aligned} pre(apply_{\xi,\omega}) &= \{pre_f(\xi) \implies p(\omega)\}_{\forall p \in \Psi, f=p(pars(\xi))} \cup \{\neg mode_{val}\}, \\ cond(apply_{\xi,\omega}) &= \{del_f(\xi)\} \triangleright \{\neg p(\omega)\}_{\forall p \in \Psi, f=p(pars(\xi))}, \\ &\quad \{add_f(\xi)\} \triangleright \{p(\omega)\}_{\forall p \in \Psi, f=p(pars(\xi))}, \\ &\quad \{mode_{prog}\} \triangleright \{\neg mode_{prog}\}, \\ &\quad \{\emptyset\} \triangleright \{mode_{val}\}. \end{aligned}$$

The extra conditional effects  $\{at_i, plan(name(a_i), \Omega^{ar(a_i)}, i)\} \triangleright \{\neg at_i, at_{i+1}\}_{\forall i \in [1,n]}$  are included in the  $apply_{\xi,\omega}$  actions to validate that actions are applied, exclusively, in the same order as in  $\mathcal{T}$ .

3. Actions for *validating* the partially observed state  $s_i \in \mathcal{T}$ ,  $1 \leq i < n$ .

$$\begin{aligned} pre(validate_i) &= s_i \cup \{test_j\}_{j \in [1, i-1]} \cup \{\neg test_j\}_{j \in [i, n]} \cup \{mode_{val}\}, \\ cond(validate_i) &= \{\emptyset\} \triangleright \{test_i, \neg mode_{val}\}. \end{aligned}$$

```

(:action apply_stack
:parameters (?o1 - object ?o2 - object)
:precondition
  (and (or (not (pre_on_stack_v1_v1)) (on ?o1 ?o1))
        (or (not (pre_on_stack_v1_v2)) (on ?o1 ?o2))
        (or (not (pre_on_stack_v2_v1)) (on ?o2 ?o1))
        (or (not (pre_on_stack_v2_v2)) (on ?o2 ?o2))
        (or (not (pre_ontable_stack_v1)) (ontable ?o1))
        (or (not (pre_ontable_stack_v2)) (ontable ?o2))
        (or (not (pre_clear_stack_v1)) (clear ?o1))
        (or (not (pre_clear_stack_v2)) (clear ?o2))
        (or (not (pre_holding_stack_v1)) (holding ?o1))
        (or (not (pre_holding_stack_v2)) (holding ?o2))
        (or (not (pre_handempty_stack)) (handempty))))
:effect
  (and (when (del_on_stack_v1_v1) (not (on ?o1 ?o1)))
        (when (del_on_stack_v1_v2) (not (on ?o1 ?o2)))
        (when (del_on_stack_v2_v1) (not (on ?o2 ?o1)))
        (when (del_on_stack_v2_v2) (not (on ?o2 ?o2)))
        (when (del_ontable_stack_v1) (not (ontable ?o1)))
        (when (del_ontable_stack_v2) (not (ontable ?o2)))
        (when (del_clear_stack_v1) (not (clear ?o1)))
        (when (del_clear_stack_v2) (not (clear ?o2)))
        (when (del_holding_stack_v1) (not (holding ?o1)))
        (when (del_holding_stack_v2) (not (holding ?o2)))
        (when (del_handempty_stack) (not (handempty)))
        (when (add_on_stack_v1_v1) (on ?o1 ?o1))
        (when (add_on_stack_v1_v2) (on ?o1 ?o2))
        (when (add_on_stack_v2_v1) (on ?o2 ?o1))
        (when (add_on_stack_v2_v2) (on ?o2 ?o2))
        (when (add_ontable_stack_v1) (ontable ?o1))
        (when (add_ontable_stack_v2) (ontable ?o2))
        (when (add_clear_stack_v1) (clear ?o1))
        (when (add_clear_stack_v2) (clear ?o2))
        (when (add_holding_stack_v1) (holding ?o1))
        (when (add_holding_stack_v2) (holding ?o2))
        (when (add_handempty_stack) (handempty))
        (when (modeProg) (not (modeProg)))))

```

Figure 3: PDDL action for applying an already programmed schema *stack* (implications are coded as disjunctions).

Known preconditions and effects (that is, a partially specified STRIPS action model) can be encoded as fluents  $pre_f(\xi)$ ,  $del_f(\xi)$  and  $add_f(\xi)$  set to true at the initial state  $I_\Lambda$ . In this case, the corresponding programming actions,  $programPre_{f,\xi}$  and  $programEff_{f,\xi}$ , become unnecessary and are removed from  $A_\Lambda$  making the classical planning task  $P_\Lambda$  easier to be solved. When a *fully* or *partially specified* STRIPS action model  $\mathcal{M}$  is given, the  $P_\Lambda$  compilation validates whether the observation of the plan execution follows the given model:

- $\mathcal{M}$  is proved to be a *valid* STRIPS action model for the given input data in  $\mathcal{T}$  iff a solution plan for  $P_\Lambda$  can be found.
- $\mathcal{M}$  is proved to be a *invalid* STRIPS action model for the given input data  $\mathcal{T}$  iff  $P_\Lambda$  is unsolvable. This means that  $\mathcal{M}$  cannot be compliant with the given observation of the plan execution.

This feature of our compilation is beyond the functionality of VAL, the plan validation tool [11], because VAL requires (1) a full plan and (2), a full action model for plan validation. On the other hand our  $P_\Lambda$  compilation can test *model validation* with a partial (or even an empty) action model and a partially observed plan trace.

The classical plan of Figure 4 shows a solution to the classical planning task  $P_\Lambda$  that encodes a  $\Lambda = \langle \mathcal{M}, \Psi, \mathcal{T} \rangle$  learning task for getting the *blocksworld* action model where operator schemes for *pickup*, *putdown* and *unstack* are specified in  $\mathcal{M}$ . This plan programs and validates the operator schema *stack* from *blocksworld*, using the plan  $\pi$  and the two state observations  $s_0$  and  $s_4$  shown in Figure 2. Plan steps [0, 8] program the preconditions of the *stack* operator, steps [9, 13] program the operator effects and steps [14, 18] validate the programmed operators following the four-action plan shown in Figure 2.

Note that the  $P_\Lambda$  compilation is flexible to an unbound number of *missing states* or *missing actions* in the input plan trace  $\mathcal{T}$ . If any reference to the  $mode_{val}$  fluent is removed the compilation can learn STRIPS action models when there are missing state observations in  $\mathcal{T}$ . Likewise some of the actions in  $\mathcal{T}$  may be unknown so they are not

```

00 : (program_pre_clear_stack_v1)
01 : (program_pre_handempty_stack)
02 : (program_pre_holding_stack_v2)
03 : (program_pre_on_stack_v1_v1)
04 : (program_pre_on_stack_v1_v2)
05 : (program_pre_on_stack_v2_v1)
06 : (program_pre_on_stack_v2_v2)
07 : (program_pre_ontable_stack_v1)
08 : (program_pre_ontable_stack_v2)
09 : (program_eff_clear_stack_v1)
10 : (program_eff_clear_stack_v2)
11 : (program_eff_handempty_stack)
12 : (program_eff_holding_stack_v1)
13 : (program_eff_on_stack_v1_v2)
14 : (apply_unstack blockB blockA i1 i2)
15 : (apply_putdown blockB i2 i3)
16 : (apply_pickup blockA i3 i4)
17 : (apply_stack blockA blockB i4 i5)
18 : (validate_1)

```

Figure 4: Plan for programming and validating the *stack* schema (using plan  $\pi$  and state observations shown in Figure 2) as well as previously specified operator schemes for *pickup*, *putdown* and *unstack*.

specified in  $I_\Lambda$ . In both cases the output planning problem becomes harder since the plan horizon is no longer bound and the classical planner must determine how many *apply* actions are necessary between any two state observations, i.e. between the application of two *validate* actions (classical planning is *PSPACE complete* while classical planning with a bound plan horizon is *NP* [29]).

Last but not least we explain how to address learning STRIPS action models from the observation of the execution of multiple plans  $\Pi = \{\pi_1, \dots, \pi_\tau\}$ ,  $1 \leq t \leq \tau$ . Let us first define a set of classical planning instances  $P_t = \langle F, \emptyset, I_t, G_t \rangle$  that belong to the same planning frame (i.e. same fluents and actions but different initial states and goals). The set of actions,  $A = \emptyset$ , is empty because the action model is initially unknown. Finally, the initial state  $I_t$  is given by the state  $s_0^t$  and the plan  $\pi_t$ , and the goals  $G_t$  are defined by the state  $s_n^t$ . Addressing the learning task  $\Lambda = \langle \mathcal{M}, \Psi, \mathcal{T} \rangle$  where  $\mathcal{T} = \{t_1, \dots, t_\tau\}$  requires introducing a small modification to our compilation. In particular, the actions in  $P_\Lambda$  for *validating* the plan  $\pi_t \in \Pi$ ,  $1 \leq t \leq \tau$  resets the current state, and the current plan, and are now redefined as:

$$\begin{aligned}
\text{pre}(\text{validate}_t) &= G_t \cup \{test_j\}_{1 \leq j < t} \cup \{\neg test_j\}_{t \leq j \leq \tau} \cup \{\neg mode_{prog}\}, \\
\text{cond}(\text{validate}_t) &= \{\emptyset\} \triangleright \{test_t\} \cup \{\neg f\}_{f \in G_t, f \notin I_{t+1}} \cup \{f\}_{f \in I_{t+1}, f \notin G_t}.
\end{aligned}$$

### 5.3. Compilation properties

**Lemma 1.** *Soundness. Any classical plan  $\pi$  that solves  $P_\Lambda$  induces an action model  $\mathcal{M}'$  that solves  $\Lambda = \langle \mathcal{M}, \Psi, \mathcal{T} \rangle$ .*

*Proof sketch.* Once operator schemas  $\mathcal{M}'$  are programmed, they can only be applied and validated, because of the *mode<sub>prog</sub>* fluent. In addition,  $P_\Lambda$  is only solvable if fluents  $\{test_i\}$ ,  $1 \leq i \leq n$  hold at the last reached state. These goals can only be achieved executing an applicable sequence of programmed operator schemas that reaches every state  $s_i \in \mathcal{T}$ , starting from the corresponding initial state and following the sequence of actions defined by  $\mathcal{T}$ . This means that the programmed action model  $\mathcal{M}'$  complies with the provided input knowledge and hence, solves  $\Lambda$ .  $\square$

**Lemma 2.** *Completeness. Any STRIPS action model  $\mathcal{M}'$  that solves a  $\Lambda = \langle \mathcal{M}, \Psi, \mathcal{T} \rangle$  learning task, is computable solving the corresponding classical planning task  $P_\Lambda$ .*

*Proof sketch.* By definition,  $F_v(\xi) \subseteq F_\Lambda$  fully captures the full set of elements that can appear in a STRIPS action schema  $\xi \in \mathcal{M}$  given its header and the set of predicates  $\Psi$ . The compilation does not discard any possible STRIPS action schema  $\mathcal{M}'$

definable within  $F_v$  that satisfies the state trajectory constraint given by  $\mathcal{T}$ . This means that a solution plan can be built selecting the corresponding  $\text{programPre}_{t,\xi}$  and  $\text{programEff}_{t,\xi}$  actions according to  $\mathcal{M}'$  and later, selecting the corresponding  $\text{apply}_{\xi,\omega}$  and  $\text{validate}_i$  actions according to  $\mathcal{T}$ .  $\square$

The size of the classical planning task  $P_\Lambda$  output by the compilation depends on:

- The arity of the actions headers in  $\mathcal{M}$  and the predicates  $\Psi$  that are given as input to the  $\Lambda$  learning task. The larger these numbers, the larger the size of the  $F_v(\xi)$  sets. This is the term that dominates the compilation size because it defines the  $\text{pre}_f(\xi)/\text{del}_f(\xi)/\text{add}_f(\xi)$  fluents and the corresponding set of *programming* actions.
- The length of  $\mathcal{T}$ , the observed plan execution. The larger  $1 \leq i \leq n$ , the more  $\{\text{test}_i\}$  fluents and  $\{\text{validate}_i\}$  actions in  $P_\Lambda$ .

#### 5.4. Tuning the compilation with background knowledge

A distinctive feature of Inductive Logic Programming (ILP) is that ILP can leverage *background knowledge* to learn logic programs from data [30]. Inspired by ILP, we show that our approach for the learning of STRIPS action models can also leverage *background knowledge* in this case to optimize the performance of the  $P_\Lambda$  compilation.

##### 5.4.1. Static predicates

A *static predicate*  $p \in \Psi$  is a predicate that does not appear in the effects of any action [31]. Therefore, one can get rid of the mechanism for programming these predicates in the effects of any action schema while keeping the compilation complete. Given a static predicate  $p$ :

- Fluents  $\text{del}_f(\xi)$  and  $\text{add}_f(\xi)$ , such that  $f \in F_v$  is an instantiation of the static predicate  $p$  in the set of *variable objects*  $\Omega_v$ , can be discarded for every  $\xi \in \Xi$ .
- Actions  $\text{programEff}_{t,\xi}$  (s.t.  $f \in F_v$  is an instantiation of  $p$  in  $\Omega_v$ ) can also be discarded for every  $\xi \in \Xi$ .

Static predicates can also constrain the space of possible preconditions by looking at the given set of state observations in  $\mathcal{T}$ . One can assume that if a precondition  $f \in F_v$  (s.t.  $f \in F_v$  is an instantiation of a static predicate in  $\Omega_v$ ) is not compliant with the observations in  $\mathcal{T}$  then, fluents  $\text{pre}_f(\xi)$  and actions  $\text{programPre}_{t,\xi}$  can be discarded for every  $\xi \in \mathcal{M}$ . For instance, in the *zenotravel* [32] domain  $\text{pre\_next\_board\_v1\_v1}$ ,  $\text{pre\_next\_debark\_v1\_v1}$ ,  $\text{pre\_next\_fly\_v1\_v1}$ ,  $\text{pre\_next\_zoom\_v1\_v1}$ ,  $\text{pre\_next\_refuel\_v1\_v1}$  can be discarded (and their corresponding programming actions) because a precondition  $(\text{next } ?v1 \text{ } ?v1 - \text{flevel})$  will never hold at any state in  $\mathcal{T}$ .

Furthermore looking as well at the given example plans, fluents  $\text{pre}_f(\xi)$  and actions  $\text{programPre}_{t,\xi}$  are also discardable for every  $\xi \in \Xi$  if a precondition  $f \in F_v$  (s.t.  $f \in F_v$  is an instantiation of a static predicate in  $\Omega_v$ ) is not possible according to  $\mathcal{T}$ . Back to the *zenotravel* domain, if an example plan  $\pi_t \in \Pi$  contains the action  $(\text{fly plane1 city2 city0 f13 f12})$  and the corresponding state observations contain the static literal  $(\text{next f12 f13})$  but does not contain  $(\text{next f12 f12})$ ,  $(\text{next f13 f13})$  or  $(\text{next f13 f12})$  the only possible precondition including the static predicate is  $\text{pre\_next\_fly\_v5\_v4}$ .

##### 5.4.2. State constraints

The notion of *state-constraint* is very general and has been used in different areas of AI and for different purposes. If we restrict ourselves to planning, *state-constraints* are abstractions for compactly specifying sets of states. For instance, *state-constraints* in planning allow to specify the set of states where a given action is applicable, the set of states where a given *derived predicate* holds or the set of states that are considered goal states.

*State invariants* is a kind of state-constraints useful for computing more compact state representations [33] or making *satisfiability planning* and *backward search* more efficient [34, 35]. Given a classical planning problem  $P = \langle F, A, I, G \rangle$ , a *state invariant* is a formula  $\phi$  that holds at the initial state of a given classical planning problem,  $I \models \phi$ , and at every state  $s$ , built from  $F$ , that is reachable from  $I$  by applying actions in  $A$ .

The formula  $\phi_{I,A}^*$  represents the *strongest invariant* and exactly characterizes the set of all states reachable from  $I$  with the actions in  $A$ . For instance Figure 5 shows five clauses that define the *strongest invariant* for *blocksworld*. There are infinitely many strongest invariants, but they are all logically equivalent, and computing the strongest invariant is PSPACE-hard as hard as testing plan existence.

$$\begin{aligned}
& \forall x_1, x_2 \text{ ontable}(x_1) \leftrightarrow \neg \text{on}(x_1, x_2). \\
& \forall x_1, x_2 \text{ clear}(x_1) \leftrightarrow \neg \text{on}(x_2, x_1). \\
& \forall x_1, x_2, x_3 \neg \text{on}(x_1, x_2) \vee \neg \text{on}(x_1, x_3) \text{ such that } x_2 \neq x_3. \\
& \forall x_1, x_2, x_3 \neg \text{on}(x_2, x_1) \vee \neg \text{on}(x_3, x_1) \text{ such that } x_2 \neq x_3. \\
& \forall x_1, \dots, x_n \neg (\text{on}(x_1, x_2) \wedge \text{on}(x_2, x_3) \wedge \dots \wedge \text{on}(x_{n-1}, x_n) \wedge \text{on}(x_n, x_1)).
\end{aligned}$$

Figure 5: An example of the strongest invariant for the *blocksworld* domain.

A *mutex* (mutually exclusive) is a state invariant that takes the form of a binary clause and indicates a pair of different properties that cannot be simultaneously true [36]. For instance in a three-block *blocksworld*,  $\phi_1 = \neg \text{on}(\text{block}_A, \text{block}_B) \vee \neg \text{on}(\text{block}_A, \text{block}_C)$  is a mutex because *block<sub>A</sub>* can only be on top of a single block.

A *domain invariant* is an instance-independent invariant, i.e. holds for any possible initial state and set of objects. Therefore, if a given state  $s$  holds  $s \not\models \phi$  such that  $\phi$  is a *domain invariant*, it means that  $s$  is not a valid state. Domain invariants are often compactly defined as *lifted invariants* (also called schematic invariants) [37]. For instance,  $\phi_2 = \forall x : (\neg \text{handempty} \vee \neg \text{holding}(x))$ , is a *domain mutex* for the *blocksworld* because the robot hand is never empty and holding a block at the same time.

An interesting contribution of our compilation is that the validation of an action model can also be done with *state constraints*. Given  $\Phi$ , a set of either state or trajectory constraints, our validate actions can be adapted to check also that the learned model satisfy a constraint  $\phi \in \Phi$ :

$$\begin{aligned}
\text{pre}(\text{validate}_i) &= \phi \cup \{\text{test}_j\}_{j \in I \leq j < i} \cup \{\neg \text{test}_j\}_{j \in I \leq j \leq |I|} \cup \{\text{mode}_{\text{val}}\}, \\
\text{cond}(\text{validate}_i) &= \{\emptyset\} \triangleright \{\text{test}_i, \neg \text{mode}_{\text{val}}\}.
\end{aligned}$$

This redefinition of validate actions applies also to *trajectory constraints* because LTL formulae can be represented using classical action preconditions and goals by encoding the Non-deterministic Büchi Automaton (NBA), that is equivalent to the corresponding LTL formula, as part of the classical planning tasks [38].

Because of the combinatorial nature of the search for a solution plan, the sooner unpromising nodes are pruned from the search the more efficient the computation of a solution plan. Constraints can be used to confine earlier the set of possible STRIPS action models and reduce then the learning hypothesis space. With regard to our compilation, *domain mutex* are useful to reduce the amount of applicable actions for programming a precondition or an effect for a given action schema. For example given the *domain mutex*  $\phi = (\neg f_1 \vee \neg f_2)$  such that  $f_1 \in F_v(\xi)$  and  $f_2 \in F_v(\xi)$ , we can redefine the corresponding programming actions for **removing** the *precondition*  $f_1 \in F_v(\xi)$  from the action schema  $\xi \in \mathcal{M}$  as:

$$\begin{aligned}
\text{pre}(\text{programPre}_{f_1, \xi}) &= \{\neg \text{del}_{f_1}(\xi), \neg \text{add}_{f_1}(\xi), \text{mode}_{\text{prog}}, \text{pre}_{f_1}(\xi), \text{pre}_{f_2}(\xi)\}, \\
\text{cond}(\text{programPre}_{f_1, \xi}) &= \{\emptyset\} \triangleright \{\neg \text{pre}_{f_1}(\xi)\}.
\end{aligned}$$

## 6. Evaluating STRIPS Action Models with Classical Planning

If the actual model is available, the quality of a learned action model is quantifiable using the *precision* and *recall* metrics. *Precision* and *recall* are two syntactic metrics frequently used in *pattern recognition*, *information retrieval* and *binary classification* and are more informative than simply counting the number of errors in the learned model or computing the *symmetric difference* between the learned and the reference model [23]. Intuitively, precision gives a notion of *soundness* while recall gives a notion of the *completeness* of the learned models:

- *Precision* =  $\frac{tp}{tp+fp}$ , where  $tp$  is the number of *true positives* (predicates that correctly appear in the action model) and  $fp$  is the number of *false positives* (predicates of the learned model that should not appear).
- *Recall* =  $\frac{tp}{tp+fn}$ , where  $fn$  is the number of *false negatives* (predicates that should appear in the learned model but are missing).

The roles of two *comparable* action schemes, or the roles of two action parameters that belong to the same type, can be swapped by a  $\Lambda$  learning task when the observed input data, given in  $\mathcal{T}$ , is insufficient. For instance, when  $\mathcal{T}$  does not contain any intermediate action the *blocksworld* operator `stack` can be *learned* with the preconditions and effects of the `unstack` operator and vice versa, or the parameters of the `stack` operator can be swapped. Pure syntax-based evaluation metrics (like *precision* and *recall*) can report low scores for learned models that are actually good but correspond to *reformulations* of the actual model; i.e. a learned model semantically equivalent but syntactically different to the reference model.

Here we introduce a novel evaluation approach that is robust to role changes of this particular kind. The intuition of the approach is to *semantically* assess how well a STRIPS action model  $\mathcal{M}$  explains given observations of plan executions according to the amount of *edition* required by  $\mathcal{M}$  to induce that observations. This semantic evaluation approach is again flexible to various amount and kind of available input knowledge.

### 6.1. The STRIPS edit distance

We first define the two allowed *operations* to edit a given STRIPS action model  $\mathcal{M}$ :

- *Deletion*. A fluent  $pre_f(\xi)/del_f(\xi)/add_f(\xi)$  is removed from the operator schema  $\xi \in \mathcal{M}$ , such that  $f \in F_v(\xi)$ .
- *Insertion*. A fluent  $pre_f(\xi)/del_f(\xi)/add_f(\xi)$  is added to the operator schema  $\xi \in \mathcal{M}$ , s.t.  $f \in F_v(\xi)$ .

We can now formalize an *edit distance* that quantifies how similar two given STRIPS action models are. The distance is symmetric and meets the *metric axioms* provided that the two *edit operations*, deletion and insertion, have the same positive cost.

**Definition 3.** Let  $\mathcal{M}$  and  $\mathcal{M}'$  be two STRIPS action models, such that they are comparable. The **edit distance**, denoted as  $\delta(\mathcal{M}, \mathcal{M}')$ , is the minimum number of edit operations that is required to transform  $\mathcal{M}$  into  $\mathcal{M}'$ .

Since  $F_v$  is a bound set, the maximum number of edits that can be introduced to a given action model defined within  $F_v$  is bound as well. In more detail, for an operator schema  $\xi \in \mathcal{M}$  the maximum number of edits that can be introduced to their precondition set is  $|F_v(\xi)|$  while the max number of edits that can be introduced to the effects is twice  $|F_v(\xi)|$ .

**Definition 4.** The **maximum edit distance** of an STRIPS action model  $\mathcal{M}$  built from the set of possible elements  $F_v$  is  $\delta(\mathcal{M}, *) = \sum_{\xi \in \mathcal{M}} 3 \times |F_v(\xi)|$ .

Note that the number of deletions indicate the number of *false positives* while the number of insertions represents the number of *false negatives*. As explained, these numbers can be normalized with the amount of *true positives* to compute the *precision* and *recall* of a learned model with respect to a reference model. Normally evaluating a given learned domain with respect to the actual generative model is not possible because the actual model is not available. As the ARMS system shows, the error of a learned action model can also be estimated with respect to a set of observations of plan executions [13]. With this regard, we define now an edit distance to asses the quality of a learned action model with respect to a plan trace  $\mathcal{T} = \langle s_0, a_1, s_1, \dots, a_n, s_n \rangle$  obtained watching the execution of a plan  $\pi = \langle a_1, \dots, a_n \rangle$  such that, for each  $1 \leq i \leq n$ ,  $a_i$  is applied in  $s_{i-1}$  and generates the successor state  $s_i$ .

**Definition 5.** Given  $\mathcal{M}$ , a STRIPS action model built from  $F_v$ , and a plan trace  $\mathcal{T} = \langle s_0, a_1, s_1, \dots, a_n, s_n \rangle$  whose state observation are built with fluents in  $F$ . The **observation edit distance**, denoted by  $\delta(\mathcal{M}, \mathcal{T})$ , is the minimal edit distance from  $\mathcal{M}$  to any comparable model  $\mathcal{M}'$ , such that  $\mathcal{M}'$  can produce a valid plan trace  $\mathcal{T}$ ;

$$\delta(\mathcal{M}, \mathcal{T}) = \min_{\mathcal{M}' \rightarrow \mathcal{T}} \delta(\mathcal{M}, \mathcal{M}')$$

The *observation edit distance* is mappable into a likelihood with the following expression  $1 - \frac{\delta(\mathcal{M}, \mathcal{T})}{\delta(\mathcal{M}, *)}$ . Further, following the previous correspondances (*false positives*  $\equiv$  *deletions* and *false negatives*  $\equiv$  *insertions*) we can redefine a *semantic* version of the *precision* and *recall* metrics of a learned model with respect to a partially observed plan trace  $\mathcal{T} = \langle s_0, a_1, s_1, \dots, a_n, s_n \rangle$ . In this case, for each action schema  $\xi \in \mathcal{M}$ , the corresponding number of *true positives* is given by  $tp(\xi) = |pre(\xi)| + |del(\xi)| + |add(\xi)| - fp(\xi)$ .



## 6.2. Computing the edit distance with classical planning

Our compilation is extensible to compute the *observation edit distance* by simply considering that the input STRIPS model  $\mathcal{M}$ , given in a learning task  $\Lambda = \langle \mathcal{M}, \Psi, \mathcal{T} \rangle$ , is *non-empty*. In other words, now  $\mathcal{M}$  is a set of given operator schemas, wherein each  $\xi \in \mathcal{M}$  initially contains  $head(\xi)$  but also the  $pre(\xi)$ ,  $del(\xi)$  and  $add(\xi)$  sets. A solution to the planning task resulting from the extended compilation is a sequence of actions that:

1. **Edits the action model  $\mathcal{M}$  to build  $\mathcal{M}'$ .** A solution plan starts with a *prefix* that modifies the preconditions and effects of the action schemes in  $\mathcal{M}$  using to the two *edit operations* defined above, *deletion* and *insertion*. In theory, we could implement a third edit operation for *substituting* a fluent from a given operator schema. However, and with the aim of keeping a tractable branching factor of the planning instances that result from our compilations, we only implement *deletion* and *insertion*.
2. **Validates the edited model  $\mathcal{M}'$  in the observed plan trace.** The solution plan continues with a postfix that validates the edited model  $\mathcal{M}'$  on the given observations  $\mathcal{T}$ , as explained in Section ?? for the models that are programmed from scratch.

Now  $\Lambda$  does not formalize a learning task but the task of editing  $\mathcal{M}$  to produce the plan trace  $\mathcal{T}$ , which results in the edited model  $\mathcal{M}'$ . The output of the extended compilation is a classical planning task  $P'_\Lambda = \langle F_\Lambda, A'_\Lambda, I'_\Lambda, G_\Lambda \rangle$ :

- $F_\Lambda$ ,  $I_\Lambda$  and  $G_\Lambda$  are defined as in the previous compilation. Note that, the input action model  $\mathcal{M}$  is encoded in the initial state. This means that the fluents  $pre_f(\xi)/del_f(\xi)/add_f(\xi)$ ,  $f \in F_v(\xi)$ , hold in  $I_\Lambda$  iff they appear in  $\mathcal{M}$ .
- $A'_\Lambda$ , comprises the same three kinds of actions of  $A_\Lambda$ . The actions for *applying* an already programmed operator schema and the actions for *validating* an observation are defined exactly as in the previous compilation. The only difference here is that each action for *programming* an operator schema now implement the two *edit operations* (i.e. include actions for *inserting* a precondition and for *deleting* a negative/positive effect).

To illustrate this, the plan of Figure 6 shows the plan for editing a given *blocksworld* action model where again the positive effects (`handempty`) and (`clear ?v1`) of the `stack` schema are missing. In this case the edited action model is however validated at the plan shown in Figure 2.

```

00 : (insert_add_handempty_stack)
01 : (insert_add_clear_stack_var1)
02 : (apply_unstack blockB blockA i1 i2)
03 : (apply_putdown blockB i2 i3)
04 : (apply_pickup blockA i3 i4)
05 : (apply_stack blockA blockB i4 i5)
06 : (validate_1)

```

Figure 6: Plan for editing a given *blocksworld* schema and validating it at the plan shown in Figure 2.

Our interest when computing the *observation edit distance* is not in the resulting action model  $\mathcal{M}'$  but in the number of required *edit operations* (insertions and deletions) for that  $\mathcal{M}'$  is validated in the given observations, e.g.  $\delta(\mathcal{M}, \mathcal{T}) = 2$  for the example in Figure 6. In this case  $\delta(\mathcal{M}, *) = 3 \times 2 \times (11 + 5)$  since there are 4 action schemes (`pickup`, `putdown`, `stack` and `unstack`) and  $|F_v| = |F_v(stack)| = |F_v(unstack)| = 11$  while  $|F_v(pickup)| = |F_v(putdown)| = 5$  (as shown in Section ??). The *observation edit distance* is exactly computed if the classical planning task resulting from our compilation is optimally solved (according to the number of edit actions); is approximated if it is solved with a satisfying planner; and is a less accurate estimate (but faster to be computed) if the solved task is a relaxation of the classical planning task that results from our compilation [39].

Last but not least, this compilation is flexible to compute the *edit distance* between two *comparable* STRIPS action models,  $\mathcal{M}$  and  $\mathcal{M}'$ . A solution to the planning task resulting from this compilation is a sequence of actions that edits the action model  $\mathcal{M}$  to produce  $\mathcal{M}'$  using to the two *edit operations*, deletion and insertion. In this case the edited model is not validated on a sequence of observations or plans but on the given action model  $\mathcal{M}'$  that acts as a reference. The sets of fluents  $F_\Lambda$  and  $I_\Lambda$  are defined like in the previous compilation. With respect to the actions,  $A_\Lambda$  again implement the two *edit operations* (i.e. include actions for *inserting* a precondition and for *deleting* a

negative/positive effect) but does not contain  $\text{apply}_{\xi,\omega}$  or  $\text{validate}_i$  actions because the STRIPS action model are not validated in any observation of plan executions. Finally, the goals are also different and are now defined by the set of fluents,  $\text{pre}_f(\xi)/\text{del}_f(\xi)/\text{add}_f(\xi)$  that represent all the operator schema  $\xi \in \mathcal{M}'$ , such that  $f \in F_v(\xi)$ . To illustrate this, the plan of Figure 7 solves the classical planning task that corresponds to computing the distance between a *blocksworld* action model, where the positive effects (`handempty`) and (`clear ?v1`) of the `stack` schema are missing, and the actual four-operator *blocksworld* model. The plan edits first the `stack` schema, *inserting* these two positive effects. Again our interest is in the number of required *edit operations*, e.g.  $\delta(\mathcal{M}, \mathcal{M}') = 2$ .

```
00 : (insert_add_handempty_stack)
01 : (insert_add_clear_stack_var1)
```

Figure 7: Plan for computing the distance between a *blocksworld* action model, where the positive effects (`handempty`) and (`clear ?v1`) of the `stack` schema are missing, and the actual four-operator *blocksworld* model.

## 7. Experimental results

### 7.1. Setup

The domains used in the evaluation are IPC domains that satisfy the STRIPS requirement [25], taken from the PLANNING.DOMAINS repository [40]. We only use 5 learning examples for each domain and they are fixed for all the experiments so we can evaluate the impact of the input knowledge in the quality of the learned models. All experiments are run on an Intel Core i5 3.10 GHz x 4 with 8 GB of RAM.

- **Planner.** The classical planner we use to solve the instances that result from our compilations is MADAGASCAR [34]. We use MADAGASCAR because its ability to deal with planning instances populated with dead-ends. In addition, SAT-based planners can apply the actions for programming preconditions in a single planning step (in parallel) because these actions do not interact. Actions for programming action effects can also be applied in a single planning step reducing significantly the planning horizon.
- **Reproducibility.** We make fully available the compilation source code, the evaluation scripts and the used benchmarks at this repository <https://github.com/sjimenezgithub/strips-learning> so any experimental data reported in the paper is fully reproducible.

### 7.2. Evaluating with a reference model

Here we evaluate the learned models with respect to the actual generative model.

#### 7.2.1. Learning from plans

We start evaluating our approach with  $\Lambda = \langle \mathcal{M}, \Psi, \mathcal{T} \rangle$  learning tasks, where the action of the executed plans are available and the state observation sequence contains only the corresponding initial and goal states,  $s_o^t$  and  $s_n^t$ , for every trace plan  $t \in \mathcal{T}$ . We then repeat the evaluation but exploiting potential *static predicates* computed from the observed states in  $\mathcal{T}$ , which are the predicates that appear unaltered in the states that belong to the same plan. Static predicates are used to constrain the space of possible action models as explained in Section ??.

Table 4 shows the obtained results. Precision (**P**) and recall (**R**) are computed separately for the preconditions (**Pre**), positive effects (**Add**) and negative Effects (**Del**), while the last two columns of each setting and the last row report averages values. We can observe that identifying static predicates leads to models with better precondition *recall*. This fact evidences that many of the missing preconditions corresponded to static predicates because there is no incentive to learn them as they always hold [41].

Table 5 reports the total planning time, the preprocessing time (in seconds) invested by MADAGASCAR to solve the planning instances that result from our compilation as well as the number of actions of the solution plans. All the learning tasks are solved in a few seconds. Interestingly, one can identify the domains with static predicates by just looking at the reported plan length. In these domains some of the preconditions that correspond to static predicates are directly derived from the learning examples and therefore fewer programming actions are required.

	No Static								Static							
	Pre		Add		Del				Pre		Add		Del			
	P	R	P	R	P	R	P	R	P	R	P	R	P	R	P	R
Blocks	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Driverlog	1.0	0.36	0.75	0.86	1.0	0.71	0.92	0.64	0.9	0.64	0.56	0.71	0.86	0.86	0.78	0.73
Ferry	1.0	0.57	1.0	1.0	1.0	1.0	1.0	0.86	1.0	0.57	1.0	1.0	1.0	1.0	1.0	0.86
Floortile	0.52	0.68	0.64	0.82	0.83	0.91	0.66	0.80	0.68	0.68	0.89	0.73	1.0	0.82	0.86	0.74
Grid	0.62	0.47	0.75	0.86	0.78	1.0	0.71	0.78	0.79	0.65	1.0	0.86	0.88	1.0	0.89	0.83
Gripper	1.0	0.67	1.0	1.0	1.0	1.0	1.0	0.89	1.0	0.67	1.0	1.0	1.0	1.0	1.0	0.89
Hanoi	1.0	0.50	1.0	1.0	1.0	1.0	1.0	0.83	0.75	0.75	1.0	1.0	1.0	1.0	0.92	0.92
Miconic	0.75	0.33	0.50	0.50	0.75	1.0	0.67	0.61	0.89	0.89	1.0	0.75	0.75	1.0	0.88	0.88
Satellite	0.60	0.21	1.0	1.0	1.0	0.75	0.87	0.65	0.82	0.64	1.0	1.0	1.0	0.75	0.94	0.80
Transport	1.0	0.40	1.0	1.0	1.0	0.80	1.0	0.73	1.0	0.70	0.83	1.0	1.0	0.80	0.94	0.83
Visitall	1.0	0.50	1.0	1.0	1.0	1.0	1.0	0.83	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Zenotravel	1.0	0.36	1.0	1.0	1.0	0.71	1.0	0.69	1.0	0.64	0.88	1.0	1.0	0.71	0.96	0.79
	0.88	0.50	0.88	0.92	0.95	0.91	0.90	0.78	0.90	0.74	0.93	0.92	0.96	0.91	0.93	0.86

Table 4: *Precision and recall scores for learning tasks from labeled plans without (left) and with (right) static predicates.*

	No Static			Static		
	Total	Preprocess	Length	Total	Preprocess	Length
Blocks	0.04	0.00	72	0.03	0.00	72
Driverlog	0.14	0.09	83	0.06	0.03	59
Ferry	0.06	0.03	55	0.06	0.03	55
Floortile	2.42	1.64	168	0.67	0.57	77
Grid	4.82	4.75	88	3.39	3.35	72
Gripper	0.03	0.01	43	0.01	0.00	43
Hanoi	0.12	0.06	48	0.09	0.06	39
Miconic	0.06	0.03	57	0.04	0.00	41
Satellite	0.20	0.14	67	0.18	0.12	60
Transport	0.59	0.53	61	0.39	0.35	48
Visitall	0.21	0.15	40	0.17	0.15	36
Zenotravel	2.07	2.04	71	1.01	1.00	55

Table 5: Total planning time, preprocessing time and plan length for learning tasks from labeled plans without/with static predicates.

When static predicates are identified, the resulting compilation is also much more compact and produces smaller planning/instantiation times.

We evaluate now the ability of our approach to support partially specified action models; that is, when the input model  $\mathcal{M}$  is not empty because some preconditions and effects of the actions are initially known. In this particular experiment, the model of half of the actions is given in  $\mathcal{M}$  as an extra input of the learning task. Tables 6 and 7 summarize the obtained results, which include the identification of static predicates. We only report the *precision* and *recall* of the *unknown* actions since the values of the metrics of the *known* action models is 1.0. In this experiment, a low value of *precision* or *recall* has a greater impact than in the previous learning tasks because the evaluation is done only over half of the actions. This occurs, for instance, in the precondition *recall* of domains such as *Floortile*, *Gripper* or *Satellite*.

Remarkably, the overall *precision* is now 0.98, which means that the contents of the learned models is highly reliable. The value of *recall*, 0.87, is an indication that the learned models still miss some information (preconditions are again the component more difficult to be fully learned). Overall, the results confirm the previous trend: the more input knowledge of the task, the better the models and the less planning time. Additionally, the solution plans required for this task are smaller because it is only necessary to program half of the actions (the other half are included in the input knowledge  $\mathcal{M}$ ). *Visitall* and *Hanoi* are excluded from this evaluation because they only contain one action schema.

### 7.2.2. Learning from state observations

Here we evaluate our approach with learning tasks of the kind  $\Lambda = \langle \mathcal{M}, \Psi, \mathcal{T} \rangle$ , where the action of the executed plans are not available but the initial and goal states are known. When input plans are not available, the planner must

	Pre		Add		Del			
	P	R	P	R	P	R	P	R
Blocks	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Driverlog	1.0	0.71	1.0	1.0	1.0	1.0	1.0	0.90
Ferry	1.0	0.67	1.0	1.0	1.0	1.0	1.0	0.89
Floortile	0.75	0.60	1.0	0.80	1.0	0.80	0.92	0.73
Grid	1.0	0.67	1.0	1.0	1.0	1.0	0.84	0.78
Gripper	1.0	0.50	1.0	1.0	1.0	1.0	1.0	0.83
Miconic	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Satellite	1.0	0.57	1.0	1.0	1.0	1.0	1.0	0.86
Transport	1.0	0.75	1.0	1.0	1.0	1.0	1.0	0.92
Zenotravel	1.0	0.67	1.0	1.0	1.0	0.67	1.0	0.78
	0.98	0.71	1.0	0.98	1.0	0.95	0.98	0.87

Table 6: *Precision* and *recall* scores for learning tasks with partially specified action models.

	Total time	Preprocess	Plan length
Blocks	0.07	0.01	54
Driverlog	0.03	0.01	40
Ferry	0.06	0.03	45
Floortile	0.43	0.42	55
Grid	3.12	3.07	53
Gripper	0.03	0.01	35
Miconic	0.03	0.01	34
Satellite	0.14	0.14	47
Transport	0.23	0.21	37
Zenotravel	0.90	0.89	40

Table 7: Time and plan length learning for learning tasks with partially specified action models.

not only compute the action models but also the plans that satisfy the input observations. Table 8 and 9 summarize the results obtained for this using static predicates and partially specified models. Values for the *Zenotravel* and *Grid* domains are not reported because MADAGASCAR was not able to solve the corresponding planning tasks within a 1000 sec. time bound. The values of *precision* and *recall* are significantly lower than in Table 4. Given that the learning hypothesis space is now fairly under-constrained, actions can be reformulated and still be compliant with the inputs (e.g. the *blocksworld* operator *stack* can be *learned* with the preconditions and effects of the *unstack* operator and vice versa). We tried to minimize this effect with the additional input knowledge (static predicates and partially specified action models) and yet the results are below the scores obtained when learning from labeled plans.

Now we evaluate our approach with learning tasks of the kind  $\Lambda = \langle \mathcal{M}, \Psi, \mathcal{T} \rangle$ , where the action of the executed plans are not available but where the plan trace  $\mathcal{T}$  contains all the intermediate states, not just the initial and final

	Pre		Add		Del			
	P	R	P	R	P	R	P	R
Blocks	0.33	0.33	0.75	0.50	0.33	0.33	0.47	0.39
Driverlog	1.0	0.29	0.33	0.67	1.0	0.50	0.78	0.48
Ferry	1.0	0.67	0.50	1.0	1.0	1.0	0.83	0.89
Floortile	0.67	0.40	0.50	0.40	1.0	0.40	0.72	0.40
Grid	-	-	-	-	-	-	-	-
Gripper	1.0	0.50	1.0	1.0	1.0	1.0	1.0	0.83
Miconic	0.0	0.0	0.33	0.50	0.0	0.0	0.11	0.17
Satellite	1.0	0.14	0.67	1.0	1.0	1.0	0.89	0.71
Transport	0.0	0.0	0.25	0.5	0.0	0.0	0.08	0.17
Zenotravel	-	-	-	-	-	-	-	-
	0.63	0.29	0.54	0.70	0.67	0.53	0.61	0.51

Table 8: *Precision* and *recall* scores for learning from (initial,final) state pairs.

	Total time	Preprocess	Plan length
Blocks	2.14	0.00	58
Driverlog	0.09	0.00	88
Ferry	0.17	0.01	65
Floortile	6.42	0.15	126
Grid	-	-	-
Gripper	0.03	0.00	47
Miconic	0.04	0.00	68
Satellite	4.34	0.10	126
Transport	2.57	0.21	47
Zenotravel	-	-	-

Table 9: Time and plan length when learning from (initial,final) state pairs.

states. Table 10 shows the precision (**P**) and recall (**R**) computed separately for the preconditions (**Pre**), positive effects (**Add**) and negative Effects (**Del**) while the last two columns report averages values. The reason why the scores in Table 10 are still low, despite more state observations are available, is because the syntax-based nature of *precision* and *recall* make these two metrics report low scores for learned models that are semantically correct but correspond to *reformulations* of the actual model (changes in the roles of actions with matching headers or parameters with matching types).

	Pre		Add		Del		P	R
	P	R	P	R	P	R		
blocks	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44
driverlog	0.0	0.0	0.25	0.43	0.0	0.0	0.08	0.14
ferry	1.0	0.71	1.0	1.0	1.0	1.0	1.0	0.9
floortile	0.38	0.55	0.4	0.18	0.56	0.45	0.44	0.39
grid	0.5	0.47	0.33	0.29	0.25	0.29	0.36	0.35
gripper	0.83	0.83	0.75	0.75	0.75	0.75	0.78	0.78
hanoi	0.5	0.25	0.5	0.5	0.0	0.0	0.33	0.25
hiking	0.43	0.43	0.5	0.35	0.44	0.47	0.46	0.42
miconic	0.6	0.33	0.33	0.25	0.33	0.33	0.42	0.31
npuzzle	0.33	0.33	0.0	0.0	0.0	0.0	0.11	0.11
parking	0.25	0.21	0.0	0.0	0.0	0.0	0.08	0.07
satellite	0.6	0.21	0.8	0.8	1.0	0.5	0.8	0.5
transport	1.0	0.3	0.8	0.8	1.0	0.6	0.93	0.57
visitall	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
zenotravel	0.67	0.29	0.33	0.29	0.33	0.14	0.44	0.24

Table 10: Precision and recall values obtained without computing the  $f_{P\&R}$  mapping with the reference model.

To give an insight of the actual quality of the learned models, we defined a method for computing *Precision* and *Recall* that is robust to the mentioned model *reformulations*. Precision and recall are often combined using the *harmonic mean*. This expression, called the *F-measure* or the balanced *F-score*, is defined as  $F = 2 \times \frac{Precision \times Recall}{Precision + Recall}$ . Given the learned action model  $\mathcal{M}$  and the reference action model  $\mathcal{M}^*$ , the bijective function  $f_{P\&R} : \mathcal{M} \mapsto \mathcal{M}^*$  is the mapping between the learned and the reference model that maximizes the accumulated *F-measure* (considering swaps in the actions with matching headers or parameters with matching types).

Table 11 shows that significantly higher values of *precision* and *recall* are reported when a learned action schema,  $\xi \in \mathcal{M}$ , is compared to its corresponding reference schema given by the  $f_{P\&R}$  mapping ( $f_{P\&R}(\xi) \in \mathcal{M}^*$ ). The *blocksworld* and *gripper* domains are perfectly learned from only 25 state observations. These results evidence that in all of the evaluated domains, except for *ferry* and *satellite*, the learning task swaps the roles of some actions (or parameters) with respect to their role in the reference model.

### 7.3. Evaluating with a test set

When a reference model is not available, the learned models are tested with an observation set. Table 12 summarizes the results obtained when evaluating the quality of the learned models with respect to a test set of state observations. Each test set comprises between 20 and 50 observations per domain and is generated executing the

	Pre		Add		Del		P	R
	P	R	P	R	P	R		
blocks	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
driverlog	0.67	0.14	0.33	0.57	0.67	0.29	0.56	0.33
ferry	1.0	0.71	1.0	1.0	1.0	1.0	1.0	0.9
floortile	0.44	0.64	1.0	0.45	0.89	0.73	0.78	0.61
grid	0.63	0.59	0.67	0.57	0.63	0.71	0.64	0.62
gripper	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
hanoi	1.0	0.5	1.0	1.0	1.0	1.0	1.0	0.83
hiking	0.78	0.6	0.93	0.82	0.88	0.88	0.87	0.77
miconic	0.8	0.44	1.0	0.75	1.0	1.0	0.93	0.73
npuzzle	0.67	0.67	1.0	1.0	1.0	1.0	0.89	0.89
parking	0.56	0.36	0.5	0.33	0.5	0.33	0.52	0.34
satellite	0.6	0.21	0.8	0.8	1.0	0.5	0.8	0.5
transport	1.0	0.3	1.0	1.0	1.0	0.6	1.0	0.63
visitall	0.67	1.0	1.0	1.0	1.0	1.0	0.89	1.0
zenotravel	1.0	0.43	0.67	0.57	1.0	0.43	0.89	0.48

Table 11: Precision and recall values obtained when computing the  $f_{P\&R}$  mapping with the reference model.

plans for various instances of the IPC domains and collecting the intermediate states. The table shows, for each domain, the *observation edit distance* (computed with our extended compilation), the *maximum edit distance*, and their ratio. The reported results show that, despite learning only from 25 state observations, 12 out of 15 learned domains yield ratios of 90% or above. This fact evidences that the learned models require very small amounts of edition to match the observations of the given test set.

	$\delta(\mathcal{M}, O)$	$\delta(\mathcal{M}, *)$	$1 - \frac{\delta(\mathcal{M}, O)}{\delta(\mathcal{M}, *)}$
blocks	0	90	1.0
driverlog	5	144	0.97
ferry	2	69	0.97
floortile	34	342	0.90
grid	42	153	0.73
gripper	2	30	0.93
hanoi	1	63	0.98
hiking	69	174	0.60
miconic	3	72	0.96
npuzzle	2	24	0.92
parking	4	111	0.96
satellite	24	75	0.68
transport	4	78	0.95
visitall	2	24	0.92
zenotravel	3	63	0.95

Table 12: Evaluation of the quality of the learned models with respect to an observations test set.

The learning scores of several domains in Table 11 are above the ones reported in Table 10. The reason lies in the particular observations comprised by the test sets. As an example, in the *driverlog* domain, the action schema *disembark-truck* is missing from the learned model because this action is never induced from the observations in the training set; that is, such action never appears in the corresponding *unobserved* plan. The same happens with the *paint-down* action of the *floortile* domain or *move-curb-to-curb* in the *parking* domain. Interestingly, these actions do not appear either in the test sets and so the learned action models are not penalized in Table 12. Generating *informative* and *representative* observations for learning planning action models is an open issue. Planning actions include preconditions that are only satisfied by specific sequences of actions, often, with a low probability of being chosen by chance [42].

## 8. Conclusions

We presented a novel approach for learning STRIPS action models from examples using classical planning. The approach is flexible to various amount and kind of input knowledge and accepts partially specified action models.

Unlike extensive-data ML approaches, our work explores an alternative research direction to learn sound models from very small data sets. The action models of the *blocksworld* or *gripper* domains were perfectly learned from only 25 state observations. Moreover, in 12 out of the 15 domains, the learned models yield *Precision* values over 0.75.

To the best of our knowledge, this is the first work on learning STRIPS action models from state observations, using exclusively an *off-the-shelf* classical planner, and evaluated over a wide range of different domains. Recently, the work in [43] proposes a planning compilation for learning action models from plan traces following the *finite domain* representation for the state variables. This is a theoretical study on the boundaries of the learned models and no experimental results are reported.

We also introduced the *precision* and *recall* metrics, widely used in ML, for evaluating the learned action models with respect to a given reference model. These two metrics measure the soundness and completeness of the learned models and facilitate the identification of model flaws.

When example plans are available, we can compute accurate action models from small sets of learning examples in little computation time, less than a second. In many applications, the actual actions executed by the observed agent are not available but, instead, the resulting states can be observed. With this regard, we extended our approach for learning also from state observations as it broadens the range of application to external observers and facilitates the representation of imperfect observability, as shown in plan recognition [44], as well as learning from unstructured data, like state images [22]. When action plans are not available, our approach still produces action models that are compliant with the input information. In this case, since learning is not constrained by actions, operators can be reformulated changing their semantics, in which case the comparison with a reference model turns out to be tricky.

We also introduced a semantic method for evaluating the learned STRIPS action models with respect to observations of plan executions. Generating *informative* examples for learning planning action models is still an open issue. Planning actions include preconditions that are only satisfied by specific sequences of actions which have low probability of being chosen by chance [42]. The success of recent algorithms for exploring planning tasks [45] motivates the development of novel techniques that enable to autonomously collect informative learning examples. The combination of such exploration techniques with our learning approach is an appealing research direction that opens up the door to the bootstrapping of planning action models.

### Acknowledgment

This work is supported by the Spanish MINECO project TIN2017-88476-C2-1-R. Diego Aineto is partially supported by the *FPUI6/03184* and Sergio Jiménez by the *RYC15/18009*, both programs funded by the Spanish government.

### References

- [1] M. Ghallab, D. Nau, P. Traverso, *Automated Planning: theory and practice*, Elsevier, 2004.
- [2] M. Ramírez, *Plan recognition as planning*, Ph.D. thesis, Universitat Pompeu Fabra (2012).
- [3] H. Geffner, B. Bonet, *A concise introduction to models and methods for automated planning* (2013).
- [4] S. Kambhampati, *Model-lite planning for the web age masses: The challenges of planning with incomplete and evolving domain models*, in: National Conference on Artificial Intelligence, AAAI-07, 2007.
- [5] R. S. Michalski, J. G. Carbonell, T. M. Mitchell, *Machine learning: An artificial intelligence approach*, Springer Science & Business Media, 2013.
- [6] R. E. Fikes, N. J. Nilsson, *Strips: A new approach to the application of theorem proving to problem solving*, *Artificial Intelligence* 2 (3-4) (1971) 189–208.
- [7] B. Bonet, H. Palacios, H. Geffner, *Automatic derivation of memoryless policies and finite-state controllers using classical planners*, in: International Conference on Automated Planning and Scheduling (ICAPS), 2009.
- [8] J. Segovia, S. Jiménez, A. Jonsson, *Generalized planning with procedural domain control knowledge*, 2016.
- [9] J. Segovia-Aguas, S. Jiménez, A. Jonsson, *Hierarchical finite state controllers for generalized planning*, in: International Joint Conference on Artificial Intelligence, IJCAI-16, AAAI Press, 2016, pp. 3235–3241.
- [10] J. Segovia-Aguas, S. Jiménez, A. Jonsson, *Generating context-free grammars using classical planning*, in: International Joint Conference on Artificial Intelligence, ICAPS-17, 2017.
- [11] R. Howey, D. Long, M. Fox, *VAL: Automatic plan validation, continuous effects and mixed initiative planning using PDDL*, in: Tools with Artificial Intelligence, 2004. ICTAI 2004. 16th IEEE International Conference on, IEEE, 2004, pp. 294–301.
- [12] D. Aineto, S. Jiménez, E. Onaindia, *Learning strips action models with classical planning*.
- [13] Q. Yang, K. Wu, Y. Jiang, *Learning action models from plan examples using weighted max-sat*, *Artificial Intelligence* 171 (2-3) (2007) 107–143.
- [14] E. Amir, A. Chang, *Learning partially observable deterministic action models*, *Journal of Artificial Intelligence Research* 33 (2008) 349–402.

- [15] H. H. Zhuo, Q. Yang, D. H. Hu, L. Li, Learning complex action models with quantifiers and logical implications, *Artificial Intelligence* 174 (18) 1540–1569.
- [16] H. H. Zhuo, S. Kambhampati, Action-model acquisition from noisy plan traces., in: *International Joint Conference on Artificial Intelligence, IJCAI-13*, 2013, pp. 2444–2450.
- [17] K. Mourão, L. S. Zettlemoyer, R. P. A. Petrick, M. Steedman, Learning STRIPS operators from noisy and incomplete observations, in: *Conference on Uncertainty in Artificial Intelligence (UAI)*, 2012, pp. 614–623.
- [18] H. H. Zhuo, Crowdsourced action-model acquisition for planning, in: *National Conference on Artificial Intelligence, AAAI-15*, 2015, pp. 3439–3446.
- [19] S. Cresswell, P. Gregory, Generalised domain model acquisition from action traces, in: *International Conference on Automated Planning and Scheduling, ICAPS-11*, 2011.
- [20] P. Gregory, S. Cresswell, Domain model acquisition in the presence of static relations in the LOP system, in: *International Joint Conference on Artificial Intelligence, IJCAI-16*, 2016, pp. 4160–4164.
- [21] S. J. Russell, P. Norvig, *Artificial intelligence: a modern approach*, Pearson Education Limited., 2016.
- [22] M. Asai, A. Fukunaga, Classical planning in deep latent space: Bridging the subsymbolic-symbolic boundary, in: *National Conference on Artificial Intelligence, AAAI-18*, 2018.
- [23] J. Davis, M. Goadrich, The relationship between precision-recall and ROC curves, in: *International Conference on Machine learning, ACM*, 2006, pp. 233–240.
- [24] D. McDermott, M. Ghallab, A. Howe, C. Knoblock, A. Ram, M. Veloso, D. Weld, D. Wilkins, *PDDL – The Planning Domain Definition Language* (1998).
- [25] M. Fox, D. Long, PDDL2.1: An extension to PDDL for expressing temporal planning domains., *Journal of Artificial Intelligence Research* 20 (2003) 61–124.
- [26] J. Slaney, S. Thiébaux, Blocks world revisited, *Artificial Intelligence* 125 (1-2) (2001) 119–153.
- [27] S. Jiménez, T. De La Rosa, S. Fernández, F. Fernández, D. Borrajo, A review of machine learning for automated planning, *The Knowledge Engineering Review* 27 (04) (2012) 433–467.
- [28] M. Vallati, L. Chrapa, M. Grzes, T. L. McCluskey, M. Roberts, S. Sanner, The 2014 international planning competition: Progress and trends, *AI Magazine* 36 (3) (2015) 90–98.
- [29] J. Rintanen, Planning as satisfiability: Heuristics, *Artificial Intelligence* 193 (2012) 45–86.
- [30] S. Muggleton, L. De Raedt, Inductive logic programming: Theory and methods, *The Journal of Logic Programming* 19 (1994) 629–679.
- [31] M. Fox, D. Long, The automatic inference of state invariants in TIM, *Journal of Artificial Intelligence Research* 9 (1998) 367–421.
- [32] D. Long, M. Fox, The 3rd international planning competition: Results and analysis, *Journal of Artificial Intelligence Research* 20 (2003) 1–59.
- [33] M. Helmert, Concise finite-domain representations for pddl planning tasks, *Artificial Intelligence* 173 (5-6) (2009) 503–535.
- [34] J. Rintanen, Madagascar: Scalable planning with sat, *Proceedings of the 8th International Planning Competition (IPC-2014)*.
- [35] V. Alcázar, A. Torralba, A reminder about the importance of computing and exploiting invariants in planning., in: *ICAPS*, 2015, pp. 2–6.
- [36] H. Kautz, B. Selman, Unifying sat-based and graph-based planning, in: *IJCAI*, Vol. 99, 1999, pp. 318–325.
- [37] J. Rintanen, et al., Schematic invariants by reduction to ground invariants., in: *AAAI*, 2017, pp. 3644–3650.
- [38] J. A. Baier, S. A. McIlraith, Planning with first-order temporally extended goals using heuristic search, in: *Proceedings of the National Conference on Artificial Intelligence*, Vol. 21, Menlo Park, CA; Cambridge, MA; London; AAAI Press; MIT Press; 1999, 2006, p. 788.
- [39] B. Bonet, H. Geffner, Planning as heuristic search, *Artificial Intelligence* 129 (1-2) (2001) 5–33.
- [40] C. Muise, Planning. domains, *ICAPS system demonstration*.
- [41] P. Gregory, S. Cresswell, Domain model acquisition in the presence of static relations in the LOP system., in: *International Conference on Automated Planning and Scheduling, ICAPS-15*, 2015, pp. 97–105.
- [42] A. Fern, S. W. Yoon, R. Givan, Learning domain-specific control knowledge from random walks., in: *International Conference on Automated Planning and Scheduling, ICAPS-04*, 2004, pp. 191–199.
- [43] R. Stern, B. Juba, Efficient, safe, and probably approximately complete learning of action models, in: *International Joint Conference on Artificial Intelligence, IJCAI-17*, 2017, pp. 4405–4411.
- [44] S. Sohrabi, A. V. Riabov, O. Udrea, Plan recognition as planning revisited, in: *International Joint Conference on Artificial Intelligence, IJCAI-16*, 2016, pp. 3258–3264.
- [45] G. Francès, M. Ramírez, N. Lipovetzky, H. Geffner, Purely declarative action descriptions are overrated: Classical planning with simulators, in: *International Joint Conference on Artificial Intelligence, IJCAI-17*, 2017, pp. 4294–4301.

## Appendix



```

(define (domain BLOCKS)
  (:requirements :strips)
  (:predicates (on ?x ?y)
    (ontable ?x)
    (clear ?x)
    (handempty)
    (holding ?x)
  )

  (:action pick-up
    :parameters (?x)
    :precondition (and (clear ?x) (ontable ?x) (handempty))
    :effect
    (and (not (ontable ?x))
    (not (clear ?x))
    (not (handempty))
    (holding ?x))

  (:action put-down
    :parameters (?x)
    :precondition (holding ?x)
    :effect
    (and (not (holding ?x))
    (clear ?x)
    (handempty)
    (ontable ?x)))

  (:action stack
    :parameters (?x ?y)
    :precondition (and (holding ?x) (clear ?y))
    :effect
    (and (not (holding ?x))
    (not (clear ?y))
    (clear ?x)
    (handempty)
    (on ?x ?y)))

  (:action unstack
    :parameters (?x ?y)
    :precondition (and (on ?x ?y) (clear ?x) (handempty))
    :effect
    (and (holding ?x)
    (clear ?y)
    (not (clear ?x))
    (not (handempty))
    (not (on ?x ?y))))

```

Figure 8: PDDL domain file for the blocksworld domain.

```

(define (problem BLOCKS-4-1)
  (:domain BLOCKS)
  (:objects A C D B )
  (:INIT (CLEAR B) (ONTABLE D) (ON B C) (ON C A) (ON A D) (HANDEEMPTY))
  (:goal (AND (ON D C) (ON C A) (ON A B)))
)

```

Figure 9: PDDL problem file for the blocksworld domain.

```

(define (domain BLOCKS)
  (:requirements :strips)
  (:predicates (on ?x ?y)
    (ontable ?x)
    (clear ?x)
    (handempty)
    (holding ?x)
  )

  (:action pick-up
    :parameters (?x)
    :precondition (and (clear ?x) (ontable ?x) (handempty))
    :effect
    (and (not (ontable ?x))
    (not (clear ?x))
    (not (handempty))
    (holding ?x))

  (:action put-down
    :parameters (?x)
    :precondition (holding ?x)
    :effect
    (and (not (holding ?x))
    (clear ?x)
    (handempty)
    (ontable ?x)))

  (:action stack
    :parameters (?x ?y)
    :precondition (and (holding ?x) (clear ?y))
    :effect
    (and (not (holding ?x))
    (not (clear ?y))
    (clear ?x)
    (handempty)
    (on ?x ?y)))

  (:action unstack
    :parameters (?x ?y)
    :precondition (and (on ?x ?y) (clear ?x) (handempty))
    :effect
    (and (holding ?x)
    (clear ?y)
    (not (clear ?x))
    (not (handempty))
    (not (on ?x ?y))))

```

Figure 10: Compiled PDDL domain file for the blocksworld domain.

```

(define (problem BLOCKS-4-1)
  (:domain BLOCKS)
  (:objects A C D B )
  (:INIT (CLEAR B) (ONTABLE D) (ON B C) (ON C A) (ON A D) (HANDEEMPTY))
  (:goal (AND (ON D C) (ON C A) (ON A B)))
)

```

Figure 11: Compiled PDDL problem file for the blocksworld domain.