

>>> **Privacy-preserving Data Generation:**
>>> Towards generating privacy-preserving, synthetic and
useful time series ECG data for anomaly detection

Sijun John Tu (KTH x RISE)
March 4, 2024

```
>>> Outline
```

1. Project introduction
2. Heartbeat Arrhythmia
3. Privacy-preserving Time Series Data Generation
4. Results
5. Summary
6. References

>>> Outline

1. Project introduction

2. Heartbeat Arrhythmia

3. Privacy-preserving Time Series Data Generation

4. Results

5. Summary

6. References

>>> Anomaly detection using privacy-preserving, synthetic time series data

- \$ ECG data can be used for different downstream tasks like arrhythmia detection or other cardiac diseases and even studies on sleep, emotions and stress.
- \$ Heartbeat data can be used for biometrics authentication similar to the fingerprint. Hence, ensuring privacy is important.
- \$ Synthetic data with differential privacy (DP) guarantees is a promising solution to ensure privacy independent of downstream task.
- \$ Commonly, a gain in privacy results in a loss of utility.
- \$ For anomaly detection this might not be the case (?).

Goal: generate useful and privacy-preserving ECG data for anomaly detection.

>>> Structure

1. Train baseline model for anomaly detection only on regular heartbeat data using an LSTM-AE.
2. Generate heartbeat data (without DP) using two approaches:
 - AE-MERF
 - RTSGAN
3. Train LSTM-AE for anomaly detection on synthetic data and test on real (TSTR).
4. Add DP noise and repeat:
 - AE-DPMERF
 - DP-RTSGAN
5. Contaminate training data with anomalous heartbeats and repeat

>>> Outline

1. Project introduction

2. Heartbeat Arrhythmia

3. Privacy-preserving Time Series Data Generation

4. Results

5. Summary

6. References

>>> Heartbeat Arrhythmia




Figure: Different heartbeat arrhythmias ¹

¹source: <https://www.parkwayshenton.com.sg/health-plus/article/arrhythmia-guide>

>>> Arrhythmia Detection as an Anomaly Detection Problem

We treat the problem of detecting irregular heartbeats as an anomaly detection problem from machine learning based on the reconstruction error:

- \$ We train a model on regular heartbeats that is able to reconstruct that regular heartbeat.
- \$ Given an irregular heartbeat the model should give higher reconstruction error.
- \$ Based on an optimal threshold for that error we classify this heartbeat as either regular or irregular.

Two reasons for this semi-supervised approach: high class imbalance and no need for labelling.

>>> Baseline Model

Model is a LSTM-AE that is trained only on normal samples with the goal to reconstruct normal samples. The classification is made based on the reconstruction error.




Figure: reconstruction on normal sample




Figure: reconstruction on anomalous sample

>>> Outline

1. Project introduction
2. Heartbeat Arrhythmia
3. Privacy-preserving Time Series Data Generation
4. Results
5. Summary
6. References

>>> Models

AE-MERF

- \$ AE-MERF is based on the non-private version of DP-MERF (best state of the art generator for tabular data).
- \$ Simple architecture with mathematically sophisticated loss function.
- \$ Does not work with time series data out of the box, but we will modify it so it works.

RTSGAN

- \$ Model based on GAN network, which are commonly used in image generation.
- \$ Delivers state of the art performance for time series data.
- \$ No private counterpart, hence we will implement our own private version.

>>> Outline

1. Project introduction
2. Heartbeat Arrhythmia
3. Privacy-preserving Time Series Data Generation
4. Results
5. Summary
6. References

>>> AE-(DP)MERF




Figure: Results of AE-(DP)MERF with different privacy budgets (lower epsilon means higher privacy)

>>> (DP-)RTSGAN




Figure: Results of (DP-)RTSGAN with different privacy budgets (lower epsilon means higher privacy)

>>> Conclusion

- \$ DPMERF performs best and is very efficient computationally.
- \$ DPMERF can work in lower epsilon ranges, which translates to higher privacy guarantees.
- \$ DP-RTSGAN gives worse generative performance and can only work with meaningless privacy budgets epsilon.
- \$ Adding privacy does not impact the utility for anomaly detection too much until too much noise is added.

>>> Contamination

We contaminate the train set that only consists of normal samples with 1%, 2%, 5% anomalous samples (the percentage of heartbeat arrhythmias is estimated to be around max. 5%).

>>> Contamination: AE-(DP)MERF




Figure: Contaminated training set: AE-(DP)MERF

>>> Outline






1. Project introduction
2. Heartbeat Arrhythmia
3. Privacy-preserving Time Series Data Generation
4. Results
5. Summary
6. References

>>> Summary

tba

>>> Outline

1. Project introduction
2. Heartbeat Arrhythmia
3. Privacy-preserving Time Series Data Generation
4. Results
5. Summary
6. References

-  Ang, Yihao et al. (2023). TSGBench: Time Series Generation Benchmark. [arXiv: 2309.03755 \[cs.LG\]](#).
-  Giomi, Matteo et al. (2022). A Unified Framework for Quantifying Privacy Risk in Synthetic Data. [arXiv: 2211.10459 \[cs.CR\]](#).
-  Greenwade, George D. (1993). “The Comprehensive Tex Archive Network (CTAN)”. In: TUGBoat 14.3, pp. 342–351.
-  Hu, Yuzheng et al. (2023). SoK: Privacy-Preserving Data Synthesis. [arXiv: 2307.02106 \[cs.CR\]](#).
-  Kotelevskii, Nikita et al. (2022). “FedPop: A Bayesian Approach for Personalised Federated Learning”. In: Advances in Neural Information Processing Systems. Ed. by S. Koyejo et al. Vol. 35. Curran Associates, Inc., pp. 8687–8701. URL: https://proceedings.neurips.cc/paper_files/paper/2022/file/395409679270591fd2a70abc694cf5a1-Paper-Conference.pdf.



Lin, Zinan et al. (2020). “Using GANs for Sharing Networked Time Series Data”. In: Proceedings of the ACM Internet Measurement Conference. ACM. DOI: 10.1145/3419394.3423643. URL: <https://doi.org/10.1145%2F3419394.3423643>.



Pei, Hengzhi et al. (2021). “Towards Generating Real-World Time Series Data”. In: Proceedings of the 2021 IEEE International Conference on Data Mining (ICDM), Auckland.



Prediger, Lukas et al. (2023). Collaborative Learning From Distributed Data With Differentially Private Synthetic Time Series. arXiv: 2308.04755 [cs.LG].



Shokri, Reza et al. (2017). Membership Inference Attacks against Machine Learning Models. arXiv: 1610.05820 [cs.CR].



Stadler, Theresa, Bristena Oprisanu, and Carmela Troncoso (2020). “Synthetic Data - A Privacy Mirage”. In: CoRR abs/2011.07018. arXiv: 2011.07018. URL: <https://arxiv.org/abs/2011.07018>.



Tan, Alysa Ziyang et al. (2022). “Towards Personalized Federated Learning”. In: IEEE Transactions on Neural Networks and Learning Systems, pp. 1–17. DOI: [10.1109/TNNLS.2022.3160699](https://doi.org/10.1109/TNNLS.2022.3160699).



Yoon, Jinsung, Daniel Jarrett, and Mihaela van der Schaar (2019). “Time-series Generative Adversarial Networks”. In: Advances in Neural Information Processing Systems. Ed. by H. Wallach et al. Vol. 32. Curran Associates, Inc. URL: https://proceedings.neurips.cc/paper_files/paper/2019/file/c9efe5f26cd17ba6216bbe2a7d26d490-Paper.pdf.