# MATERIAL SAFETY DATA SHEET

Supplier: Johnsonite, Inc. Product: 945 Contact Bond Adhesive

16910 Munn Road, Chagrin Falls, Ohio 44023

24-Hour Emergency Telephone - Chemtrec: (800-424-9300)

#### SECTION 1. PRODUCT IDENTIFICATION

PRODUCT NAME: JOHNSONITE 945 Contact Bond Adhesive CHEMICAL FAMILY: Water Base, Latex Contact Cement

## SECTION 2. HAZARDOUS INGREDIENTS AND EXPOSURE LIMITS

Chemical Name CAS Number % by Weight ACGIH TLV OSHA PEL

None

## **SECTION 3. HAZARDS IDENTIFICATION**

PRIMARY ROUTES OF ENTRY: Eyes, skin.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: No known chronic over exposure effects.

POTENTIAL HEALTH EFFECTS: EYE CONTACT: May cause irritation.

SKIN CONTACT: Prolonged contact may cause slight irritation.

INGESTION: May Cause irritation to mouth, throat, and digestive system.

INHALATION: No effects known.

CHRONIC: None known.

CARCINOGENICITY: No information.

## **SECTION 4. FIRST AID MEASURES**

EYE CONTACT: Immediately flush with flowing water for 15 minutes. Get medical attention.

SKIN CONTACT: Immediately wash with soap and water. If irritation develops get medical attention.

INGESTION: Get immediate medical attention.

INHALATION: Move to fresh air. Administer artificial respiration or oxygen as necessary. If severe reaction

occurs get medical attention.

## **SECTION 5. FIRE-FIGHTING MEASURES**

FLAMABLE LIMITS: Non-flammable

FLASH POINT: >212°F.

FIRE-FIGHTING INSTRUCTIONS: Use protective clothing and self-contained breathing apparatus.

EXTINGUISHING MEDIA: Foam, water fog, or carbon dioxide.

DECOMPOSITION PRODUCTS: None Known

## SECTION 6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Cover small spills with inert absorbent, then sweep up and place waste in a disposal container.

#### **SECTION 7. HANDLING AND STORAGE**

HANDLING: Use good hygienic practices. (Wash hands before eating, using washroom, or smoking.)

# MATERIAL SAFETY DATA SHEET

Supplier: Johnsonite, Inc. Product: 945 Contact Bond Adhesive

16910 Munn Road, Chagrin Falls, Ohio 44023

24-Hour Emergency Telephone - Chemtrec: (800-424-9300)

\*\*\* Keep out of the reach of children \*\*\*.

STORAGE: Store above 60° F and below 100° F. Do not allow to freeze. Open in well ventilated area.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT:

EYE/FACE PROTECTION: Safety Glasses.

SKIN PROTECTION: Protective gloves recommended.

RESPIRATORY PROTECTION: Not normally required with good ventilation.

ENGINEERING CONTROLS: Normal room ventilation. Use site-specific mechanical exhaust where processing conditions or enclosed work areas create accumulation or concentration of fumes.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (°F): 212

SPECIFIC GRAVITY (WATER = 1): 1.12 VAPOR PRESSURE: Same as water. VAPOR DENSITY(air=1): Same as water. % VOLATILE BY WEIGHT: 36-40

pH: 9.8

APPEARANCE AND ODOR: Light blue-liquid with slight ammonia odor. VOLATILE ORGANIC COMPOUNDS (AS SOLVENT): 0 grams / liter.

## **SECTION 10. STABILITY AND REACTIVITY**

CHEMICAL STABILITY: Stable. POLYMERIZATION: Will not occur. INCOMPATIBILITY: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: None known, normal (CO2, CO).

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

No information Available.

#### **SECTION 12. ECOLOGICAL INFORMATION**

No information.

# MATERIAL SAFETY DATA SHEET

Supplier: Johnsonite, Inc. Product: 945 Contact Bond Adhesive

16910 Munn Road, Chagrin Falls, Ohio 44023

24-Hour Emergency Telephone - Chemtrec: (800-424-9300)

## SECTION 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with Federal, State and Local regulations.

## **SECTION 14. TRANSPORT INFORMATION**

For domestic transportation purposes, this product is not designated as a hazardous material by the U.S. Department of Transportation.

### SECTION 15. REGULATORY INFORMATION

TSCA: The components SARA TITLE III:	of this product are li	isted on the TSCA invent	ory.	
Section 311 and 312 Hea	alth and Physical Ha	zards:		
Immediate	Delayed	Fire	Pressure	Reactivity
[ ]	[ ]	[ ]	[ ]	[ ]
Section 313 Chemicals: <u>Chemical Name</u> None known	CAS#	% by Weigh		
CALIFORNIA VOC (Vo Solvent Free Product	olatile Organic Com	pound) COMPLIANCE:		
SCAQMD Rule 1168	VOC Compliant			
SCAQMD Rule 443.1:	Grams of VOC per Liter of Material 0 grams/liter			
	Grams of VOC per Liter of Coating 0 grams/liter			

## **SECTION 16. OTHER INFORMATION**

HMIS RATINGS: Health = 1 Flammability = 0 Reactivity = 0

Personal Protective Equipment = B

Hazard rating scale: 0=Minimal 1=Slight 2=Moderate 3=Serious 4=Severe

Johnsonite believes the statements, technical information and recommendations contained herein are reliable. They are given without warranty or guarantee of any kind, expressed or implied.

DATE ISSUED: January 2012 Contact Don Styka