

CSC263 Tutorial #8

Graphs!



March 10, 2023

Things covered in this tutorial

- ★ What is a graph?
- ★ How can I perform BFS on a graph?
- ★ How can I find the shortest distance between two vertices in a graph?
- ★ How can I convert a real-life problem into a problem about graphs?
- ★ What's the tallest elevator in the world?

What is a graph?



A graph is a funny-looking network of bubbles that are connected to each other.



Left: An undirected graph. Right: A directed graph.



The bubbles are called the **vertices** (also called **nodes**). The connections between vertices are called **edges**. The edges may be **directed** or **undirected**.

What is a graph?



Formally, a graph $G = (V, E)$ consists of:



What is a graph?



Formally, a graph $G = (V, E)$ consists of:

- ★ A set of vertices V . V can be any set, perhaps infinite.



What is a graph?



Formally, a graph $G = (V, E)$ consists of:

- ★ A set of vertices V . V can be any set, perhaps infinite.
- ★ A set of edges $E \subseteq V^2$. Given two vertices $u, v \in V$, we use $(u, v) \in E$ to denote that u and v are connected.

What is a graph?



Formally, a graph $G = (V, E)$ consists of:


- ★ A set of vertices V . V can be any set, perhaps infinite.
- ★ A set of edges $E \subseteq V^2$. Given two vertices $u, v \in V$, we use $(u, v) \in E$ to denote that u and v are connected.

For **undirected** graphs, E must be *symmetric*:

$$(u, v) \in E \Leftrightarrow (v, u) \in E.$$


Shortest Path

Task: Find the shortest path from u to v .



Shortest Path

Task: Find the shortest path from u to v .



The shortest path from u to v has **length 4**.

BFS

BFS stands for

BFS


BFS stands for **Breadth-First Search**. BFS *traverses* every vertex in a graph, starting from a vertex $s \in V$.

BFS(G, s) :

```
for each vertex  $v$  in  $V - \{s\}$ : # Initialize vertices
   $v.colour = \text{White}$ 
   $v.d = \infty$ 
   $v.p = \text{Nil}$ 
 $Q = \{\}$ 
 $s.colour = \text{Gray}$ 
 $s.d = 0$ 
Enqueue( $Q, s$ )
While  $Q$  not empty:
   $u = \text{Dequeue}(Q)$ 
  for each  $v$  in  $G.adj[u]$ :
    if  $v.colour == \text{White}$  # only visit unvisited vertices
       $v.colour[v] = \text{Gray}$ 
       $v.d = u.d + 1$ 
       $v.p = u$ 
      Enqueue( $Q, v$ )
   $colour[u] = \text{Black}$ 
```

BFS

Task: Perform BFS starting from s , labelling the distances.



BFS

Task: Perform BFS starting from s , labelling the distances.

Upon finishing, every node's d value is equal to the shortest path's distance from s to d .

Elevator problem

Tutorial Activity: Open [Tutorial 8](#), and read the instructions.

Elevator problem

Tutorial Activity: Open [Tutorial 8](#), and read the instructions.

Here's an illustration of the sample test case 10 1 10 2 1:




You start at X , and want to reach Y . You may only go up by 2 or down by 1 each move.

Fun facts about elevators


Fun facts about elevators

- ★ The tallest elevator in the world is found in the Mponeng Gold Mine in South Africa, owned by AngloGold Ashanti. The elevator is 2283 metres in height.



Fun facts about elevators

- ★ The tallest elevator in the world is found in the Mponeng Gold Mine in South Africa, owned by AngloGold Ashanti. The elevator is 2283 metres in height.



- ★ The deadliest elevator disaster in history happened in Vaal Reefs in South Africa, also owned by AngloGold Ashanti. A locomotive fell into the elevator shaft and caused the cage to detach and plunge 460 metres, killing 104 miners.