


CSC363 Tutorial #7

Alternative TMs

March 9, 2022



Learning objectives this tutorial

- ▶ Define some aliases we'll be using for this part of the course (complexity).
- ▶ Describe a “multi-tape” TM.
- ▶ Show that a multi-tape TM is effectively just a TM, but slightly better.



Some aliases


In the *computability* part of the course, we've discussed the “solvability” of *sets* (all subsets of our universe \mathbb{N}).



Some aliases

In the *computability* part of the course, we've discussed the "solvability" of sets (all subsets of our universe \mathbb{N}).

In the *complexity* part of the course, our universe is Σ^* (the set of strings using characters from Σ) instead of \mathbb{N} , where Σ is some predetermined alphabet (binary, decimals, ASCII characters, and others).




Some aliases

In the *computability* part of the course, we've discussed the "solvability" of *sets* (all subsets of our universe \mathbb{N}).

In the *complexity* part of the course, our universe is Σ^* (the set of strings using characters from Σ) instead of \mathbb{N} , where Σ is some predetermined alphabet (binary, decimals, ASCII characters, and others).

Task: Let Σ be any finite alphabet. There is a natural correspondence between Σ^* and \mathbb{N} , as we can assign each string a *unique* natural number. Recall what we used to show this.



Some aliases

In the *computability* part of the course, we've discussed the "solvability" of sets (all subsets of our universe \mathbb{N}).


In the *complexity* part of the course, our universe is Σ^* (the set of strings using characters from Σ) instead of \mathbb{N} , where Σ is some predetermined alphabet (binary, decimals, ASCII characters, and others).

Task: Let Σ be any finite alphabet. There is a natural correspondence between Σ^* and \mathbb{N} , as we can assign each string a *unique* natural number. Recall what we used to show this.

Ans: Gödel Numbers!


$$g \rightarrow 7, o \rightarrow 15, d \rightarrow 4, e \rightarrow 5, l \rightarrow 12$$

$$\text{godel} \rightarrow 2^7 3^{15} 5^4 7^5 11^{12}$$



Some aliases

Task: Let Σ be any finite alphabet. There is a natural correspondence between Σ^* and \mathbb{N} , as we can assign each string a *unique* natural number. Recall what we used to show this.



Some aliases


Task: Let Σ be any finite alphabet. There is a natural correspondence between Σ^* and \mathbb{N} , as we can assign each string a *unique* natural number. Recall what we used to show this.

Ans: Gödel Numbers!

$$g \rightarrow 7, o \rightarrow 15, d \rightarrow 4, e \rightarrow 5, l \rightarrow 12$$

$$\text{godel} \rightarrow 2^7 3^{15} 5^4 7^5 11^{12}$$

So in this sense, subsets of Σ^* can be thought of as subsets of \mathbb{N} by mapping $S \subseteq \Sigma^*$ to $g(S) = \{g(w) : w \in S\} \subseteq \mathbb{N}$, where g is the Gödel mapping function.



Some aliases

Task: Let Σ be any finite alphabet. There is a natural correspondence between Σ^* and \mathbb{N} , as we can assign each string a *unique* natural number. Recall what we used to show this.


Ans: Gödel Numbers!

$$g \rightarrow 7, o \rightarrow 15, d \rightarrow 4, e \rightarrow 5, l \rightarrow 12$$

$$\text{godel} \rightarrow 2^7 3^{15} 5^4 7^5 11^{12}$$

So in this sense, subsets of Σ^* can be thought of as subsets of \mathbb{N} by mapping $S \subseteq \Sigma^*$ to $g(S) = \{g(w) : w \in S\} \subseteq \mathbb{N}$, where g is the Gödel mapping function.

Question: What is another term for a subset of Σ^* ?



Some aliases

Task: Let Σ be any finite alphabet. There is a natural correspondence between Σ^* and \mathbb{N} , as we can assign each string a *unique* natural number. Recall what we used to show this.

Ans: Gödel Numbers!


$$g \rightarrow 7, o \rightarrow 15, d \rightarrow 4, e \rightarrow 5, l \rightarrow 12$$

$$\text{godel} \rightarrow 2^7 3^{15} 5^4 7^5 11^{12}$$

So in this sense, subsets of Σ^* can be thought of as subsets of \mathbb{N} by mapping $S \subseteq \Sigma^*$ to $g(S) = \{g(w) : w \in S\} \subseteq \mathbb{N}$, where g is the Gödel mapping function.

Question: What is another term for a subset of Σ^* ?


Ans: *Language*.



Some aliases

In complexity, we will consider the efficient *decidability* of languages.

Question: What is another word for *decidable*?




Some aliases

In complexity, we will consider the efficient *decidability* of languages.

Question: What is another word for *decidable*?

Ans: *Computable*.

Most languages we consider in complexity theory are decidable; we examine whether they are decidable *efficiently*.



Some aliases

In complexity, we will consider the efficient *decidability* of languages.


Question: What is another word for *decidable*?

Ans: *Computable*.

Most languages we consider in complexity theory are decidable; we examine whether they are decidable *efficiently*.

Definition: A *decider* for a language L is a TM that:

1. always halts *on any input*,
2. accepts the input x if and only if $x \in L$.



Some aliases

In complexity, we will consider the efficient *decidability* of languages.

Question: What is another word for *decidable*?




Some aliases

In complexity, we will consider the efficient *decidability* of languages.

Question: What is another word for *decidable*?

Ans: *Computable*.

Most languages we consider in complexity theory are decidable; we examine whether they are decidable *efficiently*.



Some aliases

In complexity, we will consider the efficient *decidability* of languages.


Question: What is another word for *decidable*?

Ans: *Computable*.

Most languages we consider in complexity theory are decidable; we examine whether they are decidable *efficiently*.

Definition: A *decider* for a language L is a TM that:

1. always halts *on any input*,
2. accepts the input x if and only if $x \in L$.



Multi-tape TM


Task: Describe some attributes we could add to a TM to make it “multi-tape”. What will the transition function look like? How is input handled?



Multi-tape TM

Task: Describe some attributes we could add to a TM to make it “multi-tape”. What will the transition function look like? How is input handled?

Here's what I have in mind:




Multi-tape TM

Definition: A *k*-tape Turing Machine is like an ordinary Turing Machine, but its transition function is now

$$\delta : Q \times \Gamma^k \rightarrow Q \times \Gamma^k \times \{L, R\}^k.$$

In effect, this gives us *k* distinct tapes, each with its own read/write head. We read and write *k* symbols at once.




Multi-tape TM

Definition: A *k*-tape Turing Machine is like an ordinary Turing Machine, but its transition function is now

$$\delta : Q \times \Gamma^k \rightarrow Q \times \Gamma^k \times \{L, R\}^k.$$


In effect, this gives us *k* distinct tapes, each with its own read/write head. We read and write *k* symbols at once.

The input is placed on the first tape; all other tapes start blank.




Multi-tape TM Example

Let's construct a multi-tape TM over the language $\{0, 1\}$ that accepts palindromes. Here's what we will do:




1. Copy the string on tape 1 to tape 2.
2. Move head1 to the beginning of the first tape.
3. Compare characters from head1 and head2, scanning right and left respectively.





Multi-tape TM Example

1. Copy the string on tape 1 to tape 2.




Multi-tape TM Example

3. Compare characters from head1 and head2, scanning right and left respectively.



Multi-tape TM Example

Question: What runtime (in terms of length of input n) does this 2-tape TM have?



Multi-tape TM Example

Question: What runtime (in terms of length of input n) does this 2-tape TM have?

Ans: $O(n)$ (because we have to keep jumping back and forth).




Multi-tape TM Example

Question: What runtime (in terms of length of input n) does this 2-tape TM have?

Ans: $O(n)$ (because we have to keep jumping back and forth).

Question: What runtime (in terms of length of input n) would a “naive” single-tape TM use to detect palindromes?




Multi-tape TM Example

Question: What runtime (in terms of length of input n) does this 2-tape TM have?

Ans: $O(n)$ (because we have to keep jumping back and forth).


Question: What runtime (in terms of length of input n) would a “naive” single-tape TM use to detect palindromes?

Ans: $O(n^2)$ (because we have to keep jumping back and forth).



Multi-tape TM Example

Task: Construct a $O(n)$ 2-tape TM that decides the language $\{0^n 1^n : k \in \mathbb{N}\}$. You may use a high-level description if you want.




Multi-tape TM Example

Task: Construct a $O(n)$ 2-tape TM that decides the language $\{0^n 1^n : k \in \mathbb{N}\}$. You may use a high-level description if you want.


Ans: Here's the procedure I have in mind.

1. Copy the string on tape 1 to tape 2.
2. Move head1 to the beginning of the first tape.
3. Compare character by character; if head1 and head2 both read 0 or both read 1, then reject.



Multi-tape TM Example

Question: How fast can we decide $\{0^n 1^n : k \in \mathbb{N}\}$ same language with a TM?



Multi-tape TM Example

Question: How fast can we decide $\{0^n 1^n : k \in \mathbb{N}\}$ same language with a TM?

Ans: Naively, $O(n^2)$. The procedure is as follows:

1. Cross out a 0; move to the right end of the string.
2. Cross out a 1; move to the left end of the string.

Try <https://turingmachinesimulator.com/shared/prsswhkkyb>.



Multi-tape TM Example


Question: How fast can we decide $\{0^n 1^n : k \in \mathbb{N}\}$ same language with a TM?

Ans: Naively, $O(n^2)$. The procedure is as follows:

1. Cross out a 0; move to the right end of the string.
2. Cross out a 1; move to the left end of the string.

Try <https://turingmachinesimulator.com/shared/prsswhkkyb>.

But we can do better! There is a $O(n \log n)$ procedure!



Multi-tape TM Example

Question: How fast can we decide $\{0^n 1^n : k \in \mathbb{N}\}$ same language with a TM?


Ans: Naively, $O(n^2)$. The procedure is as follows:

1. Cross out a 0; move to the right end of the string.
2. Cross out a 1; move to the left end of the string.

Try <https://turingmachinesimulator.com/shared/prsswhkkyb>.

But we can do better! There is a $O(n \log n)$ procedure:

1. Scan across the tape and reject if a 0 is found to the right of a 1.
2. Repeat the following as long as there is both a 0 and a 1 on the tape:
 - 2.1 Scan across the tape, and reject if the total number of 0s and 1s remaining is odd.
 - 2.2 Scan again across the tape, crossing off every other 0, and crossing off every other 1.
3. If the tape doesn't have any 0s or 1s, accept. Else, reject.



Multi-tape TM Example

Question: How fast can we decide $\{0^n 1^n : k \in \mathbb{N}\}$ same language with a TM?

Ans: Naively, $O(n^2)$. The procedure is as follows:


1. Cross out a 0; move to the right end of the string.
2. Cross out a 1; move to the left end of the string.

Try <https://turingmachinesimulator.com/shared/prsswhkkyb>.

But we can do better! There is a $O(n \log n)$ procedure:

1. Scan across the tape and reject if a 0 is found to the right of a 1.
2. Repeat the following as long as there is both a 0 and a 1 on the tape:
 - 2.1 Scan across the tape, and reject if the total number of 0s and 1s remaining is odd.
 - 2.2 Scan again across the tape, crossing off every other 0, and crossing off every other 1.
3. If the tape doesn't have any 0s or 1s, accept. Else, reject.

Try <https://turingmachinesimulator.com/shared/prsswhkkyb>.



Multi-tape TMs in P


It turns out, just as with NTMs, the question of *decidability* doesn't change with multi-tape TMs.



Multi-tape TMs in P

It turns out, just as with NTMs, the question of *decidability* doesn't change with multi-tape TMs.

- ▶ Everything that is decidable with a NTM is also decidable with a TM (since we can simulate a NTM on a TM).
- ▶ Everything that is decidable with a k -tape TM is also decidable with a TM.




Multi-tape TMs in P

It turns out, just as with NTMs, the question of *decidability* doesn't change with multi-tape TMs.

- ▶ Everything that is decidable with a NTM is also decidable with a TM (since we can simulate a NTM on a TM).
- ▶ Everything that is decidable with a k -tape TM is also decidable with a TM.

In fact, there is an even stronger theorem.

Theorem: Everything that is decidable with a k -tape TM in $O(f(n))$ time is decidable with a TM in $O((f(n))^2)$ time. (See Sipser page 137)



Multi-tape TMs in P


It turns out, just as with NTMs, the question of *decidability* doesn't change with multi-tape TMs.

- ▶ Everything that is decidable with a NTM is also decidable with a TM (since we can simulate a NTM on a TM).
- ▶ Everything that is decidable with a k -tape TM is also decidable with a TM.

In fact, there is an even stronger theorem.

Theorem: Everything that is decidable with a k -tape TM in $O(f(n))$ time is decidable with a TM in $O((f(n))^2)$ time. (See Sipser page 137)

Task: Using the above, show that any language that is poly-time decidable by a k -tape TM is also poly-time decidable by a TM.



Multi-tape TMs in P

It turns out, just as with NTMs, the question of *decidability* doesn't change with multi-tape TMs.


- ▶ Everything that is decidable with a NTM is also decidable with a TM (since we can simulate a NTM on a TM).
- ▶ Everything that is decidable with a k -tape TM is also decidable with a TM.

In fact, there is an even stronger theorem.

Theorem: Everything that is decidable with a k -tape TM in $O(f(n))$ time is decidable with a TM in $O((f(n))^2)$ time. (See Sipser page 137)

Task: Using the above, show that any language that is poly-time decidable by a k -tape TM is also poly-time decidable by a TM.

Ans: If a language is decidable by a $O(n^p)$ k -tape TM, then according to the theorem, it is decidable by a $O(n^{2p})$ TM.



Multi-tape TMs in P

It turns out, just as with NTMs, the question of *decidability* doesn't change with multi-tape TMs.

- ▶ Everything that is decidable with a NTM is also decidable with a TM (since we can simulate a NTM on a TM).
- ▶ Everything that is decidable with a k -tape TM is also decidable with a TM.

In fact, there is an even stronger theorem.

Theorem: Everything that is decidable with a k -tape TM in $O(f(n))$ time is decidable with a TM in $O((f(n))^2)$ time. (See Sipser page 137)

Task: Using the above, show that any language that is poly-time decidable by a k -tape TM is also poly-time decidable by a TM.

Ans: If a language is decidable by a $O(n^p)$ k -tape TM, then according to the theorem, it is decidable by a $O(n^{2p})$ TM.

In effect, this shows that multi-tape TMs are “better”, but don't fundamentally change the set of poly-time decidable languages.

