

Code Template for ACM-ICPC

UESTC Life and Lemons

October 13, 2016

Contents

1	DataStructure	1
1.1	Size Balanced Tree	1
1.2	Treap	3
1.3	Splay	5
1.4	Scapegoat Tree	7
1.5	Leftist Tree	8
1.6	Link Cut Tree	9
1.7	Partition Tree	11
1.8	Range Minimum Query	13
1.9	BIT for Kth-Element	13
1.10	Neighbors for Tree Path	13
1.11	Scan Line for Disjoint Circles	14
1.12	Manhattan Distance MST	17
1.13	Dynamic MST	19
1.14	Dynamic Convex	20
2	String	22
2.1	Manacher	22
2.2	Minimum Representation	23
2.3	EX KMP	23
2.4	Palindromic Tree	24
2.5	Palindromic Tree AF	25
2.6	Suffix Automaton	26
2.7	Suffix Array	27
2.8	Suffix Tree	28
2.9	Suffix Tree DF	29
2.10	Palindromic Factorization	32
2.11	Palindromic Factorization PT	34
2.12	KMP	35
2.13	AC Automaton	35
3	Graph	36
3.1	Directed MST	36
3.2	Directed MST SOL	37
3.3	MCMF	40
3.4	ZKW MCMF	41
3.5	SAP	43
3.6	Global Minimum Cut	45
3.7	Blossom Tree	46
3.8	KM	47
3.9	General Graph MWM	49
4	Geometry	56
4.1	Closet Point Pair	56
4.2	Geometry Lweb	57
4.3	Geometry Hezhu	62
4.4	3D Convex	72

5	Math	77
5.1	EX GCD	77
5.2	Romberg	77
5.3	Miller Rabin-Pollard rho	78
5.4	FWT XOR	80
5.5	FNT Base 2	81
5.6	FNT Base 3	82
5.7	FNT All	84
5.8	FFT Normal	85
5.9	FFT	86
6	Others	88
6.1	Big Number	88
6.2	Long Long Mul	91
6.3	Fast IO	91

1 DataStructure

1.1 Size Balanced Tree

```
const int N = 100005;
struct SBT {
    int lc, rc, sz, key;
    void init(int k) {
        lc = rc = 0;
        sz = 1;
        key = k;
    }
} T[N];
int tot;

inline void push_up(int x) {
    T[x].sz = T[T[x].lc].sz + T[T[x].rc].sz + 1;
}

void L_rotate(int &x) {
    int k = T[x].rc;
    T[x].rc = T[k].lc;
    T[k].lc = x;
    push_up(x);
    push_up(k);
    x = k;
}

void R_rotate(int &x) {
    int k = T[x].lc;
    T[x].lc = T[k].rc;
    T[k].rc = x;
    push_up(x);
    push_up(k);
    x = k;
}

void Maintain(int &x, bool fg) {
    if(fg) {
        if(T[T[x].rc].rc.sz > T[T[x].lc].sz) L_rotate(x);
        else if(T[T[x].rc].lc.sz > T[T[x].lc].sz) {
            R_rotate(T[x].rc);
            L_rotate(x);
        }
        else return;
    }
    else {
        if(T[T[x].lc].lc.sz > T[T[x].rc].sz) R_rotate(x);
        else if(T[T[x].lc].rc.sz > T[T[x].rc].sz) {
            L_rotate(T[x].lc);
            R_rotate(x);
        }
        else return;
    }
    Maintain(T[x].lc, 0);
    Maintain(T[x].rc, 1);
    Maintain(x, 0);
    Maintain(x, 1);
}
```

```

}

void Insert(int &x, int k) {
    if(!x) {
        x = ++tot;
        T[x].init(k);
    }
    else {
        Insert(k < T[x].key ? T[x].lc : T[x].rc, k);
        push_up(x);
        Maintain(x, k >= T[x].key);
    }
}

int d_key;
void Delete(int &x, int k) {
    if(T[x].key == k || (k < T[x].key && !T[x].lc) || (k > T[x].key && !T[x].rc)) {
        if(!T[x].lc || !T[x].rc) {
            d_key = T[x].key;
            x = T[x].lc + T[x].rc;
        }
        else {
            Delete(T[x].lc, k + 1);
            T[x].key = d_key;
        }
    }
    else Delete(k < T[x].key ? T[x].lc : T[x].rc, k);
    if(x) push_up(x);
}

int get_rank(int x, int k) {
    int res = 1;
    while(x) {
        if(T[x].key < k) {
            res += T[T[x].lc].sz + 1;
            x = T[x].rc;
        }
        else x = T[x].lc;
    }
    return res;
}

int get_kth(int x, int k) {
    while(T[T[x].lc].sz + 1 != k) {
        if(T[T[x].lc].sz + 1 < k) {
            k -= T[T[x].lc].sz + 1;
            x = T[x].rc;
        }
        else x = T[x].lc;
    }
    return T[x].key;
}

int get_pre(int x, int k) {
    int res;
    while(x) {
        if(T[x].key < k) {
            res = T[x].key;
            x = T[x].rc;
        }
    }
}

```

```

    }
    else x = T[x].lc;
}
return res;
}

int get_nxt(int x, int k) {
    int res;
    while(x) {
        if(T[x].key > k) {
            res = T[x].key;
            x = T[x].lc;
        }
        else x = T[x].rc;
    }
    return res;
}

```

1.2 Treap

```

const int N = 100005;
struct Treap {
    int key, val, sz;
    Treap *lc, *rc;
} pool[N], *nill, *root;
int tot;

void init() {
    srand(0);
    root = nill = pool;
    nill->sz = 0;
    tot = 0;
}

Treap* newnode(int v) {
    Treap *t = pool + (++tot);
    t->val = v;
    t->sz = 1;
    t->key = (rand() << 16) | rand();
    t->lc = t->rc = nill;
    return t;
}

inline void push_up(Treap *p) {
    p->sz = p->lc->sz + p->rc->sz + 1;
}

Treap* Merge(Treap *a, Treap *b) {
    if(a == nill) return b;
    if(b == nill) return a;
    if(a->key < b->key) {
        a->rc = Merge(a->rc, b);
        push_up(a);
        return a;
    }
    else {
        b->lc = Merge(a, b->lc);
    }
}

```

```

        push_up(b);
        return b;
    }
}

typedef pair <Treap*, Treap*> pii;
pii Split(Treap *a, int k) {
    if(!k) return make_pair(nill, a);
    int cnt = a->lc->sz;
    if(cnt >= k) {
        pii u = Split(a->lc, k);
        a->lc = u.SE;
        push_up(a);
        return make_pair(u.FI, a);
    }
    else {
        pii u = Split(a->rc, k - cnt - 1);
        a->rc = u.FI;
        push_up(a);
        return make_pair(a, u.SE);
    }
}

int get_rank(int k) {
    Treap *p = root;
    int res = 1;
    while(p != nill) {
        if(p->val < k) {
            res += p->lc->sz + 1;
            p = p->rc;
        }
        else p = p->lc;
    }
    return res;
}

int get_kth(int k) {
    Treap *p = root;
    while(p->lc->sz + 1 != k) {
        if(p->lc->sz + 1 < k) {
            k -= p->lc->sz + 1;
            p = p->rc;
        }
        else p = p->lc;
    }
    return p->val;
}

int get_pre(int k) {
    int res;
    Treap *p = root;
    while(p != nill) {
        if(p->val < k) {
            res = p->val;
            p = p->rc;
        }
        else p = p->lc;
    }
    return res;
}

```

```

}

int get_nxt(int k) {
    int res;
    Treap *p = root;
    while(p != null) {
        if(p->val > k) {
            res = p->val;
            p = p->lc;
        }
        else p = p->rc;
    }
    return res;
}

void Insert(int k) {
    Treap *t = newnode(k);
    pii u = Split(root, get_rank(k) - 1);
    root = Merge(u.FI, t);
    root = Merge(root, u.SE);
}

void Delete(int k) {
    int p = get_rank(k);
    pii a = Split(root, p - 1);
    pii b = Split(a.SE, 1);
    root = Merge(a.FI, b.SE);
}

```

1.3 Splay

```

#define keyTree (ch[ch[root][1]][0])
const int N = 100005;
int pre[N], ch[N][2], sz[N];
int val[N], mx[N], add[N];
int tot, root;

void init() {
    root = tot = 0;
    ch[0][0] = ch[0][1] = pre[0] = 0;
    sz[0] = val[0] = mx[0] = 0;
    add[0] = 0;
}

inline void push_up(int x) {
    sz[x] = sz[ch[x][0]] + sz[ch[x][1]] + 1;
    mx[x] = max(val[x], max(mx[ch[x][0]], mx[ch[x][1]]));
}

inline void Add(int x, int v) {
    if(!x) return;
    val[x] += v;
    mx[x] += v;
    add[x] += v;
}

inline void push_down(int x) {

```



```

    if(!add[x]) return;
    Add(ch[x][0], add[x]);
    Add(ch[x][1], add[x]);
    add[x] = 0;
}

inline void newnode(int &x, int v, int fa) {
    x = ++tot;
    pre[x] = fa;
    ch[x][0] = ch[x][1] = 0;
    sz[x] = 1;
    mx[x] = val[x] = v;
    add[x] = 0;
}

inline void Rotate(int x, bool kind) {
    int y = pre[x];
    ch[y][!kind] = ch[x][kind];
    pre[ch[x][kind]] = y;
    pre[x] = pre[y];
    if(pre[x]) ch[pre[x]][ch[pre[x]][1] == y] = x;
    ch[x][kind] = y;
    pre[y] = x;
    push_up(y);
}

void P(int x) {
    if(!x) return;
    P(pre[x]);
    push_down(x);
}

void Splay(int x, int goal) {
    P(x);
    while(pre[x] != goal) {
        if(pre[pre[x]] == goal) Rotate(x, ch[pre[x]][0] == x);
        else {
            int y = pre[x];
            bool kind = (ch[pre[y]][0] == y);
            if(ch[pre[x]][kind] == x)
                Rotate(x, !kind), Rotate(x, kind);
            else
                Rotate(y, kind), Rotate(x, kind);
        }
    }
    push_up(x);
    if(!goal) root = x;
}

int get_kth(int k) {
    int x = root;
    push_down(x);
    while(sz[ch[x][0]] + 1 != k) {
        if(sz[ch[x][0]] + 1 < k) {
            k -= sz[ch[x][0]] + 1;
            x = ch[x][1];
        }
        else x = ch[x][0];
    }
    push_down(x);
}

```

```

    }
    return x;
}

void RotateTo(int k, int goal) {
    int t = get_kth(k);
    Splay(t, goal);
}

void update(int l, int r, int v) {
    RotateTo(l, 0);
    RotateTo(r + 2, root);
    Add(keyTree, v);
    push_up(ch[root][1]);
    push_up(root);
}

void Delete(int x) {
    RotateTo(x, 0);
    RotateTo(x + 2, root);
    keyTree = 0;
    push_up(ch[root][1]);
    push_up(root);
}

void Insert(int x, int v) {
    RotateTo(x + 1, 0);
    RotateTo(x + 2, root);
    newnode(keyTree, v, ch[root][1]);
    push_up(ch[root][1]);
    push_up(root);
}

```

1.4 Scapegoat Tree

```

const int N = 100005;
const double alpha = 0.6;
struct Scapegoat_Tree {
    int lc, rc, sz, key;
    void init(int k) {
        lc = rc = 0;
        sz = 1;
        key = k;
    }
} T[N];
int tot, root, *Adjnode;

inline void push_up(int x) {
    T[x].sz = T[T[x].lc].sz + T[T[x].rc].sz + 1;
}

inline bool Balance(int x) {
    return max(T[T[x].lc].sz, T[T[x].rc].sz) <= T[x].sz * alpha;
}

int tr[N], cc;
void Travel(int x) {

```

```

        if(!x) return;
        Travel(T[x].lc);
        tr[cc++] = x;
        Travel(T[x].rc);
    }

void build(int &x, int l, int r) {
    if(l > r) return;
    int mid = (l + r) >> 1;
    x = tr[mid];
    T[x].init(T[x].key);
    build(T[x].lc, l, mid - 1);
    build(T[x].rc, mid + 1, r);
    push_up(x);
}

void Adjust(int *x) {
    if(!x) return;
    cc = 0;
    Travel(*x);
    build(*x, 0, cc - 1);
}

void Insert(int &x, int k) {
    if(!x) {
        x = ++tot;
        T[x].init(k);
    }
    else {
        Insert(k < T[x].key ? T[x].lc : T[x].rc, k);
        push_up(x);
    }
    if(!Balance(x)) Adjnode = &x;
}

int d_key;
void Delete(int &x, int k) {
    if(T[x].key == k || (k < T[x].key && !T[x].lc) || (k > T[x].key && !T[x].rc)) {
        if(!T[x].lc || !T[x].rc) {
            d_key = T[x].key;
            x = T[x].lc + T[x].rc;
        }
        else {
            Delete(T[x].lc, k + 1);
            T[x].key = d_key;
        }
    }
    else Delete(k < T[x].key ? T[x].lc : T[x].rc, k);
    if(x) push_up(x);
    if(!Balance(x)) Adjnode = &x;
}

```

1.5 Leftist Tree

```

const int N = 100005;

struct LHeap {

```

```

    int dis, key;
    LHeap *lc, *rc;
} pool[N], *nill;
int tot;

inline void init() {
    tot = 0;
    nill = pool;
    nill->dis = -1;
}

inline LHeap* MakeTree(int v) {
    LHeap *t = pool + (++tot);
    t->lc = t->rc = nill;
    t->dis = 0;
    t->key = v;
    return t;
}

LHeap* Merge(LHeap *a, LHeap *b) {
    if(a == nill) return b;
    if(b == nill) return a;
    if(a->key > b->key) swap(a, b);
    a->rc = Merge(a->rc, b);
    if(a->rc->dis > a->lc->dis) swap(a->rc, a->lc);
    a->dis = a->rc->dis + 1;
    return a;
}

inline void Insert(LHeap* &a, int v) {
    LHeap *b = MakeTree(v);
    a = Merge(a, b);
}

inline int DeleteMin(LHeap* &a) {
    int t = a->key;
    a = Merge(a->lc, a->rc);
    return t;
}

```

1.6 Link Cut Tree

```

const int N = 100005;

struct Link_Cut_Tree {
    int pre[N], ch[N][2], bef[N];
    bool rev[N];
    inline void init() {

    }

    inline void Rev(int x) {
        if(!x) return;
        swap(ch[x][0], ch[x][1]);
        rev[x] ^= 1;
    }

    inline void push_down(int x) {

```

```

}
inline void P(int x) {
    if(pre[x]) P(pre[x]);
    push_down(x);
}
inline void push_up(int x) {

}
inline void Rotate(int x, bool kind) {
    int y = pre[x];
    ch[y][!kind] = ch[x][kind];
    pre[ch[x][kind]] = y;
    pre[x] = pre[y];
    if(pre[x]) ch[pre[x]][ch[pre[x]][1] == y] = x;
    ch[x][kind] = y;
    pre[y] = x;
    //push_up(y);
}
inline void Splay(int x) {
    P(x); int r = x;
    while(pre[r]) r = pre[r];
    if(r != x) bef[x] = bef[r], bef[r] = 0;
    while(pre[x]) {
        if(pre[pre[x]] == 0) Rotate(x, ch[pre[x]][0] == x);
        else {
            int y = pre[x], k = ch[pre[y]][0] == y;
            if(ch[pre[x]][k] == x)
                Rotate(x, !k), Rotate(x, k);
            else
                Rotate(y, k), Rotate(x, k);
        }
    }
    push_up(x);
}
inline void Access(int x) {
    int fa = 0;
    for(; x; x = bef[x]) {
        Splay(x);
        bef[ch[x][1]] = x;
        bef[fa] = 0;
        pre[ch[x][1]] = 0;
        ch[x][1] = fa;
        pre[fa] = x;
        fa = x;
        //push_up(x);
    }
}
inline int get_rt(int x) {
    Access(x);
    Splay(x);
    //push_down(x);
    while(ch[x][0]) {
        x = ch[x][0];
        //push_down(x);
    }
    Splay(x);
    return x;
}
inline void make_rt(int x) {

```

```

    Access(x);
    Splay(x);
    Rev(x);
}
inline void Cut(int u, int v) {
    make_rt(u);
    Access(v);
    Splay(v);
    pre[ch[v][0]] = 0;
    ch[v][0] = 0;
    //push_up(v);
}
inline void Link(int u, int v) {
    make_rt(v);
    bef[v] = u;
    Access(v);
    /*make_rt(v);
    push_down(v);
    Access(u);
    Splay(u);
    pre[u] = v;
    ch[v][0] = u;
    push_up(v);*/
}
inline int Query(int x, int y) {
    Access(y);
    for(y = 0; x; x = bef[x]) {
        Splay(x);
        if(!bef[x]) return max(mx[y], mx[ch[x][1]]);
        bef[ch[x][1]] = x;
        bef[y] = 0;
        pre[ch[x][1]] = 0;
        ch[x][1] = y;
        pre[y] = x;
        y = x;
        push_up(x);
    }
}
} lct;

```

1.7 Partition Tree

```

int a[maxn], as[maxn];
int n, m;
int sum[20][maxn];
int tree[20][maxn];
void build(int c, int l, int r){
    int i, mid = (l + r) >> 1, lm = mid - 1 + 1, lp = 1, rp = mid + 1;
    for (i = l; i <= mid; i++){
        if (as[i] < as[mid]){
            lm--;
        }
    }
    for (i = l; i <= r; i++){
        if (i == l){
            sum[c][i] = 0;
        }else{

```

```

        sum[c][i] = sum[c][i - 1];
    }
    if (tree[c][i] == as[mid]){
        if (lm){
            lm--;
            sum[c][i]++;
            tree[c + 1][lp++] = tree[c][i];
        }else
            tree[c + 1][rp++] = tree[c][i];
    } else if (tree[c][i] < as[mid]){
        sum[c][i]++;
        tree[c + 1][lp++] = tree[c][i];
    } else{
        tree[c + 1][rp++] = tree[c][i];
    }
}
if (l == r)return;
build(c + 1, l, mid);
build(c + 1, mid + 1, r);
}

int query(int c, int l, int r, int ql, int qr, int k){
    int s;
    int ss;
    int mid = (l + r) >> 1;
    if (l == r){
        return tree[c][l];
    }
    if (l == ql){
        s = 0;
        ss = sum[c][qr];
    }else{
        s = sum[c][ql - 1];
        ss = sum[c][qr] - s;
    }
    if (k <= ss){
        return query(c + 1, l, mid, l + s, l + s + ss - 1, k);
    }else{
        return query(c + 1, mid + 1, r, mid - l + 1 + ql - s, mid - l + 1 + qr - s - ss, k - ss);
    }
}

int main(){
    int i, j, k;
    while(~scanf("%d%d", &n, &m)){
        for (i = 1; i <= n; i++){
            scanf("%d", &a[i]);
            tree[0][i] = as[i] = a[i];
        }
        sort(as + 1, as + 1 + n);
        build(0, 1, n);
        while(m--){
            scanf("%d%d%d", &i, &j, &k);
            printf("%d\n", query(0, 1, n, i, j, k));
        }
    }
    return 0;
}

```

1.8 Range Minimum Query

```
void initRMQ(int n) {
    Lg[1] = 0;
    for(int i = 2; i <= n; ++i) Lg[i] = Lg[i >> 1] + 1;
    for(int j = 1; j < 20; ++j) {
        for(int i = 1; i <= n; ++i) {
            if(i + (1 << j) - 1 > n) break;
            minx[i][j] = min(minx[i][j - 1], minx[i + (1 << (j - 1))][j - 1]);
        }
    }
}

inline int query(int l, int r) {
    int t = Lg[r - l + 1];
    return min(minx[l][t], minx[r - (1 << t) + 1][t]);
}
```

1.9 BIT for Kth-Element

```
int findkth(int k) {
    int idx = 0;
    for(int i = 20; i >= 0; --i) {
        idx ^= 1 << i;
        if(idx <= N && bit[idx] < k) k -= bit[idx];
        else idx ^= 1 << i;
    }
    return idx + 1;
}
```

1.10 Neighbors for Tree Path

```
inline int query(int u, int v) {
    int ans = 0;
    int f1 = top[u], f2 = top[v];
    while(f1 ^ f2) {
        if(dep[f1] < dep[f2]) {
            swap(f1, f2);
            swap(u, v);
        }
        //Heavy son of the end of this chain
        if(son[u]) add(ans, sqr(bt1.query(L[son[u]], R[son[u]])));
        //All the light sons on this chain
        add(ans, bt2.query(L[f1], L[u]));
        //Subtract the value of the top of the chain, since we will count it when count the light
        //sons on the above chain
        add(ans, -sqr(bt1.query(L[f1], R[f1])));
        u = fa[f1]; f1 = top[u];
    }
    if(dep[u] > dep[v]) swap(u, v);
    //All the light sons on the last chain
    add(ans, bt2.query(L[u], L[v]));
    //Heavy son of the bottom of the last chain
    if(son[v]) add(ans, sqr(bt1.query(L[son[v]], R[son[v]])));
}
```



```

//Subtree above the LCA
if(u != 1) add(ans, sqr(sum - bt1.query(L[u], R[u])));
return ans;
}

```

1.11 Scan Line for Disjoint Circles

```

const int N = 150005;
int x[N], y[N], r[N], id[N];
int op[N];

struct Event {
    int x, tp, id;
    bool operator < (const Event &a) const {
        if(x != a.x) return x < a.x;
        return tp > a.tp;
    }
} C[N * 2];
int tot = 0;

void add(int x, int tp, int id) {
    C[tot].x = x;
    C[tot].tp = tp;
    C[tot++].id = id;
}

inline double sqr(double x) {
    return x * x;
}

inline int sgn(double x) {
    if(x < -eps) return -1;
    return x > eps;
}

double X;
struct HC {
    int id, up;
    double get_y() const {
        double v = sqr(r[id]) - sqr(x[id] - X);
        v = sqrt(max(v, 0.0));
        return up ? y[id] + v : y[id] - v;
    }
    bool operator < (const HC &a) const {
        int ck = sgn(get_y() - a.get_y());
        if(ck) return ck > 0;
        return up > a.up;
    }
};

inline bool OnCircle(int c, int p) {
    int dx = (x[c] - x[p]), dy = (y[c] - y[p]);
    return r[c] * r[c] == dx * dx + dy * dy;
}

set <HC> st;
int fa[N], belong[N];

```

```

vector <int> G[N];

int L[N], R[N], label = 0;
void dfs(int u) {
    L[u] = ++label;
    for(int i = 0; i < (int)G[u].size(); ++i) {
        int v = G[u][i];
        dfs(v);
    }
    R[u] = label;
}

struct BIT {
    int bit[N];
    void add(int x, int v) {
        for(; x <= label; x += x & -x) bit[x] += v;
    }
    int read(int x) {
        int res = 0;
        for(; x; x ^= x & -x) res += bit[x];
        return res;
    }
    void init() {
        memset(bit, 0, sizeof(bit));
    }
} t1, t2;

void get_fa(int &x, int up, int down) {
    if(up == down) x = up;
    else if(fa[down] == up) x = up;
    else if(fa[up] == down) x = down;
    else x = fa[up];
}

int main() {
    int n, m;
    scanf("%d%d", &n, &m);
    for(int i = 0; i < n; ++i) {
        op[i] = 1;
        scanf("%d", &id[i]);
        scanf("%d%d%d", &x[id[i]], &y[id[i]], &r[id[i]]);
        add(x[id[i]] - r[id[i]], -1, id[i]);
        add(x[id[i]] + r[id[i]], 1, id[i]);
    }
    for(int i = n; i < n + m; ++i) {
        op[i] = 2;
        scanf("%d", &id[i]);
        scanf("%d%d", &x[id[i]], &y[id[i]]);
        add(x[id[i]], 0, id[i]);
    }
    int q;
    scanf("%d", &q);
    q += n + m;
    for(int i = n + m; i < q; ++i) {
        scanf("%d%d", &op[i], &id[i]);
        if(op[i] == 1) {
            scanf("%d%d%d", &x[id[i]], &y[id[i]], &r[id[i]]);
            add(x[id[i]] - r[id[i]], -1, id[i]);
            add(x[id[i]] + r[id[i]], 1, id[i]);
        }
    }
}

```

```

    }
    else if(op[i] == 2) {
        scanf("%d%d", &x[id[i]], &y[id[i]]);
        add(x[id[i]], 0, id[i]);
    }
}
sort(C, C + tot);
HC t;
for(int i = 0; i < tot; ++i) {
    X = C[i].x;
    if(C[i].tp == -1) {
        t.id = C[i].id;
        t.up = 0;
        set <HC>::iterator it = st.upper_bound(t);
        int up = 0, down = 0;
        if(it != st.end()) down = it->id;
        if(it != st.begin()) up = (--it)->id;
        get_fa(fa[t.id], up, down);
        G[fa[t.id]].push_back(t.id);
        st.insert(t);
        t.up = 1;
        st.insert(t);
    }
    else if(C[i].tp == 0) {
        t.id = C[i].id;
        t.up = 1;
        set <HC>::iterator it = st.lower_bound(t);
        if(it == st.end()) continue;
        if(OnCircle(it->id, t.id)) {
            belong[t.id] = fa[it->id];
            continue;
        }
        if(it == st.begin()) continue;
        int down = it->id, up = (--it)->id;
        get_fa(belong[t.id], up, down);
    }
    else {
        t.id = C[i].id;
        t.up = 0;
        st.erase(t);
        t.up = 1;
        st.erase(t);
    }
}
dfs(0);
t1.init(); t2.init();
for(int i = 0; i < q; ++i) {
    if(op[i] == 1) {
        int u = id[i];
        t1.add(L[u], 1);
        t1.add(R[u] + 1, -1);
    }
    else if(op[i] == 2) {
        int u = belong[id[i]];
        t2.add(L[u], 1);
    }
    else if(op[i] == 3) {
        int u = id[i];
        if(r[u]) {

```

```

        t1.add(L[u], -1);
        t1.add(R[u] + 1, 1);
    }
    else {
        u = belong[u];
        t2.add(L[u], -1);
    }
}
else {
    int ans, u = id[i];
    if(r[u]) {
        ans = t2.read(R[u]) - t2.read(L[u] - 1);
    }
    else {
        ans = t1.read(L[belong[u]]);
    }
    printf("%d\n", ans);
}
}
return 0;
}

```

1.12 Manhattan Distance MST

```

struct Point {
    int x, y, id;
} po[10005];
int data[10005], cc;

struct Edge {
    int u, v, l;
} ed[50005];
int ecnt = 0;

inline int Find( int x ) {
    return lower_bound( data, data + cc, x ) - data + 1;
}

inline bool cmp( Point a, Point b ) {
    return a.x > b.x || ( a.x == b.x && a.y > b.y );
}

inline int AB( int x ) {
    return x > 0 ? x : -x;
}

inline int Dis( Point a, Point b ) {
    return AB( a.x - b.x ) + AB( a.y - b.y );
}

inline void addedge( int u, int v, int l ) {
    ed[ecnt].u = u;
    ed[ecnt].v = v;
    ed[ecnt++].l = l;
}

int bitv[10005], bitid[10005];

```

```

inline void add( int x, int v, int id ) {
    x = cc - x + 1;
    for( ; x <= cc; x += x & -x ) if( bitv[x] > v ) {
        bitv[x] = v;
        bitid[x] = id;
    }
}

inline int read( int x ) {
    int v = INF, id = -1;
    x = cc - x + 1;
    for( ; x; x ^= x & -x ) if( bitv[x] < v ) {
        v = bitv[x];
        id = bitid[x];
    }
    return id;
}

inline bool ecmp( Edge a, Edge b ) {
    return a.l < b.l;
}

int F[10005];
int findroot( int x ) {
    return F[x] == x ? x : F[x] = findroot( F[x] );
}

int main() {
    int n, K;
    while( ~scanf( "%d%d", &n, &K ) ) {
        for( int i = 0; i < n; ++i ) {
            scanf( "%d%d", &po[i].x, &po[i].y );
            po[i].id = i;
        }
        for( int dir = 0; dir < 4; ++dir ) {
            if( dir == 1 || dir == 3 ) {
                for( int i = 0; i < n; ++i ) swap( po[i].x, po[i].y );
            } else if( dir == 2 ) {
                for( int i = 0; i < n; ++i ) po[i].x *= -1;
            }
        }
        cc = 0;
        for( int i = 0; i < n; ++i ) data[cc++] = po[i].y - po[i].x;
        sort( data, data + cc );
        cc = unique( data, data + cc ) - data;
        sort( po, po + n, cmp );
        memset( bitv, 0x3f, sizeof( bitv ) );
        for( int i = 0; i < n; ++i ) {
            int v = Find( po[i].y - po[i].x );
            int id = read( v );
            if( id != -1 ) addedge( po[i].id, po[id].id, Dis( po[i], po[id] ) );
            add( v, po[i].x + po[i].y, i );
        }
    }
    sort( ed, ed + ecnt, ecmp );
    for( int i = 0; i < n; ++i ) F[i] = i;
    int cnt = 0;
    for( int i = 0; i < ecnt; ++i ) {
        int fu = findroot( ed[i].u ), fv = findroot( ed[i].v );
        if( fu == fv ) continue;
    }
}

```

```

        ++cnt;
        if( cnt == n - K ) {
            printf( "%d\n", ed[i].l );
            break;
        }
        F[fu] = fv;
    }
}
return 0;
}

```

1.13 Dynamic MST

```

const int maxn = 50005;
struct Edge {
    int u, v, c, id;
} ed[20][maxn], e[maxn];
int cnt[20], val[maxn], pos[maxn];
struct Query {
    int id, c;
} qry[maxn];
LL ans[maxn];
int F[maxn];

inline void init(int m) {
    for(int i = 0; i < m; ++i) F[e[i].u] = e[i].u, F[e[i].v] = e[i].v;
}

int findroot(int x) {
    return F[x] == x ? x : F[x] = findroot(F[x]);
}

inline bool cmp(const Edge &a, const Edge &b) {
    return a.c < b.c;
}

int must[maxn];
void solve(int dep, int l, int r, LL sum) {
    if(l == r) val[qry[l].id] = qry[l].c;
    int m = cnt[dep];
    for(int i = 0; i < m; ++i) {
        e[i] = ed[dep][i];
        e[i].c = val[e[i].id];
    }
    if(l == r) {
        sort(e, e + m, cmp);
        init(m);
        for(int i = 0; i < m; ++i) {
            int fu = findroot(e[i].u), fv = findroot(e[i].v);
            if(fu == fv) continue;
            sum += e[i].c;
            F[fu] = fv;
        }
        ans[l] = sum;
        return;
    }
    for(int i = 0; i < m; ++i) pos[e[i].id] = i;
}

```

```

for(int i = 1; i <= r; ++i) e[pos[qry[i].id]].c = -1;
sort(e, e + m, cmp);
init(m);
int mcnt = 0;
for(int i = 0; i < m; ++i) {
    int fu = findroot(e[i].u), fv = findroot(e[i].v);
    if(fu == fv) continue;
    if(e[i].c != -1) sum += e[i].c, must[mcnt++] = i;
    F[fu] = fv;
}
init(m);
for(int i = 0; i < mcnt; ++i) F[findroot(e[must[i]].u)] = findroot(e[must[i]].v);
for(int i = 0; i < m; ++i) {
    if(e[i].c == -1) e[i].c = INF;
    e[i].u = findroot(e[i].u);
    e[i].v = findroot(e[i].v);
}
sort(e, e + m, cmp);
cnt[dep + 1] = 0;
for(int i = 0; i < m; ++i) {
    int fu = findroot(e[i].u), fv = findroot(e[i].v);
    if(fu == fv) {
        if(e[i].c == INF) ed[dep + 1][cnt[dep + 1]++] = e[i];
        continue;
    }
    ed[dep + 1][cnt[dep + 1]++] = e[i];
    F[fu] = fv;
}
int mid = (l + r) >> 1;
solve(dep + 1, l, mid, sum);
solve(dep + 1, mid + 1, r, sum);
}

int main() {
    int n, m, q;
    scanf("%d%d%d", &n, &m, &q);
    for(int i = 0; i < m; ++i) {
        scanf("%d%d%d", &ed[0][i].u, &ed[0][i].v, &ed[0][i].c);
        ed[0][i].id = i;
        val[i] = ed[0][i].c;
    }
    for(int i = 0; i < q; ++i) scanf("%d%d", &qry[i].id, &qry[i].c), --qry[i].id;
    cnt[0] = m;
    solve(0, 0, q - 1, 0);
    for(int i = 0; i < q; ++i) printf("%I64d\n", ans[i]);
    return 0;
}

```

1.14 Dynamic Convex

```

const double pi = acos(-1.0);
const double eps = 1e-8;
inline int sgn(double x) {
    if(x < -eps) return -1;
    return x > eps;
}

```

```

double Ox, Oy;
struct Vector {
    LL x, y;
    double arg;
    inline void read() {
        scanf("%I64d%I64d", &x, &y);
    }
    Vector(LL _x = 0, LL _y = 0) {
        x = _x;
        y = _y;
    }
    Vector operator +(Vector a) const {
        return Vector(x + a.x, y + a.y);
    }
    Vector operator +=(Vector a) {
        return *this = *this + a;
    }
    Vector operator -(Vector a) const {
        return Vector(x - a.x, y - a.y);
    }
    Vector operator -=(Vector a) {
        return *this = *this - a;
    }
    Vector operator *(double p) const {
        return Vector(x * p, y * p);
    }
    Vector operator *=(double p) {
        return *this = *this * p;
    }
    bool operator <(const Vector a) const {
        return arg < a.arg;
    }
    //bool operator ==(const Vector a) const { return sgn(x-a.x)==0 && sgn(y-a.y)==0; }
    double len() const {
        return sqrt(x * x + y * y);
    }
    double angle() const {
        return atan2(y - Oy, x - Ox);
    }
};

inline LL cross(Vector a, Vector b) {
    return a.x * b.y - a.y * b.x;
}

set <Vector> pst;
inline void init() {
    int t;
    Vector a, b, c;
    a.read();
    b.read();
    c.read();
    Ox = (a.x + b.x + c.x) / 3.0;
    Oy = (a.y + b.y + c.y) / 3.0;
    a.arg = a.angle();
    b.arg = b.angle();
    c.arg = c.angle();
    pst.insert(a);
    pst.insert(b);
}

```



```

    pst.insert(c);
}

typedef set <Vector>::iterator pit;
inline pit pre(pit it) {
    if(it == pst.begin()) it = pst.end();
    return --it;
}

inline pit next(pit it) {
    ++it;
    if(it == pst.end()) it = pst.begin();
    return it;
}

inline void updata(Vector p) {
    p.arg = p.angle();
    pit L = pre(pst.lower_bound(p));
    pit R = next(L);
    if(cross(*R - p, *L - p) <= 0) return;
    while(cross(*next(R) - p, *R - p) >= 0) R = next(R);
    while(cross(*L - p, *pre(L) - p) >= 0) L = pre(L);
    L = next(L);
    while(L != R) L = next(L), pst.erase(pre(L));
    pst.insert(p);
}

inline bool query(Vector p) {
    p.arg = p.angle();
    pit L = pre(pst.lower_bound(p));
    pit R = next(L);
    return cross(*R - p, *L - p) <= 0;
}

```

2 String

2.1 Manacher

```

const int N = 2e5 + 5;
char s[N], str[N];
int p[N];

int Manacher(char *s) {
    str[0] = '$';
    int cc = 1;
    for(int i = 0; s[i]; ++i) {
        str[cc++] = '#';
        str[cc++] = s[i];
    }
    str[cc++] = '#';
    str[cc] = 0;
    int mx = 0, id;
    for(int i = 1; str[i]; ++i) {
        if(mx > i) {
            p[i] = min(p[2 * id - i], mx - i);
        }
    }
}

```

```

        else p[i] = 1;
        for(; str[i + p[i]] == str[i - p[i]]; ++p[i]);
        if(p[i] + i > mx) {
            mx = p[i] + i;
            id = i;
        }
    }
    return cc;
}

```

2.2 Minimum Representation

```

int minP(char s[])
{
    int l=strlen(s);
    int i = 0, j = 1, k = 0;
    while (1)
    {
        if (i + k >= l || j + k >= l) break;
        if (s[i + k] == s[j + k])
        {
            k++;
            continue;
        }
        else
        {
            if (s[j + k] < s[i + k]) j += k + 1;
            else i += k + 1;
            k = 0;
            if (i == j) j++;
        }
    }
    return min(i, j);
}

```

2.3 EX KMP

```

const int N = 1e5 + 5;
int next[N], extand[N];

void getnext(char *T) {
    int i, length = strlen(T);
    next[0] = length;
    for(i = 0; i < length - 1 && T[i] == T[i + 1]; i++);
    next[1] = i;
    int a = 1;
    for(int k = 2; k < length; k++) {
        int p = a + next[a] - 1, L = next[k - a];
        if((k - 1) + L >= p) {
            int j = (p - k + 1) > 0 ? (p - k + 1) : 0;
            while(k + j < length && T[k + j] == T[j]) j++;
            next[k] = j, a = k;
        }
        else next[k] = L;
    }
}

```

```

}

void gettextand(char *S, char *T) {
    memset(next, 0, sizeof(next));
    getnext(T);
    int Slen = strlen(S), Tlen = strlen(T), a = 0;
    int MinLen = Slen > Tlen ? Tlen : Slen;
    while(a < MinLen && S[a] == T[a]) a++;
    extand[0] = a, a = 0;
    for(int k = 1; k < Slen; k++) {
        int p = a + extand[a] - 1, L = next[k - a];
        if((k - 1) + L >= p) {
            int j = (p - k + 1) > 0 ? (p - k + 1) : 0;
            while(k + j < Slen && j < Tlen && S[k + j] == T[j]) j++;
            extand[k] = j; a = k;
        }
        else extand[k] = L;
    }
}
}

```

2.4 Palindromic Tree

```

const int MAXN = 100005 ;
const int N = 26 ;

struct Palindromic_Tree {
    int next[MAXN][N];
    int fail[MAXN];
    int cnt[MAXN];
    int num[MAXN];
    int len[MAXN];
    int S[MAXN];
    int last;
    int n;
    int p;

    int newnode(int l) {
        for(int i = 0; i < N; ++i) next[p][i] = 0;
        cnt[p] = 0;
        num[p] = 0;
        len[p] = l;
        return p++;
    }

    void init() {
        p = 0;
        newnode(0) ;
        newnode(-1);
        last = 0;
        n = 0;
        S[n] = -1;
        fail[0] = 1;
    }

    int get_fail(int x) {
        while(S[n - len[x] - 1] != S[n]) x = fail[x];
        return x;
    }
}

```

```

}

void add(int c) {
    c -= 'a';
    S[++n] = c;
    int cur = get_fail(last);
    if(!next[cur][c]) {
        int now = newnode(len[cur] + 2);
        fail[now] = next[get_fail(fail[cur])][c];
        next[cur][c] = now;
        num[now] = num[fail[now]] + 1;
    }
    last = next[cur][c];
    cnt[last]++;
}

void count() {
    for(int i = p - 1; i >= 0; --i) cnt[fail[i]] += cnt[i];
}
} T;

```

2.5 Palindromic Tree AF

```

const int MAXN = 200005;
const int base = 100002;
const int N = 26;

struct Palindromic_Tree {
    int next[MAXN][N];
    int fail[MAXN];
    int num[MAXN];
    int len[MAXN];
    int S[MAXN];
    int suflast, prelast;
    int L, R;
    int p;

    int newnode(int l) {
        for(int i = 0; i < N; ++i) next[p][i] = 0;
        num[p] = 0;
        len[p] = l;
        return p++;
    }

    void init() {
        p = 0;
        newnode(0);
        newnode(-1);
        suflast = prelast = 0;
        L = base + 1; R = base;
        fail[0] = 1;
    }

    int get_back_fail(int x) {
        while(R - len[x] - 1 < L || S[R - len[x] - 1] != S[R]) x = fail[x];
        return x;
    }
}

```

```

int get_front_fail(int x) {
    while(L + len[x] + 1 > R || S[L + len[x] + 1] != S[L]) x = fail[x];
    return x;
}

void add_back(int c) {
    c -= 'a';
    S[++R] = c;
    int cur = get_back_fail(suflast);
    if(!next[cur][c]) {
        int now = newnode(len[cur] + 2);
        fail[now] = next[get_back_fail(fail[cur])][c];
        next[cur][c] = now;
        num[now] = num[fail[now]] + 1;
    }
    suflast = next[cur][c];
    if(len[suflast] == R - L + 1) prelast = suflast;
}

void add_front(int c) {
    c -= 'a';
    S[--L] = c;
    int cur = get_front_fail(prelast);
    if(!next[cur][c]) {
        int now = newnode(len[cur] + 2);
        fail[now] = next[get_front_fail(fail[cur])][c];
        next[cur][c] = now;
        num[now] = num[fail[now]] + 1;
    }
    prelast = next[cur][c];
    if(len[prelast] == R - L + 1) suflast = prelast;
}
} T;

```

2.6 Suffix Automaton

```

const int N = 1e5 + 5;
struct Sam {
    Sam *next[26], *par;
    int step;
} pool[N * 2], *root, *last;
int tot;

Sam* newnode(int step) {
    Sam *t = pool + (tot++);
    memset(t->next, 0, sizeof(t->next));
    t->par = NULL;
    t->step = step;
    return t;
}

void init() {
    tot = 0;
    last = root = newnode(0);
}

```

```

void Extend(int w) {
    Sam *p = last;
    Sam *newv = newnode(p->step + 1);
    for(; p && !p->next[w]; p = p->par) p->next[w] = newv;
    if(!p) newv->par = root;
    else {
        Sam *q = p->next[w];
        if(q->step == p->step + 1) newv->par = q;
        else {
            Sam *nq = newnode(p->step + 1);
            memcpy(nq->next, q->next, sizeof(q->next));
            nq->par = q->par;
            q->par = nq;
            newv->par = nq;
            for(; p && p->next[w] == q; p = p->par) p->next[w] = nq;
        }
    }
    last = newv;
}

```

2.7 Suffix Array

```

struct Suffix_Array {
    int wa[N], wb[N], wv[N], wd[N];
    inline int cmp(int *r, int a, int b, int l) {
        return r[a] == r[b] && r[a + 1] == r[b + 1];
    }
    void da(int *r, int *sa, int n, int m) {
        int i, j, p, *x = wa, *y = wb, *t;
        for(i = 0; i < m; ++i) wd[i] = 0;
        for(i = 0; i < n; ++i) wd[x[i]] = r[i]++;
        for(i = 1; i < m; ++i) wd[i] += wd[i - 1];
        for(i = n - 1; i >= 0; --i) sa[--wd[x[i]]] = i;
        for(j = 1, p = 1; p < n; j *= 2, m = p) {
            for(p = 0, i = n - j; i < n; ++i) y[p++] = i;
            for(i = 0; i < n; ++i) if(sa[i] >= j) y[p++] = sa[i] - j;
            for(i = 0; i < n; ++i) wv[i] = x[y[i]];
            for(i = 0; i < m; ++i) wd[i] = 0;
            for(i = 0; i < n; ++i) wd[wv[i]]++;
            for(i = 1; i < m; ++i) wd[i] += wd[i - 1];
            for(i = n - 1; i >= 0; --i) sa[--wd[wv[i]]] = y[i];
            for(t = x, x = y, y = t, p = 1, x[sa[0]] = 0, i = 1; i < n; ++i)
                x[sa[i]] = cmp(y, sa[i - 1], sa[i], j) ? p - 1 : p++;
        }
    }
    int rank[N], height[N], data[N], sa[N];
    void calheight(int *r, int *sa, int n) {
        int i, j, k = 0;
        for(i = 1; i <= n; ++i) rank[sa[i]] = i;
        for(i = 0; i < n; height[rank[i++]] = k)
            for(k ? k-- : 0, j = sa[rank[i] - 1]; r[i + k] == r[j + k]; ++k);
    }
    int minx[N][20], Lg[N];
    void initRMQ(int n) {
        Lg[1] = 0;
        for(int i = 2; i <= n; ++i) Lg[i] = Lg[i >> 1] + 1;
        for(int j = 1; j < 20; ++j) {

```

```

        for(int i = 1; i <= n; ++i) {
            if(i + (1 << j) - 1 > n) break;
            minx[i][j] = min(minx[i][j - 1], minx[i + (1 << (j - 1))][j - 1]);
        }
    }
}

inline int lcp(int l, int r) {
    int t = Lg[r - l + 1];
    return min(minx[l][t], minx[r - (1 << t) + 1][t]);
}

int len;
void work(char *s) {
    len = strlen(s);
    for(int i = 0; i < len; ++i) data[i] = s[i];
    data[len] = 0;
    da(data, sa, len + 1, 128);
    calheight(data, sa, len);
    for(int i = 1; i <= len; ++i) minx[i][0] = height[i];
    initRMQ(len);
}
} sa;

```

2.8 Suffix Tree

```

const int SIGMA = 26;

const int N = 100005;

int alloc, curPos, actEdge, actLen, remaind;

struct node {
    int l, r;
    node *nxt[SIGMA], *slink;
    inline int edgeLen() {
        return min(r, curPos + 1) - l;
    }
} S[N + N], *root, *actNode, *needSL;

inline node* newnode(int l, int r = INF) {
    node *t = S + (alloc ++);
    t->l = l; t->r = r;
    t->slink = 0;
    memset(t->nxt, 0, sizeof(t->nxt));
    return t;
}

int text[N];

inline int actedge() {
    return text[actEdge];
}

inline void addSL(node *p) {
    if(needSL) needSL->slink = p;
    needSL = p;
}

```

```

bool walkDown(node *p) {
    if(actLen < p->edgeLen()) return false;
    actEdge += p->edgeLen();
    actLen -= p->edgeLen();
    actNode = p;
    return true;
}

void init() {
    needSL = 0; alloc = 0; curPos = -1;
    remaind = actEdge = actLen = 0;
    root = actNode = newnode(-1, -1);
}

void extend(int c) {
    text[++ curPos] = c;
    needSL = 0;
    ++ remaind;
    while(remaind > 0) {
        if(actLen == 0) actEdge = curPos;
        if(actNode->nxt[actEdge()] == 0) {
            node* leaf = newnode(curPos);
            actNode->nxt[actEdge()] = leaf;
            addSL(actNode);
        } else {
            node* nt = actNode->nxt[actEdge()];
            if(walkDown(nt)) continue;
            if(text[nt->l + actLen] == c) {
                ++ actLen;
                addSL(actNode);
                break;
            }
            node* split = newnode(nt->l, nt->l + actLen);
            actNode->nxt[actEdge()] = split;
            node* leaf = newnode(curPos);
            split->nxt[c] = leaf;
            nt->l += actLen;
            split->nxt[text[nt->l]] = nt;
            addSL(split);
        }
        -- remaind;
        if(actNode == root && actLen > 0) {
            -- actLen;
            actEdge = curPos - remaind + 1;
        } else {
            actNode = actNode->slink ? actNode->slink : root;
        }
    }
}

```

2.9 Suffix Tree DF

```

const int SIGMA = 26;

const int N = 100005;

int alloc, curPos, actEdge, actLen, remaind;

```



```

struct node {
    int l, r, son;
    node *nxt[SIGMA], *slink, *fa;
    inline int edgeLen() {
        return min(r, curPos + 1) - l;
    }
} S[N + N], *root, *actNode, *needSL;

inline node* newnode(int l, int r = INF) {
    node *t = S + (alloc ++);
    t->l = l; t->r = r;
    t->slink = t->fa = 0;
    t->son = 0;
    memset(t->nxt, 0, sizeof(t->nxt));
    return t;
}

int text[N];

inline int actedge() {
    return text[actEdge];
}

inline void addSL(node *p) {
    if(needSL) needSL->slink = p;
    needSL = p;
}

bool walkDown(node *p) {
    if(actLen < p->edgeLen()) return false;
    actEdge += p->edgeLen();
    actLen -= p->edgeLen();
    actNode = p;
    return true;
}

void doneins() {
    -- remaind;
    if(actNode == root && actLen > 0) {
        -- actLen;
        actEdge = curPos - remaind + 1;
    } else {
        actNode = actNode->slink ? actNode->slink : root;
    }
}

int head, tail;

node* leaves[N + N];

ll curAns;

void init() {
    curAns = head = tail = 0;
    needSL = 0; alloc = 0; curPos = -1;
    remaind = actEdge = actLen = 0;
    root = actNode = newnode(-1, -1);
}

```

```

void extend(int c) {
    text[++ curPos] = c;
    needSL = 0;
    ++ remaind;
    curAns += tail - head;
    while(remaind > 0) {
        if(actLen == 0) actEdge = curPos;
        if(actNode->nxt[actedge()] == 0) {
            node* leaf = newnode(curPos);
            actNode->nxt[actedge()] = leaf;
            leaf->fa = actNode;
            ++ actNode->son;
            addSL(actNode);
            leaves[tail ++] = leaf;
        } else {
            node* nt = actNode->nxt[actedge()];
            if(walkDown(nt)) continue;
            if(text[nt->l + actLen] == c) {
                ++ actLen;
                addSL(actNode);
                break;
            }
            node* split = newnode(nt->l, nt->l + actLen);
            actNode->nxt[actedge()] = split;
            split->fa = actNode;
            node* leaf = newnode(curPos);
            split->nxt[c] = leaf;
            leaf->fa = split;
            nt->l += actLen;
            split->nxt[text[nt->l]] = nt;
            nt->fa = split;
            addSL(split);
            split->son = 2;
            leaves[tail ++] = leaf;
        }
        doneins();
        ++ curAns;
    }
}

void erasefront() {
    while(actLen > 0 && actNode->nxt[actedge()] && walkDown(actNode->nxt[actedge()]));
    node* u = leaves[head ++], *f = u->fa;
    while(u != root && u->son == 0 && actNode != f) {
        curAns -= u->edgeLen();
        f->nxt[text[u->l]] = 0;
        -- f->son;
        u = f; f = u->fa;
    }
    if(u == root || u->son > 0) return;
    if(actLen == 0 || f->nxt[actedge()] != u) {
        curAns -= u->edgeLen();
        f->nxt[text[u->l]] = 0;
        if(-- f->son) return;
        if(remaind) doneins();
        if(f != root) {
            leaves[tail ++] = f;
            f->l = curPos - f->edgeLen() + 1;
        }
    }
}

```

```

        f->r = INF;
    }
} else {
    curAns -= u->edgeLen() - actLen;
    u->l = curPos - actLen + 1;
    u->r = INF;
    doneins();
    leaves[tail++] = u;
}
}
}

```

2.10 Palindromic Factorization

```

/**
 * Alforithm from this paper -- A Subquadratic Algorithm for Minimum Palindromic Factorization
 *
 * pl[i][0] -- minimal even factorization
 * pl[i][1] -- minimal odd factorization
 * 1 <= i <= n
 *
 * time complexity: O(n log n)
 */
const int MAXN = 300000 + 10;
int pl[MAXN][2], gpl[MAXN][2];

inline void set(int *a, int x, int y, int z) {
    a[0] = x, a[1] = y, a[2] = z;
}

inline void set(int *a, int *b) {
    a[0] = b[0], a[1] = b[1], a[2] = b[2];
}

inline void set(int pl[][2], int idx, int val) {
    if (val <= 0) return;
    pl[idx][val & 1] = val;
}

inline void upd(int pl[][2], int idx, int val) {
    if (val <= 0) return;
    int &r = pl[idx][val & 1];
    if (r == -1 || r > val) r = val;
}

void factorization(char s[]) {
    int n = strlen(s);
    for (int i = 0; i <= n; ++i) {
        gpl[i][0] = 1e9;
        gpl[i][1] = 1e9 + 1;
    }
    static int g[32][3], gp[32][3], gpp[32][3];
    int pg = 0;
    for (int j = 0; j < n; ++j) {
        // g->gp
        int pgp = 0;
        for (int u = 0; u < pg; ++u) {
            int i = g[u][0];
            if (i - 1 >= 0 && s[i - 1] == s[j]) {
                g[u][0]--;
                set(gp[pgp++], g[u]);
            }
        }
    }
}

```

```

    }
}
// gp->gpp
int pgpp = 0, r = -j - 2;
for (int u = 0; u < pgp; ++u) {
    int i = gp[u][0], d = gp[u][1], k = gp[u][2];
    if (i - r != d) {
        set(gpp[pgpp++], i, i - r, 1);
        if (k > 1) set(gpp[pgpp++], i + d, d, k - 1);
    } else set(gpp[pgpp++], i, d, k);
    r = i + (k - 1) * d;
}
if (j - 1 >= 0 && s[j - 1] == s[j]) {
    set(gpp[pgpp++], j - 1, j - 1 - r, 1);
    r = j - 1;
}
set(gpp[pgpp++], j, j - r, 1);
// gpp->g
pg = 0;
int *front = gpp[0];
for (int u = 1; u < pgpp; ++u) {
    int *x = gpp[u];
    if (x[1] == front[1]) front[2] += x[2];
    else {
        set(g[pg++], front);
        front = x;
    }
}
set(g[pg++], front);
// dp update
if ((j + 1) % 2 == 0) {
    pl[j + 1][0] = j + 1;
    pl[j + 1][1] = 1e9 + 1;
} else {
    pl[j + 1][0] = 1e9;
    pl[j + 1][1] = j + 1;
}
for (int u = 0; u < pg; ++u) {
    int i = g[u][0], d = g[u][1], k = g[u][2];
    r = i + (k - 1) * d;
    upd(pl, j + 1, pl[r][0] + 1);
    upd(pl, j + 1, pl[r][1] + 1);
    if (k > 1) {
        upd(pl, j + 1, gpl[i + 1 - d][0]);
        upd(pl, j + 1, gpl[i + 1 - d][1]);
    }
    if (i + 1 >= d) {
        if (k > 1) {
            upd(gpl, i + 1 - d, pl[r][0] + 1);
            upd(gpl, i + 1 - d, pl[r][1] + 1);
        } else {
            set(gpl, i + 1 - d, pl[r][0] + 1);
            set(gpl, i + 1 - d, pl[r][1] + 1);
        }
    }
}
}
}
}
}

```

2.11 Palindromic Factorization PT

```
const int MAXN = 300005;

const int N = 26;

const int inf = 0x3f3f3f3f;

struct Palindromic_Tree {
    int nxt[MAXN][N], fail[MAXN];
    int occ[MAXN], num[MAXN], len[MAXN];
    int S[MAXN], last, n, p;
    int sfail[MAXN], diff[MAXN], dp[2][MAXN], ans[2][MAXN];

    int newnode(int l) {
        memset(nxt[p], 0, N * sizeof(int));
        occ[p] = num[p] = 0;
        len[p] = l;
        return p++;
    }

    void init() {
        p = 0;
        newnode(0);
        newnode(-1);
        last = 0;
        n = 0;
        S[n] = -1;
        fail[0] = 1;
        ans[0][0] = 0;
        ans[1][0] = inf;
    }

    int get_fail(int x) {
        while(S[n - len[x] - 1] != S[n]) x = fail[x];
        return x;
    }

    void add(int c) {
        c -= 'a';
        S[++n] = c;
        int cur = get_fail(last);
        if(!nxt[cur][c]) {
            int v = newnode(len[cur] + 2);
            fail[v] = nxt[get_fail(fail[cur])][c];
            nxt[cur][c] = v;
            num[v] = num[fail[v]] + 1;
            diff[v] = len[v] - len[fail[v]];
            sfail[v] = diff[v] ^ diff[fail[v]] ? fail[v] : sfail[fail[v]];
        }
        last = nxt[cur][c];
        occ[last]++;
        update();
    }

    void update() {
        ans[0][n] = ans[1][n] = inf;
        for(int u = last; u; u = sfail[u]) {
            ans[0][n] = min(ans[0][n], ans[0][u] + 1);
            ans[1][n] = min(ans[1][n], ans[1][u] + 1);
        }
    }
};
```

```

        dp[0][u] = ans[1][n - len[sfail[u]] - diff[u]];
        dp[1][u] = ans[0][n - len[sfail[u]] - diff[u]];
        if(diff[u] == diff[fail[u]]) {
            dp[0][u] = min(dp[0][u], dp[0][fail[u]]);
            dp[1][u] = min(dp[1][u], dp[1][fail[u]]);
        }
        ans[0][n] = min(ans[0][n], dp[0][u] + 1);
        ans[1][n] = min(ans[1][n], dp[1][u] + 1);
    }
}

void count() {
    for(int i = p - 1; i >= 0; --i) occ[fail[i]] += occ[i];
}

} T;

```

2.12 KMP

```

void getNext(char *p, int *next) {
    int j = 0, k = -1;
    next[0] = -1;
    int len = strlen(p);
    while(j < len) {
        if(k == -1 || p[j] == p[k]) {
            ++j; ++k;
            next[j] = k;
        }
        else k = next[k];
    }
}

int KMPMatch(char *s, char *p) {
    int i = 0, j = 0;
    int len = strlen(s), lenp = strlen(p);
    while(i < len) {
        if(j == -1 || s[i] == p[j]) {
            ++i;
            ++j;
        }
        else j = next[j];
        if(j == lenp) return i - lenp;
    }
    return -1;
}

```

2.13 AC Automaton

```

const int N = 1e5 + 5;
struct Trie {
    Trie *next[26];
    Trie *fail;
} pool[N], *root;
int tot;

```

```

Trie* newnode() {
    Trie *t = pool + (tot++);
    memset(t->next, 0, sizeof(t->next));
    t->fail = NULL;
    return t;
}

void init() {
    tot = 0;
    root = newnode();
}

void Insert(char *s) {
    Trie *p = root;
    for(int i = 0; s[i]; ++i) {
        int k = s[i] - 'a';
        if(!p->next[k]) p->next[k] = newnode();
        p = p->next[k];
    }
}

queue <Trie*> Q;
void Build_Ac() {
    Trie *p, *temp;
    Q.push(root);
    while(!Q.empty()) {
        temp = Q.front(); Q.pop();
        for(int i = 0; i < 26; ++i) if(temp->next[i]) {
            p = temp->fail;
            while(p) {
                if(p->next[i]) {
                    temp->next[i]->fail = p->next[i];
                    break;
                }
                p = p->fail;
            }
            if(!p) temp->next[i]->fail = root;
            Q.push(temp->next[i]);
        }
        else {
            temp->next[i] = temp->fail ? temp->fail->next[i] : root;
        }
    }
}

```

3 Graph

3.1 Directed MST

```

#define M 600
#define type int
const type inf = (1) << 30;
struct Node {
    int u, v;
    type cost;
} E[M * M + 5];

```

```

int pre[M], ID[M], vis[M];
type In[M];

type Directed_MST(int root, int NV, int NE) {
    type ret = 0;
    while(true) {
        for(int i = 0; i < NV; i++) In[i] = inf;
        for(int i = 0; i < NE; i++) {
            int u = E[i].u;
            int v = E[i].v;
            if(E[i].cost < In[v] && u != v) {
                pre[v] = u;
                In[v] = E[i].cost;
            }
        }
        for(int i = 0; i < NV; i++) {
            if(i == root) continue;
            if(In[i] == inf) return -1;
        }
        int cntnode = 0;
        memset(ID, -1, sizeof(ID));
        memset(vis, -1, sizeof(vis));
        In[root] = 0;
        for(int i = 0; i < NV; i++) {
            ret += In[i];
            int v = i;
            while(vis[v] != i && ID[v] == -1 && v != root) {
                vis[v] = i;
                v = pre[v];
            }
            if(v != root && ID[v] == -1) {
                for(int u = pre[v] ; u != v ; u = pre[u]) {
                    ID[u] = cntnode;
                }
                ID[v] = cntnode ++;
            }
        }
        if(cntnode == 0) break;
        for(int i = 0; i < NV; i++) if(ID[i] == -1) {
            ID[i] = cntnode ++;
        }
        for(int i = 0; i < NE; i++) {
            int v = E[i].v;
            E[i].u = ID[E[i].u];
            E[i].v = ID[E[i].v];
            if(E[i].u != E[i].v) {
                E[i].cost -= In[v];
            }
        }
        NV = cntnode;
        root = ID[root];
    }
    return ret;
}

```

3.2 Directed MST SOL

```

const int N = 505;

const int DN = N << 1;

const int M = N * N + 5;

const int inf = 1 << 30;

struct EDGE { int u, v, w; };

struct D_MST {

    EDGE E[M];

    int pre[DN], ID[DN], vis[DN];

    int In[DN], inE[DN], ring;

    int nV[DN], nnV[DN];

    vector < pair <int, int> > R[DN];

    bool ans[M], newR[DN];

    map <int, int> dirE[DN];

    void del(int u, int e) {
        if(R[u].empty()) return;
        int pu = dirE[u][e];
        for(auto &x : R[u]) {
            if(x.first == pu) {
                ans[x.second] = false;
                del(x.first, e);
            } else {
                del(x.first, x.second);
            }
        }
    }

    int Directed_MST(int rt, int n, int m) {
        while(true) {
            for(int i = 0; i < n; ++ i) In[nV[i]] = inf;
            for(int i = 0; i < m; ++ i) {
                int u = E[i].u, v = E[i].v;
                if(E[i].w < In[v] && u != v) {
                    pre[v] = u;
                    In[v] = E[i].w;
                    inE[v] = i;
                }
            }
            if(nV[rt] != rt && In[nV[rt]] == inf)
                return -1;
            int cntnode = 0;
            memset(ID, -1, sizeof(ID));
            memset(vis, -1, sizeof(vis));
            memset(newR, 0, sizeof(newR));

```

```

In[rt] = 0;
for(int i = 0; i < n; ++ i) {
    int v = nV[i], s = v;
    while(vis[v] != s && ID[v] == -1 && v != rt) {
        vis[v] = s;
        v = pre[v];
    }
    if(v != rt && ID[v] == -1) {
        for(int u = pre[v]; ; u = pre[u]) {
            ID[u] = ring;
            R[ring].push_back( {u, inE[u]} );
            ans[inE[u]] = true;
            newR[u] = true;
            if(u == v) break;
        }
        nnV[cntnode++] = ring++;
    }
}
if(cntnode == 0) {
    for(int i = 0; i < n; ++ i) {
        if(nV[i] == rt) continue;
        ans[inE[nV[i]]] = true;
        del(nV[i], inE[nV[i]]);
    }
    return 0;
}
for(int i = 0; i < n; ++ i) {
    int v = nV[i];
    if(ID[v] != -1) continue;
    ID[v] = v;
    nnV[cntnode++] = v;
}
for(int i = 0; i < m; ++ i) {
    int v = E[i].v;
    E[i].u = ID[E[i].u];
    E[i].v = ID[E[i].v];
    if(!newR[v]) continue;
    if(E[i].u != E[i].v) {
        E[i].w -= In[v];
        dirE[E[i].v][i] = v;
    }
}
n = cntnode; rt = ID[rt];
for(int i = 0; i < n; ++ i) nV[i] = nnV[i];
}

vector <int> solve(int rt, int n, int m, EDGE *e) {
    for(int i = 0; i < m; ++ i) E[i] = e[i];
    memset(ans, 0, m * sizeof(bool));
    for(int i = 0; i < n; ++ i) nV[i] = i;
    ring = n; vector <int> ret;
    if(Directed_MST(rt, n, m) == -1) return ret;
    for(int i = 0; i < ring; ++ i)
        dirE[i].clear(), R[i].clear();
    for(int i = 0; i < m; ++ i) if(ans[i]) ret.push_back(i);
    return ret;
}

```

```
} mst;
```

3.3 MCMF

```
const int N = 305, M = 100005;
int head[N];
struct Edge {
    int nxt, to, cow, cost;
    Edge() {}
    Edge(int _nxt, int _to, int _cow, int _cost) {
        nxt = _nxt; to = _to; cow = _cow; cost = _cost;
    }
} ed[M];
int ecnt, mx_flow, mi_cost;

void init() {
    mx_flow = mi_cost = ecnt = 0;
    memset(head, -1, sizeof(head));
}

void addedge(int u, int v, int cow, int cost) {
    ed[ecnt] = Edge(head[u], v, cow, cost);
    head[u] = ecnt++;
    ed[ecnt] = Edge(head[v], u, 0, -cost);
    head[v] = ecnt++;
}

queue<int> Q;
int dis[N], pre[N], inq[N];
bool Spfa(int S, int T) {
    memset(dis, 0x3f, sizeof(dis));
    dis[S] = 0;
    Q.push(S);
    while(!Q.empty()) {
        int u = Q.front(); Q.pop();
        inq[u] = 0;
        for(int e = head[u]; ~e; e = ed[e].nxt) {
            if(!ed[e].cow) continue;
            int v = ed[e].to;
            if(dis[v] > dis[u] + ed[e].cost) {
                dis[v] = dis[u] + ed[e].cost;
                pre[v] = e;
                if(!inq[v]) {
                    inq[v] = 1;
                    Q.push(v);
                }
            }
        }
    }
    return dis[T] != INF;
}

void End(int S, int T) {
    int flow = INF;
    for(int u = T; u != S; u = ed[pre[u] ^ 1].to) {
        flow = min(flow, ed[pre[u]].cow);
    }
}
```

```

for(int u = T; u != S; u = ed[pre[u] ^ 1].to) {
    ed[pre[u]].cow -= flow;
    ed[pre[u] ^ 1].cow += flow;
    mi_cost += flow * ed[pre[u]].cost;
}
mx_flow += flow;
}

```

3.4 ZKW MCMF

```

const int maxn=105,maxm=10005;
struct MaxFlow
{
    int size, n;
    int st, en, maxflow, mincost;
    bool vis[maxn];
    int net[maxn], pre[maxn], cur[maxn], dis[maxn];
    std::queue<int> Q;
    struct EDGE
    {
        int v, cap, cost, next;
        EDGE(){}
        EDGE(int a, int b, int c, int d)
        {
            v = a, cap = b, cost = c, next = d;
        }
    }E[maxm];
    void init(int _n)
    {
        n = _n, size = 0;
        memset(net, -1, sizeof(net));
    }
    void add(int u, int v, int cap, int cost)
    {
        E[size] = EDGE(v, cap, cost, net[u]);
        net[u] = size++;
        E[size] = EDGE(u, 0, -cost, net[v]);
        net[v] = size++;
    }
    bool modell()
    {
        int v, min = INF;
        for(int i = 0; i <= n; i++)
        {
            if(!vis[i])
                continue;
            for(int j = net[i]; v = E[j].v, j != -1; j = E[j].next)
                if(E[j].cap)
                    if(!vis[v] && dis[v]-dis[i]+E[j].cost < min)
                        min = dis[v] - dis[i] + E[j].cost;
        }
        if(min == INF)
            return false;
        for(int i = 0; i <= n; i++)
            if(vis[i])
                cur[i] = net[i], vis[i] = false, dis[i] += min;
        return true;
    }
}

```

```

}
int augment(int i, int flow)
{
    if(i == en)
    {
        mincost += dis[st] * flow;
        maxflow += flow;
        return flow;
    }
    vis[i] = true;
    for(int j = cur[i], v; v = E[j].v, j != -1; j = E[j].next)
    {
        if(!E[j].cap)
            continue;
        if(vis[v] || dis[v]+E[j].cost != dis[i])
            continue;
        int delta = augment(v, std::min(flow, E[j].cap));
        if(delta)
        {
            E[j].cap -= delta;
            E[j^1].cap += delta;
            cur[i] = j;
            return delta;
        }
    }
    return 0;
}

void spfa()
{
    int u, v;
    for(int i = 0; i <= n; i++)
        vis[i] = false, dis[i] = INF;
    dis[st] = 0;
    Q.push(st);
    vis[st] = true;
    while(!Q.empty())
    {
        u = Q.front(), Q.pop();
        vis[u] = false;
        for(int i = net[u]; v = E[i].v, i != -1; i = E[i].next)
        {
            if(!E[i].cap || dis[v] <= dis[u] + E[i].cost)
                continue;
            dis[v] = dis[u] + E[i].cost;
            if(!vis[v])
            {
                vis[v] = true;
                Q.push(v);
            }
        }
    }
    for(int i = 0; i <= n; i++)
        dis[i] = dis[en] - dis[i];
}

int zkw(int s, int t)
{
    st = s, en = t;
    spfa();
    mincost=maxflow=0;

```

```

        for(int i = 0; i <= n; i++)
            vis[i] = false, cur[i] = net[i];
        do
        {
            while(augment(st, INF))
                memset(vis, false, sizeof(vis));
        }while(modell());
        return mincost;
    }
}cf;

```

3.5 SAP

```

const int MAXN = 20010;
const int MAXM = 880010;
const int INF = 0x3f3f3f3f;

struct Node {
    int from, to, next;
    int cap;
} edge[MAXM];
int tol;
int head[MAXN];
int dep[MAXN];
int gap[MAXN];

int n;

void init() {
    tol = 0;
    memset(head, -1, sizeof(head));
}

void addedge(int u, int v, int w) {
    edge[tol].from = u;
    edge[tol].to = v;
    edge[tol].cap = w;
    edge[tol].next = head[u];
    head[u] = tol++;
    edge[tol].from = v;
    edge[tol].to = u;
    edge[tol].cap = 0;
    edge[tol].next = head[v];
    head[v] = tol++;
}

void BFS(int start, int end) {
    memset(dep, -1, sizeof(dep));
    memset(gap, 0, sizeof(gap));
    gap[0] = 1;
    int que[MAXN];
    int front, rear;
    front = rear = 0;
    dep[end] = 0;
    que[rear++] = end;
    while(front != rear) {
        int u = que[front++];
    }
}

```

```

        if(front == MAXN)front = 0;
        for(int i = head[u]; i != -1; i = edge[i].next) {
            int v = edge[i].to;
            if(dep[v] != -1)continue;
            que[rear++] = v;
            if(rear == MAXN)rear = 0;
            dep[v] = dep[u] + 1;
            ++gap[dep[v]];
        }
    }
}

int SAP(int start, int end) {
    int res = 0;
    BFS(start, end);
    int cur[MAXN];
    int S[MAXN];
    int top = 0;
    memcpy(cur, head, sizeof(head));
    int u = start;
    int i;
    while(dep[start] < n) {
        if(u == end) {
            int temp = INF;
            int inser;
            for(i = 0; i < top; i++)
                if(temp > edge[S[i]].cap) {
                    temp = edge[S[i]].cap;
                    inser = i;
                }
            for(i = 0; i < top; i++) {
                edge[S[i]].cap -= temp;
                edge[S[i] ^ 1].cap += temp;
            }
            res += temp;
            top = inser;
            u = edge[S[top]].from;
        }
        if(u != end && gap[dep[u] - 1] == 0)
            break;
        for(i = cur[u]; i != -1; i = edge[i].next)
            if(edge[i].cap != 0 && dep[u] == dep[edge[i].to] + 1)
                break;
        if(i != -1) {
            cur[u] = i;
            S[top++] = i;
            u = edge[i].to;
        } else {
            int min = n;
            for(i = head[u]; i != -1; i = edge[i].next) {
                if(edge[i].cap == 0)continue;
                if(min > dep[edge[i].to]) {
                    min = dep[edge[i].to];
                    cur[u] = i;
                }
            }
            --gap[dep[u]];
            dep[u] = min + 1;
            ++gap[dep[u]];
        }
    }
}

```

```

        if(u != start)u = edge[S[--top]].from;
    }
}
return res;
}

```

3.6 Global Minimum Cut

```

const int maxn = 510;

int G[maxn][maxn];

int n, m;

void contract(int x, int y) {
    for(int i = 0; i < n; ++i) if(i != x) G[x][i] += G[y][i], G[i][x] += G[i][y];
    for(int i = y + 1; i < n; ++i) for(int j = 0; j < n; ++j) {
        G[i - 1][j] = G[i][j];
        G[j][i - 1] = G[j][i];
    }
    n--;
}

int w[maxn], c[maxn];

int sx, tx;

int mincut() {
    int t, k;
    memset(c, 0, sizeof(c));
    c[0] = 1;
    for(int i = 0; i < n; ++i) w[i] = G[0][i];
    for(int i = 1; i + 1 < n; ++i) {
        t = k = -1;
        for(int j = 0; j < n; ++j) if(c[j] == 0 && w[j] > k) k = w[t = j];
        c[sx = t] = 1;
        for(int j = 0; j < n; ++j) w[j] += G[t][j];
    }
    for(int i = 0; i < n; ++i) if(c[i] == 0) return w[tx = i];
}

int main() {
    while(~scanf("%d%d", &n, &m)) {
        memset(G, 0, sizeof(G));
        while(m--) {
            int u, v, c;
            scanf("%d%d%d", &u, &v, &c);
            G[u][v] += c;
            G[v][u] += c;
        }
        int mint = INF;
        while(n > 1) {
            int t = mincut();
            mint = min(mint, t);
            contract(sx, tx);
        }
        printf("%d\n", mint);
    }
}

```



```

    }
    return 0;
}

```

3.7 Blossom Tree

```

const int N = 250;

int belong[N];
int findb(int x) {
    return belong[x] == x ? x : belong[x] = findb(belong[x]);
}
void unit(int a, int b) {
    a = findb(a);
    b = findb(b);
    if (a != b) belong[a] = b;
}

int n, match[N];
vector<int> e[N];
int Q[N], rear;
int next[N], mark[N], vis[N];

int LCA(int x, int y) {
    static int t = 0; t++;
    while (true) {
        if (x != -1) {
            x = findb(x);
            if (vis[x] == t) return x;
            vis[x] = t;
            if (match[x] != -1) x = next[match[x]];
            else x = -1;
        }
        swap(x, y);
    }
}

void group(int a, int p) {
    while (a != p) {
        int b = match[a], c = next[b];
        if (findb(c) != p) next[c] = b;
        if (mark[b] == 2) mark[Q[rear++] = b] = 1;
        if (mark[c] == 2) mark[Q[rear++] = c] = 1;
        unit(a, b); unit(b, c);
        a = c;
    }
}

void aug(int s) {
    for (int i = 0; i < n; i++)
        next[i] = -1, belong[i] = i, mark[i] = 0, vis[i] = -1;
    mark[s] = 1;
    Q[0] = s; rear = 1;
    for (int front = 0; match[s] == -1 && front < rear; front++) {
        int x = Q[front];
        for (int i = 0; i < (int)e[x].size(); i++) {

```

```

        int y = e[x][i];
        if (match[x] == y) continue;
        if (findb(x) == findb(y)) continue;
        if (mark[y] == 2) continue;
        if (mark[y] == 1) {
            int r = LCA(x, y);
            if (findb(x) != r) next[x] = y;
            if (findb(y) != r) next[y] = x;

            group(x, r);
            group(y, r);
        }
        else if (match[y] == -1) {
            next[y] = x;
            for (int u = y; u != -1; ) {
                int v = next[u];
                int mv = match[v];
                match[v] = u, match[u] = v;
                u = mv;
            }
            break;
        }
        else {
            next[y] = x;
            mark[Q[rear++] = match[y]] = 1;
            mark[y] = 2;
        }
    }
}

bool g[N][N];
int main() {
    scanf("%d", &n);
    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++) g[i][j] = false;

    int x, y; while (scanf("%d%d", &x, &y) != EOF) {
        x--, y--;
        if (x != y && !g[x][y])
            e[x].push_back(y), e[y].push_back(x);
        g[x][y] = g[y][x] = true;
    }

    for (int i = 0; i < n; i++) match[i] = -1;
    for (int i = 0; i < n; i++) if (match[i] == -1) aug(i);

    int tot = 0;
    for (int i = 0; i < n; i++) if (match[i] != -1) tot++;
    printf("%d\n", tot);
    for (int i = 0; i < n; i++) if (match[i] > i)
        printf("%d %d\n", i + 1, match[i] + 1);
    return 0;
}

```

3.8 KM

```

/*****
Bipartite Graph Maximum Weighted Matching
(kuhn munkras algorithm O(m*m*n))
adjacent matrix: mat
notice: m <= n
init: for(i=0;i<MAXN;i++)
    for(j=0;j<MAXN;j++) mat[i][j]=-inf;
for existing edges: mat[i][j]=val;
*****/

#define MAXN 310
#define inf 1000000000
#define _clr(x) memset(x,-1,sizeof(int)*MAXN)
int KM(int m, int n, int mat[][MAXN], int *match1, int *match2) {
    int s[MAXN], t[MAXN], l1[MAXN], l2[MAXN];
    int p, q, i, j, k, ret = 0;
    for(i = 0; i < m; i++) {
        l1[i] = -inf;
        for(j = 0; j < n; j++)
            l1[i] = mat[i][j] > l1[i] ? mat[i][j] : l1[i];
        if(l1[i] == -inf) return -1;
    }
    for(i = 0; i < n; i++)
        l2[i] = 0;
    _clr(match1);
    _clr(match2);
    for(i = 0; i < m; i++) {
        _clr(t);
        p = 0;
        q = 0;
        for(s[0] = i; p <= q && match1[i] < 0; p++) {
            for(k = s[p], j = 0; j < n && match1[i] < 0; j++) {
                if(l1[k] + l2[j] == mat[k][j] && t[j] < 0) {
                    s[++q] = match2[j];
                    t[j] = k;
                    if(s[q] < 0) {
                        for(p = j; p >= 0; j = p) {
                            match2[j] = k = t[j];
                            p = match1[k];
                            match1[k] = j;
                        }
                    }
                }
            }
        }
        if(match1[i] < 0) {
            i--;
            p = inf;
            for(k = 0; k <= q; k++) {
                for(j = 0; j < n; j++) {
                    if(t[j] < 0 && l1[s[k]] + l2[j] - mat[s[k]][j] < p)
                        p = l1[s[k]] + l2[j] - mat[s[k]][j];
                }
            }
            for(j = 0; j < n; j++)
                l2[j] += t[j] < 0 ? 0 : p;
            for(k = 0; k <= q; k++)
                l1[s[k]] -= p;
        }
    }
}

```

```

    }
}
for(i = 0; i < m; i++)
    ret += mat[i][match1[i]];
return ret;
}

```

3.9 General Graph MWM

```

#include <iostream>
#include <cstdio>
#include <algorithm>
#include <vector>
using namespace std;

typedef long long s64;

const int INF = 2147483647;

const int MaxN = 400;
const int MaxM = 79800;

template <class T>
inline void tension(T &a, const T &b)
{
    if (b < a)
        a = b;
}
template <class T>
inline void relax(T &a, const T &b)
{
    if (b > a)
        a = b;
}
template <class T>
inline int size(const T &a)
{
    return (int)a.size();
}

inline int getint()
{
    char c;
    while (c = getchar(), '0' > c || c > '9');

    int res = c - '0';
    while (c = getchar(), '0' <= c && c <= '9')
        res = res * 10 + c - '0';
    return res;
}

const int MaxNX = MaxN + MaxN;

struct edge
{
    int v, u, w;
}

```

```

    edge(){}
    edge(const int &_v, const int &_u, const int &_w)
        : v(_v), u(_u), w(_w){}
};

int n, m;
edge mat[MaxNX + 1][MaxNX + 1];

int n_matches;
s64 tot_weight;
int mate[MaxNX + 1];
int lab[MaxNX + 1];

int q_n, q[MaxN];
int fa[MaxNX + 1], col[MaxNX + 1];
int slackv[MaxNX + 1];

int n_x;
int bel[MaxNX + 1], blofrom[MaxNX + 1][MaxN + 1];
vector<int> bloch[MaxNX + 1];

inline int e_delta(const edge &e) // does not work inside blossoms
{
    return lab[e.v] + lab[e.u] - mat[e.v][e.u].w * 2;
}
inline void update_slackv(int v, int x)
{
    if (!slackv[x] || e_delta(mat[v][x]) < e_delta(mat[slackv[x]][x]))
        slackv[x] = v;
}
inline void calc_slackv(int x)
{
    slackv[x] = 0;
    for (int v = 1; v <= n; v++)
        if (mat[v][x].w > 0 && bel[v] != x && col[bel[v]] == 0)
            update_slackv(v, x);
}

inline void q_push(int x)
{
    if (x <= n)
        q[q_n++] = x;
    else
    {
        for (int i = 0; i < size(bloch[x]); i++)
            q_push(bloch[x][i]);
    }
}

inline void set_mate(int xv, int xu)
{
    mate[xv] = mat[xv][xu].u;
    if (xv > n)
    {
        edge e = mat[xv][xu];
        int xr = blofrom[xv][e.v];
        int pr = find(bloch[xv].begin(), bloch[xv].end(), xr) - bloch[xv].begin();
        if (pr % 2 == 1)
        {
            reverse(bloch[xv].begin() + 1, bloch[xv].end());
        }
    }
}

```

```

        pr = size(bloch[xv]) - pr;
    }

    for (int i = 0; i < pr; i++)
        set_mate(bloch[xv][i], bloch[xv][i ^ 1]);
    set_mate(xr, xu);

    rotate(bloch[xv].begin(), bloch[xv].begin() + pr, bloch[xv].end());
}

inline void set_bel(int x, int b)
{
    bel[x] = b;
    if (x > n)
    {
        for (int i = 0; i < size(bloch[x]); i++)
            set_bel(bloch[x][i], b);
    }
}

inline void augment(int xv, int xu)
{
    while (true)
    {
        int xnu = bel[mate[xv]];
        set_mate(xv, xu);
        if (!xnu)
            return;
        set_mate(xnu, bel[fa[xnu]]);
        xv = bel[fa[xnu]], xu = xnu;
    }
}

inline int get_lca(int xv, int xu)
{
    static bool book[MaxNX + 1];
    for (int x = 1; x <= n_x; x++)
        book[x] = false;
    while (xv || xu)
    {
        if (xv)
        {
            if (book[xv])
                return xv;
            book[xv] = true;
            xv = bel[mate[xv]];
            if (xv)
                xv = bel[fa[xv]];
        }
        swap(xv, xu);
    }
    return 0;
}

inline void add_blossom(int xv, int xa, int xu)
{
    int b = n + 1;
    while (b <= n_x && bel[b])
        b++;
    if (b > n_x)

```

```

        n_x++;

lab[b] = 0;
col[b] = 0;

mate[b] = mate[xa];

bloch[b].clear();
bloch[b].push_back(xa);
for (int x = xv; x != xa; x = bel[fa[bel[mate[x]]]])
    bloch[b].push_back(x), bloch[b].push_back(bel[mate[x]]), q_push(bel[mate[x]]);
reverse(bloch[b].begin() + 1, bloch[b].end());
for (int x = xu; x != xa; x = bel[fa[bel[mate[x]]]])
    bloch[b].push_back(x), bloch[b].push_back(bel[mate[x]]), q_push(bel[mate[x]]);

set_bel(b, b);

for (int x = 1; x <= n_x; x++)
{
    mat[b][x].w = mat[x][b].w = 0;
    blofrom[b][x] = 0;
}
for (int i = 0; i < size(bloch[b]); i++)
{
    int xs = bloch[b][i];
    for (int x = 1; x <= n_x; x++)
        if (mat[b][x].w == 0 || e_delta(mat[xs][x]) < e_delta(mat[b][x]))
            mat[b][x] = mat[xs][x], mat[x][b] = mat[x][xs];
    for (int x = 1; x <= n_x; x++)
        if (blofrom[xs][x])
            blofrom[b][x] = xs;
}
calc_slackv(b);
}
inline void expand_blossom1(int b) // lab[b] == 1
{
    for (int i = 0; i < size(bloch[b]); i++)
        set_bel(bloch[b][i], bloch[b][i]);

    int xr = blofrom[b][mat[b][fa[b]].v];
    int pr = find(bloch[b].begin(), bloch[b].end(), xr) - bloch[b].begin();
    if (pr % 2 == 1)
    {
        reverse(bloch[b].begin() + 1, bloch[b].end());
        pr = size(bloch[b]) - pr;
    }

    for (int i = 0; i < pr; i += 2)
    {
        int xs = bloch[b][i], xns = bloch[b][i + 1];
        fa[xs] = mat[xns][xs].v;
        col[xs] = 1, col[xns] = 0;
        slackv[xs] = 0, calc_slackv(xns);
        q_push(xns);
    }
    col[xr] = 1;
    fa[xr] = fa[b];
    for (int i = pr + 1; i < size(bloch[b]); i++)
    {

```

```

        int xs = bloch[b][i];
        col[xs] = -1;
        calc_slackv(xs);
    }

    bel[b] = 0;
}

inline void expand_blossom_final(int b) // at the final stage
{
    for (int i = 0; i < size(bloch[b]); i++)
    {
        if (bloch[b][i] > n && lab[bloch[b][i]] == 0)
            expand_blossom_final(bloch[b][i]);
        else
            set_bel(bloch[b][i], bloch[b][i]);
    }
    bel[b] = 0;
}

inline bool on_found_edge(const edge &e)
{
    int xv = bel[e.v], xu = bel[e.u];
    if (col[xu] == -1)
    {
        int nv = bel[mate[xu]];
        fa[xu] = e.v;
        col[xu] = 1, col[nv] = 0;
        slackv[xu] = slackv[nv] = 0;
        q_push(nv);
    }
    else if (col[xu] == 0)
    {
        int xa = get_lca(xv, xu);
        if (!xa)
        {
            augment(xv, xu), augment(xu, xv);
            for (int b = n + 1; b <= n_x; b++)
                if (bel[b] == b && lab[b] == 0)
                    expand_blossom_final(b);
            return true;
        }
        else
            add_blossom(xv, xa, xu);
    }
    return false;
}

bool match()
{
    for (int x = 1; x <= n_x; x++)
        col[x] = -1, slackv[x] = 0;

    q_n = 0;
    for (int x = 1; x <= n_x; x++)
        if (bel[x] == x && !mate[x])
            fa[x] = 0, col[x] = 0, slackv[x] = 0, q_push(x);
    if (q_n == 0)
        return false;
}

```



```

while (true)
{
    for (int i = 0; i < q_n; i++)
    {
        int v = q[i];
        for (int u = 1; u <= n; u++)
            if (mat[v][u].w > 0 && bel[v] != bel[u])
            {
                int d = e_delta(mat[v][u]);
                if (d == 0)
                {
                    if (on_found_edge(mat[v][u]))
                        return true;
                }
                else if (col[bel[u]] == -1 || col[bel[u]] == 0)
                    update_slackv(v, bel[u]);
            }
    }

    int d = INF;
    for (int v = 1; v <= n; v++)
        if (col[bel[v]] == 0)
            tension(d, lab[v]);
    for (int b = n + 1; b <= n_x; b++)
        if (bel[b] == b && col[b] == 1)
            tension(d, lab[b] / 2);
    for (int x = 1; x <= n_x; x++)
        if (bel[x] == x && slackv[x])
        {
            if (col[x] == -1)
                tension(d, e_delta(mat[slackv[x]][x]));
            else if (col[x] == 0)
                tension(d, e_delta(mat[slackv[x]][x]) / 2);
        }

    for (int v = 1; v <= n; v++)
    {
        if (col[bel[v]] == 0)
            lab[v] -= d;
        else if (col[bel[v]] == 1)
            lab[v] += d;
    }
    for (int b = n + 1; b <= n_x; b++)
        if (bel[b] == b)
        {
            if (col[bel[b]] == 0)
                lab[b] += d * 2;
            else if (col[bel[b]] == 1)
                lab[b] -= d * 2;
        }

    q_n = 0;
    for (int v = 1; v <= n; v++)
        if (lab[v] == 0) // all unmatched vertices' labels are zero! cheers!
            return false;
    for (int x = 1; x <= n_x; x++)
        if (bel[x] == x && slackv[x] && bel[slackv[x]] != x &&
            e_delta(mat[slackv[x]][x]) == 0)
        {

```

```

        if (on_found_edge(mat[slackv[x]][x]))
            return true;
    }
    for (int b = n + 1; b <= n_x; b++)
        if (bel[b] == b && col[b] == 1 && lab[b] == 0)
            expand_blossom1(b);
}
return false;
}

void calc_max_weight_match()
{
    for (int v = 1; v <= n; v++)
        mate[v] = 0;

    n_x = n;
    n_matches = 0;
    tot_weight = 0;

    bel[0] = 0;
    for (int v = 1; v <= n; v++)
        bel[v] = v, bloch[v].clear();
    for (int v = 1; v <= n; v++)
        for (int u = 1; u <= n; u++)
            blofrom[v][u] = v == u ? v : 0;

    int w_max = 0;
    for (int v = 1; v <= n; v++)
        for (int u = 1; u <= n; u++)
            relax(w_max, mat[v][u].w);
    for (int v = 1; v <= n; v++)
        lab[v] = w_max;

    while (match())
        n_matches++;

    for (int v = 1; v <= n; v++)
        if (mate[v] && mate[v] < v)
            tot_weight += mat[v][mate[v]].w;
}

int main()
{
    n = getint(), m = getint();

    for (int v = 1; v <= n; v++)
        for (int u = 1; u <= n; u++)
            mat[v][u] = edge(v, u, 0);

    for (int i = 0; i < m; i++)
    {
        int v = getint(), u = getint(), w = getint();
        mat[v][u].w = mat[u][v].w = w;
    }

    calc_max_weight_match();

    printf("%lld\n", tot_weight);
    for (int v = 1; v <= n; v++)

```

```

        printf("%d ", mate[v]);
    printf("\n");

    return 0;
}

```

4 Geometry

4.1 Closet Point Pair

```

const int Max=100005;
struct Point
{
    double x, y;
};
Point p[Max], *px[Max], *py[Max];

inline int Cmp_x(Point *a, Point *b)
{
    return a->x < b->x;
}

inline int Cmp_y(Point *a, Point *b)
{
    return a->y < b->y;
}

inline double Dis(Point *a, Point *b)
{
    return sqrt((a->x - b->x) * (a->x - b->x) + (a->y - b->y) * (a->y - b->y));
}

double Close(int l, int r)
{
    if (l + 1 == r)
        return Dis(px[l], px[r]);
    else if (l + 2 == r)
        return min(min(Dis(px[l], px[l + 1]), Dis(px[l + 1], px[r])), Dis(
            px[l], px[r]));
    int mid = (l + r) / 2;
    double ans = min(Close(l, mid), Close(mid + 1, r));
    int i, j, cnt;
    for (i = l, cnt = 0; i <= r; i++)
        if (px[i]->x >= px[mid]->x - ans && px[i]->x <= px[mid]->x + ans)
            py[cnt++] = px[i];
    sort(py, py + cnt, Cmp_y);
    for (i = 0; i < cnt; i++)
        for (j = i + 1; j < cnt; j++)
        {
            if (py[j]->y - py[i]->y >= ans)
                break;
            ans = min(ans, Dis(py[i], py[j]));
        }
    return ans;
}

```

4.2 Geometry Lweb

```
const double pi = acos(-1.0);

inline int sgn(double x) {
    if(x < -eps) return -1;
    return x > eps;
}

struct Vector {
    double x, y;
    inline void read() {
        scanf("%lf%lf", &x, &y);
    }
    Vector(double _x = 0, double _y = 0) {
        x = _x;
        y = _y;
    }
    Vector operator +(Vector a) const {
        return Vector(x + a.x, y + a.y);
    }
    Vector operator +=(Vector a) {
        return *this = *this + a;
    }
    Vector operator -(Vector a) const {
        return Vector(x - a.x, y - a.y);
    }
    Vector operator -=(Vector a) {
        return *this = *this - a;
    }
    Vector operator *(double p) const {
        return Vector(x * p, y * p);
    }
    Vector operator *=(double p) {
        return *this = *this * p;
    }
    Vector normal() {
        return Vector(x / len(), y / len());
    }
    bool operator <(const Vector a) const {
        if(x == a.x) return y < a.y;
        return x < a.x;
    }
    bool operator ==(const Vector a) const {
        return sgn(x - a.x) == 0 && sgn(y - a.y) == 0;
    }
    double len() const {
        return sqrt(x * x + y * y);
    }
    double angle() const {
        return atan2(y, x);
    }
};

inline double cross(Vector a, Vector b) {
    return a.x * b.y - a.y * b.x;
}

inline double scalar(Vector a, Vector b) {
```

```

    return a.x * b.x + a.y * b.y;
}
inline double dist(Vector A, Vector B) {
    return sqrt(1.0 * (A.x - B.x) * (A.x - B.x) + (A.y - B.y) * (A.y - B.y));
}
inline bool parallel(Vector a, Vector b, Vector c, Vector d) {
    return sgn(cross(b - a, d - c)) == 0;
}
Vector Rotate(Vector A, double rad) {
    return Vector(A.x * cos(rad) - A.y * sin(rad), A.x * sin(rad) + A.y * cos(rad));
}

Vector GetLineProjection(Vector P, Vector A, Vector B) {
    //Projection of point P on line AB
    Vector v = B - A;
    Vector v1 = P - A;
    double t = scalar(v, v1) / scalar(v, v);
    return A + v * t;
}

Vector GetLineSymmetry(Vector P, Vector A, Vector B) {
    //Symmetry point of P according to line AB
    double dis = DistoLine(A, B, P) * 2;
    if(sgn(dis) == 0) return P;
    Vector v = Rotate(B - A, pi / 2).normal();
    if(sgn(scalar(P - A, v)) > 0) v = v * -1;
    return P + (v * dis);
}

inline bool between(Vector a, Vector b, Vector c) {
    //a is between bc
    return sgn(a.x - min(b.x, c.x)) >= 0 && sgn(a.x - max(b.x, c.x)) <= 0 && sgn(a.y - min(b.y,
        c.y)) >= 0 &&
        sgn(a.y - max(b.y, c.y)) <= 0;
}

//Distance of C to segment AB
inline double DistoSegment(Vector A, Vector B, Vector C) {
    if(dist(A, B) < eps) return dist(B, C);
    if(scalar(B - A, C - A) < -eps) return dist(A, C);
    if(scalar(A - B, C - B) < -eps) return dist(B, C);
    return fabs(cross(B - A, C - A) / dist(A, B));
}

//Distance of C to line AB
inline double DistoLine(Vector A, Vector B, Vector C) {
    return fabs(cross(B - A, C - A) / dist(A, B));
}

inline int segmentsegment(Vector a, Vector b, Vector c, Vector d) {
    //-1 No intersection point
    //0 Parallel && No intersection point
    //1 Parallel && Inf intersection point
    //2 Parallel && Intersect at end point
    //3 Intersect at end point
    //4 Strictly intersect
    double d1 = cross(a - c, a - d), d2 = cross(b - c, b - d), d3 = cross(c - a, c - b), d4 =
        cross(d - a, d - b);
    if(sgn(d1 * d2) < 0 && sgn(d3 * d4) < 0) return 4;
}

```

```

    if(sgn(d1) == 0 && sgn(d2) == 0 && sgn(d3) == 0 && sgn(d4) == 0) {
        if(a == c && !between(d, a, b)) return 2;
        if(a == d && !between(c, a, b)) return 2;
        if(b == c && !between(d, a, b)) return 2;
        if(b == d && !between(c, a, b)) return 2;
        if(between(c, a, b) || between(d, a, b)) return 1;
        if(between(a, c, d) || between(b, c, d)) return 1;
        return 0;
    }
    if(sgn(d1) == 0 && between(a, c, d)) return 3;
    if(sgn(d2) == 0 && between(b, c, d)) return 3;
    if(sgn(d3) == 0 && between(c, a, b)) return 3;
    if(sgn(d4) == 0 && between(d, a, b)) return 3;
    return -1;
}

inline bool in(Vector t, Vector *po, int n) {
    int cnt = 0;
    for(int i = 0; i < n; ++i) {
        int a = i, b = (i + 1) % n;
        if(sgn(po[a].y - po[b].y) < 0) swap(a, b);
        int x = sgn(cross(po[a] - t, po[b] - t));
        if(!x) {
            if(between(t, po[a], po[b])) return 1;
        } else if(x < 0 && sgn(po[a].y - t.y) >= 0 && sgn(t.y - po[b].y) > 0) ++cnt;
    }
    return cnt & 1;
}

inline int get_convex(Vector *p, Vector *convex, int n) {
    sort(p, p + n);
    int cnt = 0;
    for(int i = 0; i < n; ++i) {
        while(cnt >= 2 && sgn(cross(convex[cnt - 1] - p[i], convex[cnt - 2] - p[i])) <= 0) --cnt;
        convex[cnt++] = p[i];
    }
    int half = cnt;
    for(int i = n - 2; i >= 0; --i) {
        while(cnt - half >= 1 && sgn(cross(convex[cnt - 1] - p[i], convex[cnt - 2] - p[i])) <= 0)
            --cnt;
        convex[cnt++] = p[i];
    }
    return cnt - 1;
}

inline double PolygonArea(Vector *p, int n) {
    double area = 0;
    for(int i = 1; i < n - 1; i++) area += cross(p[i] - p[0], p[i + 1] - p[0]);
    return area / 2;
}

double CircleCircleArea(double r1, double r2, double s) {
    //Circle area intersection
    //r1 r2: radius
    //s: Circle center distance
    if(r1 + r2 < s)
        return 0;
    else if(r2 - r1 >= s)

```

```

        return pi * r1 * r1;
    else if(r1 - r2 >= s)
        return pi * r2 * r2;
    double q1 = acos((r1 * r1 + s * s - r2 * r2) / (2 * r1 * s));
    double q2 = acos((r2 * r2 + s * s - r1 * r1) / (2 * r2 * s));
    return (r1 * r1 * q1 + r2 * r2 * q2 - r1 * s * sin(q1));
}

typedef Vector Point;
struct Circle {
    Point c;
    double r;
    Circle(Point c = Point(0, 0), double r = 0): c(c), r(r) {}
    Point point(double a) {
        return Point(c.x + r * cos(a), c.y + r * sin(a));
    }
};

struct Line {
    Point p;
    Vector v;
    Line(Point p = Point(0, 0), Vector v = Vector(0, 1)): p(p), v(v) {}
    Point point(double t) {
        return Point(p + v * t);
    }
};

int getLineCircleIntersection(Line L, Circle C, double &t1, double &t2, vector<Point> &sol) {
    double a = L.v.x;
    double b = L.p.x - C.c.x;
    double c = L.v.y;
    double d = L.p.y - C.c.y;
    double e = a * a + c * c;
    double f = 2 * (a * b + c * d);
    double g = b * b + d * d - C.r * C.r;
    double delta = f * f - 4 * e * g;
    if(sgn(delta) < 0) return 0;
    if(sgn(delta) == 0) {
        t1 = t2 = -f / (2 * e);
        sol.push_back(L.point(t1));
        return 1;
    } else {
        t1 = (-f - sqrt(delta)) / (2 * e);
        t2 = (-f + sqrt(delta)) / (2 * e);
        sol.push_back(L.point(t1));
        sol.push_back(L.point(t2));
        return 2;
    }
}

double angle(Vector v) {
    return atan2(v.y, v.x);
}

double Length(Vector v) {
    return sqrt(scalar(v, v));
}

int getCircleCircleIntersection(Circle C1, Circle C2, vector<Point> &sol) {
    double d = Length(C1.c - C2.c);
    if(sgn(d) == 0) {

```

```

        if(sgn(C1.r - C2.r) == 0) return -1; // coincidence
        else return 0; // contains
    }
    if(sgn(C1.r + C2.r - d) < 0) return 0; // away from
    if(sgn(fabs(C1.r - C2.r) - d) > 0) return 0; // contains
    double a = angle(C2.c - C1.c);
    double da = acos((C1.r * C1.r + d * d - C2.r * C2.r) / (2 * C1.r * d));
    Point p1 = C1.point(a - da);
    Point p2 = C1.point(a + da);
    sol.push_back(p1);
    if(p1 == p2) return 1; // tangent
    else {
        sol.push_back(p2);
        return 2;
    }
}

int getTangents(Point p, Circle C, vector<Point> &sol) {
    //Tangent for p to C
    Vector u = C.c - p;
    double dist = Length(u);
    if(sgn(dist - C.r) < 0) return 0;
    else if(sgn(dist - C.r) == 0) {
        sol.push_back(Rotate(u, pi / 2));
        return 1;
    } else {
        double ang = asin(C.r / dist);
        sol.push_back(Rotate(u, -ang));
        sol.push_back(Rotate(u, +ang));
        return 2;
    }
}

bool flag = 0;
int getTangents(Circle A, Circle B, Point *a, Point *b) {
    //Common tangent for A B
    int cnt = 0;
    if(A.r < B.r) {
        flag = 1;
        swap(A, B);
        swap(a, b);
    }
    double d = Length(A.c - B.c);
    double rdif = A.r - B.r;
    double rsum = A.r + B.r;
    if(sgn(d - rdif) < 0) return 0; // contains
    double base = angle(B.c - A.c);
    if(sgn(d) == 0 && sgn(rdif) == 0) return -1; // coincidence
    if(sgn(d - rdif) == 0) { // tangent inside
        a[cnt] = A.point(base);
        b[cnt] = B.point(base);
        cnt++;
        return 1;
    }

    double ang = acos(rdif / d);
    a[cnt] = A.point(base + ang);
    b[cnt] = B.point(base + ang);
    cnt++;
}

```



```

    a[cnt] = A.point(base - ang);
    b[cnt] = B.point(base - ang);
    cnt++;
    if(sgn(d - rsum) == 0) { // tangent outside
        a[cnt] = A.point(base);
        b[cnt] = B.point(base + pi);
        cnt++;
    } else if(sgn(d - rsum) > 0) { // away from
        double ang_in = acos(rsum / d);
        a[cnt] = A.point(base + ang_in);
        b[cnt] = B.point(base + ang_in + pi);
        cnt++;
        a[cnt] = A.point(base - ang_in);
        b[cnt] = B.point(base - ang_in + pi);
        cnt++;
    }
    return cnt;
}

```

4.3 Geometry Hezhu

```

Point GetLineIntersection(Point p, Vector v, Point q, Vector w) {
    Vector u = p - q;
    double t = Cross(w, u) / Cross(v, w);
    return p + v * t;
}

Point GetLineProjection(Point P, Point A, Point B) {
    Vector v = B - A;
    return A + v * (Dot(v, P - A) / Dot(v, v));
}

double DistanceToLine(Point P, Point A, Point B) {
    Vector v1 = B - A, v2 = P - A;
    return fabs(Cross(v1, v2)) / Length(v1);
}

bool OnSegment(Point p, Point a1, Point a2) {
    return dcmp(Cross(a1 - p, a2 - p)) == 0 && dcmp(Dot(a1 - p, a2 - p)) < 0;
}

void getLineGeneralEquation(const Point &p1, const Point &p2, double &a,
                           double &b, double &c) {
    a = p2.y - p1.y;
    b = p1.x - p2.x;
    c = -a * p1.x - b * p1.y;
}

double DistanceToSegment(Point p, Point a, Point b) {
    if (a == b) return Length(p - a);
    Vector v1 = b - a, v2 = p - a, v3 = p - b;
    if (dcmp(Dot(v1, v2)) < 0)
        return Length(v2);
    else if (dcmp(Dot(v1, v3)) > 0)
        return Length(v3);
    else
        return fabs(Cross(v1, v2)) / Length(v1);
}

double dis_pair_seg(Point p1, Point p2, Point p3, Point p4) {
    return min(
        min(DistanceToSegment(p1, p3, p4), DistanceToSegment(p2, p3, p4)),
        min(DistanceToSegment(p3, p1, p2), DistanceToSegment(p4, p1, p2)));
}

```

```

}
bool SegmentIntersection(Point a1, Point a2, Point b1, Point b2) {
    double c1 = Cross(a2 - a1, b1 - a1), c2 = Cross(a2 - a1, b2 - a1),
        c3 = Cross(b2 - b1, a1 - b1), c4 = Cross(b2 - b1, a2 - b1);
    return dcmp(c1) * dcmp(c2) < 0 && dcmp(c3) * dcmp(c4) < 0;
}
struct Line {
    Point P;
    Vector v;
    double ang;
    Line() {}
    Line(Point P, Vector v) : P(P), v(v) { ang = atan2(v.y, v.x); }
    Point point(double a) { return p + (v * a); }
    bool operator<(const Line &L) const { return ang < L.ang; }
};
bool OnLeft(const Line &L, const Point &p) { return Cross(L.v, p - L.P) > 0; }
vector<Point> HalfplaneIntersection(vector<Line> L) {
    int n = L.size();
    sort(L.begin(), L.end());
    int first, last;
    vector<Point> p(n);
    vector<Line> q(n);
    vector<Point> ans;
    q[first = last = 0] = L[0];
    for (int i = 1; i < n; i++) {
        while (first < last && !OnLeft(L[i], p[last - 1])) last--;
        while (first < last && !OnLeft(L[i], p[first])) first++;
        q[++last] = L[i];
        if (fabs(Cross(q[last].v, q[last - 1].v)) < eps) {
            last--;
            if (OnLeft(q[last], L[i].P)) q[last] = L[i];
        }
        if (first < last)
            p[last - 1] = GetLineIntersection(q[last - 1], q[last]);
    }
    while (first < last && !OnLeft(q[first], p[last - 1])) last--;
    if (last - first <= 1) return ans;
    p[last] = GetLineIntersection(q[last], q[first]);
    for (int i = first; i <= last; i++) ans.push_back(p[i]);
    return ans;
}
Point PolyGravity(Point *p, int n) {
    Point tmp, g = Point(0, 0);
    double sumArea = 0, area;
    for (int i = 2; i < n; ++i) {
        area = Cross(p[i - 1] - p[0], p[i] - p[0]);
        sumArea += area;
        tmp.x = p[0].x + p[i - 1].x + p[i].x;
        tmp.y = p[0].y + p[i - 1].y + p[i].y;
        g.x += tmp.x * area;
        g.y += tmp.y * area;
    }
    g.x /= (sumArea * 3.0);
    g.y /= (sumArea * 3.0);
    return g;
}
vector<Point> ConvexHull(vector<Point> &p) {
    sort(p.begin(), p.end());
    p.erase(unique(p.begin(), p.end()), p.end());
}

```

```

int n = p.size();
int m = 0;
vector<Point> ch(n + 1);
for (int i = 0; i < n; i++) {
    while (m > 1 && Cross(ch[m - 1] - ch[m - 2], p[i] - ch[m - 2]) <= 0)
        m--;
    ch[m++] = p[i];
}
int k = m;
for (int i = n - 2; i >= 0; i--) {
    while (m > k && Cross(ch[m - 1] - ch[m - 2], p[i] - ch[m - 2]) <= 0)
        m--;
    ch[m++] = p[i];
}
if (n > 1) m--;
ch.resize(m);
return ch;
}

int isPointInPolygon(Point p, Polygon poly) {
    int wn = 0;
    int n = poly.size();
    for (int i = 0; i < n; i++) {
        if (OnSegment(p, poly[i], poly[(i + 1) % n])) return -1;
        int k = dcmp(Cross(poly[(i + 1) % n] - poly[i], p - poly[i]));
        int d1 = dcmp(poly[i].y - p.y);
        int d2 = dcmp(poly[(i + 1) % n].y - p.y);
        if (k > 0 && d1 <= 0 && d2 > 0) wn++;
        if (k < 0 && d2 <= 0 && d1 > 0) wn--;
    }
    if (wn != 0) return 1;
    return 0;
}

int diameter2(vector<Point> &points) {
    vector<Point> p = ConvexHull(points);
    int n = p.size();
    if (n == 1) return 0;
    if (n == 2) return Dist2(p[0], p[1]);
    p.push_back(p[0]);
    int ans = 0;
    for (int u = 0, v = 1; u < n; u++) {
        for (;;) {
            int diff = Cross(p[u + 1] - p[u], p[v + 1] - p[v]);
            if (diff <= 0) {
                ans = max(ans, Dist2(p[u], p[v]));
                if (diff == 0) ans = max(ans, Dist2(p[u], p[v + 1]));
                break;
            }
            v = (v + 1) % n;
        }
    }
    return ans;
}

double RC_Distance(Point *ch1, Point *ch2, int n, int m) {
    int q = 0, p = 0;
    REP(i, n) if (ch1[i].y - ch1[p].y < -eps) p = i;
    REP(i, m) if (ch2[i].y - ch2[q].y > eps) q = i;
    ch1[n] = ch1[0];
    ch2[m] = ch2[0];
    double tmp, ans = 1e100;

```

```

REP(i, n) {
    while ((tmp = Cross(ch1[p + 1] - ch1[p], ch2[q + 1] - ch1[p]) -
        Cross(ch1[p + 1] - ch1[p], ch2[q] - ch1[p])) > eps)
        q = (q + 1) % m;
    if (tmp < -eps)
        ans = min(ans, DistanceToSegment(ch2[q], ch1[p], ch1[p + 1]));
    else
        ans =
            min(ans, dis_pair_seg(ch1[p], ch1[p + 1], ch2[q], ch2[q + 1]));
    p = (p + 1) % n;
}
return ans;
}
double RC_Triangle(Point *res, int n) {
    if (n < 3) return 0;
    double ans = 0, tmp;
    res[n] = res[0];
    int j, k;
    REP(i, n) {
        j = (i + 1) % n;
        k = (j + 1) % n;
        while ((j != k) && (k != i)) {
            while (Cross(res[j] - res[i], res[k + 1] - res[i]) >
                Cross(res[j] - res[i], res[k] - res[i]))
                k = (k + 1) % n;
            tmp = Cross(res[j] - res[i], res[k] - res[i]);
            if (tmp > ans) ans = tmp;
            j = (j + 1) % n;
        }
    }
    return ans;
}
double fermat_point(Point *pt, int n, Point &ptres) {
    Point u, v;
    double step = 0.0, curlen, explen, minlen;
    int i, j, k, idx;
    bool flag;
    u.x = u.y = v.x = v.y = 0.0;
    REP(i, n) {
        step += fabs(pt[i].x) + fabs(pt[i].y);
        u.x += pt[i].x;
        u.y += pt[i].y;
    }
    u.x /= n;
    u.y /= n;
    flag = 0;
    while (step > eps) {
        for (k = 0; k < 10; step /= 2, ++k)
            for (i = -1; i <= 1; ++i)
                for (j = -1; j <= 1; ++j) {
                    v.x = u.x + step * i;
                    v.y = u.y + step * j;
                    curlen = explen = 0.0;
                    REP(idx, n) {
                        curlen += dist(u, pt[idx]);
                        explen += dist(v, pt[idx]);
                    }
                    if (curlen > explen) {
                        u = v;

```

```

        minlen = explen;
        flag = 1;
    }
}

ptres = u;
return flag ? minlen : curlen;
}

bool cmpy(const int &a, const int &b) { return point[a].y < point[b].y; }
double Closest_Pair(int left, int right) {
    double d = INF;
    if (left == right) return d;
    if (left + 1 == right) return dis(left, right);
    int mid = (left + right) >> 1;
    double d1 = Closest_Pair(left, mid);
    double d2 = Closest_Pair(mid + 1, right);
    d = min(d1, d2);
    int i, j, k = 0;
    for (i = left; i <= right; i++) {
        if (fabs(point[mid].x - point[i].x) <= d) tmp[k++] = i;
    }
    sort(tmp, tmp + k, cmpy);
    for (i = 0; i < k; i++) {
        for (j = i + 1; j < k && point[tmp[j]].y - point[tmp[i]].y < d; j++) {
            double d3 = dis(tmp[i], tmp[j]);
            if (d > d3) d = d3;
        }
    }
    return d;
}

int getLineCircleIntersection(Line L, Circle C, double &t1, double &t2, vector<Point> &sol) {
    double a = L.v.x, b = L.p.x - C.c.x, c = L.v.y, d = L.p.y - C.c.y;
    double e = a * a + c * c, f = 2 * (a * b + c * d),
        g = b * b + d * d - C.r * C.r;
    double delta = f * f - 4 * e * g;
    if (dcmp(delta) < 0) return 0;
    if (dcmp(delta) == 0) {
        t1 = t2 = -f / (2 * e);
        sol.push_back(L.point(t1));
        return 1;
    }
    t1 = (-f - sqrt(delta)) / (2 * e);
    sol.push_back(L.point(t1));
    t2 = (-f + sqrt(delta)) / (2 * e);
    sol.push_back(L.point(t2));
    return 2;
}

int getCircleCircleIntersection(Circle C1, Circle C2, vector<Point> &sol) {
    double d = Length(C1.c - C2.c);
    if (dcmp(d) == 0) {
        if (dcmp(C1.r - C2.r) == 0) return -1;
        return 0;
    }
    if (dcmp(C1.r + C2.r - d) < 0) return 0;
    if (dcmp(fabs(C1.r - C2.r) - d) > 0) return 0;
    double a = angle(C2.c - C1.c);
    double da = acos((C1.r * C1.r + d * d - C2.r * C2.r) / (2 * C1.r * d));
    Point p1 = C1.point(a - da), p2 = C1.point(a + da);
    sol.push_back(p1);

```

```

    if (p1 == p2) return 1;
    sol.push_back(p2);
    return 2;
}

int getTangents(Point p, Circle C, Vector *v) {
    Vector u = C.c - p;
    double dist = Length(u);
    if (dist < C.r)
        return 0;
    else if (dcmp(dist - C.r) == 0) {
        v[0] = Rotate(u, PI / 2);
        return 1;
    } else {
        double ang = asin(C.r / dist);
        v[0] = Rotate(u, -ang);
        v[1] = Rotate(u, +ang);
        return 2;
    }
}

int getTangents(Circle A, Circle B, Point *a, Point *b) {
    int cnt = 0;
    if (A.r < B.r) swap(A, B), swap(a, b);
    int d2 =
        (A.c.x - B.c.x) * (A.c.x - B.c.x) + (A.c.y - B.c.y) * (A.c.y - B.c.y);
    int rdif = A.r - B.r;
    int rsum = A.r + B.r;
    if (d2 < rdif * rdif) return 0;
    double base = atan2(B.c.y - A.c.y, B.c.x - A.c.x);
    if (d2 == 0 && A.r == B.r) return -1;
    if (d2 == rdif * rdif) {
        a[cnt] = A.point(base);
        b[cnt] = B.point(base);
        cnt++;
        return 1;
    }
    double ang = acos((A.r - B.r) / sqrt(d2));
    a[cnt] = A.point(base + ang);
    b[cnt] = B.point(base + ang);
    cnt++;
    a[cnt] = A.point(base - ang);
    b[cnt] = B.point(base - ang);
    cnt++;
    if (d2 == rsum * rsum) {
        a[cnt] = A.point(base);
        b[cnt] = B.point(PI + base);
        cnt++;
    } else if (d2 > rsum * rsum) {
        double ang = acos((A.r + B.r) / sqrt(d2));
        a[cnt] = A.point(base + ang);
        b[cnt] = B.point(PI + base + ang);
        cnt++;
        a[cnt] = A.point(base - ang);
        b[cnt] = B.point(PI + base - ang);
        cnt++;
    }
    return cnt;
}

Circle CircumscribedCircle(Point p1, Point p2, Point p3) {
    double Bx = p2.x - p1.x, By = p2.y - p1.y;

```

```

    double Cx = p3.x - p1.x, Cy = p3.y - p1.y;
    double D = 2 * (Bx * Cy - By * Cx);
    double cx = (Cy * (Bx * Bx + By * By) - By * (Cx * Cx + Cy * Cy)) / D + p1.x;
    double cy = (Bx * (Cx * Cx + Cy * Cy) - Cx * (Bx * Bx + By * By)) / D + p1.y;
    Point p = Point(cx, cy);
    return Circle(p, Length(p1 - p));
}

Circle InscribedCircle(Point p1, Point p2, Point p3) {
    double a = Length(p2 - p3);
    double b = Length(p3 - p1);
    double c = Length(p1 - p2);
    Point p = (p1 * a + p2 * b + p3 * c) / (a + b + c);
    return Circle(p, DistanceToLine(p, p1, p2));
}

vector<Point> CircleThroughPointTangentToLineGivenRadius(Point p, Line L, double r) {
    vector<Point> ans;
    double t1, t2;
    getLineCircleIntersection(L.move(-r), Circle(p, r), t1, t2, ans);
    getLineCircleIntersection(L.move(r), Circle(p, r), t1, t2, ans);
    return ans;
}

vector<Point> CircleTangentToLinesGivenRadius(Line a, Line b, double r) {
    vector<Point> ans;
    Line L1 = a.move(-r), L2 = a.move(r);
    Line L3 = b.move(-r), L4 = b.move(r);
    ans.push_back(GetLineIntersection(L1, L3));
    ans.push_back(GetLineIntersection(L1, L4));
    ans.push_back(GetLineIntersection(L2, L3));
    ans.push_back(GetLineIntersection(L2, L4));
    return ans;
}

vector<Point> CircleTangentToTwoDisjointCirclesWithRadius(Circle c1, Circle c2, double r) {
    vector<Point> ans;
    Vector v = c2.c - c1.c;
    double dist = Length(v);
    int d = dcmp(dist - c1.r - c2.r - r * 2);
    if (d > 0) return ans;
    getCircleCircleIntersection(Circle(c1.c, c1.r + r), Circle(c2.c, c2.r + r), ans);
    return ans;
}

int getSegCircleIntersection(Line L, Circle C, Point *sol) {
    Vector nor = normal(L.v);
    Line pl = Line(C.c, nor);
    Point ip = GetIntersection(pl, L);
    double dis = Length(ip - C.c);
    if (dcmp(dis - C.r) > 0) return 0;
    Point dxy = vecunit(L.v) * sqrt(sqr(C.r) - sqr(dis));
    int ret = 0;
    sol[ret] = ip + dxy;
    if (OnSegment(sol[ret], L.p, L.point(1))) ret++;
    sol[ret] = ip - dxy;
    if (OnSegment(sol[ret], L.p, L.point(1))) ret++;
    return ret;
}

double SegCircleArea(Circle C, Point a, Point b) {
    double a1 = angle(a - C.c);
    double a2 = angle(b - C.c);
    double da = fabs(a1 - a2);
    if (da > PI) da = PI * 2.0 - da;
}

```

```

    return dcmp(Cross(b - C.c, a - C.c)) * da * sqr(C.r) / 2.0;
}
double PolyCiclrArea(Circle C, Point *p, int n) {
    double ret = 0.0;
    Point sol[2];
    p[n] = p[0];
    REP(i, n) {
        double t1, t2;
        int cnt = getSegCircleIntersection(Line(p[i], p[i + 1] - p[i]), C, sol);
        if (cnt == 0) {
            if (!OnOrInCircle(p[i], C) || !OnOrInCircle(p[i + 1], C))
                ret += SegCircleArea(C, p[i], p[i + 1]);
            else
                ret += Cross(p[i + 1] - C.c, p[i] - C.c) / 2.0;
        }
        if (cnt == 1) {
            if (OnOrInCircle(p[i], C) && !OnOrInCircle(p[i + 1], C))
                ret += Cross(sol[0] - C.c, p[i] - C.c) / 2.0,
                ret += SegCircleArea(C, sol[0], p[i + 1]);
            else
                ret += SegCircleArea(C, p[i], sol[0]),
                ret += Cross(p[i + 1] - C.c, sol[0] - C.c) / 2.0;
        }
        if (cnt == 2) {
            if ((p[i] < p[i + 1]) ^ (sol[0] < sol[1])) swap(sol[0], sol[1]);
            ret += SegCircleArea(C, p[i], sol[0]);
            ret += Cross(sol[1] - C.c, sol[0] - C.c) / 2.0;
            ret += SegCircleArea(C, sol[1], p[i + 1]);
        }
    }
    return fabs(ret);
}
double area[N];
int n;
struct cp {
    double x, y, r, angle;
    int d;
    cp() {}
    cp(double xx, double yy, double ang = 0, int t = 0) {
        x = xx;
        y = yy;
        angle = ang;
        d = t;
    }
    void get() {
        scanf("%lf%lf%lf", &x, &y, &r);
        d = 1;
    }
} cir[N], tp[N * 2];
double dis(cp a, cp b) { return sqrt(sqr(a.x - b.x) + sqr(a.y - b.y)); }
double cross(cp p0, cp p1, cp p2) {
    return (p1.x - p0.x) * (p2.y - p0.y) - (p1.y - p0.y) * (p2.x - p0.x);
}
bool circmp(const cp &u, const cp &v) { return dcmp(u.r - v.r) < 0; }
bool cmp(const cp &u, const cp &v) {
    if (dcmp(u.angle - v.angle)) return u.angle < v.angle;
    return u.d > v.d;
}
double calc(cp cir, cp cp1, cp cp2) {

```



```

    double ans = (cp2.angle - cp1.angle) * sqr(cir.r) - cross(cir, cp1, cp2) +
        cross(cp(0, 0), cp1, cp2);
    return ans / 2;
}

void CirUnion(cp cir[], int n) {
    cp cp1, cp2;
    sort(cir, cir + n, circmp);
    for (int i = 0; i < n; ++i)
        for (int j = i + 1; j < n; ++j)
            if (dcmp(dis(cir[i], cir[j]) + cir[i].r - cir[j].r) <= 0)
                cir[i].d++;
    for (int i = 0; i < n; ++i) {
        int tn = 0, cnt = 0;
        for (int j = 0; j < n; ++j) {
            if (i == j) continue;
            if (CirCrossCir(cir[i], cir[i].r, cir[j], cir[j].r, cp2, cp1) < 2)
                continue;
            cp1.angle = atan2(cp1.y - cir[i].y, cp1.x - cir[i].x);
            cp2.angle = atan2(cp2.y - cir[i].y, cp2.x - cir[i].x);
            cp1.d = 1;
            tp[tn++] = cp1;
            cp2.d = -1;
            tp[tn++] = cp2;
            if (dcmp(cp1.angle - cp2.angle) > 0) cnt++;
        }
        tp[tn++] = cp(cir[i].x - cir[i].r, cir[i].y, pi, -cnt);
        tp[tn++] = cp(cir[i].x - cir[i].r, cir[i].y, -pi, cnt);
        sort(tp, tp + tn, cmp);
        int p, s = cir[i].d + tp[0].d;
        for (int j = 1; j < tn; ++j) {
            p = s;
            s += tp[j].d;
            area[p] += calc(cir[i], tp[j - 1], tp[j]);
        }
    }
}

void solve() {
    scanf("%d", &n);
    for (int i = 0; i < n; ++i) cir[i].get();
    memset(area, 0, sizeof(area));
    CirUnion(cir, n);
    for (int i = 1; i <= n; ++i) { area[i] -= area[i + 1]; }
    double tot = 0;
    for (int i = 1; i <= n; i++) tot += area[i];
    printf("%f\n", tot);
}

inline double cross(point o, point a, point b) { return (a - o) * (b - o); }
PDI s[maxN * maxp * 2];
Polygon P[maxN];
double S, ts;
int N;
inline double seg(point o, point a, point b) {
    if (cmp(b.x - a.x) == 0) return (o.y - a.y) / (b.y - a.y);
    return (o.x - a.x) / (b.x - a.x);
}

double PolygonUnion() {
    int M, c1, c2;
    double s1, s2, ret = 0;
    for (int i = 0; i < N; i++)

```

```

for (int ii = 0; ii < P[i].n; ii++) {
    M = 0;
    s[M++] = mp(0.00, 0);
    s[M++] = mp(1.00, 0);
    for (int j = 0; j < N; j++)
        if (i != j)
            for (int jj = 0; jj < P[j].n; jj++) {
                c1 = cmp(cross(P[i][ii], P[i][ii + 1], P[j][jj]));
                c2 = cmp(cross(P[i][ii], P[i][ii + 1], P[j][jj + 1]));
                if (c1 == 0 && c2 == 0) {
                    if (((P[i][ii + 1] - P[i][ii]) ^
                        (P[j][jj + 1] - P[j][jj])) > 0 &&
                        i > j) {
                        s[M++] = mp(
                            seg(P[j][jj], P[i][ii], P[i][ii + 1]), 1);
                        s[M++] = mp(
                            seg(P[j][jj + 1], P[i][ii], P[i][ii + 1]),
                            -1);
                    }
                } else {
                    s1 = cross(P[j][jj], P[j][jj + 1], P[i][ii]);
                    s2 = cross(P[j][jj], P[j][jj + 1], P[i][ii + 1]);
                    if (c1 >= 0 && c2 < 0)
                        s[M++] = mp(s1 / (s1 - s2), 1);
                    else if (c1 < 0 && c2 >= 0)
                        s[M++] = mp(s1 / (s1 - s2), -1);
                }
            }
        }
    sort(s, s + M);
    double pre = min(max(s[0].x, 0.0), 1.0), now;
    double sum = 0;
    int cov = s[0].y;
    for (int j = 1; j < M; j++) {
        now = min(max(s[j].x, 0.0), 1.0);
        if (!cov) sum += now - pre;
        cov += s[j].y;
        pre = now;
    }
    ret += P[i][ii] * P[i][ii + 1] * sum;
}
return ret / 2;
}

int main() {
    for (int i = 0; i < N; i++) {
        P[i].n = 4;
        P[i].input();
        ts = P[i].Area();
        if (cmp(ts < 0)) {
            reverse(P[i].p, P[i].p + P[i].n);
            P[i][P[i].n] = P[i][0];
            ts = -ts;
        }
        S += ts;
    }
    printf("%.9lf\n", S / PolygonUnion());
}

// count(c / a + 1, c % a, a, b) + c / a + 1
long long count(long long n, long long a, long long b, long long m) {
    if (b == 0) { return n * (a / m); }
}

```

```

    if (a >= m) { return n * (a / m) + count(n, a % m, b, m); }
    if (b >= m) { return (n - 1) * n / 2 * (b / m) + count(n, a, b % m, m); }
    return count((a + b * n) / m, (a + b * n) % m, m, b);
}

bool TriSegIntersection(Point3 P0, Point3 P1, Point3 P2, Point3 A, Point3 B, Point3 &P) {
    Vector3 n = Cross(P1 - P0, P2 - P0);
    if (dcmp(Dot(n, B - A)) == 0) return false;
    double t = Dot(n, P0 - A) / Dot(n, B - A);
    if (dcmp(t) < 0 || dcmp(t - 1) > 0) return false;
    P = A + (B - A) * t;
    return PointInTri(P, P0, P1, P2);
}

struct Face {
    int v[3];
    Vector3 normal(Point3 *P) const {
        return Cross(P[v[1]] - P[v[0]], P[v[2]] - P[v[0]]);
    }
    int cansee(Point3 *p, int i) const {
        return Dot(P[i] - P[v[0]], normal(P)) > 0 ? 1 : 0;
    }
};

vector<Face> CH3D(Point3 *P, int n) {
    vector<Face> cur;
    cur.push_back((Face){0, 1, 2});
    cur.push_back((Face){2, 1, 0});
    for (int i = 3; i < n; ++i) {
        vector<Face> next;
        for (int j = 0; j < cur.size(); ++j) {
            Face &f = cur[j];
            int res = f.cansee(P, i);
            if (!res) next.push_back(f);
            for (int k = 0; k < 3; ++k) vis[f.v[k]][f.v[(k + 1) % 3]] = res;
        }
        for (int j = 0; j < cur.size(); ++j)
            for (int k = 0; k < 3; ++k) {
                int a = cur[j].v[k], b = cur[j].v[(k + 1) % 3];
                if (vis[a][b] != vis[b][a] && vis[a][b])
                    next.push_back((Face){a, b, i});
            }
        cur = next;
    }
    return cur;
}

```

4.4 3D Convex

```

const int MAXN = 100;
const double EPS = 1e-8;

struct Point
{
    double x,y,z;
    Point(){}
    Point(double xx,double yy,double zz):x(xx),y(yy),z(zz){}

    Point operator -(const Point p1)
    {

```

```

        return Point(x-p1.x,y-p1.y,z-p1.z);
    }

    Point operator *(Point p)
    {
        return Point(y*p.z-z*p.y,z*p.x-x*p.z,x*p.y-y*p.x);
    }

    double operator ^(Point p)
    {
        return (x*p.x+y*p.y+z*p.z);
    }
};

struct CH3D
{
    struct face
    {
        int a,b,c;
        bool ok;
    };

    int n;
    Point P[MAXN];

    int num;
    face F[8*MAXN];

    int g[MAXN][MAXN];

    double vlen(Point a)
    {
        return sqrt(a.x*a.x+a.y*a.y+a.z*a.z);
    }

    Point cross(const Point &a, const Point &b, const Point &c)
    {
        return Point((b.y-a.y)*(c.z-a.z)-(b.z-a.z)*(c.y-a.y),-((b.x-a.x)*(c.z-a.z)
            -(b.z-a.z)*(c.x-a.x)),(b.x-a.x)*(c.y-a.y)-(b.y-a.y)*(c.x-a.x));
    }

    double area(Point a,Point b,Point c) // *2
    {
        return vlen((b-a)*(c-a));
    }

    double volume(Point a,Point b,Point c,Point d) // *6
    {
        return (b-a)*(c-a)^(d-a);
    }

    double dblcmp(Point &p,face &f)
    {
        Point m=P[f.b]-P[f.a];
        Point n=P[f.c]-P[f.a];
        Point t=p-P[f.a];
        return (m*n)^t;
    }

    void deal(int p,int a,int b)

```

```

{
    int f=g[a][b];
    face add;
    if(F[f].ok)
    {
        if(dblcmp(P[p],F[f])>EPS)
            dfs(p,f);
        else
        {
            add.a=b;
            add.b=a;
            add.c=p;
            add.ok=1;
            g[p][b]=g[a][p]=g[b][a]=num;
            F[num++]=add;
        }
    }
}

void dfs(int p,int now)
{
    F[now].ok=0;
    deal(p,F[now].b,F[now].a);
    deal(p,F[now].c,F[now].b);
    deal(p,F[now].a,F[now].c);
}

bool same(int s,int t)
{
    Point &a=P[F[s].a];
    Point &b=P[F[s].b];
    Point &c=P[F[s].c];
    return fabs(volume(a,b,c,P[F[t].a]))<EPS && fabs(volume(a,b,c,P[F[t].b]))<EPS
        && fabs(volume(a,b,c,P[F[t].c]))<EPS;
}

void solve()
{
    int i,j,tmp;
    face add;
    bool flag=true;
    num=0;
    if(n<4)
        return;
    for(i=1;i<n;i++)
    {
        if(vlen(P[0]-P[i])>EPS)
        {
            swap(P[1],P[i]);
            flag=false;
            break;
        }
    }
    if(flag)
        return;
    flag=true;
    for(i=2;i<n;i++)
    {
        if(vlen((P[0]-P[1])*(P[1]-P[i]))>EPS)

```

```

        {
            swap(P[2],P[i]);
            flag=false;
            break;
        }
    }
    if(flag)
        return;
    flag=true;
    for(i=3;i<n;i++)
    {
        if(fabs((P[0]-P[1])*(P[1]-P[2])^(P[0]-P[i]))>EPS)
        {
            swap(P[3],P[i]);
            flag=false;
            break;
        }
    }
    if(flag)
        return;
    for(i=0;i<4;i++)
    {
        add.a=(i+1)%4;
        add.b=(i+2)%4;
        add.c=(i+3)%4;
        add.ok=true;
        if(dblcmp(P[i],add)>0)
            swap(add.b,add.c);
        g[add.a][add.b]=g[add.b][add.c]=g[add.c][add.a]=num;
        F[num++]=add;
    }
    for(i=4;i<n;i++)
    {
        for(j=0;j<num;j++)
        {
            if(F[j].ok && dblcmp(P[i],F[j])>EPS)
            {
                dfs(i,j);
                break;
            }
        }
    }
    tmp=num;
    for(i=num=0;i<tmp;i++)
        if(F[i].ok)
        {
            F[num++]=F[i];
        }
}

double area()
{
    double res=0.0;
    if(n==3)
    {
        Point p=cross(P[0],P[1],P[2]);
        res=vlen(p)/2.0;
        return res;
    }
}

```

```

        for(int i=0;i<num;i++)
            res+=area(P[F[i].a],P[F[i].b],P[F[i].c]);
        return res/2.0;
    }

double volume()
{
    double res=0.0;
    Point tmp(0,0,0);
    for(int i=0;i<num;i++)
        res+=volume(tmp,P[F[i].a],P[F[i].b],P[F[i].c]);
    return fabs(res/6.0);
}

int triangle()
{
    return num;
}

int polygon()
{
    int i,j,res,flag;
    for(i=res=0;i<num;i++)
    {
        flag=1;
        for(j=0;j<i;j++)
            if(same(i,j))
            {
                flag=0;
                break;
            }
        res+=flag;
    }
    return res;
}

Point getcent()
{
    Point ans(0,0,0),temp=P[F[0].a];
    double v = 0.0,t2;
    for(int i=0;i<num;i++){
        if(F[i].ok == true){
            Point p1=P[F[i].a],p2=P[F[i].b],p3=P[F[i].c];
            t2 = volume(temp,p1,p2,p3)/6.0;
            if(t2>0){
                ans.x += (p1.x+p2.x+p3.x+temp.x)*t2;
                ans.y += (p1.y+p2.y+p3.y+temp.y)*t2;
                ans.z += (p1.z+p2.z+p3.z+temp.z)*t2;
                v += t2;
            }
        }
    }
    ans.x /= (4*v); ans.y /= (4*v); ans.z /= (4*v);
    return ans;
}

double function(Point fuck){
    double min=99999999;
    for(int i=0;i<num;i++){
        if(F[i].ok==true){
            Point p1=P[F[i].a] , p2=P[F[i].b] , p3=P[F[i].c];

```

```

        double a = ( (p2.y-p1.y)*(p3.z-p1.z)-(p2.z-p1.z)*(p3.y-p1.y) );
        double b = ( (p2.z-p1.z)*(p3.x-p1.x)-(p2.x-p1.x)*(p3.z-p1.z) );
        double c = ( (p2.x-p1.x)*(p3.y-p1.y)-(p2.y-p1.y)*(p3.x-p1.x) );
        double d = ( 0-(a*p1.x+b*p1.y+c*p1.z) );
        double temp = fabs(a*fuck.x+b*fuck.y+c*fuck.z+d)/sqrt(a*a+b*b+c*c);
        if(temp<min)min = temp;
    }
}
return min;
}
};

```

5 Math

5.1 EX GCD

```

void gcd(int a, int b, int &d, int &x, int &y) {
    if(!b) {
        d = a;
        x = 1;
        y = 0;
    } else {
        gcd(b, a % b, d, y, x);
        y -= x * (a / b);
    }
}

//ax + by = gcd(a, b)
//when gcd(a, b) = 1, ax = 1 (mod b)

```

5.2 Romberg

```

const int MAX = 18;

double f(double x) {

}

double Romberg (double a, double b) {
#define MAX_N 18

    int i, j, temp2, min;
    double h, R[2][MAX_N], temp4;

    for (i = 0; i < MAX_N; i++) {
        R[0][i] = 0.0;
        R[1][i] = 0.0;
    }
    h = b - a;
    min = (int)(log(h * 10.0) / log(2.0)); //h should be at most 0.1
    R[0][0] = (f(a) + f(b)) * h * 0.50;
    i = 1;
    temp2 = 1;

```



```

while (i < MAX_N) {
    i++;
    R[1][0] = 0.0;
    for (j = 1; j <= temp2; j++)
        R[1][0] += f(a + h * ((double)j - 0.50));
    R[1][0] = (R[0][0] + h * R[1][0]) * 0.50;
    temp4 = 4.0;
    for (j = 1; j < i; j++) {
        R[1][j] = R[1][j - 1] + (R[1][j - 1] - R[0][j - 1]) / (temp4 - 1.0);
        temp4 *= 4.0;
    }
    if ((fabs(R[1][i - 1] - R[0][i - 2]) < eps) && (i > min))
        return R[1][i - 1];
    h *= 0.50;
    temp2 *= 2;
    for (j = 0; j < i; j++)
        R[0][j] = R[1][j];
}
return R[1][MAX_N - 1];
}

```

5.3 Miller Rabin-Pollard rho

```

#include<stdio.h>
#include<string.h>
#include<stdlib.h>
#include<time.h>
#include<iostream>
#include<algorithm>
using namespace std;

//*****
// Miller_Rabin Prime Test
// for number < 2^63
//*****
const int S = 20; //test times

//cal (a*b)%c.
// a,b,c <2^63
long long mult_mod(long long a, long long b, long long c) {
    a %= c;
    b %= c;
    long long ret = 0;
    while(b) {
        if(b & 1) {
            ret += a;
            ret %= c;
        }
        a <<= 1;
        if(a >= c) a %= c;
        b >>= 1;
    }
    return ret;
}

```

```

//cal x^n %c
long long pow_mod(long long x, long long n, long long mod) { //x^n%c
    if(n == 1)return x % mod;
    x %= mod;
    long long tmp = x;
    long long ret = 1;
    while(n) {
        if(n & 1) ret = mult_mod(ret, tmp, mod);
        tmp = mult_mod(tmp, tmp, mod);
        n >>= 1;
    }
    return ret;
}

//true for composite numbers
bool check(long long a, long long n, long long x, long long t) {
    long long ret = pow_mod(a, x, n);
    long long last = ret;
    for(int i = 1; i <= t; i++) {
        ret = mult_mod(ret, ret, n);
        if(ret == 1 && last != 1 && last != n - 1) return true;
        last = ret;
    }
    if(ret != 1) return true;
    return false;
}

bool Miller_Rabin(long long n) {
    if(n < 2)return false;
    if(n == 2)return true;
    if((n & 1) == 0) return false; // even number
    long long x = n - 1;
    long long t = 0;
    while((x & 1) == 0) {
        x >>= 1;
        t++;
    }
    for(int i = 0; i < S; i++) {
        long long a = rand() % (n - 1) + 1;
        if(check(a, n, x, t))
            return false; //composite numbers
    }
    return true;
}

//*****
//pollard_rho prime factor decomposition
//*****
long long factor[100]; //decomposition result

int tol; //prime factor count

long long gcd(long long a, long long b) {
    if(a == 0)return 1;
    if(a < 0) return gcd(-a, b);
    while(b) {
        long long t = a % b;

```

```

        a = b;
        b = t;
    }
    return a;
}

long long Pollard_rho(long long x, long long c) {
    long long i = 1, k = 2;
    long long x0 = rand() % x;
    long long y = x0;
    while(1) {
        i++;
        x0 = (mult_mod(x0, x0, x) + c) % x;
        long long d = gcd(y - x0, x);
        if(d != 1 && d != x) return d;
        if(y == x0) return x;
        if(i == k) {
            y = x0;
            k += k;
        }
    }
}

//decomposition n
void findfac(long long n) {
    if(n == 1) return;
    if(Miller_Rabin(n)) {
        factor[tol++] = n;
        return;
    }
    long long p = n;
    while(p >= n)p = Pollard_rho(p, rand() % (n - 1) + 1);
    findfac(p);
    findfac(n / p);
}

int main() {
    srand(time(NULL));
    long long n;
    while(scanf("%I64d", &n) != EOF) {
        tol = 0;
        findfac(n);
        for(int i = 0; i < tol; i++)printf("%I64d ", factor[i]);
        printf("\n");
        if(Miller_Rabin(n))printf("Yes\n");
        else printf("No\n");
    }
    return 0;
}

```

5.4 FWT XOR

```

inline int ck(int x) {
    if(x < 0) x += mod;
    if(x >= mod) x -= mod;
    return x;
}

```

```

int tmp[1 << 16];

void tf(int a[], int ta[], int n) {
    if(n == 1) {
        ta[0] = a[0];
        return;
    }
    int x = n >> 1;
    tf(a, ta, x);
    tf(a + x, ta + x, x);
    for(int i = 0; i < x; ++ i) {
        tmp[i] = ck(ta[i] - ta[x + i]);
        tmp[x + i] = ck(ta[i] + ta[x + i]);
    }
    for(int i = 0; i < n; ++ i) ta[i] = tmp[i];
}

LL inv2;

void utf(int a[], int ta[], int n) {
    if(n == 1) {
        ta[0] = a[0];
        return;
    }
    int x = n >> 1;
    for(int i = 0; i < x; ++ i) {
        tmp[i] = (a[i] + a[i + x]) * inv2 % mod;
        tmp[i + x] = (a[i + x] - a[i] + mod) * inv2 % mod;
    }
    for(int i = 0; i < n; ++ i) a[i] = tmp[i];
    utf(a, ta, x);
    utf(a + x, ta + x, x);
}

```

5.5 FNT Base 2

```

//1004535809 3
//211812353 3
//10000000025100289 22
//11000000009994241 17
//100000000135659521 3
//mod:prime g:prime root
const int mod = 998244353, g = 3;
int _g[30], _ig[30];
LL invl;

int pow_mod(LL a, int b) {
    LL c = 1;
    while(b) {
        if(b & 1) c = c * a % mod;
        b >>= 1;
        a = a * a % mod;
    }
    return c;
}

```

```

void init() {
    for(int i = 0; i < 30; ++i) {
        _g[i] = pow_mod(g, (mod - 1) / (1 << i));
        _ig[i] = pow_mod(_g[i], mod - 2);
    }
}

void FNT(int F[], int len, int f) {
    int i, j, k, cnt = 1;
    LL x, y, w = 1, wn;
    for(i = 1, j = len >> 1; i < len - 1; ++i) {
        if(i < j) swap(F[i], F[j]);
        k = len >> 1;
        while(j >= k) j ^= k, k >>= 1;
        j |= k;
    }
    for(i = 1; i < len; i <= 1) {
        wn = f ? _g[cnt++] : _ig[cnt++];
        for(j = 0; j < len; j += i << 1, w = 1) {
            for(k = j; k < j + i; ++k, w = w * wn % mod) {
                x = F[k]; y = w * F[k + i] % mod;
                F[k] = x + y;
                F[k + i] = x - y;
                if(F[k] >= mod) F[k] -= mod;
                if(F[k + i] < 0) F[k + i] += mod;
            }
        }
    }
    if(!f) {
        for(i = 0; i < len; ++i) {
            F[i] = F[i] * invl % mod;
        }
    }
}

int a[150000], b[150000];
void conv(int ca[], int l1, int cb[], int l2, int c[], int &l) {
    l = 1; while(l < l1 + l2) l <= 1;
    init(); invl = pow_mod(l, mod - 2);
    for(int i = 0; i < l; ++i) {
        a[i] = i < l1 ? ca[i] : 0;
        b[i] = i < l2 ? cb[i] : 0;
    }
    FNT(a, l, 1); FNT(b, l, 1);
    for(int i = 0; i < l; ++i) a[i] = (LL)a[i] * b[i] % mod;
    FNT(a, l, 0);
    for(int i = 0; i < l; ++i) c[i] = a[i];
}

```

5.6 FNT Base 3

```

const int P = 258280327, G = 5, B = 3;

const int N = 531441;

int pow_mod(ll a, int b) {
    int c = 1;

```

```

while(b) {
    if(b & 1) c = c * a % P;
    b >>= 1;
    a = a * a % P;
}
return c;
}

int w[2][N], rev[N];

void init() {
    ll t = pow_mod(G, (P - 1) / N);
    w[0][0] = w[1][0] = 1;
    for(int i = 1; i < N; ++ i) {
        w[0][i] = w[0][i - 1] * t % P;
    }
    for(int i = 1; i < N; ++ i) {
        w[1][i] = w[0][N - i];
    }
    for(int i = 0; i < N; ++ i) {
        for(int j = 1; j < N; j *= B) {
            (rev[i] *= B) += i / j % B;
        }
    }
}

void ntt(int *a, int n, int o) {
    int tt = N / n, d = N / B;
    for(int i = 0; i < n; ++ i) {
        int j = rev[i] / tt;
        if(i < j) swap(a[i], a[j]);
    }
    for(int i = 1; i < n; i *= B) {
        for(int j = 0, t = N / (i * B); j < n; j += i * B) {
            for(int k = 0, l = 0; k < i; ++ k, l += t) {
                int x = a[j + k], y = a[j + k + i], z = a[j + k + i + i];
                a[j + k] = (x + (ll)y * w[o][l] + (ll)z * w[o][l + l]) % P;
                a[j + k + i] = (x + (ll)y * w[o][l + d] + (ll)z * w[o][(l + l + d + d) % N]) % P;
                a[j + k + i + i] = (x + (ll)y * w[o][l + d + d] + (ll)z * w[o][(l + d + d) * 2 - N]) % P;
            }
        }
    }
    if(o == 1) {
        ll inv = pow_mod(n, P - 2);
        for(int i = 0; i < n; ++ i) {
            a[i] = a[i] * inv % P;
        }
    }
}

int getlen(int n) {
    int r = 1;
    while(r < n) r *= B;
    return r;
}

```

5.7 FNT All

```
const int P = 258280327, G = 5;

struct Number_Theory_Transform {
    #define size 531441
    int N, *W, w[2][size], tmp[size];
    int pow_mod(ll a, int b) {
        int c = 1;
        while(b) {
            if(b & 1) c = c * a % P;
            b >>= 1;
            a = a * a % P;
        }
        return c;
    }
    void prepare(int n) {
        if(N == n) return;
        N = n;
        int x = pow_mod(G, (P - 1) / n);
        int y = pow_mod(x, P - 2);
        w[0][0] = w[1][0] = 1;
        for(int i = 1; i < n; ++i) {
            w[0][i] = (ll)w[0][i - 1] * x % P;
            w[1][i] = (ll)w[1][i - 1] * y % P;
        }
    }
    void work(int *A, int n) {
        if(n == 1) return;
        int i, j, k = 0, l, x, m, u = W[N / n], w = 1;
        for(x = 2; n % x; ++x); m = n / x;
        for(i = 0; i < x; ++i) {
            for(j = i; j < n; j += x) {
                tmp[k++] = A[j];
            }
        }
        for(i = 0; i < n; ++i) A[i] = tmp[i];
        for(i = l = 0; i < x; ++i, l += m) work(A + l, m);
        for(i = j = 0; i < n; ++i) {
            for(l = j + x * m - m, k = x, tmp[i] = 0; k; --k, l -= m) {
                tmp[i] = ((ll)w * tmp[i] + A[l]) % P;
            }
            w = (ll) w * u % P;
            if(++j == m) j = 0;
        }
        for(int i = 0; i < n; ++i) A[i] = tmp[i];
    }
    void DFT(int *A, int n) {
        prepare(n);
        W = w[0];
        work(A, n);
    }
    void IDFT(int *A, int n) {
        prepare(n);
        W = w[1];
        work(A, n);
        for(int i = 0, x = pow_mod(n, P - 2); i < n; ++i) {
            A[i] = (ll)A[i] * x % P;
        }
    }
};
```

```

    }
}
#undef size
} NTT;

```

5.8 FFT Normal

```

const double PI = acos(-1.0);

struct Virt {
    double r, i;

    Virt(double r = 0.0, double i = 0.0) {
        this->r = r;
        this->i = i;
    }

    Virt operator + (const Virt &x) {
        return Virt(r + x.r, i + x.i);
    }

    Virt operator - (const Virt &x) {
        return Virt(r - x.r, i - x.i);
    }

    Virt operator * (const Virt &x) {
        return Virt(r * x.r - i * x.i, i * x.r + r * x.i);
    }
};

void Rader(Virt F[], int len) {
    int i, j, k;
    for(i = 1, j = len / 2; i < len - 1; i++) {
        if(i < j) swap(F[i], F[j]);
        k = len / 2;
        while(j >= k) {
            j -= k;
            k >>= 1;
        }
        if(j < k) j += k;
    }
}

void FFT(Virt F[], int len, int on) {
    Rader(F, len);
    for(int h = 2; h <= len; h <= 1) {
        Virt wn(cos(-on * 2 * PI / h), sin(-on * 2 * PI / h));
        for(int j = 0; j < len; j += h) {
            Virt w(1, 0);
            for(int k = j; k < j + h / 2; k++) {
                Virt u = F[k];
                Virt t = w * F[k + h / 2];
                F[k] = u + t;
                F[k + h / 2] = u - t;
                w = w * wn;
            }
        }
    }
}

```



```

    }
    if(on == -1)
        for(int i = 0; i < len; i++)
            F[i].r /= len;
}

```

5.9 FFT

```

#include <algorithm>
#include <cmath>

using namespace std;

const int mod = 1e9 + 7;

const int max0 = 1 << 17;

struct comp
{
    double x, y;

    comp() : x(0), y(0) {}
    comp(const double &x, const double &y) : x(_x), y(_y) {}
};

inline comp operator+(const comp &a, const comp &b)
{
    return comp(a.x + b.x, a.y + b.y);
}

inline comp operator-(const comp &a, const comp &b)
{
    return comp(a.x - b.x, a.y - b.y);
}

inline comp operator*(const comp &a, const comp &b)
{
    return comp(a.x * b.x - a.y * b.y, a.x * b.y + a.y * b.x);
}

inline comp conj(const comp &a) { return comp(a.x, -a.y); }

const double PI = acos(-1);

int N, L;

comp w[max0 + 5];
int bitrev[max0 + 5];

void fft(comp *a, const int &n)
{
    for (int i = 0; i < n; ++i)
        if (i < bitrev[i])
            swap(a[i], a[bitrev[i]]);
    for (int i = 2, lyc = n >> 1; i <= n; i <= 1, lyc >>= 1)
        for (int j = 0; j < n; j += i)
            {

```

```

        comp *l = a + j, *r = a + j + (i >> 1), *p = w;
        for (int k = 0; k < i >> 1; ++k)
        {
            comp tmp = *r * *p;
            *r = *l - tmp, *l = *l + tmp;
            ++l, ++r, p += lyc;
        }
    }

inline void fft_prepare()
{
    for (int i = 0; i < N; ++i)
        bitrev[i] = bitrev[i >> 1] >> 1 | ((i & 1) << (L - 1));
    for (int i = 0; i < N; ++i)
        w[i] = comp(cos(2 * PI * i / N), sin(2 * PI * i / N));
}

inline vector<int> conv(const vector<int> &x, const vector<int> &y)
{
    static comp a[max0 + 5], b[max0 + 5];
    static comp dfta[max0 + 5], dftb[max0 + 5], dftc[max0 + 5], dftd[max0 + 5];
    L = 0;
    while ((1 << L) < x.size() + y.size() - 1)
        ++L;
    N = 1 << L;
    fft_prepare();
    for (int i = 0; i < N; ++i)
        a[i] = b[i] = comp(0, 0);
    for (int i = 0; i < x.size(); ++i)
        a[i] = comp(x[i] & 32767, x[i] >> 15);
    for (int i = 0; i < y.size(); ++i)
        b[i] = comp(y[i] & 32767, y[i] >> 15);
    fft(a, N), fft(b, N);
    for (int i = 0; i < N; ++i)
    {
        int j = (N - i) & (N - 1);
        static comp da, db, dc, dd;
        da = (a[i] + conj(a[j])) * comp(0.5, 0);
        db = (a[i] - conj(a[j])) * comp(0, -0.5);
        dc = (b[i] + conj(b[j])) * comp(0.5, 0);
        dd = (b[i] - conj(b[j])) * comp(0, -0.5);
        dfta[j] = da * dc;
        dftb[j] = da * dd;
        dftc[j] = db * dc;
        dftd[j] = db * dd;
    }
    for (int i = 0; i < N; ++i)
        a[i] = dfta[i] + dftb[i] * comp(0, 1);
    for (int i = 0; i < N; ++i)
        b[i] = dftc[i] + dftd[i] * comp(0, 1);
    fft(a, N), fft(b, N);
    vector<int> z(x.size() + y.size() - 1);
    for (int i = 0; i < x.size() + y.size() - 1; ++i)
    {
        int da = (long long)(a[i].x / N + 0.5) % mod;
        int db = (long long)(a[i].y / N + 0.5) % mod;
        int dc = (long long)(b[i].x / N + 0.5) % mod;
        int dd = (long long)(b[i].y / N + 0.5) % mod;
    }
}

```

```

        z[i] = (da + ((long long)(db + dc) << 15) + ((long long)dd << 30)) % mod;
    }
    return z;
}

```

6 Others

6.1 Big Number

```

#include<iostream>
#include<string>
#include<iomanip>
#include<algorithm>
using namespace std;

#define MAXN 9999
#define DLEN 4

class BigNum{
private:
    int a[300]; //DLEN digs for a position
    int len;
public:
    BigNum(){len = 1;memset(a,0,sizeof(a));}
    BigNum(const int b);
    BigNum(const BigNum & T);

    bool    Bigger(const BigNum &) const;
    BigNum & operator=(const BigNum &);
    BigNum & Add(const BigNum &);
    BigNum & Sub(const BigNum &);
    BigNum operator+(const BigNum &) const;
    BigNum operator-(const BigNum &) const;
    BigNum operator*(const BigNum &) const;
    BigNum operator/(const int &) const;
    void Print();
};

BigNum::BigNum(const int b)
{
    int c,d = b;

    len = 0;
    memset(a,0,sizeof(a));
    while(d > MAXN){
        c = d - d / (MAXN + 1) * (MAXN + 1);
        d = d / (MAXN + 1);
        a[len++] = c;
    }
    a[len++] = d;
}

BigNum::BigNum(const BigNum & T) : len(T.len)
{
    int i;
    memset(a,0,sizeof(a));
    for(i = 0 ; i < len ; i++)
        a[i] = T.a[i];
}

```

```

}
bool BigNum::Bigger(const BigNum & T) const
{
    int ln;
    if(len > T.len) return true;
    else if(len == T.len){
        ln = len - 1;
        while(a[ln] == T.a[ln] && ln >= 0) ln--;
        if(ln >= 0 && a[ln] > T.a[ln]) return true;
        else return false;
    }
    else return false;
}
BigNum & BigNum::operator=(const BigNum & n)
{
    len = n.len;
    memset(a,0,sizeof(a));
    for(int i = 0 ; i < len ; i++)
        a[i] = n.a[i];
    return *this;
}
BigNum & BigNum::Add(const BigNum & T)
{
    int i,big;

    big = T.len > len ? T.len : len;
    for(i = 0 ; i < big ; i++)
    {
        a[i] = a[i] + T.a[i];
        if(a[i] > MAXN)
        {
            a[i + 1]++;
            a[i] = a[i] - MAXN - 1;
        }
    }
    if(a[big] != 0) len = big + 1;
    else len = big;

    return *this;
}
BigNum & BigNum::Sub(const BigNum & T)
{
    int i,j,big;

    big = T.len > len ? T.len : len;
    for(i = 0 ; i < big ; i++){
        if(a[i] < T.a[i]){
            j = i + 1;
            while(a[j] == 0) j++;
            a[j--]--;
            while(j > i) a[j--] += MAXN;
            a[i] = a[i] + MAXN + 1 - T.a[i];
        }
        else a[i] -= T.a[i];
    }
    len = big;
    while(a[len - 1] == 0 && len > 1) len--;
    return *this;
}

```

```

BigNum BigNum::operator+(const BigNum & n) const
{
    BigNum a = *this;

    a.Add(n);
    return a;
}
BigNum BigNum::operator-(const BigNum & T) const
{
    BigNum b = *this;

    b.Sub(T);
    return b;
}
BigNum BigNum::operator*(const BigNum & T) const
{
    BigNum ret;
    int i,j,up;
    int temp,temp1;

    for(i = 0 ; i < len ; i++){
        up = 0;
        for(j = 0 ; j < T.len ; j++){
            temp = a[i] * T.a[j] + ret.a[i + j] + up;
            if(temp > MAXN){
                temp1 = temp - temp / (MAXN + 1) * (MAXN + 1);
                up = temp / (MAXN + 1);
                ret.a[i + j] = temp1;
            }
            else {
                up = 0;
                ret.a[i + j] = temp;
            }
        }
        if(up != 0)
            ret.a[i + j] = up;
    }
    ret.len = i + j;
    while(ret.a[ret.len - 1] == 0 && ret.len > 1) ret.len--;
    return ret;
}
BigNum BigNum::operator/(const int & b) const
{
    BigNum ret;
    int i,down = 0;

    for(i = len - 1 ; i >= 0 ; i--){
        ret.a[i] = (a[i] + down * (MAXN + 1)) / b;
        down = a[i] + down * (MAXN + 1) - ret.a[i] * b;
    }
    ret.len = len;
    while(ret.a[ret.len - 1] == 0) ret.len--;
    return ret;
}
void BigNum::Print()
{
    int i;

    cout << a[len - 1];

```

```
for(i = len - 2 ; i >= 0 ; i--){
    cout.width(DLEN);
    cout.fill('0');
    cout << a[i];
}
cout << endl;
}
```

6.2 Long Long Mul

```
long long Mul(long long x, long long y) {
    return (x * y - (long long)(x / (long double)P * y + 1e-3) * P + P) % P;
}
```

6.3 Fast IO

```
inline void R(int &x) {
    char c; bool sign = false;
    for (c = getchar(); c<'0' || c>'9'; c = getchar()) if (c=='-') sign = true;
    for (x = 0; c>='0' && c<='9'; c = getchar()) x = x*10+c-'0';
    sign && (x=-x);
}
```
