

The Rössler System

Steven Rosendahl

Introduction

- Created by Otto Rössler in 1976

Introduction

- Created by Otto Rössler in 1976
- System constructed to display simplest possible *Strange Attractor*

Introduction

- Created by Otto Rössler in 1976
- System constructed to display simplest possible *Strange Attractor*

Definition

An **attractor** is a set of values towards which a system moves when initial conditions are *near* the attractor.

Introduction

- Created by Otto Rössler in 1976
- System constructed to display simplest possible *Strange Attractor*

Definition

An **attractor** is a set of values towards which a system moves when initial conditions are *near* the attractor. An attractor is called **strange** if it exhibits fractal behavior.

Introduction

- Created by Otto Rössler in 1976
- System constructed to display simplest possible *Strange Attractor*

Definition

An **attractor** is a set of values towards which a system moves when initial conditions are *near* the attractor. An attractor is called **strange** if it exhibits fractal behavior.

- Strange attractors are often associated with chaotic systems.

System

$$\dot{x} = -y - z$$

$$\dot{y} = x + ay$$

$$\dot{z} = b + z(x - c)$$

System

$$\dot{x} = -y - z$$

$$\dot{y} = x + ay$$

$$\dot{z} = b + z(x - c)$$

- a, b, c are responsible for attractive behavior

System

$$\dot{x} = -y - z$$

$$\dot{y} = x + ay$$

$$\dot{z} = b + z(x - c)$$

- a, b, c are responsible for attractive behavior
- Want to analyze the effect small a and b have on system