


AutoNetKit

A Type-Safe Framework for Network Topology Modelling

Simon Knight, Ph.D.

Principal Architect, AutoNetKit Research

March 2026 • Version 2.3.0



Abstract. AutoNetKit (current package name `ank_pydantic`) is a Python framework for type-safe network topology modelling built on Pydantic v2 and backed by NTE, a Rust graph engine. Its central design principle is that network models should be *statically typed end-to-end*. By enforcing strict typing at the graph level, ANK eliminates configuration drift and prevents common topological errors by construction. This report covers the data model, architecture, multi-layer system, query API, and the "Correctness-by-Construction" philosophy derived from the Whiteboard-to-Plan (W2P) methodology.

Version	Date	Changes
2.3.0	March 2026	Integrated v2.3 Ph.D. Insights & Design Rules.
2.2.0	March 2026	Upgraded to sk-techreport v2.2 standard; Integrated W2P Isomorphism.
0.1.0	Jan 2026	Initial release of the Pydantic-based topology framework.

Contents

List of Design Decisions & Rules	2
1 Introduction	3
1.1 What AutoNetKit Is.	3
1.2 Design Principles	3
1.3 Audience	3
1.4 Document Map	4
2 Background — Network Modelling Concepts	4
2.1 Nodes, Endpoints, and Edges	4
2.2 Layers	5
2.3 Ownership.	5
3 The Category Theory of Intent Synthesis	5
4 Data Model — Generic Pydantic Models	6
4.1 Problem: Type Safety vs. Flexibility	6
4.2 Decision: Generic Data Field	6
4.3 Node Hierarchy.	6
4.4 Edge Hierarchy	7
4.5 Worked Example: Defining a Datacenter Model	8
5 Architecture — Manager-First Façade	8
5.1 Problem: God-Object vs. Scattered API	8
5.2 Decision: Topology as Thin Façade	8
5.3 Data Flow: Adding a Node	9
6 Layer Architecture	10
6.1 Motivation: More Layers > Fewer	10
6.2 Layer Mechanics	10
6.2.1 Cloning Nodes to Derive a Layer.	10
6.2.2 Declarative Layer Building	11
6.3 Layer Handles	11
6.4 Freeze Semantics.	11
6.5 Design Functions.	12
7 Query API	12
7.1 Entry Points	12
7.2 NodeQuery Chaining	13
7.3 Expression Filtering	13
7.4 Pattern Matching	14
7.5 Worked Example: Finding Under-Provisioned Links.	14
8 Design Rules — The Network Linter	15
8.1 Problem: Imperative Checks vs. Declarative Rules	15
8.2 Core Framework	15
8.2.1 Severity.	15
8.2.2 Rule ABC	15
8.2.3 RuleResult and RuleFinding.	15
8.3 Rule Composition	16

8.4	Built-In Rules Catalogue	16
8.5	RuleSet and Execution	17
8.6	AnalysisReport	17
8.7	Worked Example: Writing a Custom Rule	18
9	Configuration Generation	18
9.1	Compiler Pipeline	18
9.2	Supported Platforms	19
9.3	Usage	19
9.4	Design Rules	19
9.5	Environment Generators	19
10	Insights and Evaluation	20
11	End-to-End Tutorial	20
11.1	Step 1: Install	20
11.2	Step 2: Define Models	20
11.3	Step 3: Build Physical Topology	21
11.4	Step 4: Derive Protocol Layers	21
11.5	Step 5: Query	22
11.6	Step 6: Validate	22
11.7	Step 7: Generate Configuration	22
11.8	Step 8: batteries_included Shortcut	22
12	Limitations	23
13	Future Work	23
A	Model Quick Reference	23
B	Built-In Rules Catalogue	24
C	Supported Compiler Platforms	25
D	batteries_included Topologies	25

List of Figures

1	System context: AutoNetKit sits between the user and the NTE Rust engine.	4
2	Running example: 7-router ISP network. Solid lines are primary links; dashed lines are backup paths; dotted lines connect the route server.	5
3	Node class hierarchy. All classes are generic over a data model T.	7
4	Edge class hierarchy with connection rules.	7
5	Container diagram: Topology wires managers over a shared store.	9
6	Multi-layer stack: protocol layers derived from the physical layer. Solid arrows show parent relationships; dashed arrows show derivation.	12
7	Compiler pipeline: topology to device configuration.	19
8	Synthesis Performance Metrics: ANK maintains linear complexity.	20

List of Tables

List of Design Decisions & Rules

1	Design Rule: End-to-End Type Safety	3
2	Design Rule: Algorithmic Complexity	20

1 Introduction

AutoNetKit is a Python framework for building, querying, validating, and compiling network topologies. It sits between the network engineer who thinks in terms of routers and protocols, and the NTE Rust engine that provides high-performance graph storage.

: End-to-End Type Safety

Every graph element (Node, Edge, Endpoint) must be bound to a concrete Pydantic model. This ensures that user-defined attributes are validated at the ingestion point and remain consistent across all synthesis stages.

Insight:
Fidelity in network synthesis requires that the modelling framework be as rigorous as the target vendor's CLI parser.

1.1 What AutoNetKit Is

At its core, AutoNetKit provides:

1. A **typed data model** where every node, edge, and endpoint carries a generic data: `T` field backed by a Pydantic BaseModel.
2. A **manager-first API** where operations like `topology.nodes.add()`, `topology.layers.get()`, and `topology.query.nodes()` are namespaced under domain-specific managers.
3. A **multi-layer architecture** where the same physical network can be viewed through independent protocol lenses (OSPF, BGP, ISIS, etc.).
4. A **fluent query API** inspired by Polars, with expression filtering, pattern matching, and Rust-accelerated execution.
5. A **rule engine** that validates topologies against composable, declarative design rules—the “network linter.”
6. A **configuration generation pipeline** that compiles validated topologies into vendor-specific device configurations.

1.2 Design Principles

Five principles guide every design decision:

Type safety end-to-end. Generic Pydantic models ensure that user data is validated at the boundary and carries type information through to queries, rules, and configuration generation.

More layers are better than fewer. Each protocol gets its own layer rather than overloading a single graph. Layers are cheap—they are just filtered views over the shared store.

Managers own behaviour. The `Topology` class is a thin façade; all domain logic lives in managers that can be tested and extended independently.

Validate before you generate. The rule engine runs before configuration generation, catching design errors (single points of failure, disconnected components, naming violations) before they become operational incidents.

Rust for speed, Python for ergonomics. The NTE engine handles graph storage, traversal, and columnar queries in Rust; AutoNetKit provides the Pythonic API, Pydantic models, and domain logic.

1.3 Audience

This report targets three overlapping audiences:

- **Network engineers** building topology models for design validation and configuration generation.
- **SRE / NetDevOps engineers** integrating AutoNetKit into CI/CD pipelines for automated network testing.
- **Network architects** designing multi-layer topologies and custom design rules for organisational standards.

1.4 Document Map

Companion Document

This report covers the Python framework. For the Rust engine internals (graph storage, columnar queries, PyO3 bindings), see **NTE-TR-001: Network Topology Engine — Technical Reference**.

The package is currently published as `ank_pydantic`. A rename to `autonetkit` is planned before public launch.

Section 2 introduces network modelling concepts. Section 4 details the generic Pydantic data model. Section 5 describes the manager-first architecture. Section 6 covers the layer system. Section 7 presents the query API. Section 8 explains the rule engine. Section 9 outlines configuration generation. Section 11 walks through an end-to-end example. Sections 12 and 13 discuss limitations and future work. Appendices provide quick-reference tables.




Figure 1. System context: AutoNetKit sits between the user and the NTE Rust engine.

2 Background — Network Modelling Concepts

This section provides a domain primer for software engineers who may not have a networking background. Experienced network engineers may skim or skip ahead to Section 4.

2.1 Nodes, Endpoints, and Edges

A network topology is a graph. The vertices represent *devices* (routers, switches, hosts) and the edges represent *connections* between them. In AutoNetKit, we distinguish three kinds of graph element:

Nodes represent devices or logical elements: routers, switches, VLANs, VRFs. They are first-class graph citizens that can be queried, filtered, and traversed.

Endpoints represent connection points on devices: physical interfaces (Ethernet0/0), loopbacks, subinterfaces. An endpoint belongs to exactly one node.

Edges represent relationships between elements. AutoNetKit defines three kinds of edge, each with strict connection rules (Section 4.4).

2.2 Layers

A single physical network supports multiple protocol views. An OSPF process sees only the routers within its area; a BGP session sees only the routers within its autonomous system. AutoNetKit models each view as a separate *layer*—a filtered projection of the topology graph.

Layers are *derived*, not duplicated. When a layer is created, nodes are *cloned* from a parent layer (typically the physical layer), and edges are selectively copied based on filtering rules (e.g., “keep edges where the source and destination share the same ASN” for an OSPF layer). Each derived node maintains a pointer back to its plan-layer counterpart, enabling cross-layer traversal.

2.3 Ownership

Not all relationships are peer connections. A router *owns* its interfaces; a VRF *belongs to* a router. AutoNetKit models these with *ownership edges*, which are structurally distinct from inter-device connections and intra-device relationships.

Running Example: 7-Router ISP Network

Throughout this report we use a small ISP network as a running example: two core routers (Core1, Core2) and four edge routers (Edge1–Edge4), plus a route server (RS1). Cores form a fully-connected backbone; each edge router peers with both cores. This topology is small enough to diagram yet rich enough to illustrate multi-layer derivation, queries, and design rules.




Figure 2. Running example: 7-router ISP network. Solid lines are primary links; dashed lines are backup paths; dotted lines connect the route server.

3 The Category Theory of Intent Synthesis

To achieve true “Correctness-by-Construction”, AutoNetKit formalizes the Whiteboard-to-Plan (W2P) strategy using concepts from Category Theory.

We define the visual architecture as the category of Intent $\mathcal{I}$, and the target schema as the category of Blueprints $\mathcal{B}$. The synthesis engine acts as a strictly structure-preserving functor $F : \mathcal{I} \rightarrow \mathcal{B}$.

Theorem 1 (Morphism Preservation). *For every visual link $f : A \rightarrow B$ in the Whiteboard domain $\mathcal{I}$, there exists a corresponding typed edge $F(f) : F(A) \rightarrow F(B)$ in the Blueprint domain $\mathcal{B}$ such that the topological invariants (e.g., collision domain isolation) are perfectly preserved.*

Proof. The GraphBuilder stage validates all objects in $\mathcal{I}$ against the formal primitives in $\mathcal{B}$. Any object or morphism in $\mathcal{I}$ that cannot be mapped via F (such as an illegal Host-to-Host connection) causes the functor to fail, rejecting the synthesis before any state is mutated. $\square$

4 Data Model – Generic Pydantic Models

The data model is the foundation of AutoNetKit. Every node, edge, and endpoint carries a typed data field that holds user-defined attributes. This section explains the design decisions behind this pattern and walks through the class hierarchy.

4.1 Problem: Type Safety vs. Flexibility

Network modelling tools face a tension. On one hand, different users model different attributes: a datacenter engineer cares about spine/leaf roles and fabric bandwidth; an ISP engineer cares about ASN, OSPF area, and BGP communities. The data model must be *flexible* enough to accommodate any domain.

On the other hand, a stringly-typed dictionary of attributes provides no IDE support, no validation, and no documentation. Typos in field names (bandwith vs. bandwidth) silently corrupt data. The data model must be *type-safe*.

4.2 Decision: Generic Data Field

AutoNetKit resolves this tension with a generic data: `T` field, where `T` is a user-defined Pydantic `BaseModel`:

Listing 1. The generic data pattern.

```
from pydantic import BaseModel
from ank_pydantic.core.models.base import BaseTopologyNode

class RouterData(BaseModel):
    label: str
    vendor: str = "Generic"
    asn: int = 0

class Router(BaseTopologyNode[RouterData]):
    pass

# Full type safety: IDE knows router.data.vendor is str
router = Router(layer="physical", data=RouterData(label="R1", asn=65001))
print(router.data.vendor) # "Generic"
```

Consequences:

- Full IDE autocompletion on `data.*` fields.
- Runtime validation by Pydantic: invalid types raise `ValidationError`.
- Free serialisation (`model_dump()`, `model_dump_json()`).
- System fields (`id`, `layer`) are separated from user data.
- A `FlexibleData` default (with `extra="allow"`) supports untyped prototyping.

4.3 Node Hierarchy

The node hierarchy (Figure 3) provides four concrete base classes:

BaseTopologyNode[T] — First-class graph elements: routers, switches, VLANs. Supports layer traversal (`in_layer()`, `in_plan()`), neighbour queries, and internal namespaces.

BaseTopologyEndpoint[T] — Connection points on devices: interfaces, ports. Connected via `connect_to()` which creates connection links.




Figure 3. Node class hierarchy. All classes are generic over a data model T .

BaseLogicalNode[T] — Internal structures within a device: VRFs, routing instances, line cards. Not first-class graph citizens; accessed via their parent node.

RootlessNode[T] — Derived-layer-only nodes with no plan-layer counterpart: collision domains, broadcast domains. Created by design functions.

All nodes share three system fields managed by the topology:

Field	Type	Description
id	Optional[int]	Assigned by topology on add()
layer	str	Layer this node belongs to
data	T	User-defined data model

4.4 Edge Hierarchy

Edges follow the same generic pattern but enforce strict connection rules:




Figure 4. Edge class hierarchy with connection rules.

BaseIntranodeEdge[E] connects BaseTopologyNode to BaseTopologyNode within the same device (e.g., VLAN membership).

BaseInternodeEdge[E] connects BaseTopologyEndpoint to BaseTopologyEndpoint across devices (e.g., physical links).

BaseOwnershipEdge[E] connects any BaseNode to any BaseNode for containment (e.g., “router owns interface”).

Edge system fields include id, layer, type (a string discriminator), src_id, dst_id, and data: E.

4.5 Worked Example: Defining a Datacenter Model

Datacenter Model Definition

The `batteries_included` module ships a leaf-spine datacenter topology. Here is how the models are defined:

```
from pydantic import BaseModel
from ank_pydantic.core.models.base import BaseTopologyNode, BaseTopologyEndpoint
from ank_pydantic.core.models.edge import BaseInternodeEdge

class SpineRouterData(BaseModel):
    label: str
    role: str = "spine"
    platform: str = "arista_eos"

class SpineRouter(BaseTopologyNode[SpineRouterData]):
    pass

class LeafSwitchData(BaseModel):
    label: str
    role: str = "leaf"
    platform: str = "arista_eos"

class LeafSwitch(BaseTopologyNode[LeafSwitchData]):
    pass

class FabricEndpointData(BaseModel):
    label: str
    speed: str | None = None

class FabricEndpoint(BaseTopologyEndpoint[FabricEndpointData]):
    pass

class FabricLinkData(BaseModel):
    bandwidth: int | None = None

class FabricLink(BaseInternodeEdge[FabricLinkData]):
    type: str = "fabriclink"
```

Each model is fully typed: `SpineRouter.data` is always `SpineRouterData`, never an untyped dictionary.

5 Architecture — Manager-First Façade

5.1 Problem: God-Object vs. Scattered API

A topology object that exposes every operation directly becomes a god-object with hundreds of methods. Conversely, splitting operations across unrelated modules forces users to discover and import many classes. AutoNetKit needs a middle ground.

5.2 Decision: Topology as Thin Façade

The `Topology` class is a thin wiring container. Its `__init__` instantiates approximately eighteen managers, each responsible for a domain of functionality, and wires them together over a shared `TopologyStore`:

Listing 2. Topology manager wiring (simplified).

```
class Topology:
    def __init__(self, layer="whiteboard", *, auto_freeze=True):
        self._store = TopologyStore()
```

```

# Core managers
self.nodes: NodeManager = NodeManager(self._store)
self.edges: EdgeManager = EdgeManager(self._store)
self.links: LinkManager = LinkManager(self._store)
self.layers: LayerManager = LayerManager(self._store)
self.ancestors: AncestorManager = AncestorManager(self._store)
self.sync: SyncManager = SyncManager(self._store)
self.io: IOManager = IOManager(self._store)

# Analysis and design
self.analysis: AnalysisManager = AnalysisManager(self._store)
self.design: DesignManager = DesignManager(self._store)
self.workflow: WorkflowManager = WorkflowManager(self._store)

# Query API
self.query: QueryManager = QueryManager(self)

# Wire inter-manager dependencies
self.layers.set_managers(self.nodes, self.ancestors)
self.nodes.set_managers(self.endpoint_mgr, self.links)
# ... (further wiring omitted)

```

Consequences:

- Users discover functionality through dot-completion: `topology.` → `nodes`, `edges`, `layers`, `query`, etc.
- Each manager can be unit-tested with a mock store.
- New domains (e.g., `LayoutManager`) are added by creating a manager class and wiring it into `Topology.__init__`.
- The shared `TopologyStore` holds the NTE engine handle and the identity map, avoiding global state.

NTE Rust Engine

The `TopologyStore` wraps the NTE Rust engine, which provides the actual graph storage (`petgraph::StableDiGraph`) and columnar property tables (Polars DataFrames). Communication between Python and Rust uses NDJSON serialisation for bulk operations and direct PyO3 calls for single-element access. See NTE-TR-001 for engine internals.




Figure 5. Container diagram: Topology wires managers over a shared store.

5.3 Data Flow: Adding a Node

When the user calls `topology.nodes.add(router)`, the following occurs:

1. **Pydantic validation:** the Router model validates all fields (including data).
2. **NodeManager** serialises the node to NDJSON and calls `store.nte.add_node()`.
3. **NTE engine** inserts a vertex into the petgraph graph and a row into the Polars DataFrame.
4. **ID assignment:** NTE returns the assigned node ID, which is set on the Python model (`router.id = 42`).
5. **Identity map:** the node is registered in the identity map so that future mutations to `router.data.vendor` write through to Rust storage.

6 Layer Architecture

Layers are AutoNetKit’s mechanism for maintaining multiple independent views of the same network. This section covers the motivation, mechanics, and usage patterns.

6.1 Motivation: More Layers > Fewer

A naïve approach stores all protocol information on a single node: a router object carries OSPF area, BGP ASN, ISIS NET, and MPLS label range as top-level fields. This conflates concerns and makes it impossible to answer questions like “which routers participate in OSPF area 0?” without filtering by a magic field.

AutoNetKit’s principle is *more layers are better than fewer*. Each protocol view is a separate layer with its own nodes and edges:

- The **whiteboard** layer is the initial design input.
- The **plan** layer is the formalised device structure.
- The **physical** layer represents the physical topology.
- Protocol layers (**ospf**, **bgp**, **isis**, etc.) are derived from the physical layer using filtering rules.

6.2 Layer Mechanics

Three classes implement the layer system:

LayerManager (`topology.layers`) — the central orchestrator. Manages layer creation, querying, cloning, freezing, and configuration.

LayerHandle — a fluent accessor returned by `topology.layers.get("ospf")`. Provides type-safe querying and configuration for a specific layer.

LayerBuilder — handles declarative layer configuration, validating and building layers from configuration dictionaries.

6.2.1 Cloning Nodes to Derive a Layer

Layer derivation works by *cloning* nodes from a parent layer:

Listing 3. Cloning nodes to a derived layer.

```
# Get source nodes
source_nodes = topology.layers.get("physical").nodes().models()

# Clone to new OSPF layer
result = topology.layers.clone_to_layer(
    nodes=source_nodes,
    target_layer="ospf",
)

# result.source_to_target maps physical IDs to OSPF IDs
# result.target_ids lists all created OSPF node IDs
```

Each cloned node gets a *ParentNode* edge back to its source, and a *PlanOrigin* edge back to the plan layer. This enables cross-layer traversal: given an OSPF router, call `router.in_plan(topology)` to get its plan-layer counterpart, or `router.in_layer("bgp", topology)` to find it in the BGP layer.

6.2.2 Declarative Layer Building

For common patterns, layers can be built declaratively:

Listing 4. Declarative layer configuration.

```
LAYERS = {
    "physical": {
        "parent": "whiteboard",
    },
    "ospf": {
        "parent": "physical",
        "keep_edges_where_same": "asn", # OSPF within same AS
    },
    "ebgp": {
        "parent": "physical",
        "keep_edges_where_different": "asn", # BGP across AS boundaries
    },
    "ibgp": {
        "parent": "physical",
        "copy_edges": False,
        "group_by": "asn",
        "create": "full_mesh", # iBGP full mesh within each AS
    },
}

errors = topology.layers.validate(LAYERS)
if not errors:
    topology.layers.build(LAYERS)
```

The builder resolves dependencies (e.g., ospf depends on physical), validates the configuration, and builds layers in topological order.

6.3 Layer Handles

A *LayerHandle* is a fluent interface for querying and configuring a specific layer:

```
layer = topology.layers.get("physical")

# Query nodes in this layer
routers = layer.nodes(Router).where(asn=65001).models()

# Query links
links = layer.links().collect()

# Set default types for this layer
layer.set_defaults(node=Router, endpoint=Interface, link=PhysicalLink)

# Create simplified device-to-device view
simplified = layer.to_simplified(promote={"bandwidth": "max"})
```

6.4 Freeze Semantics

Layers can be *frozen* to prevent accidental modification:

```
topology.layers.freeze("whiteboard")
assert topology.layers.frozen("whiteboard") == True
# Any mutation to a frozen layer raises an error
```

This is particularly important for the whiteboard and plan layers, which serve as the “source of truth” for derived layers.




Figure 6. Multi-layer stack: protocol layers derived from the physical layer. Solid arrows show parent relationships; dashed arrows show derivation.

6.5 Design Functions

A `DesignFunction` encapsulates reusable layer configurations:

```

from ank_pydantic.core.designs.base import DesignFunction

class SmallInternetDesign(DesignFunction):
    name = "small_internet"
    description = "Small internet topology with BGP and OSPF"
    version = "1.0"

    layers = {
        "physical": {"parent": "whiteboard"},
        "ospf": {
            "parent": "physical",
            "keep_edges_where_same": "asn",
        },
        "ebgp": {
            "parent": "physical",
            "keep_edges_where_different": "asn",
        },
    }

# Apply to any topology
design = SmallInternetDesign()
design.apply(topology)
  
```

7 Query API

AutoNetKit provides a Polars-style fluent query API for exploring and filtering topology data. Queries are lazy builders: filtering methods return new query objects, and terminal methods (`models()`, `ids()`, `count()`) execute against the Rust engine.

7.1 Entry Points

All queries start from `topology.query`:

```

# Node queries
routers = topology.query.nodes().of_type(Router).models()

# Link queries
links = topology.query.links().in_layer("physical").collect()

# Edge queries
  
```



```
edges = topology.query.edges().of_type(FabricLink).dataframe()

# Path queries
path = topology.query.paths().from_node(r1.id).to_node(r2.id).shortest()
```

7.2 NodeQuery Chaining

NodeQuery is generic over the model type, enabling type-safe results:

```
# Type narrowing: NodeQuery[Router] -> List[Router]
cisco_routers = (
    topology.query.nodes()
    .of_type(Router)           # NodeQuery[Router]
    .in_layer("physical")     # Still NodeQuery[Router]
    .where(vendor="Cisco")    # Still NodeQuery[Router]
    .models()                 # List[Router]
)
```

Key filtering methods:

Method	Description
of_type(Model)	Filter by Pydantic model type (includes subtypes)
in_layer(name)	Filter by layer
where(**fields)	Equality filter on data fields (Rust-optimised)
where(predicate)	Python-side predicate filter
filter(*exprs)	Expression-based filtering
to_plan()	Navigate to plan-layer counterparts
to_layer(name)	Navigate to another layer

Terminal methods:

Method	Returns
models()	List[T] — hydrated Pydantic models
ids()	List[int] — node IDs only
count()	int — match count (no materialisation)
first()	Optional[T] — first match or None
one()	T — exactly one match (raises otherwise)
exists()	bool — any match?
dataframe()	pl.DataFrame — Polars DataFrame

7.3 Expression Filtering

The q module provides Polars-style expression building:

Listing 5. Expression filtering with the q module.

```
from ank_pydantic import q

# Field comparisons
high_bw = topology.query.nodes().of_type(Router).filter(
    q.field('bandwidth') > 1000
).models()
```

```

# Logical composition
cisco_fast = topology.query.nodes().of_type(Router).filter(
    (q.field('vendor') == 'Cisco') & (q.field('bandwidth') > 1000)
).models()

# String operations
core_routers = topology.query.nodes().of_type(Router).filter(
    q.field('label').contains('Core')
).models()

# Endpoint subqueries
routers_with_fast_ports = topology.query.nodes().of_type(Router).filter(
    q.endpoints().any(q.field('speed') > 10000)
).models()

```

Expressions support the full set of comparison operators (`==`, `!=`, `>`, `>=`, `<`, `<=`), logical operators (`&`, `|`, `~`), string methods (`contains`, `startswith`, `matches`), and membership tests (`is_in`, `is_null`).

The `Model.fields` accessor provides an alternative syntax:

```

# Using Model.fields (equivalent to q.field())
high_bw = topology.query.nodes().of_type(Router).filter(
    Router.fields.bandwidth > 1000
).models()

```

7.4 Pattern Matching

For graph-structural queries, AutoNetKit supports pattern matching with the `»` operator:

```

from ank_pydantic.core.query.pattern import Pattern, P, HopSpec

# Simple pattern: Router connected to Switch via any link
pattern = Router » Link » Switch

# Named bindings with filter
pattern = P("r", Router) » Link » P("s", Switch)

# Variable-length paths
pattern = P("r", Router) » HopSpec.range(1, 3) » Switch

```

Named bindings allow filtering on pattern elements:

```

# Filter by binding fields
expr = P("r").fields.vendor == P("s").fields.vendor

```

7.5 Worked Example: Finding Under-Provisioned Links

Query: Under-Provisioned Links

Find all physical links where the bandwidth is below 1 Gbps and both endpoints have “core” in their label:

```

from ank_pydantic import q

slow_core_links = (
    topology.query.links()
    .in_layer("physical")
    .filter(
        q.field('bandwidth') < 1000,

```

```

        q.field('src_label').contains('Core'),
        q.field('dst_label').contains('Core'),
    )
    .collect()
)

for link in slow_core_links:
    print(f"Under-provisioned: {link.src_label} <-> {link.dst_label}"
          f" ({link.data.bandwidth} Mbps)")

```

8 Design Rules — The Network Linter

The rule engine is AutoNetKit’s headline feature: a composable, declarative system for validating network designs before configuration generation. It acts as a “linter for network designs,” catching errors that would otherwise become operational incidents.

8.1 Problem: Imperative Checks vs. Declarative Rules

Imperative validation (ad-hoc if/else checks scattered through code) is hard to compose, test, and report on. AutoNetKit needs a structured framework where rules are:

- Independently testable.
- Composable via logical operators.
- Self-documenting (ID, name, description, tags, severity).
- Executable in dependency order.
- Reportable in multiple formats (text, JSON, DataFrame).

8.2 Core Framework

8.2.1 Severity

Three levels of severity:

```

class Severity(str, Enum):
    INFO = "info"
    WARNING = "warning"
    ERROR = "error"

```

8.2.2 Rule ABC

Every rule inherits from Rule and implements check():

Listing 6. The Rule abstract base class.

```

class Rule(ABC):
    id: ClassVar[str]          # e.g., "validation.isolated_nodes"
    name: ClassVar[str]
    description: ClassVar[str]
    tags: ClassVar[Set[str]] = set()
    default_severity: ClassVar[Severity] = Severity.ERROR
    depends_on: ClassVar[List[type["Rule"]]] = []

    @abstractmethod
    def check(self, ctx: AnalysisContext) -> List[RuleResult]:
        """Implement rule logic here."""
        pass

```

8.2.3 RuleResult and RuleFinding

Each rule execution produces a RuleResult with optional granular RuleFinding entries:

```

@dataclass
class RuleResult:
    rule_id: str
    passed: bool
    severity: Severity
    message: str
    affected_nodes: List[int] = field(default_factory=list)
    affected_edges: List[int] = field(default_factory=list)
    findings: List[RuleFinding] = field(default_factory=list)
    tags: Set[str] = field(default_factory=set)

@dataclass
class RuleFinding:
    entity_id: int
    entity_type: Literal["node", "edge", "port"]
    message: str
    severity: Severity = Severity.ERROR
    context: dict[str, Any] = field(default_factory=dict)

```

8.3 Rule Composition

Five composition operators build complex logical rules from simple ones:

Operator	Semantics
<code>AllOf(r1, r2, ...)</code>	Passes only if <i>all</i> children pass. Failure severity is the maximum of child failures.
<code>AnyOf(r1, r2, ...)</code>	Passes if <i>at least one</i> child passes.
<code>Not(rule)</code>	Inverts the child result.
<code>IfThen(cond, conseq)</code>	Evaluates consequence only if condition passes. If condition fails, the overall rule passes (condition not met).
<code>AtLeast(n, r1, r2, ...)</code>	Passes if at least <i>n</i> of the children pass.

Listing 7. Composing rules with logical operators.

```

from ank_pydantic.core.analysis import AllOf, AnyOf, IfThen

# All mandatory checks must pass
mandatory = AllOf(
    IsolatedNodesRule(),
    MinConnectionsRule(Router, min_count=2),
    rule_id="mandatory_checks",
)

# Core routers need extra redundancy (conditional)
core_redundancy = IfThen(
    condition=NodeTypeRule(CoreRouter),
    consequence=DualHomedRule(CoreRouter, min_upstreams=3),
    rule_id="core_router_redundancy",
)

```

8.4 Built-In Rules Catalogue

AutoNetKit ships with rules across five categories:

Category	Rule	Purpose
Validation	IsolatedNodesRule	Find degree-0 nodes
	RequiredFieldRule	Ensure a field is set
	MinConnectionsRule	Minimum connections per node
Anomaly	SinglePointOfFailureRule	Find articulation points
	DisconnectedComponentsRule	Detect network partitions
Pattern	HubAndSpokePattern	Detect star topologies
	FullMeshPattern	Find fully-connected cliques
	HighDegreeNodesRule	Flag potential bottlenecks
Resilience	DualHomedRule	Multi-upstream redundancy
	PathDiversityRule	Edge-disjoint paths
	LinkRedundancyRule	Redundant links
Operational	DisconnectedDevicesRule	Find offline devices
	AsymmetricLinksRule	Directional mismatches
	MissingAttributeRule	Verify attribute presence

Additionally, the blueprints/design_rules module provides 27 protocol-specific rules for OSPF, ISIS, BGP, MPLS, SR, EVPN, L3VPN, BFD, and IXP configurations.

8.5 RuleSet and Execution

A RuleSet collects rules and executes them with dependency resolution:

Listing 8. Running a RuleSet.

```
from ank_pydantic.core.analysis import RuleSet, standard_ruleset

# Pre-built standard ruleset
report = standard_ruleset().run(topology)
print(report.to_text())

# Custom ruleset
ruleset = RuleSet("network_design")
ruleset.add(IsolatedNodesRule())
ruleset.add(MinConnectionsRule(Router, min_count=2))
ruleset.add(DualHomedRule(Router, min_upstreams=2))

report = ruleset.run(topology)
print(f"Pass rate: {report.pass_rate:.0%}")
print(f"Errors: {report.error_count}, Warnings: {report.warning_count}")
```

The standard_ruleset() factory returns a pre-configured set containing IsolatedNodesRule, DisconnectedComponentsRule, SinglePointOfFailureRule, and HighDegreeNodesRule.

8.6 AnalysisReport

The report object provides multiple output formats:

```
# Summary statistics
report.passed          # True if no error-level violations
report.error_count     # Count of ERROR severity failures
report.pass_rate       # Ratio of passed rules (0.0-1.0)

# Filtering
```

```

failed = report.filter_failed()
errors = report.filter_by_severity(Severity.ERROR)

# Export
text = report.to_text(verbose=True)
json_str = report.to_json(indent=2)
df = report.to_dataframe() # Polars DataFrame
by_tag = report.results_by_tag()

```

8.7 Worked Example: Writing a Custom Rule

Custom Rule: Minimum Interfaces per Router

```

from ank_pydantic.core.analysis.base import Rule, RuleResult, Severity

class MinInterfacesRule(Rule):
    id = "custom.min_interfaces"
    name = "Minimum Interfaces"
    description = "Each router must have at least N interfaces"
    tags = {"validation", "connectivity"}
    default_severity = Severity.ERROR

    def __init__(self, min_count: int = 2):
        self.min_count = min_count

    def check(self, ctx):
        results = []
        for router in ctx.nodes_of_type(Router):
            degree = ctx.get_degree(router.id)
            result = RuleResult(
                rule_id=self.id,
                passed=degree >= self.min_count,
                severity=self.default_severity,
                message=(f"{router.data.label} has {degree} interfaces"
                        f" (minimum: {self.min_count})"),
                affected_nodes=[router.id] if degree < self.min_count else [],
            )
            results.append(result)
        return results

# Use it
ruleset = RuleSet("custom")
ruleset.add(MinInterfacesRule(min_count=2))
report = ruleset.run(topology)

```

9 Configuration Generation

AutoNetKit compiles validated topologies into vendor-specific device configurations using a registry-based compiler pipeline.

9.1 Compiler Pipeline

The pipeline has four stages:

1. **Platform lookup:** the registry maps a platform string (e.g., "ios", "eos") to a compiler class.
2. **Data extraction:** the compiler extracts protocol configuration from the topology (OSPF areas, BGP neighbours, interface addresses).
3. **Template rendering:** Jinja2 templates produce vendor-specific CLI configuration.

4. **Output:** configuration files are written to disk, optionally wrapped in deployment environments (Containerlab, Ansible, netsim).




Figure 7. Compiler pipeline: topology to device configuration.

9.2 Supported Platforms

Vendor	Platform ID	Compiler Class
Cisco	ios, iosxr, nxos	IOSCompiler, IOSXRCompiler, NXOSCompiler
Juniper	junos	JunOSCompiler
Arista	eos	EOSCompiler
Nokia	sros, srlinux	SROSCompiler, SRLinuxCompiler
Other	frr, sonic, vyos, cumulus	FRRCompiler, etc.

9.3 Usage

```
from ank_pydantic.blueprints.compilers.registry import get_compiler

# Get compiler for a platform
compiler = get_compiler("ios")

# Compile device configuration
config = compiler.compile(topology, device_id=42)

# Render to CLI text
cli_config = compiler.render_config(config)
print(cli_config)
```

9.4 Design Rules

The blueprints/design_rules module provides 27 protocol-specific rules organised in three tiers:

Tier 1 (Critical) — Empty topology check. Short-circuits on failure.

Tier 2 (Topology) — OSPF area 0 connectivity, iBGP full mesh or route reflector requirement.

Tier 3 (Protocol) — Per-protocol configuration consistency: OSPF router IDs, ISIS NET format, BGP ASN consistency, MPLS label ranges, SR prefix SID uniqueness, EVPN RD/RT, L3VPN VRF, BFD timers, IXP members.

```
from ank_pydantic.blueprints.validation import validate_design

failures = validate_design(topology)
for f in failures:
    print(f.format_summary())
```


9.5 Environment Generators

Output can be wrapped for deployment environments:

Environment	Purpose	Output
Containerlab	Container-based emulation	topology.clab.yml
Ansible	Configuration management	Playbooks + inventory
netdim	Network simulation	topology.yml for netlab

10 Insights and Evaluation

The primary technical challenge in large-scale network synthesis is maintaining computational efficiency as the topology size grows.



Insight:
Linear scaling is achieved by ensuring that graph traversals are bounded by the degree of the nodes, which remains constant in most production designs.

Figure 8. Synthesis Performance Metrics: ANK maintains linear complexity.

: Algorithmic Complexity

All synthesis stages (Lowering, Allocation, Rendering) must maintain a worst-case complexity of $O(n + m)$, where n is the number of nodes and m is the number of edges. This prevents the synthesis engine from becoming a bottleneck in hyper-scale CI/CD pipelines.

11 End-to-End Tutorial

This section walks through a complete workflow using the ISP running example from Section 2.

11.1 Step 1: Install

```
pip install ank_pydantic
```

AutoNetKit requires the NTE Rust engine (ank_nte), which is installed automatically as a dependency.

11.2 Step 2: Define Models

```
from pydantic import BaseModel
from ank_pydantic.core.models.base import (
    BaseTopologyNode, BaseTopologyEndpoint
)
from ank_pydantic.core.models.edge import BaseInternodeEdge

class RouterData(BaseModel):
    label: str
```



```

    role: str = "core"
    asn: int = 65000
    platform: str = "cisco_ios"

class Router(BaseTopologyNode[RouterData]):
    pass

class InterfaceData(BaseModel):
    label: str
    speed: str | None = None

class Interface(BaseTopologyEndpoint[InterfaceData]):
    pass

class LinkData(BaseModel):
    bandwidth: int | None = None

class Link(BaseInternodeEdge[LinkData]):
    type: str = "link"

```

11.3 Step 3: Build Physical Topology

```

from ank_pydantic.core.topology.topology import Topology

topo = Topology()
topo.nodes.register_models([Router, Interface])
topo.edges.register_models([Link])

# Create core routers
core1 = Router(layer="physical", data=RouterData(label="Core1"))
core2 = Router(layer="physical", data=RouterData(label="Core2"))
topo.nodes.add([core1, core2])

# Create edge routers
edges = []
for i in range(1, 5):
    er = Router(
        layer="physical",
        data=RouterData(label=f"Edge{i}", role="edge"),
    )
    topo.nodes.add([er])
    edges.append(er)

# Create interfaces and connect them
for src, dst in [(core1, core2)] + [(e, core1) for e in edges]:
    src_if = topo.endpoint_mgr.add(
        Interface, layer="physical",
        data=InterfaceData(label="Te0/0"),
        parent_id=src.id,
    )
    dst_if = topo.endpoint_mgr.add(
        Interface, layer="physical",
        data=InterfaceData(label="Te0/0"),
        parent_id=dst.id,
    )
    topo.edges.add(Link(data=LinkData(bandwidth=10000), src=src_if, dst=dst_if))

```

11.4 Step 4: Derive Protocol Layers

```

LAYERS = {
    "ospf": {
        "parent": "physical",
    }
}

```

```

        "keep_edges_where_same": "asn",
    },
    "ebgp": {
        "parent": "physical",
        "keep_edges_where_different": "asn",
    },
}
topo.layers.build(LAYERS)

```

11.5 Step 5: Query

```

# How many routers per layer?
for layer_name in topo.layers.names():
    count = topo.query.nodes().in_layer(layer_name).count()
    print(f"{layer_name}: {count} nodes")

# Find core routers
cores = (
    topo.query.nodes()
    .of_type(Router)
    .where(role="core")
    .models()
)
print(f"Core routers: {[r.data.label for r in cores]}")

```

11.6 Step 6: Validate

```

from ank_pydantic.core.analysis import standard_ruleset

report = standard_ruleset().run(topo)
print(report.to_text())

if not report.passed:
    print("Design validation FAILED")
    for result in report.filter_failed():
        print(f" [{result.severity.value}] {result.message}")

```

11.7 Step 7: Generate Configuration

```

from ank_pydantic.blueprints.compilers.registry import get_compiler

for router in topo.query.nodes().of_type(Router).models():
    compiler = get_compiler(router.data.platform)
    config = compiler.compile(topo, router.id)
    cli_text = compiler.render_config(config)
    print(f"--- {router.data.label} ---")
    print(cli_text)

```

11.8 Step 8: batteries_included Shortcut

For quick prototyping, the `batteries_included` module provides pre-built topologies:

```

from ank_pydantic.batteries_included import isp_topology

topo = isp_topology()
print(f"Nodes: {topo.query.nodes().count()}")
print(f"Links: {topo.query.links().count()}")

```

Four topologies are available: `datacenter_topology()` (leaf-spine), `isp_topology()` (core/edge), `campus_topology()` (3-tier), and `wan_topology()` (hub-and-spoke).

12 Limitations

Limitation

NTE compilation requirement — the Rust engine must be compiled for the target platform, which requires a Rust toolchain.

NDJSON serialisation overhead — bulk operations between Python and Rust use NDJSON, which is slower than binary formats.

Mutable ID assignment — node IDs are assigned on `add()` and are mutable integers, not stable UUIDs.

Batch-only layer derivation — layers are derived in bulk; there is no reactive update when the parent layer changes.

Template coverage gaps — not all vendors have complete Jinja2 templates for every protocol combination.

13 Future Work

Reactive layer updates. When a node or edge in a parent layer changes, derived layers should update automatically. This requires an event system (partially implemented via `EventManager`) and incremental re-derivation.

Distributed topology. For very large networks (10,000+ devices), the NTE engine could be deployed as a server with `AutoNetKit` as a client. NTE-TR-001 discusses the distributed architecture.

Plugin maturation. The compiler and environment registries support third-party plugins, but the plugin API is not yet stable or documented.

Additional design patterns. Connection patterns beyond full-mesh, ring, chain, star, and hub-spoke (e.g., partial mesh, dual-homed leaf).

Visualisation. A web-based topology visualiser backed by the NTE engine's layout capabilities.

Rename to `autonetkit`. The package will be renamed from `ank_pydantic` to `autonetkit` before public launch.

A Model Quick Reference

Base Class	Generic	System Fields
<code>BaseNode[T]</code>	<code>T: BaseModel</code>	<code>id</code> , <code>layer</code> , <code>data</code>
<code>BaseTopologyNode[T]</code>	<code>T: BaseModel</code>	Inherits + layer traversal methods
<code>BaseTopologyEndpoint[T]</code>	<code>T: BaseModel</code>	Inherits + <code>connect_to()</code>
<code>BaseLogicalNode[T]</code>	<code>T: BaseModel</code>	Inherits (not first-class)
<code>RootlessNode[T]</code>	<code>T: BaseModel</code>	Inherits + <code>_rootless = True</code>
<code>BaseEdge[E]</code>	<code>E: BaseModel</code>	<code>id</code> , <code>layer</code> , <code>type</code> , <code>src_id</code> , <code>dst_id</code> , <code>data</code>
<code>BaseIntranodeEdge[E]</code>	<code>E: BaseModel</code>	<code>src: Node</code> , <code>dst: Node</code>
<code>BaseInternodeEdge[E]</code>	<code>E: BaseModel</code>	<code>src: Endpoint</code> , <code>dst: Endpoint</code>
<code>BaseOwnershipEdge[E]</code>	<code>E: BaseModel</code>	<code>src: Any Node</code> , <code>dst: Any Node</code>

B Built-In Rules Catalogue

Rule ID	Description	Tags
validation.isolated_nodes	Find degree-0 nodes	validation, connectivity
validation.required_field	Ensure a field is set on all nodes	validation, data_quality
validation.min_connections	Minimum connections per node type	validation, redundancy
anomaly.spof	Single points of failure (articulation points)	anomaly, reliability
anomaly.disconnected	Disconnected graph components	anomaly, connectivity
pattern.hub_spoke	Detect star topologies	pattern, topology
pattern.full_mesh	Detect fully-connected cliques	pattern, topology
pattern.high_degree	Flag high-degree bottleneck nodes	pattern, topology
resilience.dual_homed	Multi-upstream redundancy check	resilience, redundancy
resilience.path_diversity	Edge-disjoint path check	resilience, redundancy
resilience.link_redundancy	Redundant link check	resilience, redundancy
operational.disconnected	Find offline devices	operational, connectivity
operational.high_cost	Flag expensive links	operational, cost
operational.asymmetric	Detect directional mismatches	operational, connectivity
operational.missing_attr	Verify attribute presence	operational, data_quality
naming.convention	Enforce naming patterns (regex)	naming
addressing.unique	No duplicate IP addresses	addressing
addressing.subnet_overlap	No overlapping subnets	addressing
addressing.consistent_asn	BGP ASN consistency	addressing

C Supported Compiler Platforms

Vendor	Platform ID	Template	Notes
Cisco	ios	cisco/ios/device.j2	IOS and IOS-XE
Cisco	iosxr	cisco/iosxr/device.j2	IOS-XR (+ protocol templates)
Cisco	nxos	—	NX-OS
Juniper	junos	juniper/junos/device.j2	Junos (MX, EX, QFX, SRX)
Arista	eos	arista/eos/device.j2	EOS
Nokia	sros	nokia/sros/device.j2	SR OS
Nokia	srlinux	—	SR Linux
FRRouting	frr	—	Open-source routing
SONiC	sonic	—	Open-source NOS
VyOS	vyos	—	Open-source router
Cumulus	cumulus	—	Cumulus Linux

D batteries_included Topologies

Factory	Pattern	Nodes	Description
datacenter_topology()	Leaf-Spine	2 Spines, 4 Leaves	Non-blocking Clos fabric; Arista EOS
isp_topology()	Core/Edge	2 Cores, 4 Edges	Redundant backbone with dual-homed edges; Cisco IOS
campus_topology()	3-Tier	1 Core, 2 Dist, 4 Access	Enterprise campus hierarchy; Cisco IOS
wan_topology()	Hub-Spoke	1 Hub, 4 Branches	Centralised WAN with serial links; Cisco IOS

Each topology exports four model types: node data, node class, endpoint class, and link class. All models follow the generic data: T pattern and can be used as starting points for custom topologies.