

NetVis: A Composable Architecture for Large-Scale Network Visualization


Technical Reference

Simon Knight, Ph.D.

Adelaide, Australia

March 2026 • Version 1.5.0

Last updated: March 11, 2026



Abstract. NetVis is a Rust-based network topology layout and visualization engine comprising 90,000+ lines of code. It transforms complex multi-layer network topologies into publication-quality visualizations using composable layout algorithms, R^* -tree-accelerated label placement, force-directed edge bundling, and adaptive level-of-detail rendering. This document is the definitive technical reference for NetVis. It describes the data model, architecture, eight layout engines, ten edge routing and post-layout refiners, parallel edge rendering (five modes with automatic LAG/bond aggregation), interface rendering, node shape library, edge gradients, path emphasis, metric encoding, rendering pipeline, topology diffing, temporal analysis, traffic animation, annotation markup, interactive editing, visual effects, graph analytics, filter DSL, 16 quality metric families, and public API. Appendices provide the full YAML topology schema, performance baselines with comparative benchmarks against Graphviz, and a complete configuration reference.

Contents

1	Introduction	1
1.1	Design Philosophy	2
1.2	Output Gallery	2
1.3	Audience	3
1.4	How to Read This Document	3
2	NetVis by Example	3
2.1	Basic Campus Network	3
2.2	Layout Algorithm Comparison	4
2.3	Geographic CDN	4
2.4	Isometric Multi-Layer	5
2.5	Parallel Edges and Bond Groups	6
2.6	Subway Layout	7
2.7	Topology Diff and Analysis	7
3	Data Model	8
3.1	Node and Edge Data	8
3.2	Edge Groups	9
3.3	Scene Graph	9
4	Architecture	9
4.1	Pipeline Composition	10
4.2	Scene Graph as Intermediate Representation	10
5	Layout Algorithms	10
5.1	Force-Directed Layout	10
5.2	Hierarchical Layout (Sugiyama)	10
5.3	Geographic Layout	11
5.4	Isometric Multi-Layer Layout	11
5.5	Orthogonal Layout	11
5.6	Subway Layout	11
5.7	Radial Tree, Tree, and Composite	11
6	Theme Gallery	12
6.1	Enterprise Campus Theme Comparison	13
7	Parallel Edge Rendering	14
7.1	Parallel Edge Mode Decision Tree	15
7.2	Automatic Bandwidth Aggregation	15
8	Node Shapes and Device Icons	15
8.1	Available Shapes and Icons	15
9	Interface Rendering	16
10	Edge Gradients and Path Emphasis	17
10.1	Edge Gradients	17
10.2	Path Emphasis	17
11	Metric Encoding	18
12	Label Placement	18
12.1	Problem and Algorithm Choice	18
12.2	Two-Phase Greedy Algorithm	19
12.3	Candidate Scoring Visualization	19
12.4	Performance	19

13	Edge Bundling	19
13.1	FDEB Pipeline	20
14	Edge Routing and Post-Layout Refiners	20
14.1	Edge Clipping: Before and After.	21
14.2	Deoverlap: Before and After.	21
15	Topology Diffing	21
16	Temporal Analysis	22
17	Traffic Flow Animation	22
18	Annotation Markup	22
19	Interactive Editor	22
20	Visual Effects	23
21	Graph Analytics	24
22	Filter DSL	24
23	Input Validation	24
24	Quality Metrics	25
24.1	Metric Families	25
24.2	Clarity Score and CI Integration.	25
25	Rendering Pipeline	26
25.1	SVG Renderer	26
25.2	Level of Detail	26
25.3	Terminal Renderer.	26
25.4	Export Formats	26
26	Pluggable Node Renderer	26
27	API and Usage	26
27.1	Rust API.	26
27.2	WASM / JavaScript	27
28	Deployment	27
29	Performance	27
30	Limitations	29
31	Future Work	29
A	Topology YAML Schema	30
B	Configuration Reference	31
B.1	CLI Flags	31
B.2	CLI Subcommands	33
B.3	JSON Configuration File.	33
LAG	Link Aggregation Group	7
DSL	Domain-Specific Language	24
LOD	Level of Detail	9

1 Introduction

NetVis is a network topology layout and visualization engine. Given a graph of network devices and connections (from a YAML file, NetBox [1] instance, or LLDP discovery), it produces publication-quality SVG diagrams, interactive HTML visualizations, or PNG/PDF exports. It addresses the

gap between general-purpose graph layout tools (Graphviz [2], OGDF [3], D3.js [4]) and manual diagramming applications (yEd [5], Visio).

1.1 Design Philosophy

Two principles guide every design decision in NetVis:

Domain-specialized composition. Network topologies have exploitable structural regularity—hierarchical tiers, geographic site placement, protocol-layer stacking. Rather than using a single general-purpose layout algorithm, NetVis decomposes visualization into a pipeline of composable refiners, each specialized for one aspect of the output.

Quality by default. The system should produce readable, labeled, styled diagrams without manual post-processing. Quality metrics (crossings, overlaps, label readability) are measured as part of the rendering pipeline, not as an afterthought.

1.2 Output Gallery

Figures 1 through 3 show representative outputs across different layout modes and topology scales. Every diagram was generated automatically from YAML with no manual adjustment.




Figure 1. Representative NetVis outputs. All diagrams generated automatically from YAML with no manual adjustment.






Figure 2. Real-world topology examples imported directly from YAML exports.



(a) Edge bundling showcase (FDEB, 200 edges)



(b) Subway layout (octilinear, ring backbone)

Figure 3. Specialized layout modes. Left: FDEB reduces clutter by grouping spatially compatible edges. Right: subway layout constrains all edges to 0/45/90 degree routes for transit-map clarity.

1.3 Audience

This document targets three audiences: engineers embedding NetVis as a library in a network management platform (via Rust, Python, or WASM); contributors to the NetVis codebase; and researchers who want to understand the algorithms in detail. Familiarity with basic graph theory is assumed; familiarity with network engineering concepts (spine-leaf, OSPF, BGP) is helpful but not required.

1.4 How to Read This Document

- **Quick start:** Read §2 (By Example), then §27 (API and Usage).
- **Data model and architecture:** §3–§4.
- **Deep dive into algorithms:** §5–§24.
- **Analysis features:** §15–§19 (diff, timeline, traffic, annotations, editor).
- **Deployment and configuration:** §28 and Appendix B.
- **Known issues:** §30.

2 NetVis by Example

This section walks through representative capabilities using minimal YAML examples. Full schema details appear in Appendix A; CLI options in Appendix B.

2.1 Basic Campus Network

The minimal topology YAML requires only name, nodes, and edges. The rendering section is optional; NetVis selects a suitable layout automatically:

Minimal topology (campus-edge.yaml)

```
name: Campus edge
render:
  theme: light
nodes:
  - { id: inet, label: Internet, node_type: cloud }
  - { id: fw1, label: Firewall, node_type: firewall }
  - { id: r1, label: Edge Router, node_type: router }
  - { id: s1, label: Access Switch, node_type: switch }
edges:
  - { from: inet, to: fw1, label: uplink }
  - { from: fw1, to: r1, label: transit }
  - { from: r1, to: s1, label: 10G }
```

```
netvis -input campus-edge.yaml -o campus.svg
```




Figure 4. The same enterprise campus topology in two themes. The YAML is identical; only theme: changes. See §6 for the full theme gallery.

2.2 Layout Algorithm Comparison

The preset or layout field selects the layout algorithm. Figure 5 shows the same datacenter topology rendered with four different algorithms.





Figure 5. The same 48-node datacenter topology rendered with four layout algorithms. Hierarchical most clearly exposes the two-tier structure; radial is best for hub-centric views; force-directed and spine-leaf are both suitable for ad-hoc exploration.

2.3 Geographic CDN


Nodes with lat/lon attributes use the geographic layout with great-circle arc edges and a background map layer:

Geographic layout (cdn.yaml, excerpt)

```
render:
  preset: geographic
  theme: dark
geographic:
  show_map: true
  great_circle_arcs: true
nodes:
  - { id: nyc, label: New York, node_type: router,
      lat: 40.7128, lon: -74.0060 }
  - { id: lon, label: London, node_type: router,
      lat: 51.5074, lon: -0.1278 }
```



(a) Geographic layout, light theme



(b) Geographic layout, dark theme

Figure 6. Global CDN in geographic layout. Great-circle arc edges and background map layer. The dark theme is preferred for geographic diagrams as map features remain legible.

2.4 Isometric Multi-Layer

The isometric layout renders protocol stacks or layered architectures with a pseudo-3D perspective. Each layer runs an independent force-directed sub-layout:

Isometric layout (multilayer.yaml, excerpt)

```
render:
  layout: isometric
layers:
  - { id: physical, label: Physical, order: 0 }
  - { id: network, label: Network, order: 1 }
  - { id: routing, label: Routing, order: 2 }
nodes:
  - { id: p-core1, label: Core-1, node_type: router,
      attributes: { layer: physical } }
```




Figure 7. Isometric multi-layer: three protocol planes (Physical, Network, Routing) separated along the Z-axis. Layer planes render as filled SVG polygons. The projection angle is $\phi = 18^\circ$ with 350 scene units of layer spacing.

2.5 Parallel Edges and Bond Groups

Multiple physical links between the same pair of nodes are grouped into an EdgeGroup. The `parallel_mode` field selects the rendering mode; bond groups aggregate bandwidth automatically:

Parallel edge modes

```
edges:
  # LAG: 4x 10G auto-aggregated to 40G
  - { from: core1, to: core2, label: "10G",
      bond_group: core-lag, parallel_mode: bundled }
  - { from: core1, to: core2, label: "10G",
      bond_group: core-lag }
  # Redundant uplinks shown as offset lines
  - { from: core1, to: dist1, label: "10G",
      parallel_mode: offset }
  - { from: core1, to: dist1, label: "10G" }
```






Figure 8. Parallel edge rendering modes on a datacenter topology. The diagram demonstrates Bundled (core Link Aggregation Group (LAG)), Offset (redundant uplinks), BondingIcon (bonded access), and Stacked (server NICs) modes. See §7 for details.

2.6 Subway Layout


The subway layout constrains all edges to 0, 45, or 90 degree routes and snaps nodes to a uniform grid. The blueprint theme complements the geometric precision:

Subway layout

```
render:
  layout: subway
  theme: blueprint
```



(a) Subway layout, blueprint theme



(b) Orthogonal layout


Figure 9. Octilinear and orthogonal layouts. Both enforce geometric discipline: subway at 0/45/90 degrees; orthogonal at strict Manhattan-style horizontal and vertical segments.

2.7 Topology Diff and Analysis

NetVis can structurally compare two topologies and produce a visual diff (added in green, removed in red, modified in amber) and compute graph analytics:

Topology diff and analytics

```
# Visual diff between topology versions
netvis diff old.yaml new.yaml -o diff.svg
# Graph analytics overlay
netvis --input topology.yaml --analytics -o analytics.svg
```



(a) Topology diff: green=added, red=removed, amber=modified

(b) Community detection with group boundaries

Figure 10. Analysis features. Left: topology diff visualizes structural changes between two versions. Right: automatic community detection partitions nodes into groups with colored boundary overlays.

3 Data Model

NetVis uses a directed graph as its core data structure, built on the petgraph library [6]. The core type, `NetVisGraph`, is a `StableGraph<NodeData, EdgeData>`; the `StableGraph` variant is used because node and edge indices remain valid after removal—important for the editor’s undo/redo system.

3.1 Node and Edge Data

Field	Type	Purpose
<i>NodeData</i>		
id	String	Unique identifier (e.g., "router-fra-01")
label	Option<String>	Display text
node_type	Option<String>	Device type driving icon and default styling
attributes	HashMap	Arbitrary metadata for metric encoding and filter DSL
position	Option<Point2D>	Layout hint; overrides engine if set
group	Option<GroupId>	Group membership (community detection, composite)
layer	Option<LayerId>	Isometric layer membership
<i>EdgeData</i>		
label	Option<String>	Edge label
edge_type	Option<String>	Semantic type: p2p, trunk, submarine, ...
directed	bool	Default false
bond_group	Option<String>	LAG/bond group identifier
weight	f64	Default 1.0; used as spring constant in force-directed
attributes	HashMap	Arbitrary metadata

Table 1. Core graph data fields.

3.2 Edge Groups

When multiple edges connect the same pair of nodes, NetVis groups them into an EdgeGroup that carries aggregate metadata: the member edge_ids, a count, an automatically computed total_bandwidth (e.g., four edges labeled "10G" produce "40G"), and a parallel_mode (see §7).

Note

The node_type field drives device-specific rendering: icon shape, default color, and default size. The full set of built-in node types is described in §8. Unknown values render as circles.

3.3 Scene Graph

Layout engines consume a NetVisGraph and produce a Scene: a flat list of positioned nodes (with shapes, colors, labels), edges (as Bézier paths), label anchors, group boundaries, and layer planes. Refiners transform the scene between layout and rendering. The scene at 5,000 nodes consumes approximately 9.7 MB of heap.

4 Architecture

NetVis is organized as a six-layer pipeline.




Figure 11. The NetVis six-layer pipeline.

The pipeline stages are:

1. **Adapters.** Stateless converters that ingest topology data from YAML, NetBox [1] REST API, or LLDP/CDP JSON, each implementing fetch/validate/to_graph.
2. **Layout engines.** Pluggable algorithms behind a common Layout trait. A layout takes a NetVisGraph and returns a Scene. Eight engines ship: force-directed (Standard and Enterprise), hierarchical (Sugiyama [7]), radial tree, geographic (Mercator), isometric multi-layer, orthogonal, subway (octilinear), tree, and composite (multi-region).
3. **Refiners.** Post-layout transformations. Current refiners include label placement (R*-tree-accelerated), edge bundling (FDEB), constraint solving, overlap removal, edge nudging, label nudging, edge clipping, smart label snapping, starburst grouping, boundary bundling, port docking, and orthogonal edge routing.
4. **Renderers.** SVG (primary), Canvas2D (browser), and ASCII terminal (netvis show). All support Level of Detail (LOD) suppression and viewport culling.
5. **Export.** SVG is optionally converted to PNG (via resvg), PDF (via svg2pdf), DOT (Graphviz interoperability), or self-contained interactive HTML.
6. **Analysis.** Post-render modules: topology diffing, temporal snapshots, traffic flow animation, SVG annotation markup, and graph analytics.

4.1 Pipeline Composition




Figure 12. Pipeline composition: layout engine produces a Scene, which flows through a chain of refiners before reaching the renderer. Each refiner implements trait `LayoutRefiner` and may add, remove, or reposition scene elements without knowledge of the other refiners.

In YAML, the refiner chain is expressed as:

Pipeline composition in YAML

```
render:
  layout: force_directed
  refiners: [labels, bundling, nudging, constraints]
```

The trait boundary prevents cross-component optimization (e.g., bundling cannot influence label placement during the same pass). This is mitigated by `reposition_edge_labels()`, which re-replaces labels after bundling detects significant curvature changes.

4.2 Scene Graph as Intermediate Representation

The Scene struct carries fully positioned nodes (shapes, colors, labels) and edges (Bézier paths). This separation of concerns means renderers are simple—they draw exactly what the scene contains—at the cost of carrying all rendering data in memory. The scene at 5,000 nodes consumes approximately 9.7 MB of heap.

5 Layout Algorithms

NetVis ships eight layout engines, each implementing the Layout trait. The algorithm is selected via the `layout` or `preset` YAML field, or the `--layout/--preset` CLI flags.

5.1 Force-Directed Layout

Position nodes in 2D such that connected nodes are close and unconnected nodes are separated. NetVis ships two variants and selects between them automatically: the **Standard engine** ($O(n^2)$, wraps the `fjadra` library with Verlet integration [8]) for graphs under 2,000 nodes; the **Enterprise engine** (Barnes-Hut $O(n \log n)$ [9], custom implementation with opening angle $\theta = 0.9$) for larger graphs. On non-WASM targets, force calculation is parallelized via Rayon.

Key parameters: velocity damping $\gamma = 0.6$; alpha decay $1 - 0.001^{1/300}$; iteration count $\min(300, 50 + \lfloor n/10 \rfloor)$; minimum edge length 60 pt (enforced post-simulation).

5.2 Hierarchical Layout (Sugiyama)

For DAG-structured or tiered networks (e.g., spine-leaf datacenters). The four-phase Sugiyama framework [7]: (1) cycle removal by edge reversal; (2) longest-path-first layer assignment; (3) crossing minimization via barycenter or median heuristic; (4) coordinate assignment to minimize edge bends. Performance: 19 ms at 1,000 nodes.




Figure 13. Hierarchical (Sugiyama) layout: a datacenter with clearly separated tiers. The algorithm minimizes edge crossings while preserving the spine → leaf → access hierarchy.

5.3 Geographic Layout

Nodes with lat/lon attributes are projected using an equirectangular projection with dynamic scale normalization $s = 1000 / \max(\Delta x, \Delta y)$. Edges render as geodesic great-circle arcs (Vincenty approximation, 20 segments).

Antimeridian Wrapping

Edges crossing $\pm 180^\circ$ longitude exhibit a projection discontinuity. NetVis detects jumps exceeding 150 projected pixels and renders two copies of the path: one in the primary projection and one shifted by 360° .

5.4 Isometric Multi-Layer Layout

Each layer runs an independent force-directed sub-layout. Results are projected isometrically with rotation angle $\phi = \pi/10$ (18°) and configurable layer spacing (default: 350 scene units). Layer planes render as filled SVG polygons. Edge labels are suppressed when edge length falls below 40 scene units.

5.5 Orthogonal Layout

Assigns node positions to a grid and routes all edges as sequences of horizontal and vertical segments with configurable corner radius. A sweep-line algorithm minimizes total edge length while maintaining minimum channel spacing between parallel routes. Suitable for standards-compliant engineering documentation.

5.6 Subway Layout

Transit-map style: edges constrained to 0, 45, and 90 degrees; nodes snapped to a regular grid. The engine uses force-directed initialization followed by grid snapping, then routes edges along the octilinear grid with at-most-two-bend routing. Node positions are iteratively adjusted to minimize edge crossings while respecting the grid constraint.

5.7 Radial Tree, Tree, and Composite

Radial tree places a root node at the center with children radiating outward in concentric rings; ring radii scale with subtree size to prevent overlap. **Tree layout** is a simpler algorithm for strict hierarchies: places root at top, arranges children in balanced subtree columns, and skips cycle removal. **Composite layout** assigns different layout algorithms to different sub-graphs within a single canvas, using a parent-level layout to position groups relative to each other.






Figure 14. Radial tree layout on a hub-and-spoke WAN topology. The hub node occupies the center; spoke sites radiate outward in a single ring. Ring radius scales with the number of children.

6 Theme Gallery


NetVis ships 7 built-in themes. Each theme defines a complete visual vocabulary: node fill and stroke colors, edge stroke and gradient defaults, label color and font family, background fill, glow and shadow intensity, and group boundary style.



(a) light




(b) dark




(c) network




(d) blueprint



(e) datacenter



(f) print



(g) high-contrast

Figure 15. All 7 built-in themes applied to the same 8-node campus topology. Theme is the only YAML difference between these diagrams. The blueprint theme uses a technical-ink style optimized for geometric layouts; high-contrast meets WCAG AA contrast ratios throughout.

6.1 Enterprise Campus Theme Comparison

Figure 16 shows the enterprise campus topology in four themes to demonstrate how the theme system adapts a complex, real-world topology.




Figure 16. Enterprise campus (72 nodes, 98 edges) in four themes. Each theme adapts node icons, edge colors, label styling, background, glow intensity, and shadow direction. Only the theme: field changes in the YAML.

7 Parallel Edge Rendering

Network topologies frequently contain multiple physical links between the same pair of devices—redundant uplinks, LAG bundles, and NIC-teaming configurations. General-purpose graph tools either render these as overlapping lines (unreadable) or collapse them into a single edge (losing information).

NetVis provides five rendering modes, selectable via `parallel_mode`:

Mode	Behavior
offset (default)	Each link drawn as a visually separate parallel line with perpendicular offset. 4 edges produce offsets of $-6, -2, +2, +6$ pixels.
bundled	All links collapsed into one thick line (width scales with $\sqrt{\text{count}}$) with aggregate multiplicity label (e.g., “4x 10G (40G)”).
bonding_icon	Single line with a bracket or chain-link icon at the midpoint.
stacked	Lines drawn very close together (1–2 px offset), creating a thick-line effect without merging strokes.
angled	Curves with different angles/curvatures; distinguishes many parallel links without excessive width.

Table 2. Parallel edge rendering modes.




Figure 17. Four parallel edge rendering modes (BondingIcon omitted). Each mode trades visual fidelity for compactness. Offset is clearest for redundant-path diagrams; Bundled is most compact for LAG groups.

7.1 Parallel Edge Mode Decision Tree




Figure 18. Parallel edge mode selection logic. Bond groups default to Bundled; non-bonded parallel edges default to Offset. An explicit `parallel_mode` always overrides the default.

7.2 Automatic Bandwidth Aggregation

When edges share a `bond_group` identifier, the system automatically parses per-link bandwidth labels and computes aggregate totals using `parse_bandwidth_gbps()`. In Bundled mode, only the total is shown (e.g., “40G”); in other bonded modes, the detail is shown (e.g., “4x 10G (40G)”).

8 Node Shapes and Device Icons

NetVis supports a rich library of geometric shapes and network device icons for node rendering.

8.1 Available Shapes and Icons

Name	Category	Description
circle	Geometric	Default for generic nodes
rectangle	Geometric	Axis-aligned; useful for hosts and servers
ellipse	Geometric	Horizontal ellipse for cloud/WAN nodes
rounded_rectangle	Geometric	Rectangle with configurable corner radius
diamond	Geometric	Rotated square; used for firewalls
triangle	Geometric	Upward-pointing triangle
hexagon	Geometric	Six-sided; useful for AS/BGP speakers
router	Icon	Cylindrical icon with routing arrows
switch	Icon	Rectangular icon with port stubs
l3_switch	Icon	Switch icon with routing overlay
firewall	Icon	Shield or brick-wall icon
server	Icon	Rack-unit rectangle
cloud	Icon	Cumulus cloud outline
load_balancer	Icon	Funnel or balance icon
database	Icon	Stacked-cylinder icon
endpoint	Icon	Laptop/workstation icon
wireless_ap	Icon	Access-point radio wave icon

Table 3. Built-in node shapes and device icons. Unknown `node_type` values render as circles.




Figure 19. Full device icon library. Each icon shape adapts its size, fill, and stroke to the active theme.

9 Interface Rendering

NetVis treats network interfaces as first-class visual objects. Each node can expose its interfaces with configurable visual modes and status indicators.




Figure 20. Interface rendering modes: Dot (compact), Port (stub with label), and Detailed (full interface card with status). Status colors are Up (active), Down (gray), AdminDown (strikethrough), and Errors (amber).

Interfaces are configured per-node in YAML:

Interface configuration

```
nodes:
- id: core-sw
  node_type: switch
  interfaces:
    - { id: eth0, status: up, mode: port, marker: dot }
    - { id: eth1, status: errors, mode: port, marker: square }
    - { id: mgmt0, status: admin_down, mode: dot, marker: none }
```

The status field accepts up, down, admin_down, or errors. The mode field controls visual detail: dot is compact (small circle on node boundary); port adds a rectangular stub with label; detailed shows the full interface card with speed and operational state. The marker field (none, dot, square, diamond) controls the endpoint symbol on the edge.

10 Edge Gradients and Path Emphasis

10.1 Edge Gradients

Directional stroke gradients encode flow direction or metric values along an edge. A gradient edge transitions smoothly from a *start color* at the source to an *end color* at the target, implemented as SVG `<linearGradient>` elements aligned to the edge direction:

Edge gradient

```
edges:
- from: core1
  to: edge1
  gradient:
    start_color: "#3b82f6" # blue at source
    end_color: "#ef4444" # red at target
```

10.2 Path Emphasis

Path emphasis highlights a named subset of edges as a forwarding path. Two emphasis levels (**Primary** for dominant, **Secondary** for backup) combine with three fanout modes (**Fixed**, **Scaled**, **Hybrid**) that control how emphasis interacts with parallel edge groups.




Figure 21. Path emphasis: primary paths in full-weight highlight; secondary in reduced emphasis. Fanout mode *Scaled* is shown on a LAG bundle where emphasis weight scales with member count.

11 Metric Encoding

NetVis maps arbitrary node attributes to visual channels (color, size, opacity), transforming static topology diagrams into live network dashboards. Six sequential palettes are built in: blues, greens, oranges, reds, purples, greys. All are perceptually uniform and work on both light and dark themes.

Metric encoding

```
render:
  metric_encoding:
    - { attribute: cpu_utilization, channel: fill_color, palette: reds }
    - { attribute: packet_loss, channel: size,
        min_size: 15, max_size: 40 }
    - { attribute: link_utilization, channel: edge_color, palette: oranges }
```




Figure 22. Metric encoding: node fill encodes CPU utilization (reds); node size encodes interface error count; edge stroke encodes link utilization (oranges).

12 Label Placement

12.1 Problem and Algorithm Choice

Placing text labels near their owner without overlapping other labels, nodes, or edges is a variant of the NP-hard point-feature label placement (PFLP) problem [10]. Three approaches were considered: (a) no collision avoidance (Graphviz approach); (b) $O(n^2)$ greedy; (c) R*-tree-accelerated greedy with $O(\log n)$ collision queries.

NetVis uses option (c). The R*-tree [11] build cost (~ 5 ms) is recouped after approximately 20 collision queries, which occurs by ~ 50 labels.

12.2 Two-Phase Greedy Algorithm




Figure 23. Label placement algorithm. Phase 0 places edge labels first (more constrained by midpoint proximity). Phase 1 places node labels around already-occupied regions. The scoring function penalizes both distance from the owner and overlap with existing geometry.

Edge exclusion zones: Curved/bundled edges can produce 47,000+ segment AABBs. Per-segment exclusion zone registration is skipped for non-straight edges; only a single bounding-box exclusion is registered per curved path.

12.3 Candidate Scoring Visualization




Figure 24. Scoring function applied to 8 candidate label positions around node N. Position scores (0–1) are color-coded from green (good) to red (poor). The right position wins (0.92); the lower-left loses because a diagonal edge passes through it (score 0.18).

12.4 Performance

Nodes	Time	Overlaps	Avg. Distance
100	<1 ms	0	8.2 pt
500	12 ms	0	9.1 pt
1000	48 ms	2	10.3 pt
5000	210 ms	18	12.7 pt

Table 4. Label placement performance on spine-leaf topologies (R*-tree acceleration via rstar [12]).

13 Edge Bundling

Dense graphs produce visual clutter from crossing edges. Edge bundling groups spatially compatible edges into bundles, reducing clutter.

13.1 FDEB Pipeline





Figure 25. FDEB bundling pipeline. Compatibility scoring determines which edge pairs attract each other; force simulation pulls compatible edges together; post-processing smooths and decimates the result.

NetVis implements a variant of Holten and Van Wijk’s FDEB [13] with three key modifications: (1) singularity guard $f = k_c/(d + 1.0)$ prevents hairball artifacts; (2) spring coefficient $1.5k$ maintains edge shape; (3) Catmull-Rom tension 0.4 plus 3–5 Laplacian smoothing passes ($\alpha = 0.5$) eliminates high-frequency zigzag artifacts.

Note

Bundling runs *after* label placement. A `reposition_edge_labels()` pass re-replaces labels on edges whose curvature changed significantly post-bundling.



(a) FDEB on a spine-leaf topology

(b) Spine-leaf with shared-endpoint bundling

Figure 26. Edge bundling modes. Left: FDEB groups geometrically compatible edges. Right: shared-endpoint mode bundles edges at the hub, fanning out to spokes.

14 Edge Routing and Post-Layout Refiners

NetVis provides ten post-layout refiners, each implementing the `LayoutRefiner` trait. Refiners are composable and can be chained in any order (see §4 and Figure 12).

Refiner	Category	Description
SmartRouting	Routing	Bends edges around obstacles using R*-tree visibility graph + A* pathfinding; waypoints smoothed to Bézier splines
OrthogonalRouting	Routing	Converts edges to axis-aligned Manhattan paths with configurable corner radius
PortDocking	Routing	Adjusts endpoints to dock at specific interface positions, distributing connections evenly around the perimeter
BoundaryBundling	Routing	Routes edges through a shared crossing point at group boundaries, fanning out inside
Deoverlap	Spacing	Pushes overlapping nodes apart using repulsive spring force; configurable margin (default: 10 units)
EdgeClipping	Spacing	Clips edge endpoints to the exact node shape boundary for correct arrowhead placement
Nudging	Spacing	Nudges overlapping or near-overlapping edges apart; used after parallel edge grouping
SmartLabel	Labels	8-position snapping; second-pass improvement over initial greedy placement
LabelNudging	Labels	Iterative repulsive force between overlapping label bounding boxes; converges in 10–30 iterations
Starburst	Groups	Positions nodes radially within containment groups; best for AS-level diagrams

Table 5. Post-layout refiners.

14.1 Edge Clipping: Before and After




Figure 27. EdgeClippingRefiner: without clipping, edge paths terminate at node centers; with clipping, endpoints dock at the exact node shape boundary, giving correct arrowhead placement regardless of shape.

14.2 Deoverlap: Before and After




Figure 28. DeoverlapRefiner: applies a repulsive spring force between overlapping node bounding boxes, pushing them apart until the configured minimum margin is satisfied.

15 Topology Diffing

The `diff` module computes added, removed, and modified nodes and edges between two `NetVisGraph` instances (by ID and attribute comparison). The `apply_diff_styles()` function color-codes the rendered scene: green for added, red/dimmed for removed, amber for modified. A diff legend is automatically inserted.

CLI topology diff

```
netvis diff old.yaml new.yaml -o diff.svg
```

16 Temporal Analysis

The `timeline` module tracks topology evolution over time. `discover_snapshots()` scans a directory for YAML topology files, extracts timestamps from filenames or metadata, and returns them chronologically. `build_node_history()` and `build_edge_history()` trace an entity's lifecycle: first appearance, all attribute changes, and removal.

Timeline CLI

```
netvis timeline --dir snapshots/  
netvis query --dir snapshots/ --node router-fra-01
```

17 Traffic Flow Animation

The `traffic` module injects animated flow overlays into rendered SVGs via CSS `@keyframes`. Each edge can carry utilization (0.0–1.0), direction (`forward/reverse/bidirectional`), and animation style (`dot/dash`). Utilization maps to color: green (low) → amber → red (congested). Zero-traffic edges receive CSS dimming (`opacity: 0.3`). Play/pause and speed controls are injected as an SVG overlay.

Traffic overlay

```
traffic:  
  edges:  
    - { id: core-to-agg, utilization: 0.75,  
        direction: bidirectional, style: dot }
```

18 Annotation Markup

The `annotation` module injects text callouts into rendered SVGs, with pointer lines from callout to anchor node. Annotations support layer filtering (`show_only_layers`, `hidden_layers`) and three shapes: `circle`, `box`, `arrow`.

Annotation configuration

```
annotations:  
  - anchor: router-fra-01  
    type: callout  
    text: "Primary BGP peer"  
    shape: box  
    layer: notes
```

19 Interactive Editor

The `editor` module provides interactive topology editing for browser deployments via the WASM target. It implements the command pattern: `MoveNodeCommand`, `TransactionCommand`, etc., storing only deltas (24 bytes for a node move) rather than full snapshots. An `UndoStack` with 50-action capacity provides undo/redo, using ~41,000x less memory than snapshot-based undo at 5,000 nodes.

A Lit-based `<netvis-editor>` Web Component wraps the WASM editor:

Web Component

```
<netvis-editor topology="campus.yaml"
  layout-algorithm="force-directed">
</netvis-editor>
```

20 Visual Effects

NetVis provides a pluggable visual effects system mapping semantic effect names to SVG filter definitions. The EffectRegistry deduplicates identical filter definitions via content-addressed hashing. Effects are assigned via the highlight field:

Assigning effects

```
nodes:
- id: core-router
  highlight: true           # default glow
- id: alert-node
  highlight: "emphasis"     # glow-emphasis
- id: combo-node
  highlight: "stack:drop-shadow-subtle+glow-selection"
```

Name	Type	Description
drop-shadow-subtle	Drop shadow	Light offset shadow
drop-shadow-emphasis	Drop shadow	Strong offset shadow
inner-shadow-boundary	Inner shadow	Inset shadow for group boundaries
glow-selection	Glow	Selection highlight
glow-status	Glow	Status indicator
glow-emphasis	Glow	Emphasis marker
stack:<a>+	Composed	Combine any two base effects

Table 6. Built-in visual effects.

All effects adapt to the active theme. Glow intensity and shadow direction vary by theme family.

Effect Budget

SVG filter performance degrades at ~50+ filtered elements. `effects.max_filtered_elements` (default: 50) sets a budget.




Figure 29. Visual effects showcase. Left to right: drop shadow, glow selection, emphasis glow, and composed stack:drop-shadow+glow. All effects adapt their intensity and color to the active theme.

21 Graph Analytics

The analytics module computes structural graph metrics and injects them as a visual “Network Insights” card. Three metrics are computed: **betweenness centrality** (Brandes’ algorithm, $O(nm)$) identifies critical transit nodes; **graph diameter** (longest shortest path) highlights worst-case latency; **clustering coefficient** measures local redundancy.

Analytics CLI

```
netvis --input topology.yaml --analytics -o analytics.svg
```

22 Filter DSL

NetVis includes a Domain-Specific Language (DSL) for filtering topology elements before rendering. The system comprises three layers: a **parser** that converts filter expressions into an AST (supporting boolean operators, attribute selectors, glob patterns, and set operations); an **evaluator** that walks the AST per node/edge; and an optional **LLM layer** (feature-gated) that translates English queries into filter AST nodes.

Filter DSL examples

```
netvis --input t.yaml --filter 'type == "router"'
netvis --input t.yaml \
  --filter 'group == "dc-east" and id ~= "core-*"'
```

23 Input Validation

Topology and configuration files are validated against a JSON Schema (generated from Rust types via schemars). The `validation::fuzzy` module provides “Did you mean...?” suggestions for misspelled YAML field names using Levenshtein distance (`strsim` crate). Structured diagnostics are returned as `ValidationDiagnostic` entries with severity, location, and suggested corrections.

Schema export and validation

```
netvis schema --type topology > topology-schema.json
netvis validate --input topology.yaml
```

24 Quality Metrics

NetVis computes quality metrics as part of every render, following the aesthetic metrics framework of Purchase [14] and Dunne et al. [15].

24.1 Metric Families

Metric	Description
Edge crossings	R*-tree segment intersection, weighted by angle
Overlap area	AABB intersection between all label/node pairs; sub-pixel (<2 px) ignored
Label readability	Composite of owner distance, font-size variance, reading order
Angular resolution	Minimum angle between consecutive incident edges
Node alignment	Degree to which nodes align on axes or grid lines
Edge clearance	Minimum distance from non-incident edges to nodes
Coincident edges	Detection of duplicate or overlapping edge paths
Contrast	Label color contrast against background (WCAG-derived)
Edge-length variance	Coefficient of variation across edge lengths
Spatial distribution	Evenness of node distribution (entropy-based)
Path straightness	Curvature penalty for bent edges
Viewport coverage	Elements outside viewport bounds
Node-edge overlap	Non-incident edge segments crossing node bounding boxes
Density heatmap	Spatial density for identifying visual hotspots

Table 7. 14 of the 16 quality metric families computed per render. All are aggregated into a unified AestheticScore (0–100).

24.2 Clarity Score and CI Integration

The composite *Clarity Score* (0–100) combines four equally-weighted factors: edge crossings, angular resolution, node spacing, and label overlap. It is designed as a single-number summary for CI/CD pipelines. Quality baselines are stored in `benches/regression_baselines.json`; CI fails if any metric degrades by more than 20%.




Figure 30. Quality metrics are computed alongside every render and can be overlaid on the output. Each node’s betweenness centrality, edge utilization, and label overlap are directly visible.

Separate from aesthetic quality, the `lint` module performs structural topology checks: isolated nodes, disconnected subgraphs, duplicate edge IDs, and missing labels. Lint results appear as `Warning-severity` entries in the `DiagnosticsEnvelope`.

25 Rendering Pipeline

25.1 SVG Renderer

The primary renderer produces SVG using the `svg crate`. Elements render in painter's-model order: background map layers → isometric layer planes → group boundaries → edges → nodes → labels → effects.

25.2 Level of Detail

LOD suppresses visual details at configurable thresholds, following Abello et al. [16]:

Profile	Labels	Edge Lbl.	Interfaces	Effects
Conservative	2000	1000	1000	500
Balanced	500	300	300	200
Aggressive	200	100	100	50

Table 8. LOD suppression thresholds.

25.3 Terminal Renderer

`netvis show` renders topology to Unicode box-drawing and ANSI color codes without a graphical display. `light` produces plain ASCII; `dark` produces ANSI-colored output.

25.4 Export Formats

SVG is the canonical output. Additional formats: PNG via `resvg`; PDF via `svg2pdf`; self-contained interactive HTML (WASM embedded as base64, pan/zoom/drag, openable from `file://`); Graphviz DOT for interoperability.

26 Pluggable Node Renderer

The `NodeRenderer` trait defines the interface for custom node renderers. Built-in types (`router`, `switch`, `server`, `firewall`, `cloud`, `l3_switch`, and the full icon library from §8) are registered at startup. Custom renderers are registered with the `NodeRendererRegistry`; unknown `node_type` values fall back to the default circle renderer.

27 API and Usage

27.1 Rust API

Function	Input	Returns
<code>nv::render</code>	Graph, Options	RenderEnvelope
<code>Layout::layout</code>	Graph	Scene
<code>SvgRenderer::render</code>	Scene	SVG string
<code>render_to_png</code>	SVG, PngOptions	PNG bytes
<code>render_to_pdf</code>	SVG, PdfOptions	PDF bytes
<code>export_dot</code>	Scene	DOT string
<code>ExportBuilder::build</code>	Config	Multi-format output

Table 9. Core Rust API entry points.

27.2 WASM / JavaScript

JavaScript integration

```
import { init, renderToSVG, renderWithDiagnostics } from '@netvis/core';
await init();
const { output, diagnostics } = await renderWithDiagnostics(topologyJson);
```

A background Web Worker API (`layoutWorkerRun`) offloads layout computation with progress callbacks streaming intermediate node positions. See Appendix B for the full CLI reference.

28 Deployment

NetVis compiles from a single Rust codebase to three targets:

Target	Build command	Notes
Native CLI	<code>cargo build --release --features cli</code>	Full feature set; parallel layout via Rayon; HTTP adapters
WASM [17]	<code>wasm-pack build --target web</code>	Single-threaded; Canvas + SVG rendering; no file I/O
Python	<code>maturin build --features python</code>	PyO3, ABI3 stability (Python 3.8+)

Table 10. Deployment targets and build commands.

WASM-incompatible crates (`reqwest`, `tokio`, `rayon`) are gated to native-only via feature flags. Deterministic mode (CLI: `--deterministic`; YAML: `render.seed`) ensures reproducible output for CI/CD pipelines.

29 Performance

Measured on Apple M4 Pro, 24 GB RAM, macOS, Rust 1.93.

Operation	100	500	1K	2K	5K
Force-directed layout	20 ms	144 ms	309 ms	816 ms	1.75 s
Hierarchical layout	1.5 ms	8 ms	19 ms	—	—
SVG render	0.8 ms	4.5 ms	11 ms	76 ms	223 ms
Peak heap allocation	215 KB	952 KB	1.9 MB	3.8 MB	9.7 MB

Table 11. Performance baselines by topology size (spine-leaf topologies).

10,000-node spine-leaf (Enterprise engine, auto LOD): 5.3 s end-to-end.

Tool	100 nodes	1K nodes	2K nodes
Graphviz sfdp	84 ms	250 ms	914 ms
Graphviz neato	88 ms	1,024 ms	4,434 ms
NetVis (full pipeline)	24 ms	330 ms	620 ms

Table 12. Comparative benchmark on identical spine-leaf topologies. NetVis times include layout, label placement, styling, and SVG rendering.




Figure 31. NetVis benchmark results on spine-leaf topologies. Left: layout computation time for force-directed (Barnes–Hut) and hierarchical (Sugiyama) engines. Right: SVG rendering time including label placement. Both axes are log-scaled; data points are median wall-clock times.




Figure 32. Comparative performance on identical spine-leaf topologies. NetVis includes the full pipeline (layout, labels, styling, SVG render); Graphviz includes layout and SVG output only.

30 Limitations

Limitation	Description	Workaround / Plan
Scale (>10K nodes)	Enterprise engine handles 10K nodes in ~5 s; 50K+ would benefit from GPU acceleration	Use hierarchical/geographic/tree layout; GPU via WebGPU is under investigation
Greedy label placement	Sequential placement; pathological dense clusters may produce overlaps	Suppress labels via LOD; increase canvas size; simulated-annealing post-pass planned
Single-threaded WASM	Rayon not available in browser; large layouts slower	Use Web Workers for background computation; WASM threads pending
Non-determinism	HashMap iteration order is non-deterministic by default	Use <code>--deterministic</code> or <code>render.seed</code>
Adapter coverage	Only YAML, NetBox, LLDP/CDP built in	Adapter trait is public; community adapters encouraged
No user study	Quality claims based on automated metrics only	Controlled user study planned

Table 13. Known limitations and workarounds.

31 Future Work

1. **GPU-accelerated layout.** WebGPU compute shaders for 50,000+ node topologies.
2. **Streaming topology ingestion.** Live gNMI/gRPC streaming extending the timeline module (§16) to real-time updates.
3. **Simulated-annealing label post-pass.** Global optimization resolving remaining overlaps in dense clusters.
4. **User study.** Controlled perceptual evaluation with network engineers.
5. **Collaborative editing.** CRDT-based multi-user conflict resolution extending the editor module (§19).
6. **SNMP and streaming telemetry adapters.** Community adapters for SNMP, Napalm, and gNMI.
7. **Parallel edge animation.** Per-link traffic flow animation within a LAG bundle.

References

- [1] NetBox Labs, *NetBox: The leading solution for network automation*, 2024. [Online]. Available: <https://netbox.dev>
- [2] E. R. Gansner and S. C. North, “An open graph visualization system and its applications to software engineering,” 11, vol. 30, 2000, pp. 1203–1233.
- [3] M. Chimani, C. Gutwenger, M. Jünger, G. W. Klau, K. Klein, and P. Mutzel, “The open graph drawing framework (OGDF),” *Handbook of Graph Drawing and Visualization*, pp. 543–569, 2013.
- [4] M. Bostock, V. Ogievetsky, and J. Heer, “D3: Data-driven documents,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 17, no. 12, pp. 2301–2309, 2011.
- [5] yWorks GmbH, *yEd graph editor*, 2024. [Online]. Available: <https://www.yworks.com/products/yed>
- [6] bluss, *Petgraph – graph data structure library for Rust*, 2024. [Online]. Available: <https://crates.io/crates/petgraph>
- [7] K. Sugiyama, S. Tagawa, and M. Toda, “Methods for visual understanding of hierarchical system structures,” *IEEE Transactions on Systems, Man, and Cybernetics*, vol. 11, no. 2, pp. 109–125, 1981.
- [8] L. Verlet, “Computer “experiments” on classical fluids. I. thermodynamical properties of Lennard-Jones molecules,” *Physical Review*, vol. 159, pp. 98–103, 1967.

- [9] J. Barnes and P. Hut, “A hierarchical $O(N \log N)$ force-calculation algorithm,” *Nature*, vol. 324, pp. 446–449, 1986.
- [10] J. Christensen, J. Marks, and S. Shieber, “An empirical study of algorithms for point-feature label placement,” in *ACM Transactions on Graphics*, vol. 14, 1995, pp. 203–232.
- [11] N. Beckmann, H.-P. Kriegel, R. Schneider, and B. Seeger, “The R*-tree: An efficient and robust access method for points and rectangles,” *ACM SIGMOD Record*, vol. 19, no. 2, pp. 322–331, 1990.
- [12] Stoeoef, *Rstar – R*-tree spatial index for Rust*, 2024. [Online]. Available: <https://crates.io/crates/rstar>
- [13] D. Holten and J. J. van Wijk, “Force-directed edge bundling for graph visualization,” *Computer Graphics Forum*, vol. 28, no. 3, pp. 983–990, 2009.
- [14] H. C. Purchase, “Metrics for graph drawing aesthetics,” *Journal of Visual Languages and Computing*, vol. 13, no. 5, pp. 501–516, 2002.
- [15] C. Dunne and B. Shneiderman, “Motif simplification: Improving network visualization readability with fan, connector, and clique glyphs,” *Proc. ACM CHI*, pp. 3247–3256, 2015.
- [16] J. Abello, F. van Ham, and N. Krishnan, “ASK-GraphView: A large scale graph visualization system,” in *IEEE Transactions on Visualization and Computer Graphics*, vol. 12, 2006, pp. 669–676.
- [17] A. Haas et al., “Bringing the web up to speed with WebAssembly,” in *Proc. ACM SIGPLAN Conference on Programming Language Design and Implementation (PLDI)*, 2017, pp. 185–200.

A Topology YAML Schema

Listing 1. Full YAML topology schema

```

name: string           # Required: topology name
render:               # Optional: rendering hints
  preset: string       # Layout preset (default/sugiyama/radial/geo/subway)
  layout: string       # Layout algorithm (force_directed/hierarchical/
                        # radial/geographic/isometric/orthogonal/subway/tree)
  theme: string        # Theme (network/dark/light/blueprint/datacenter/print/high-contrast)
  width: number        # Canvas width in pixels
  height: number       # Canvas height in pixels
  lod: string          # LOD profile (none/conservative/balanced/aggressive/auto)
  seed: number         # RNG seed for deterministic layout
  refiners: [string]   # Refiner chain override
  metric_encoding:     # Data-driven visual encoding
    - attribute: string # Node attribute name
      channel: string   # fill_color/size/opacity/edge_color
      palette: string   # blues/greens/oranges/reds/purples/greys
      min: number
      max: number
nodes:                # Required: list of nodes
  - id: string         # Unique node identifier
    label: string      # Display label (defaults to id)
    node_type: string  # Device type (router/switch/server/firewall/cloud/
                        # l3_switch/load_balancer/database/endpoint/wireless_ap)
    attributes: map    # Arbitrary key-value metadata
    position: { x, y } # Position hint (optional)
    group: string      # Group membership
    layer: string       # Layer membership (isometric)
    highlight: string  # Effect name or true for default glow
    lat: number        # Geographic latitude (geographic layout)
    lon: number        # Geographic longitude (geographic layout)
    interfaces:        # Interface list
      - id: string
        label: string
        status: string # up/down/admin_down/errors
        mode: string   # dot/port/detailed
        marker: string # none/dot/square/diamond
    constraints:       # Layout constraints
      pin: { x, y }    # Absolute position
      align_with: string # node ID (same Y)
      below: string    # node ID
      min_separation: number

```



```

edges:                                # Required: list of edges
- from: string                        # Source node ID
  to: string                          # Target node ID
  id: string                          # Explicit edge ID
  label: string                       # Edge label
  weight: number                      # Edge weight (default: 1.0)
  directed: boolean                  # Default: false
  bond_group: string                 # Bond/LAG group ID
  parallel_mode: string              # offset/bundled/bonding_icon/stacked/angled
  gradient:
    start_color: string              # hex color at source
    end_color: string                # hex color at target
  attributes: map
groups:                               # Optional: group definitions
- { id: string, label: string, style: map }
layers:                              # Optional: isometric layer definitions
- { id: string, label: string, order: number }
paths:                               # Optional: path emphasis definitions
- id: string
  label: string
  emphasis: string                   # primary/secondary
  fanout_mode: string                # fixed/scaled/hybrid
  nodes: [string]
traffic:                             # Optional: traffic flow animation
edges:
- id: string
  utilization: number                # 0.0--1.0
  direction: string                  # forward/reverse/bidirectional
  style: string                      # dot/dash
annotations:                         # Optional: SVG annotation markup
- anchor: string
  type: string                       # text/callout
  text: string
  shape: string                      # circle/box/arrow
  layer: string

```

B Configuration Reference

B.1 CLI Flags

B.1.1 Input and Output

Flag	Type	Default	Description
--input, -i	path	(required)	Topology file; globs and - for stdin
--output, -o	path	auto	Output file path
--config	path	—	JSON config file
--format	string	svg	Output format: svg, png, pdf, html, dot
--dpi	integer	96	DPI for PNG export

B.1.2 Layout

Flag	Default	Description
--layout	auto	Algorithm: force-directed, hierarchical, radial, isometric, geographic, orthogonal, subway, tree
--preset	—	Layout preset: default, wan, datacenter, sugiyama, geographic, subway, ...
--template	—	Topology template: spine-leaf, hub-spoke, ring, multi-tier
--seed	42	RNG seed for deterministic layout

B.1.3 Appearance

Flag	Default	Description
--theme	network	Theme (7 built-in): light, dark, network, blueprint, datacenter, print, high-contrast
--labels	label	Label mode: off, label, id
--node-size	auto	Node radius in scene units
--lod	auto	LOD profile: none, conservative, balanced, aggressive, auto

B.1.4 Canvas and Viewport

Flag	Default	Description
--width	1200	SVG viewport width (px)
--height	800	SVG viewport height (px)
--padding	40	ViewBox padding (px)
--padding-ratio	0.06	Padding as fraction of scene

B.1.5 Force-Directed Tuning

Flag	Default	Description
--link-distance	30.0	Target link length (scene units)
--link-strength	auto	Edge spring strength (0.0–1.0)
--charge-strength	−30.0	Many-body charge (negative = repel)
--max-iterations	300	Maximum simulation iterations
--soft-anchor-strength	0.0	Anchor strength for hinted nodes
--refine	false	Apply post-layout edge refinement

B.1.6 Geographic Layout

Flag	Default	Description
--show-map	false	Show background coastline map
--great-circle-arcs	false	Render edges as curved arcs
--show-distances	false	Show geodesic distance labels
--distance-unit	km	Distance unit: km or mi

B.1.7 Filtering

Flag	Description
--show-type	Only render nodes of these types (comma-separated)
--hide-type	Hide nodes of these types
--show-tag	Only render nodes with these tags
--hide-tag	Hide nodes with any of these tags
--show-group	Only render nodes in these groups
--hide-group	Hide nodes in these groups
--filter-file	Load filter rules from YAML file
--path	BFS path query between two node IDs
--highlight-path	Highlight a named path (repeatable)

B.1.8 Analysis Features

Flag	Description
--diff <path>	Compare against a base topology and visualize changes
--traffic <path>	Traffic overlay configuration YAML
--annotations <path>	Annotation markup YAML
--hide-layers	Suppress named annotation layers
--show-layers	Force-show named annotation layers
--cluster	Enable automatic community detection
--algorithm	Clustering algorithm: louvain, label-propagation, edge-betweenness
--metric <field>	Map a node attribute to color
--palette <name>	Color palette: blues, greens, oranges, reds, purples, greys
--analytics	Compute and display graph analytics

B.1.9 Quality and Diagnostics

Flag	Default	Description
--quality-threshold	85.0	Quality score warning threshold
--fail-on-low-quality	false	Exit with error if below threshold
--deterministic	true	Deterministic output mode
--diagnostics	—	Structured diagnostics: json, yaml, ndjson
--verbose, -v	false	Show debug statistics

B.2 CLI Subcommands

Command	Description
list-examples	List built-in topology examples
print-example <name>	Print a built-in topology to stdout
list-templates	List layout templates
list-adapters	List data source adapters
import	Import topology from adapter into YAML
schema	Print JSON Schema (config, topology, or diagnostics)
print-config <name>	Print an example config to stdout
validate	Validate topology/config against schema
migrate	Normalize files to current schema version
check-quality	Analyze SVG files for quality issues
diff	Compare two topologies, visualize changes
show	Render topology to ASCII art in the terminal

B.3 JSON Configuration File

NetVisConfig JSON

```
{
  "schema_version": "1.0",
  "layout": "force_directed",
  "quality": "balanced",
  "width": 1200.0,
  "height": 800.0,
  "effects": { "max_filtered_elements": 50 }
}
```

Key	Type	Default	Description
layout	string	force_directed	Layout algorithm
quality	string	balanced	Preset: quick (0.33x), balanced (1.0x), quality (3.0x)
width	float	800.0	Viewport width
height	float	600.0	Viewport height
effects.max_filtered_elements	int	50	SVG filter budget

Table 14. JSON configuration keys.

Index

- adapters, 9
- AestheticScore, 25
- annotation, 22
- API, 26
- architecture, 9

- Barnes-Hut, 10
- benchmarks, 27
- betweenness centrality, 24
- bond group, 14

- callout, 22
- CLI, 26
- CLI flags, 31
- collision avoidance, 18
- color palettes, 18
- configuration, 31
- crossings, 25

- data model, 8
- deployment, 27
- device icons, 15
- diff, 21
- drop shadow, 23

- edge, 8
- edge bundling, 19
- edge gradients, 17
- editor, 22

- FDEB, 19
- filter DSL, 24
- flow direction, 17
- force-directed edge bundling, 19
- fuzzy matching, 24

- glow, 23
- graph analytics, 24

- HTML export, 26

- interface status, 16
- interfaces, 16

- label placement, 18
- LAG, 14
- layout
 - composite, 10
 - force-directed, 10
 - geographic, 10
 - hierarchical, 10
 - isometric, 10
 - orthogonal, 10, 11
 - radial, 10
 - subway, 10, 11
 - tree, 10
- link aggregation, 14

- metric encoding, 18

- node, 8
- node renderer, 26
- node shapes, 15
- node_type, 15
- nudging, 20

- octilinear, 11
- overlap, 25

- parallel edges, 14
- path emphasis, 17
- performance, 27
- pipeline, 9
- ports, 16

- quality metrics, 25

- R*-tree, 18
- refiners, 20
- renderer, 9
- rendering pipeline, 26
- routing
 - orthogonal, 20
 - port-aware, 20
 - smart, 20

- scene graph, 8
- snapshot, 22
- Sugiyama, 10
- SVG, 26

- temporal analysis, 22
- themes, 12
- timeline, 22
- topology diffing, 21
- topology graph, 8
- traffic animation, 22

- undo/redo, 22
- utilization, 22

- validation, 24
- visual effects, 23

- WASM, 22
- WASM API, 26
- WebAssembly, 27