


TopoGen: A Seed-Deterministic Network Topology Generator

Datacenter Fabrics, WANs, and Random Graph Models with Geographic Placement

Simon Knight

March 2026 • Version 0.1.0

Last updated: March 11, 2026



Abstract. TopoGen is a Rust library and CLI for generating realistic network topologies spanning datacenter fabrics (Fat-Tree, Leaf-Spine), wide-area networks (Ring, Mesh, Hierarchical WAN, POP), and random graph models (Barabási–Albert, Watts–Strogatz, Erdős–Rényi). All generation is seed-deterministic via ChaCha8Rng, producing reproducible topologies with realistic interface specifications, vendor-specific naming (Cisco, Arista, Juniper), geographic city placement with distance-aware latency, and gravity-model traffic matrices. Python bindings via PyO3 expose the full API as an installable package.

Contents

List of Design Decisions & Rules	2
1 Introduction and Motivation	3
2 System Architecture	3
3 Datacenter Generators	3
3.1 Fat-Tree	3
3.2 Leaf-Spine	3
4 WAN Generators	4
4.1 Geographic Placement	4
4.2 Hierarchical WAN	4
4.3 POP Generator	4
5 Random Graph Models	4
5.1 Traffic Matrix Generation	4
6 Export Formats	4
7 Design Summary	5
 IXP	 Internet Exchange Point
RNG	Random Number Generator
	4
	4

List of Design Decisions & Rules

1	Design Rule: Seed-Deterministic Generation	3
1	Vendor-Specific Interface Naming	4
2	Containerlab Integration	4

1 Introduction and Motivation

Network simulation and emulation tools require realistic topologies as input. Existing generators either produce unrealistic random graphs or require manual specification of every node and link. TopoGen bridges this gap by providing parameterised generators for common network architectures, each producing topologies with realistic interface naming, geographic placement, and latency characteristics.

: Seed-Deterministic Generation

Every generator accepts an explicit seed. All randomness flows through ChaCha8Rng seeded from this value, ensuring bit-identical output across platforms and Rust versions.

2 System Architecture

TopoGen is structured as a Rust library crate with a CLI binary and Python bindings:

Table 1. Module organisation.

Module	Language	Role
topogen (lib)	Rust	Core generators, topology model, export
topogen (bin)	Rust	CLI (generate, validate, export)
topogen-py	PyO3	Python package wrapping all generators

The core topology model stores nodes and edges with typed attributes:

```
pub struct Topology {
    name: String,
    nodes: Vec<Node>,
    edges: Vec<Edge>,
    metadata: TopologyMetadata,
}

pub struct Node {
    pub name: String,
    pub role: NodeRole,           // Core, Spine, Leaf, Access, etc.
    pub vendor: Vendor,          // Cisco, Arista, Juniper
    pub location: Option<GeoLocation>,
    pub interfaces: Vec<Interface>,
}
```

3 Datacenter Generators

3.1 Fat-Tree

The Fat-Tree generator [1] produces a k -ary topology with three tiers: $k^2/4$ core switches, k pods each containing $k/2$ aggregation and $k/2$ edge switches.

```
pub fn generate_fat_tree(k: usize, seed: u64, vendor: Vendor) -> Topology {
    let mut rng = ChaCha8Rng::seed_from_u64(seed);
    let cores = k * k / 4;
    let pods = k;
    let agg_per_pod = k / 2;
    let edge_per_pod = k / 2;
    // ...
}
```

For $k = 4$, this produces 20 nodes and 32 edges with a network diameter of 4. Interface names follow vendor conventions (e.g. GigabitEthernet0/0 for Cisco, Ethernet1 for Arista).

3.2 Leaf-Spine

The Leaf-Spine generator creates a two-tier fabric with configurable spine and leaf counts. Every leaf connects to every spine, producing $S \times L$ links for S spines and L leaves.

Design Decision 1: Vendor-Specific Interface Naming

Interface names are generated by a `VendorNamer` trait with implementations for Cisco (GigabitEthernet, TenGigE), Arista (Ethernet), and Juniper (et-/xe-/ge-). Port numbering is deterministic from the Random Number Generator (RNG) state, producing realistic but reproducible configurations.

4 WAN Generators

4.1 Geographic Placement

WAN generators place nodes at real-world city locations. Cities are organised by region (NA, EU, AP, etc.) and tier (1 = major hubs, 2 = secondary, 3 = regional). The generator selects cities from the requested region and tier, then computes inter-node latency from great-circle distance:

$$\text{latency}(\mu\text{s}) = \frac{d_{\text{km}} \times 1000}{c_{\text{fibre}}} \quad \text{where} \quad c_{\text{fibre}} \approx 200,000 \text{ km/s} \quad (1)$$

4.2 Hierarchical WAN

The hierarchical generator produces a three-tier access/distribution/core topology with multi-region support and configurable redundancy levels (standard, high). Each region gets a proportional allocation of nodes based on a gravity model.

4.3 POP Generator

The POP generator models ISP-style backbones with internal POP structure. Each POP contains border routers, route reflectors, and access routers. Optional Internet Exchange Point (IXP) peering nodes create inter-POP connectivity.

Insight:
The POP generator's internal structure (border/reflector/access) produces topologies with realistic traffic patterns for BGP simulation, unlike flat mesh generators that treat all nodes equally.

5 Random Graph Models

Three classic random graph models are available:

Table 2. Random graph model parameters.

Model	Parameters	Property
Barabási–Albert [2]	n, m	Scale-free degree distribution
Watts–Strogatz [3]	n, k, β	Small-world clustering
Erdős–Rényi	n, p	Uniform random edges

5.1 Traffic Matrix Generation

TopoGen can generate gravity-model traffic matrices for any topology. The traffic demand between nodes i and j is proportional to the product of their “mass” (degree or configured weight):

$$T_{ij} = \alpha \cdot \frac{m_i \cdot m_j}{d_{ij}^\gamma} \quad (2)$$

where d_{ij} is the shortest-path distance, γ controls distance decay, and α is a normalisation constant.

6 Export Formats

Topologies can be exported to YAML, JSON, and Containerlab (.clab.yaml) formats. The Containerlab exporter maps node roles to container images and generates the topology file ready for `clab deploy`.

Design Decision 2: Containerlab Integration

The exporter maps vendor and role to Docker images (e.g. `ceos:latest` for Arista, `crpd:latest` for Juniper). Interface names in the Containerlab output match those in the generated topology, enabling direct use of TopoGen configs in network emulation labs.

7 Design Summary

Table 3. Key design decisions.

Decision	Rationale
ChaCha8Rng	Cross-platform determinism; StdRng algorithm is unspecified
Vendor-specific naming	Realistic configs for lab deployment and parser testing
Geographic city DB	Distance-aware latency without external dependencies
Gravity traffic model	Produces realistic demand patterns from topology structure alone
PyO3 bindings	Native Python package for integration with simulation frameworks

References

- [1] M. Al-Fares, A. Loukissas, and A. Vahdat, “A scalable, commodity data center network architecture,” in *SIGCOMM*, 2008.
- [2] A.-L. Barabási and R. Albert, “Emergence of scaling in random networks,” *Science*, vol. 286, pp. 509–512, 1999.
- [3] D. J. Watts and S. H. Strogatz, “Collective dynamics of ‘small-world’ networks,” *Nature*, vol. 393, pp. 440–442, 1998.