

Navigation

pwd – print working directory

```
eureka@ubuntu:~$ pwd  
/home/eureka
```

cd – change directory

```
eureka@ubuntu:~/test$ pwd  
/home/eureka/test  
eureka@ubuntu:~/test$ cd /home/eureka/Desktop  
eureka@ubuntu:~/Desktop$ pwd  
/home/eureka/Desktop
```

Previous directory cd –

Move 1 directory up cd ../

Move 2 directories up cd ../../

Etc.

```
eureka@ubuntu:~/test$ pwd  
/home/eureka/test  
eureka@ubuntu:~/test$ cd ../  
eureka@ubuntu:~$ pwd  
/home/eureka  
eureka@ubuntu:~$ cd -  
/home/eureka/test  
eureka@ubuntu:~/test$ pwd  
/home/eureka/test
```

pushd – saves the current working directory in memory

popd – returns path at the top of the directory stack

dirs – displays currently remembers directories

```
eureka@ubuntu:~$ dirs  
~  
eureka@ubuntu:~$ pushd Desktop  
~/Desktop ~  
eureka@ubuntu:~/Desktop$ dirs  
~/Desktop ~  
eureka@ubuntu:~/Desktop$ popd ~  
~/Desktop  
eureka@ubuntu:~/Desktop$ dirs  
~/Desktop
```

ls – list contents of a directory

-f does not call stat(). But both ls and find call stat() when certain options are used, such as ls -l or find -mtime. Stat stats the file pointed to by *file_name* and fills in *buf* so can increase the time to run.

-h human readable

-l list

-R recursive

```
eureka@ubuntu:~/test$ ls -lhR
.:
total 4.0K
drwxrwxr-x 3 eureka eureka 4.0K Jul  1 15:59 another_dir

./another_dir:
total 4.0K
drwxrwxr-x 2 eureka eureka 4.0K Jul  1 15:59 final_dir

./another_dir/final_dir:
total 0
```

sort files by size

-S sort by file size

```
eureka@ubuntu:~/test$ ls -lSh
-rw-rw-r-- 1 eureka eureka 978K Oct 26 2012 redis-2.6.2.tar.gz
-rw-r--r-- 1 eureka eureka 8.3K Jan  9 14:42 examples.desktop
drwxr-xr-x 3 eureka eureka 4.0K Apr 16 10:37 Desktop
```

-a do not ignore entries starting with . (hidden files begin w/ .)

-r reverse order while sorting

-t sort by modification time, newest first

```
eureka@ubuntu:~$ ls -lart
total 1220
drwxrwxr-x 6 eureka eureka 4096 Oct 26 2012 redis-2.6.2
-rw-rw-r-- 1 eureka eureka 1000600 Oct 26 2012 redis-2.6.2.tar.gz
drwxr-xr-x 3 root root 4096 Jan  9 14:42 ..
-rw-r--r-- 1 eureka eureka 8445 Jan  9 14:42 examples.desktop
-rw-r--r-- 1 eureka eureka 675 Jan  9 14:42 .profile
-rw-r--r-- 1 eureka eureka 220 Jan  9 14:42 .bash_logout
```

Show only current directories

-d directory

```
eureka@ubuntu:~$ ls -d */
Desktop/    epd/        Pictures/    sites/       Videos/
Documents/  learn_pandas/ Public/      Templates/   workspace/
Downloads/  Music/      redis-2.6.2/ test/
```

Show multiple directories

```
eureka@ubuntu:~/Desktop$ ls ~ /usr
/home/eureka:
Desktop      examples.desktop  Pictures          sites           Videos
Documents    learn_pandas      Public            Templates       workspace
Downloads    Music             redis-2.6.2       test
epd          new_test.csv      redis-2.6.2.tar.gz test_file
/usr:
bin  games  include  lib  local  sbin  share  src
```

find- search for files in a directory

Find empty directories

-mindepth 1 process all files except the command line arguments

-type d - type directory. The type predicate will always match against the type of the file that a symbolic link points to rather than the link itself

```
eureka@ubuntu:~/test$ ls -l */*
-rw-rw-r-- 1 eureka eureka 0 Jul 1 16:51 a_dir/test

another_dir/final_dir:
total 0

eureka@ubuntu:~/test$ find . -mindepth 1 -type d -empty
./another_dir/final_dir
```

Find all executable files

-type f type file

-perm File's permission bits are exactly mode

```
eureka@ubuntu:~$ find / -type f -perm -o+rx | head -5
/etc/acpi/ejectbtn.sh
/etc/acpi/undock.sh
/etc/acpi/webbtn.sh
/etc/acpi/prevbtn.sh
/etc/acpi/powerbtn.sh
```

