




1st Floor
17 Baker Street
Rosebank
Johannesburg
South Africa
2196
Tel: +27 (0) 11 442 2434
Fax: +27 (0) 11 442 2454

ADC Heatsink Chassis Thermal Analysis

System: 1000 x 1000 x 1000 mm, 2 Fans on either side of the system to push air through it.

Scenario 1: ADC Heatsink as designed by Phil



Component Thermal Summary:

PCB

Minimum Temperature = 20.505806 Celsius
Maximum Temperature = 29.409340 Celsius
Volume Averaged Temperature = 26.018040 Celsius

ADC_CHIP

Minimum Temperature = 29.232372 Celsius
Maximum Temperature = 29.410778 Celsius
Volume Averaged Temperature = 29.362877 Celsius

ADC_HEATSINK_SOLID


Minimum Temperature = 28.594135 Celsius
Maximum Temperature = 29.398947 Celsius
Volume Averaged Temperature = 28.837357 Celsius

Volume

Minimum Temperature = 20.000000 Celsius
Maximum Temperature = 29.410778 Celsius
Volume Averaged Temperature = 20.224962 Celsius



Scenario 2: ADC with Solid Centre:



ADC_PCB

Minimum Temperature = 20.366674 Celsius
 Maximum Temperature = 28.649109 Celsius
 Volume Averaged Temperature = 25.628586 Celsius

ADC_CHIP

Minimum Temperature = 28.522627 Celsius
 Maximum Temperature = 28.649109 Celsius
 Volume Averaged Temperature = 28.596199 Celsius


ADC_HEATSINK_SOLID_MOD

Minimum Temperature = 27.949848 Celsius
 Maximum Temperature = 28.623741 Celsius
 Volume Averaged Temperature = 28.183914 Celsius

Volume

Minimum Temperature = 20.000000 Celsius
 Maximum Temperature = 28.765600 Celsius
 Volume Averaged Temperature = 20.077747 Celsius

Scenario 3: No Heatsink



ADC_PCB

Minimum Temperature = 20.228691 Celsius
 Maximum Temperature = 76.109299 Celsius
 Volume Averaged Temperature = 27.934515 Celsius

ADC_CHIP

Minimum Temperature = 75.511337 Celsius
 Maximum Temperature = 76.110352 Celsius
 Volume Averaged Temperature = 75.976463 Celsius

Volume

Minimum Temperature = 20.000000 Celsius
 Maximum Temperature = 76.110352 Celsius
 Volume Averaged Temperature = 20.217672 Celsius