EECS 221: Machine Learning for Science

Data–Compute Trade-offs in Neural PDE Forecasting

Suha Kagan Kose

Mid-Project Report (November 12)

Summary

The abstract set three milestones for this check-in. Their status:

1. **Data pipeline validated against The Well's released checkpoints: numerical agreement obtained.** Our data loading and metric code reproduce the paper's published test VRMSE for the released CNextU-Net and TFNO to within 1%, and recover rollout errors in the same reported range ("> 10"). The released TFNO needs the forward pass it was trained with, which differs from the corrected one our runs use (Section 1, Appendix B).
2. **Budgets fixed from pilot timings: done.** Batch 64, fp32, peak learning rate 10^{-3} for every model (from an equal-budget search), and 4-hour budgets measured in active GPU training time, with allocated GPU time reported separately.
3. **First 10%-data results: done.** All six 10% runs (3 models $\times$ 2 seeds) are trained and evaluated on the full test set at 1 and 4 hours (Section 4). After 4 hours, among our models, CNextU-Net is the most accurate in developed convection and the most stable in rollouts; AViT has a similar one-step error but degrades fastest over a rollout; TFNO is too smooth. These findings hold for these configurations, 10% of the training data and the tested budgets. A revised plan is in Section 5.

1 Setup

Data and task. `rayleigh_benard` from The Well [1]: 1,750 trajectories of 200 frames on a 512×128 grid, 35 (Rayleigh, Prandtl) regimes, official 80/10/10 splits. From four frames of buoyancy, pressure and both velocity components, a model predicts the next frame and is rolled out autoregressively. Fields are normalised with The Well's training statistics.

Models. The Well's own implementations, trained from random initialisation, with matched parameter counts (Table 1). All three use GELU activations. For TFNO, released-checkpoint reproduction and training with the current code must be distinguished: the paper-era code skipped TFNO's Fourier layers, an error fixed upstream in November 2025. We scored the released TFNO weights with the forward pass they were trained with, and our own TFNO, trained with the fixed code (The Well at `e63dec8`), uses its Fourier layers (Appendix B).

Training. All models use AdamW, one-step MSE in normalised field values, batch size 64 and fp32, with a peak learning rate of 10^{-3}, 500 warmup steps and cosine decay to zero over four hours of active GPU training on one A100. The paper trained for 12 hours on an H100 with its own learning rates and schedule, so ours is a different experiment (Appendix A). Checkpoints are saved at one and four hours. The one-hour checkpoint is an intermediate state of the four-hour schedule (learning rate about 85% of

Model	Family	Parameters	Normalisation	Relation to released checkpoint
CNextU-Net [2]	ConvNeXt U-Net, 4 stages	18.58M	LayerNorm	same architecture
TFNO [3]	Fourier operator, 16×16 modes	19.28M	none	same configuration, fixed forward
AViT [4]	axial-attention ViT	18.57M	GroupNorm, LayerNorm	none released; width 384 → 432

Table 1: The three model families.

peak), not a separately optimised one-hour run, so it measures progress along a shared schedule, not the best performance achievable in one hour.

VRMSE. For one window (one predicted frame) and one field f, The Well's metric code (its `VRMSE` class at commit `e63dec8`) computes

$$\mathrm{VRMSE}_f = \sqrt{\frac{\frac{1}{N}\sum_{i=1}^{N}(\hat{y}_{f,i} - y_{f,i})^2}{s_f^2 + \varepsilon}}, \qquad s_f^2 = \frac{1}{N-1}\sum_{i=1}^{N}(y_{f,i} - \bar{y}_f)^2, \qquad \varepsilon = 10^{-7},$$

over the $N = 512 \times 128$ grid points of the target frame. The four fields (buoyancy b, pressure p, and the velocity components u, w) are averaged with equal weights, and reported values are means over windows with equal weight per window (one-step: all 196 windows of each of the 175 test trajectories; rollouts: per step, over trajectories and start frames). Two variants use the same formula and averaging and differ only in the field values passed in: the *paper protocol* scores normalised fields, $(y_f - \mu_f)/\sigma_f$ with The Well's training statistics ($\sigma_f = 0.249, 0.149, 0.208, 0.180$ for b, p, u, w); our *physical-field VRMSE* scores the fields as stored. Without ε the two would be identical, since the ratio is invariant to an affine rescaling of each field. With ε, normalising multiplies s_f^2 by $1/\sigma_f^2$ (16–45), so the floor shrinks from 10^{-7} to the equivalent of $\varepsilon\sigma_f^2 \approx 2$–$6 \times 10^{-9}$. During the first ∼50 frames the velocity is nearly zero (exactly zero at $t = 0$) and its spatial variance is comparable to 10^{-7}, so the physical-field score is damped there and the normalised one is not. This is the whole difference between the released CNextU-Net's 0.669 (paper protocol) and 0.224 (physical fields): on early windows they score 2.510 and 0.766, while from frame 50 on both give 0.038.

Failure horizon. For a rollout, the first step whose field-mean physical-field VRMSE exceeds a threshold (1, 2 or 5, all reported). Rollouts start at frames 20, 80 and 140 of every test trajectory and run 30 steps. We report the fraction of rollouts that stay below each threshold through step 30 (Table 5) and, for threshold 1, its value at every step (Kaplan–Meier survival; Fig. 4b).

Kinetic-energy spectrum. At each grid row, the two velocity components are Fourier-transformed along the periodic x axis; $E(k_x)$ is the one-sided energy $\frac{1}{2}(|\hat{u}|^2 + |\hat{w}|^2)$ at $k_x = 2\pi n/L_x$ ($L_x = 4$), averaged over the Chebyshev-spaced rows with quadrature weights, so that summing over k_x gives the domain-mean kinetic energy. Spectra are averaged over the rollouts of each regime (5 trajectories × 3 start frames) at steps 1, 10 and 30, separately for predictions and truth.

2 Milestone 1: pipeline validated against the released checkpoints

We loaded The Well's released CNextU-Net and TFNO weights and scored them with our own data path and metric on every window of the 175 test trajectories (Table 2).

Three observations shape how we report results:

- **Aggregate relative error is sensitive to the early frames** (Fig. 1). For the first ∼50 frames

	Paper-protocol one-step VRMSE		Rollout from frame 0, steps 6–12 / 13–30	
Model	Ours (released weights)	Published	Ours	Published
CNextU-Net	0.669	0.670	36 / 35	> 10 / > 10
TFNO	0.663	0.657	142 / 169	> 10 / > 10

Table 2: Released checkpoints scored by our pipeline against the paper's Tables 2 and 3 (test split).

the fluid is nearly at rest; the evaluated models have large relative velocity errors there, and copying the last frame (persistence) is nearly exact. From frame 50 on, the released CNextU-Net scores 0.038, against an all-window mean of 0.224 in physical fields (0.669 under the paper protocol). Near-zero target variability can amplify relative error, so this does not establish that absolute errors are largest early on. We therefore also report early (*onset*) and later (*developed*) windows separately.

- **Rollout error varies substantially with Rayleigh number.** At Ra $= 10^{10}$ the released CNextU-Net's median over steps 13–30 is 1.7; at 10^6 it is 69.
- **The fixed test evaluation is the clearer reproduction target.** The paper's validation values use 20 random batches per epoch; exact agreement would additionally require the same sampled batches and evaluation state.




Figure 1: Released checkpoints' one-step VRMSE by window on the test set, mean over the 175 trajectories, under the paper protocol (left) and on physical fields (right). Shaded: windows whose first input frame is below 50, reported as *onset*; the others are *developed*. The cut at frame 50 is operational, chosen where the released checkpoints' error levels off on the validation split; it is not a transition verified for every regime. Persistence copies the last input frame.

3 Milestone 2: budgets fixed from pilot timings

Resource accounting. *Active GPU training time* is the measured training time counted against the budget (optimizer steps only; Appendix C gives the timer boundaries). *Allocated GPU time* is the duration for which a job occupies a GPU, including data waits and other overhead. *Service units (SU)* are the cluster's charges on its paid partition. Queue time is reported separately and is not allocated GPU time.

Budget clock. Data are read from the cluster's shared file system, which delivers at most ∼98 training samples per second into one node and stalls for 5–22 minutes at a time, on all nodes at once. TFNO

and AViT consume 116 and 330 samples per second of GPU time (Fig. 7), so a wall-clock budget would partly measure our storage. The 1-hour and 4-hour budgets therefore count active GPU training time; waiting for data is logged separately.

Learning rate. An equal-budget search (20 minutes of GPU training per run, 10% data, validation only) chose 10^{-3} for all three models (Table 3). The Well swept $\{10^{-4}, 5 \cdot 10^{-4}, 10^{-3}, 5 \cdot 10^{-3}, 10^{-2}\}$; we tested its lower three rates and omitted the two largest to limit tuning cost. Since 10^{-3} is the largest rate tried, it is the best candidate tested, not an established optimum, and the 20-minute ranking may differ from the ranking after four hours.

Validation VRMSE after 20 min	10^{-4}	$5 \cdot 10^{-4}$	10^{-3}
CNextU-Net	0.841	0.469	**0.408**
TFNO	0.603	0.358	**0.302**
AViT	0.646	0.332	**0.257**

Table 3: Learning-rate search.

Batch size and precision. Batch 64 (The Well's) fits every model in fp32 on an A100 80 GB; CNextU-Net peaks at 64.8 GB of memory reserved by PyTorch (60.9 GB allocated, Table 6). The current TFNO implementation requires fp32 FFT operations, so all models use fp32 for this comparison. This is an implementation constraint, not a claim that mixed-precision TFNO is impossible.

Pilot against actual. The pilots predicted 4 h of GPU training to take 6.0 / 8.0 / 9.7 h of wall time (CNextU-Net / TFNO / AViT) at the stall rate observed then; the 10% runs took 5.2–6.0 / 6.9–7.1 / 11.1–12.2 h (Appendix C).

4 Milestone 3: first 10%-data results

Training (Fig. 2). The six runs completed their 4-hour budgets (Table 9). On a fixed validation sample of 64 windows (Appendix C), AViT and CNextU-Net reach similar error after 4 hours; TFNO's loss plateaus after ∼1.5 hours. CNextU-Net's validation error peaks near one hour while its learning rate is still high; this temporal association does not establish the learning rate as the cause.




Figure 2: Training MSE in normalised units (left; smoothed over 3 minutes of training) and validation VRMSE on the 64 fixed windows, physical fields (right), against active training time, 10% data. Solid: seed 0; dashed: seed 1. Vertical lines: the 1-hour and 4-hour checkpoints.

Test evaluation (all 175 test trajectories, both seeds; Table 4, Fig. 3). After 4 hours AViT and CNextU-Net have similar one-step error over all windows (0.134 and 0.136) and TFNO a higher one (0.209), but the two phases separate them: in developed convection CNextU-Net is clearly the most accurate (0.050, against 0.075 for AViT and 0.109 for TFNO), while AViT is the most accurate during onset. At four hours the across-seed standard deviation of the all-window VRMSE is at most 0.006; at one hour it is up to 0.18 (CNextU-Net: 0.85 and 0.60), and the order is reversed: AViT (0.39) and TFNO (0.47) are ahead of CNextU-Net (0.73), whose one-hour checkpoint is far from converged. The released CNextU-Net, trained on all the data for longer, remains better in developed convection (0.038 against 0.050). Our TFNO, which uses its Fourier layers, is better than the released TFNO everywhere (developed 0.109 against 0.190; paper protocol 0.488 against 0.663) despite 10% of the data and 4 hours. Persistence is better than every model during onset and 2–4.5 times worse in developed convection.

	Physical-field one-step VRMSE			Paper protocol
Model (10% data, checkpoint)	all windows	onset	developed	(all windows)
CNextU-Net, 4 h	0.136 ± 0.006	0.387 ± 0.025	**0.050** ± 0.000	0.349 ± 0.022
TFNO, 4 h	0.209 ± 0.001	0.502 ± 0.003	0.109 ± 0.000	0.488 ± 0.001
AViT, 4 h	**0.134** ± 0.001	**0.308** ± 0.003	0.075 ± 0.000	**0.298** ± 0.002
CNextU-Net, 1 h	0.728 ± 0.176	2.618 ± 0.681	0.081 ± 0.003	2.345 ± 0.600
TFNO, 1 h	0.473 ± 0.078	1.505 ± 0.305	0.120 ± 0.000	1.362 ± 0.249
AViT, 1 h	0.394 ± 0.036	1.299 ± 0.140	0.085 ± 0.000	1.171 ± 0.125
Released CNextU-Net (100%, paper)	0.224	0.766	0.038	0.669
Released TFNO (100%, paper)	0.300	0.623	0.190	0.663
Persistence	0.199	0.121	0.226	0.202

Table 4: One-step test error: mean ± standard deviation over the two seeds (0.000: below 0.0005). Onset: first input frame < 50; developed: ≥ 50. Bold: best of our 4-hour models.




Figure 3: One-step test VRMSE (physical fields) by window, mean over the 175 test trajectories: our 10% models at 4 hours (seed mean; band: range over seeds), the released CNextU-Net trained on all the data, and persistence. Shaded: onset windows (first input frame < 50; see Fig. 1).

Rollouts (Table 5, Fig. 4). One-step accuracy does not carry over to rollouts in the same order. Among our trained models, CNextU-Net is the most stable: after 30 steps from frames 80 and 140 its error (0.53, 0.40) is below persistence's (0.86, 0.54), and 89% of its rollouts stay below VRMSE 1 through step 30. AViT, despite a similar one-step error, degrades fastest (0.80, 0.65; 63%), and from frame 20, during

onset, its error grows to 5.4. TFNO lies in between. Persistence keeps more rollouts below the thresholds because its error levels off near 0.7, while it is 2–5 times less accurate than every model over the first steps from developed flow (Fig. 4a). Under the paper's frame-0 protocol all three models land in the "> 10" range; CNextU-Net (15 / 30) is below both released checkpoints.

Model	VRMSE after 30 steps from frame 20 / 80 / 140	Fraction staying below threshold through step 30: 1 / 2 / 5	Paper protocol, steps 6–12 / 13–30 (normalised)
CNextU-Net, 4 h	1.78 / **0.53** / **0.40**	**0.89** / **0.94** / **0.98**	**15** / **30**
TFNO, 4 h	1.79 / 0.59 / 0.45	0.75 / 0.85 / 0.91	51 / 77
AViT, 4 h	5.42 / 0.80 / 0.65	0.63 / 0.80 / 0.87	75 / 167
Released CNextU-Net (100%)			36 / 35
Released TFNO (100%)			142 / 169
Persistence	0.68 / 0.86 / 0.54	0.94 / 1.00 / 1.00	0.27 / 0.50

Table 5: Rollouts on the test set, physical-field VRMSE unless stated, mean over the two seeds. Middle column: fraction of the 525 rollouts (175 trajectories × 3 start frames) whose error stays below each threshold at every step through step 30. Right: the paper's Table 3 protocol (published: > 10 in both windows); bold: best of our models.




Figure 4: Rollouts of our 10% models at 4 hours (seed mean) and persistence. (a) Physical-field VRMSE at each step, mean over the rollouts from frames 80 and 140 (developed convection). (b) Fraction of all 525 rollouts that have stayed below VRMSE 1 up to each step (Kaplan–Meier survival).

Speed and memory (Table 6). In the same 4 hours of GPU training AViT takes six times as many optimizer steps as CNextU-Net and allocates a seventh of the memory; TFNO is the fastest at inference.

Model	Optimizer steps in 4 h	Epochs	Peak training memory allocated (reserved)	Inference per step	Inference per 30-step rollout
CNextU-Net	12,122–12,194	28	60.9 (64.8) GB	8.3 ms	249 ms
TFNO	26,339–26,352	61	48.6 (56.9) GB	4.4 ms	135 ms
AViT	74,978–75,060	175	8.8 (8.9) GB	5.4 ms	163 ms

Table 6: Training throughput and memory (batch 64, fp32) and inference latency (batch 1), on one A100 80 GB. Allocated: tensors in use; reserved: memory held by PyTorch's allocator.

Physical fidelity (4-hour checkpoints; Fig. 5). The kinetic-energy spectrum shows at which scales each model's errors lie. It is a complementary diagnostic, not the paper's binned spectral error, and it describes how energy is distributed over scales, not where structures are: a model can match the spectrum with plumes in the wrong places. The values below are medians over the 35 regimes and both seeds of the

predicted-to-true ratio, taken per wavenumber at steps 1, 10 and 30 (the steps evaluated). CNextU-Net stays within 0.80–1.57 below $k_x = 100$ and reaches 190–530 at the highest wavenumbers. TFNO is too smooth: between $k_x \approx 25$ and 100 its ratio falls to 0.33 after one step and 0.09 after 30, and it reaches 9–50 at the highest wavenumbers. AViT stays within 0.97–1.34 below $k_x = 100$ after one step, but after 30 steps it ranges from 0.55 to 21 there and reaches about 5×10^4 at the highest wavenumbers. The TFNO deficit is consistent with its spectral layers keeping only the 16 lowest Fourier modes in each direction ($k_x \lesssim 25$), and AViT's growth with the patch-shaped artifacts in Fig. 6; neither is established as the cause. Persistence repeats its last input field, so its predicted spectrum is fixed within a rollout; changes in its ratio reflect the evolving true spectrum. Ratios at the smallest scales should also be read alongside absolute spectra, because very small true energy can magnify the ratio.




Figure 5: Horizontal kinetic-energy spectra. (a) True and predicted spectrum after 30 rollout steps for one regime ($\mathrm{Ra} = 10^8$, $\mathrm{Pr} = 1$). (b, c) Predicted over true spectrum after 1 and 30 steps, per wavenumber: median over the 35 regimes (band: middle 50%); 1 is exact. Shaded: small scales ($k_x > 100$).

What the predictions look like (Fig. 6; $\mathrm{Ra} = 10^{10}$ in Appendix D). The figure shows buoyancy, while the spectra are computed from velocity, so the two are related qualitative evidence rather than measurements of the same field. At $\mathrm{Ra} = 10^8$ CNextU-Net follows the true plumes through 30 steps. TFNO blurs them and builds a spurious warm layer along the bottom wall. By step 12 AViT shows rectangular artifacts at the size of its 16×16-pixel patches. At $\mathrm{Ra} = 10^{10}$ the true flow is far finer than any of the three reproduces; CNextU-Net keeps the large-scale plume pattern but smooths the small structures.




Figure 6: Buoyancy on a test trajectory at Ra = 10^8, Pr = 1, rolled out from frame 80: the true flow and our 10% / 4-hour models (seed 0) after 1, 12 and 30 steps. Bright: warm; dark: cold. One colour range is used for all panels: the 1st to 99th percentile of the true field away from the walls, so the hot bottom wall saturates.

5 Revised plan

The *core comparison* remains three families, 10% and 100% training data, two seeds, and checkpoints at one and four hours. The main changes are:

- **Budget definition.** Experimental budgets count active GPU training time. Allocated GPU time, data waits and SU are reported separately so that storage costs remain visible.
- **Evaluation.** Report the paper protocol for reference comparisons alongside the physical-field VRMSE, separate onset from developed convection, and report the failure horizon at thresholds 1, 2 and 5.
- **One-hour budget.** Dedicated one-hour runs at 10% data (same recipe, cosine ending at one hour) have been trained to check the one-hour comparison: on the validation sample they reach 0.22–0.33, against 0.42–1.04 for the one-hour checkpoints above. Their test evaluation follows.
- **Core resource estimate.** The 48 hours of active training are unchanged; the working estimate is approximately 135 allocated GPU-hours for the core study and its supporting work (Table 7), instead of the abstract's approximately 100. With all 10% work complete, Slurm accounting gives 72.6 allocated GPU-hours: 54.2 on the paid partition, billed 2,160 SU (40 SU per allocated hour for jobs with 8 cores, 36 for the 4-core pipeline check), and 18.3 on the free partition, which is not billed.
- **Optional, outside the estimate.** 24-hour runs of CNextU-Net and TFNO with the paper's learning rates (roughly 60–90 allocated GPU-hours; not an exact replication of the paper's 12-hour H100 runs), and a Dedalus [5] solver baseline on CPUs, which first needs a feasibility check.

Remaining deliverables. The 10% evaluation is complete for all three models and both seeds, including failure horizons, spectra, latency and memory. Remaining for the final report: the 100% runs and the data–compute comparison (10% against 100% at 1 and 4 hours), the dedicated one-hour runs' test evaluation, field-wise VRMSE and the Nusselt-number error per model, and the flow snapshots for the 100% runs.

Next steps, in priority order. (1) Improve data-loading robustness and assess node-local staging; (2) complete the six 100% runs (estimated approximately 2,400 SU) and the core data–compute comparison; (3) complete the promised metrics and the reproducible final report. Only after core completion, consider

Component	Allocated GPU-hours
Six 10% runs, completed (24.0 of them active training)	49.8
Learning-rate search, profiling, pipeline check, environment checks, first replication try	18.5
Test evaluation of the six 10% runs and persistence (completed)	4.2
Six 100% runs (projected, 24.0 active; Appendix C)	∼54–65
Test evaluation of the 100% runs	∼4.5
Core study	∼131–142

Table 7: Allocated GPU-hours of the core study: completed parts from Slurm accounting (2026-11-11), the rest projected. No contingency is included; the abstract's ∼100 hours included ∼30, and a similar margin would bring the total to ∼160–170.

the abstract's extensions in their original order: input-noise robustness, a third seed, a 30% fraction, and ConvLSTM. The optional runs above should not delay the core deliverables.

A Detailed training recipe

Sources of the reference settings: the paper (learning rates, 12-hour H100 budget) and The Well's training configuration at commit `e63dec8`:

- `configs/optimizer/adam.yaml`: AdamW, weight decay 10^{-4} (the paper's text says 0.01; we follow the code);
- `configs/data/rayleigh_benard.yaml`: batch 64;
- `configs/trainer/defaults.yaml`: 200 epochs;
- `configs/lr_scheduler/cosine_with_warmup.yaml` with `train.py`: 5 warmup epochs from 0.1·lr, then cosine to 0.1·lr.

Our software: The Well `e63dec8`, neuraloperator 0.3.0, PyTorch 2.8.0 (CUDA 12.8), Python 3.13; our repository at `f42b2e2` (training) and `4c0d3a8` (AViT resume, evaluation).

	This study	The Well paper / code
Activation	GELU (all three models)	GELU (same model code)
Optimizer	AdamW, $\beta = (0.9, 0.999)$, weight decay 10^{-4}, no clipping	AdamW, weight decay 10^{-4} in the code (0.01 in the text), no clipping
Loss	one-step MSE, normalised units, equal field weights	same
Batch size, precision	64, fp32	64, fp32
Learning rate	10^{-3} for all, from our search over $\{10^{-4}, 5\cdot10^{-4}, 10^{-3}\}$	per model from $\{10^{-4}, 5\cdot10^{-4}, 10^{-3}, 5\cdot10^{-3}, 10^{-2}\}$: $5\cdot10^{-4}$ (CNextU-Net), 10^{-4} (TFNO)
Schedule	500 warmup steps, cosine to 0 over the 4-hour budget	5 warmup epochs, cosine to 0.1·lr over 200 epochs, stopped at 12 h
Budget, hardware	1 h and 4 h of active GPU training on one A100	12 h on one H100, best validation epoch
Training data	10% of the trajectories (100% next)	100%

Table 8: Training recipe: ours against the paper's.

B TFNO forward pass

In The Well's code, commit `2d8d7eaf` (2024-06-03, "Added gradient checkpointing") called TFNO's Fourier blocks without keeping their output, so the model computed only its lifting and projection layers; commit `e4301602` (2025-11-17, "actually use the TFNO blocks") restored the assignment (`x =` before the block call) [6]. The paper's TFNO results and the released TFNO checkpoint (uploaded 2025-03-28) date from that period. For the pipeline check we scored the released TFNO weights with the forward pass they were trained with (Fourier blocks skipped): it reproduces the published value, while with the corrected forward pass the same weights score ≈10.5. Our own runs use The Well at commit `e63dec8`, which includes the fix. Upstream issue #49 reports related inconsistencies between released checkpoints and published numbers [7].

C Resource accounting

Timer. Active training time is measured per optimizer step with a host-side monotonic clock (Python's `perf_counter`), from the moment the data loader returns the batch to just after a CUDA synchronisation

(`torch.cuda.synchronize`) following the optimizer update. It includes the host-to-device copy of the batch (pinned memory, non-blocking), setting the learning rate, the forward pass, the loss, the backward pass, the optimizer step and the host-side launch overhead of these operations. It excludes the wait for the next batch (logged as data-wait time), reading the loss value, logging, validation, checkpoint writes and start-up. After a crash the clock resumes from the last saved checkpoint, so lost steps are not counted. A milestone checkpoint is written after the first step at which the cumulative time reaches 1 h or 4 h (overshoot below one step).

Validation sample. The 64 validation windows are fixed and evenly spaced over the 34,300 one-step windows of the validation split (175 trajectories × 196), taken in the dataset's order (regime, trajectory, time): indices round(linspace(0, 34299, 64)). They cover all 35 regimes (one or two windows each) and 64 different trajectories; 18 of them (28%) are onset windows, close to the 26% of all windows. The learning-rate search used 512 windows chosen the same way (all 35 regimes, all 175 trajectories, 25% onset); the two samples share 8 windows. This monitoring sample does not replace the full test evaluation.

Billing. Paid jobs are billed 32 SU per GPU-hour plus 1 SU per core-hour of allocated time (40 SU per hour for one A100 and 8 cores); the free partition is not billed. Runs that started on the free partition and resumed on the paid one are billed only for the paid part.

	Validation VRMSE (seed 0 / 1)		Epochs	Allocated time	SU
Model	1 h	4 h	in 4 h	per run	per run
CNextU-Net	1.043 / 0.772	0.167 / 0.178	28	5.2–6.0 h	189–191
TFNO	0.508 / 0.524	0.310 / 0.325	61	6.9–7.1 h	274–286
AViT	0.468 / 0.418	0.161 / 0.167	175	11.1–12.2 h	443–488

Table 9: The 10% runs (140 training trajectories). Validation: 64 fixed windows, physical-field VRMSE. SU covers the paid partition only: CNextU-Net's first attempts ran on the free partition, so its SU corresponds to 4.8 h of its 5.2–6.0 h.

Hours per run	CNextU-Net	TFNO	AViT
10% runs, measured			
Queue wait before training started	0.1–0.9	0.5–0.7	6.7–8.8
GPU training (the budget)	4.0	4.0	4.0
Waiting for data	0.8–1.1	2.5–2.8	6.1–7.3
Start-up, and steps replayed after a preemption or crash[a]	0.13–0.65	0.14–0.15	0.68–0.69
Validation (64 windows every 30 minutes)	0.01–0.02	0.02–0.10	0.18
Checkpoint writes	0.23–0.24	0.08–0.15	0.03–0.13
Allocated time of training	**5.2–6.0**	**6.9–7.1**	**11.1–12.2**
Test evaluation job (1-hour and 4-hour checkpoints)	0.87–0.95	0.57	0.34–0.38
Queue wait before the evaluation started	1.0–14.0	1.9–2.4	3.0–3.3
Training attempts (seed 0 / seed 1)	2 / 2	1 / 1	2 / 2
100% runs, projected			
Waiting for data	1.0–2.0	3.0–4.5	9.5–12.5
Allocated time of training	**5.5–6.5**	**7.5–9**	**14–17**
Test evaluation job	∼0.9	∼0.6	∼0.4

Table 10: Time per run (range over the two seeds). [a]A run that starts once spends about 0.15 h in start-up (environment, data index, model build); the larger values belong to runs with two attempts, which also replayed the steps since their last saved checkpoint. Projection for 100%: the shared file system delivers at most ∼98 samples/s, below TFNO's (116) and AViT's (330) demand, and the full training split (∼290 GB) no longer fits in a node's page cache; start-up, validation, checkpoint writes and evaluation as measured. Queue waits depend on the cluster's load and are not projected.




Figure 7: Training samples per second read from the shared file system by one node, against the rate at which each model consumes them on the GPU (horizontal lines).

D Flow snapshots at $\mathrm{Ra} = 10^{10}$




Figure 8: As Fig. 6, at $\mathrm{Ra} = 10^{10}$, $\mathrm{Pr} = 1$.

References

[1] Ohana, R., et al. "The Well: a Large-Scale Collection of Diverse Physics Simulations for Machine Learning." NeurIPS, Datasets and Benchmarks Track, 2024.
https://arxiv.org/abs/2412.00568

[2] Liu, Z., Mao, H., Wu, C.-Y., Feichtenhofer, C., Darrell, T., and Xie, S. "A ConvNet for the 2020s." CVPR, 2022.
https://arxiv.org/abs/2201.03545

[3] Kossaifi, J., Kovachki, N., Azizzadenesheli, K., and Anandkumar, A. "Multi-Grid Tensorized Fourier Neural Operator for High-Resolution PDEs." TMLR, 2024.
https://arxiv.org/abs/2310.00120

[4] McCabe, M., et al. "Multiple Physics Pretraining for Spatiotemporal Surrogate Models." NeurIPS, 2024.
https://arxiv.org/abs/2310.02994

[5] Burns, K. J., Vasil, G. M., Oishi, J. S., Lecoanet, D., and Brown, B. P. "Dedalus: A flexible framework for numerical simulations with spectral methods." Physical Review Research 2, 023068, 2020.
https://arxiv.org/abs/1905.10388

[6] The Well source code, commits 2d8d7eaf9eb46b96f215abf39c94b6be4bf9ea5c (2024-06-03) and e4301602e57f2dddeaa87856dda49bbba47c663b (2025-11-17).
https://github.com/PolymathicAI/the_well/commit/2d8d7eaf9eb46b96f215abf39c94b6be4bf9ea5c
https://github.com/PolymathicAI/the_well/commit/e4301602e57f2dddeaa87856dda49bbba47c663b

[7] The Well, issue #49, "Inconsistent Pre-trained Baseline Performance" (open since 2025-04-21).
https://github.com/PolymathicAI/the_well/issues/49