/* DDL Commands

Consider the following Schema

Supplier (SID, Sname, branch, city, phone)

Part (PID, Pname, color, price)

Supplies (SID, PID, qty, date supplied) */

```
CREATE TABLE SUPPLIER (
  SID INT,
  Sname VARCHAR(50),
  branch VARCHAR(30),
  city VARCHAR(30),
  phone VARCHAR(15)
);
```

OUTPUT:

```
Table created.
```

```
CREATE TABLE PART (
  PID INT,
  Pname VARCHAR(50),
  color VARCHAR(20),
  price DECIMAL(10, 2)
);
```

OUTPUT:

```
Table created.
```

```
CREATE TABLE SUPPLIES (
  SID INT ,
  PID INT,
  qty INT,
  date_supplied DATE
);
```

OUTPUT:

```
Table created.

--To describe the table use desc keyword

Desc supplier
```

OUTPUT:

Object Type **TABLE** Object **SUPPLIER**

Table	Column	Data Type	Length	Precision	Scale	Primary Key	Nullable	Default	Comment
SUPPLIER	SID	Number	-	-	0	-	✓	-	-
	SNAME	Varchar2	50	-	-	-	✓	-	-
	BRANCH	Varchar2	30	-	-	-	✓	-	-
	CITY	Varchar2	30	-	-	-	✓	-	-
	PHONE	Varchar2	15	-	-	-	✓	-	-

1 - 5

```
Desc part
```

OUTPUT:

Object Type **TABLE** Object **PART**

Table	Column	Data Type	Length	Precision	Scale	Primary Key	Nullable	Default	Comment
PART	PID	Number	-	-	0	-	✓	-	-
	PNAME	Varchar2	50	-	-	-	✓	-	-
	COLOR	Varchar2	20	-	-	-	✓	-	-
	PRICE	Number	-	10	2	-	✓	-	-

1 - 4

```
Desc supplies
```

OUTPUT:

Object Type **TABLE** Object **SUPPLIES**

Table	Column	Data Type	Length	Precision	Scale	Primary Key	Nullable	Default	Comment
SUPPLIES	SID	Number	-	-	0	-	✓	-	-
	PID	Number	-	-	0	-	✓	-	-
	QTY	Number	-	-	0	-	✓	-	-
	DATE_SUPPLIED	Date	7	-	-	-	✓	-	-

1 - 4

Add a new attribute state in supplier table.

ALTER TABLE Supplier ADD state VARCHAR(30);

//Remove attribute city from supplier table

ALTER TABLE Supplier DROP COLUMN city;

//Modify the data type of phone attribute

ALTER TABLE Supplier MODIFY phone NUMBER(15);

//Change the name of attribute city to address

(If city column is dropped from the table add the City Column)

ALTER TABLE Supplier ADD city VARCHAR(30);

ALTER TABLE Supplier RENAME COLUMN city TO address;

//Change a table's name, supplier to sup

RENAME Supplier TO Sup;

//Use truncate to delete the contents of supplies table

TRUNCATE TABLE Supplies; (apply this after inserting a record)

//Remove the part table from database.

DROP TABLE Part;

//DML Commands

//Insert at least 10 records in tables supplier, part and supplies.

//supplier (rename sup to supplier)

INSERT INTO SUPPLIER VALUES (204001, 'Ajay Kumar', 'Local', '9876543210', 'Delhi', 'Delhi');

```
INSERT INTO SUPPLIER VALUES (204002, 'Vandana', 'Global', '9123456780', 'Goa', 'Panaji');

INSERT INTO SUPPLIER VALUES (204003, 'Mike Tyson', 'Local', '9988776655', 'Maharashtra',
'Andheri');

INSERT INTO SUPPLIER VALUES (204004, 'Geeta Patel', 'Local', '8899001122', 'Gujarat',
'Navrangpura');

INSERT INTO SUPPLIER VALUES (204005, 'Ravi M', 'Global', '9012345678', 'Tamil Nadu', 'T Nagar');

INSERT INTO SUPPLIER VALUES (204006, 'John D', 'Local', '8123456789', 'Karnataka', 'Rajajinagar');

INSERT INTO SUPPLIER VALUES (204007, 'Priya R', 'Global', '9090909090', 'Kerala', 'Ernakulam');

INSERT INTO SUPPLIER VALUES (204008, 'Suresh S', 'Local', '9234567890', 'Telangana', 'Begumpet');

INSERT INTO SUPPLIER VALUES (204009, 'Kavya N', 'Local', '9345678901', 'Rajasthan', 'Vaishali
Nagar');

INSERT INTO SUPPLIER VALUES (204010, 'Nikhil P', 'Global', '9456789012', 'West Bengal', 'Salt Lake');


select * from supplier;
```

//Part (re-create part table due to earlier we dropped the Part table)

```
INSERT INTO Part VALUES (201, 'Nut', 'Red', 200);

INSERT INTO Part VALUES (202, 'Bolt', 'Green', 400);

INSERT INTO Part VALUES (203, 'Screw', 'Blue', 600);

INSERT INTO Part VALUES (204, 'Washer', 'Yellow', 800);

INSERT INTO Part VALUES (205, 'Nail', 'Red', 1000);

INSERT INTO Part VALUES (206, 'Pin', 'Black', 1200);

INSERT INTO Part VALUES (207, 'Clip', 'Silver', 1400.6);

INSERT INTO Part VALUES (208, 'Bracket', 'White', 1600.66);

INSERT INTO Part VALUES (209, 'Plate', 'Grey', 1800);

INSERT INTO Part VALUES (210, 'Pipe', 'Black', 2000);


select * from part;
```

//Supplies

```
INSERT INTO Supplies VALUES (204001, 201, 50,'10-AUGUST-2020');
```

```
INSERT INTO Supplies VALUES (204002, 202, 60,'12-march-1997' );

INSERT INTO Supplies VALUES (204003, 203, 45,'8-may-1995');

INSERT INTO Supplies VALUES (204004, 204, 70, '9-september-2021');

INSERT INTO Supplies VALUES (204005, 205, 80, '2-july-2022');

INSERT INTO Supplies VALUES (204006, 206, 55, '23-AUGUST-2024');

INSERT INTO Supplies VALUES (204007, 207, 40,'19-december-1998');

INSERT INTO Supplies VALUES (204008, 208, 65,'25-july-2020' );

INSERT INTO Supplies VALUES (204009, 209, 50,  TO_DATE('2024-07-01', 'YYYY-MM-DD'));

INSERT INTO Supplies VALUES (204010, 210, 75, TO_DATE('2024-07-01', 'YYYY-MM-DD'));


select * from supplies;
```

//Show the contents in tables supplier, part and supplies.

```
SELECT * FROM Supplier;

select * from part;

select * from supplies;
```

//Find the name and city of all suppliers

```
SELECT Sname, city FROM Supplier;
```

(Get a error due to changed city to address need to change it back to city)

```
ALTER TABLE Supplier RENAME COLUMN  address to city;
```

//Find the name and phoneno of all suppliers who stay in 'Delhi'

```
SELECT SNAME, PHONE

FROM SUPPLIER

WHERE CITY = 'Delhi';
```

//Find all distinct branches of suppliers

```
SELECT DISTINCT BRANCH

FROM SUPPLIER;
```

//Delete the record of the supplier whose SID is 204001

```
DELETE FROM SUPPLIER
```

```
WHERE SID = 204001;
```

//Delete all records of suppliers whose city starts with capital A.

```
DELETE FROM Supplier
WHERE city LIKE 'A%';
```

//Find the supplier names which have ‘lk’ in any position

```
SELECT Sname
FROM Supplier
WHERE Sname LIKE '%kh%';
```

//Find the supplier name where ‘R’ is in the second position.

```
SELECT Sname
FROM Supplier
WHERE Sname LIKE '_r%';
```

//Find the name of supplier whose name starts with ‘V’ and ends with ‘A’

```
SELECT Sname
FROM Supplier
WHERE Sname LIKE 'V%a';
```

//Change the city of all suppliers to ‘BOMBAY’.

```
UPDATE Supplier
SET city = 'BOMBAY';
```

//Change the city of supplier ‘Vandana’ to ‘Goa’

```
UPDATE Supplier
SET city = 'Goa'
WHERE Sname = 'Vandana';
```

//Delete all records of supplier table

```
DELETE * FROM Supplier;
```