Blindspot

Live on Sepolia · every request through **Anon-RPC**

Follow the whales. Leave no trace.

A private read layer for trading on Ethereum: watch, copy, look up and trade without telling any RPC provider what you care about.

useblindspot.xyz →

Built on Anon-RPC

Blindspot

Your RPC provider sees more than your balance.

Infura, Alchemy, any public node. Same requests, same view.

Your wallets

Every balance check names you.

```
eth_getBalance(your address)
```

Your watchlist

Following a whale means asking about it.

```
eth_getLogs(0xC2D7…73E9)
```

Your next trade

Copying the whale means quoting first.

```
quote(ETH → USDC, 0.0005)
```

Anon-RPC hides who you are. It doesn't hide what you ask.

Your wallet

Asks about the whale it follows.

```
getBalance(0xC2D7…)
```

Mixnet
IP hidden

Mixnet exit

Forwards the request as is.

Same question

RPC node

Doesn't know who asked.

Still learns which address matters, every block.

The request itself is the leak.

Never ask about an address.

Every request goes through Anon-RPC, and none of them names a wallet.

One relay

Same blocks for everyone.

Fetched once, downloaded by block number.

```
block 12,080,193
```

On your phone

Every block is checked.

Header, access list, receipts, and a second provider.

On your phone

Filtered locally.

Your wallets and the whales you follow never leave the device.

Lookups

Private by PIR.

The server works over every record and can't tell which one you read.

How a block reaches your phone

Relay

Fetches block N once.

Header, EIP-7928 access list, receipts. Same bytes for everyone.

Anon-RPC
Nox or Nym

Your device

Checks, then filters.

- ✓ header hash
- ✓ access list
- ✓ receipts root
- ✓ 2nd provider

On device

You

Alerts, balances, copy trade.

Lookups use PIR: the server sees ciphertexts, not an address.

The relay and the PIR server don't need to be trusted. The phone does the checking.

Blindspot

One core, many trading tools

Live today

Copy trading

Follow 0xC2D7..., copy its swap with one tap.

Live today

Wallet watching and alerts

Pending in seconds, verified within a block.

Live today

Private portfolio

Balances straight from verified blocks.

Live today

Private lookups

Any wallet's balance and history through PIR.

Partly private

Trade preparation

Your IP is hidden. The quote's pair and size are not, yet.

In the repo

The same core as an SDK

```
follow({ rpc, anchor, onBlock })
```

packages/sdk, a few lines to verify blocks.

The anchor example in this deck is live; the rest is the same core.

What each one learns, from real requests

Normal RPC

2 + IP

addresses, plus your IP on every request

Anon-RPC alone

2

addresses. Your IP is hidden.

Blindspot

0

addresses. Block numbers only.

Same blocks for every user, so the relay can't tell users apart.

98.7%

of requests through Anon-RPC (230 of 233, Nov 7)

~6 s

pending alert after a whale's swap

~20 s

verified alert, once the block lands

3–5 s

private balance lookup through the mixnet

Live on Sepolia

Demo

Watch a whale, get the alert, copy the trade, look up a wallet privately, and see what each provider learns.

Limits, and what's next

Today

- Sepolia only, until block access lists reach mainnet.
- Private lookup covers about 1,000 addresses.
- Alerts need the app open, or Watch mode on a phone.
- Copy trades are public once they land.

Next

- A light client. Lodestar already serves the sync-committee data we need.
- Faster PIR (SimplePIR or YPIR) for every active address.
- Local quotes from verified pool state, so a quote names nothing.
- A passkey wallet instead of a browser key.

All of it is in the README, with the numbers.

Blindspot

Thank you.

Anon-RPC hides who you are. Blindspot also hides what you watch.
Built bina pooche: without asking.

useblindspot.xyz →

github.com/skartik-sk/blindspot