DMS Import CCI XML Guide

Version 0.4

UDVIKLINGS OG FORENKLINGS STYRELSEN

Version control		
Version	**Date**	**Change**
0.1	**07-01-2026**	**Initial version – Clone of DMS Import XML Guide v1.18**
0.2	**27-01-2026**	**Adjustments to align with CCI declaration structure.**
0.3	**12-02-2026**	**Corrected with a list of disclaimers for limitation.**
0.4	**16-02-2026**	**Cleaned out change chases – added Submitter way.**

Limitation Disclaimer

This document has been prepared in parallel with the provision of the solution, which means that the examples presented are only of a purely theoretical nature. Additionally, due to the past layoff of key resources, insight into the solution has been limited. Since CCI has many similarities to traditional import, the document is based on a copy of the Import XML Guide. It is assumed that several elements do not differ significantly from how they are used in traditional Import.

Sections where clarification is pending:

- Declaration type/Additional declaration type
- Previous Document
- Supporting Document
- Calculation of taxes
- Duties and Taxes
- Deferred payment

Table of Contents

Limitation Disclaimer 1

1. The aim of this document 4

2. Glossary 6

3. Footnotes 8

4. Overall structures 11
Declaration Level 12
Goods Shipment Level 13
Goods Shipment Consignment Level 14
Goods Shipment Item Level 15

5. System specific fields 16
Language Code 17
Supervising customs office 18
MRN 19
Submitter 20
Extension 21

6. Group 11 – Message information (including procedure codes) 24
Declaration type/Additional declaration type 25
Declaration goods item number 26
Procedure 27
Additional procedure 28

7. Group 12 – References of messages, documents, certificates, authorizations 29
Previous Document 30
Additional Information 32
Supporting Document 33
Additional Reference 35
Transport Document 36
Reference number/UCR 37
LRN 38
Warehouse 39
Authorisation 40

8. Group 13 - Parties 41
Exporter 42
Importer 43
Declarant 44
Seller 46
Representative (Agent) 47
Buyer 49
Additional Supply Chain Actor 50
Additional fiscal reference 51
Person providing a guarantee (Surety) 52
Person paying the customs duty 53

9. Group 14 - Valuation information/Taxes 54
Delivery Terms 55
Calculation of taxes 56
Duties and Taxes 57
Additions and deductions 59
Valuation Indicators 60
Total Amount Invoiced 61
Deferred payment 62
Item Amount Invoiced 63
Exchange Rate 64
Valuation method 65

10. Group 15 - Dates – Times – Periods 66
Date of acceptance 67

11. Group 16 - Places/Countries/Regions 68
Country of destination 69
Country of dispatch 70
Origin (Country of Origin) 71
Location of goods 72

12. Group 17 – Customs Offices 76
Customs office of presentation 77
Supervising customs office 78

13. Group 18 – Goods identification 79
Goods Measure (Net Mass) 80
Goods Measure (Supplementary Units) 81
Goods Measure (Gross Mass) 82
Description of goods 83
Packaging 84
Commodity code (CUS Code) 85
Commodity code (Harmonized system sub-heading code) 86
Commodity code (Combined nomenclature code) 87
Commodity code (TARIC code) 88
Commodity code (TARIC additional code) 89
Commodity code (National Additional Code) 90
Container indicator 92
Mode of Transport at the Border 93
Arrival Transport Means (Inland mode of transport) 94
Arrival Transport Means (identification info) 95
Transport equipment 96
Active Border Transport Means 97

14. Group 99 – Goods identification 98
Quota order number 99
Guarantee 100
Guarantee reference (ObligationGuarantee) 101
Nature of Transaction 103
Statistical value 104

The aim of this document

1

The aim of this document is to give an in-depth description of the different fields and data elements contained in the XSD-files for Import CCI declarations based on the EU Customs Data Model - https://eucdm.softdev.eu.com/

The document is structured after the EUCDM grouping of the data elements as well as DMS-specific data fields that are required by the system when using the S2S solution:

- **System-specific fields**: This section includes fields that are needed by the system to recognize what declaration is sent in, who is submitting the declaration, as well other data that is needed to fulfill the desired action.
- **Group 11**: This section contains basic information about the declaration and which procedures the declaration should be processed under. All this information influences how the declaration is processed, what kind of business scenario and procedure to be expected and requested.
- **Group 12**: This section is for the submitter to present all other relevant information and documents related to the submitted declaration that is not contained in the data fields. This is especially used for references tracking documents, authorizations and supplying tracking numbers.
- **Group 13**: This section contains information on all parties involved in the Import procedure. It is here information on the importer, exporter, declarant, fiscal reference, representative, etc., is provided either by ID or other identifiable information depending on whether the party is a company or private person.
- **Group 14**: In this section valuation information is given, examples of valuations are: taxes, transportation costs, delivery terms, etc.
- **Group 16**: This section contains the location-related information, e.g., where the goods will be or are presented (depending on whether it is a pre-lodged or a standard declaration) as well as the countries involved in the export/exit process.
- **Group 17**: This section contains information regarding which customs offices have handled the goods in the export/exit process.
- **Group 18**: In this section the submitter supplies more detailed information on the goods item(s) such as a weight, description, Taric code(s), etc.
- **Group 19**: This section contains information about the form of transport of goods, e.g., modes, container information, equipment, etc.
- **Group 99**: This section contains other information in the declarations which does not fit into the other above-mentioned groups.

Under each data element in the groups is provided a detailed description on whether the field is mandatory or optional as well as what rules to adhere to depending on the desired business scenario to make use of, and XML-examples are provided to give context.
Information on the EUCDM ID6 reference code is provided to help the reader in seeking further information if needed.

Additionally, under some of the data element you will see codelist or rulecode codes identifying codes and rules for this element. These elements are relevant under the transitional period of the new system, and you can identify them in the Codelists.xslx or Rulecodelist.xlsx sheets found on GitHub. The first document can be used to identify the CLxxx errors, and the second document can be used to identify the rest. If there is an error not presented in comments of the data elements, or you cannot find it in the code-/rulecodelist sheets, please contact the Danish Customs Agency for further assistance on the subject.

Glossary

2

To make the document shorter and easier to read, some abbreviations are used. Here is a list of the abbreviations used in this document.

Abbreviation	Description	Details
M	Mandatory	The field is mandatory to declare.
O	Optional	The field is optional to declare or should only be declared if relevant information is available.
MC	Conditionally mandatory	The information is mandatory dependent on other information given in the declaration, e.g., type of declaration or commodity code.
DL	Declaration level	The information is given on header level and applies to all the goods items in the declaration.
GSL	Goods shipment level	The information is given on goods shipment level and applies to all the goods items in the goods shipment.
GIL	Goods item level	The information is given on goods item level and applies to only the goods item it is declared under.
C/A	Defines whether an element can be corrected or amended	Yes/Yes means can be corrected and amended. Yes/No means it can be corrected but not amended No/Yes means it can't be corrected but it can be amended No/No means it can't be corrected or amended
EUCDM	European Union Customs Data Model	The European Union Customs Data Model (EUCDM) is the model for Customs trans-European systems such as NCTS, AES, ICS, EOS and for Member States national customs clearance systems
XSD	XML Schema Definition	A document that specifies how to formally describe the elements in an Extensible Markup Language (XML) document. This description can be used to verify that each item of content in a document adheres to the description of the element in which the content is to be placed.
XML	Extensible Markup Language	A simple text-based format for representing structured information, storing, and sending data. It is the file format used to send declarations to DMS.
n/a	Not Applicable	The information does not apply to the given element/declaration.
Requirement Overview	Mandatory / Optional / Conditionally mandatory / Levels / Rules	Defines whether an element is M, O, MC (see abbreviations above) or whether any EUCDM rules apply to the given element in a specific declaration.
M/O	Defines whether a field is mandatory or optional when the main field is in the XML Mandatory/Optional	For a lot of input fields, the sub elements of that field are not always mandatory even though the overall input field is. For example, is Supporting Document which is optional, but when put into to an XML, SequenceNumeric and ID becomes mandatory as the only elements.
ND	Not Determined	The mandatory or optional status of these elements are not yet determined.

Footnotes

3

Throughout the XML-Guide you will see several footnotes, all of these refers to this table. All these footnotes can also be found on EUCDM.

FOOTNOTE	DESCRIPTION
[1]	This information shall not be required in case a customs declaration has been lodged prior to the presentation of the goods pursuant to Article 171 of the Code.
[2]	In the cases where Article 166(2) of the Code (simplified declarations based on authorizations) is applicable, Member States may waive the obligation to provide this information where the conditions prescribed in the authorizations associated with the procedures concerned allow them to defer the collection of this data element in the supplementary declaration.
[4]	This information needs to be provided only where Article 166(2) of the Code (simplified declarations based on authorizations) is applicable; in this case, it is the number of the authorization for simplified procedure. However, this data element can also contain the transport document number concerned.
[5]	This information is only required where the declaration of placing of goods under a customs procedure is used to discharge a customs warehousing procedure.
[6]	Where the EORI number or a third country unique identification number recognized by the Union is provided, the name and address shall not be provided.
[10]	Member States may waive this information where the customs value of the goods in question cannot be determined under the provisions of Article 70 of the Code. In such cases the declarant shall furnish or cause to be furnished to the customs authorities such other information as may be requested for the purposes of determining the customs value.
[11]	This information is not to be provided when customs administrations calculate duties on behalf of economic operators on the basis of information elsewhere in the declaration. It is otherwise optional for the Member States.
[12]	This information is not required for goods eligible for relief from import duties, unless the customs authorities consider it necessary for the application of the provisions governing the release for free circulation of the goods concerned.
[13]	This information is not to be provided when customs administrations calculate duties on behalf of economic operators on the basis of information elsewhere in the declaration.
[14]	Except where it is essential for the correct determination of the customs value, the Member State of acceptance of the declaration shall waive the obligation to provide this information, if any of the following is the case: • where the customs value of the imported goods in a consignment does not exceed EUR 20.000 provided that they do not constitute split or multiple consignments from the same consignor to the same consignee, • where the importation is of a non-commercial nature • in case of continuing traffic in goods supplied by the same seller to the same buyer under the same commercial conditions.
[15]	Member States may require this information only in cases when the rate of exchange is fixed in advance by a contract between the parties concerned.
[20]	This information is required where: a) no preferential treatment is applied or b) the country of non-preferential origin is different to the country of preferential origin.
[22]	This information shall only be used in case of centralized clearance.
[23]	This information shall only be used in case the declaration for temporary storage or the customs declaration to place the goods under a special procedure other than transit is lodged at a

	customs office different to the supervising customs office as indicated in the respective authorization.
[24]	This information shall only be required in case of commercial transactions involving at least two Member States.
[25]	This information shall only be provided for entry into the declarants' records and only if the discharge of the goods under temporary storage concerns only parts of the declaration for temporary storage lodged previously in relation with the goods concerned.
[32]	This data element does not have to be provided where the import formalities are carried out at the point of entry into the customs territory of the Union.
[34]	Not for use in the case of postal consignments or carriage by fixed transport installations.
[37]	Not for use in the case of postal consignments or carriage by fixed transport installations or rail.
[39]	This information shall only be required where the release of the goods is subject to the provision of a comprehensive guarantee.
[40]	The Member State of acceptance of the declaration may waive the obligation to provide this information where it is in the position to assess it correctly and has implemented calculation routines to provide a result compatible with statistical requirements.
[41]	This data element shall only be used in the context of a supplementary declaration for Entry into the declarant's records.
[54]	This information is not required: a) when the goods are declared for release for free circulation under the special scheme for distance sales of goods imported from third countries and territories set out in Title XII Chapter 6 Section 4 of Directive 2006/112/EC; or b) when the goods are of a non-commercial character sent from a third country by private persons to other private persons in a Member State and exempt from VAT pursuant to Article 1 of Council Directive 2006/79/EC (1).
[57]	This information is not required in cases of multiple goods packed together and for postal consignments.
[58]	For Centralized Clearance at Import where more than one MS is involved, the information relating to the national codes shall be provided for the Authorizing and Presentation MS.
[60]	This data element is to be provided when an authorization exists according to the relevant section of Annex A to this Regulation, Title I Chapter 1.
[62]	This information shall relate to the situation at the moment when the declaration is made.
[63]	This information shall be provided for decisions relating to binding information.
[66]	EORI number or third country unique identification number (TCUIN) shall be declared, where available.
[73]	This information shall be provided in the case of end-use authorization.
[84]	This information shall not be provided where it relates to a customs declaration in postal traffic for release for free circulation.
[85]	This information shall not be provided where it relates to a customs declaration for release for free circulation in respect of a consignment which benefits from a relief from import duty in accordance with Article 23(1) or Article 25(1) of Regulation (EC) No 1186/2009.

Overall structures

4

Declaration Level

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
No/No	M DL	M DL	M DL	M DL	M DL	M DL	M DL	**Basepath: Declaration**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
None	Declaration	n/a	M	
None	Extensions	n/a	O	
None	ImportOperation	n/a	M	R0907
12 12 000 000	Authorisation	n/a	M	R0932
17 09 000 000	CustomsOfficeOfPresentation	n/a	M	R0907
17 10 000 000	SupervisingCustomsOffice	n/a	O	G0631
13 04 000 000	Importer	n/a	M	
13 05 000 000	Declarant	n/a	M	R0907
13 20 000 000	PersonProvidingAGuarantee	n/a	MC	R0995 C0824
13 21 000 000	PersonPayingCustomsDuty	n/a	MC	R0995 C0809
13 06 000 000	Representative	n/a	O	R0907
99 00 000 000	Guarantee	n/a	MC	S0014 C0616 C0697
14 17 000 000	CurrencyExchange	n/a	O	G0405
12 10 000 000	DeferredPayment	n/a	MC	C0697
None	GoodsShipment	n/a	M	R0764

Description:

This is the overall structure at declaration level.

Goods Shipment Level

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
No/No	M GSL	M GSL	M GSL	M GSL	M GSL	M GSL	M GSL	**GSL:** Declaration/**GoodsShipment**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
None	GoodsShipment	n/a	M	R0764
None	sequenceNumber	n..5	M	R0987
99 05 000 000	natureOfTransaction	n..2	MC	R0012 S0031 G0642 G0984 C0002 C0627 C0715 CL091
14 06 000 000	totalAmountInvoiced	n..16,2	MC	C0619
14 05 000 000	invoiceCurrency	a3	MC	G0907 G0921 C0921 CL352
15 09 000 000	dateOfAcceptance	an19	MC	G0981 C0739
None	exchangeRate	n..12,5	O	G0656
13 14 000 000	AdditionalSupplyChainActor	n/a	O	G0642 G0654
13 09 000 000	Buyer	n/a	MC	R0012 G0642 G0671 C0728
13 08 000 000	Seller	n/a	MC	R0012 G0642 G0672 C0728
13 01 000 000	Exporter	n/a	MC	S0029 G0642 C0002 C0618
14 01 000 000	DeliveryTerms	n/a	MC	S0016 C0738 C0729 C0627
16 06 000 000	CountryOfDispatch	n/a	MC	R0012 S0028 G0642 C0002 C0654
16 04 000 000	Destination	n/a	MC	S0027 G0642 C0002 C0627
12 11 000 000	Warehouse	n/a	MC	S0017 G0999 C0625 C0626 C0829 C0853
12 01 000 000	PreviousDocument	n/a	O	G0007
12 03 000 000	SupportingDocument	n/a	O	G0007
12 04 000 000	AdditionalReference	n/a	O	G0007 G0918
12 02 000 000	AdditionalInformation	n/a	O	G0007
14 04 000 000	AdditionsAndDeductions	n/a	MC	R0010 G0616 G0620 G0642 C0938
13 16 000 000	AdditionalFiscalReference	n/a	MC	G0642 G0880 C0834
None	Consignment	n/a	M	
None	GoodsShipmentItem	n/a	M	

Description:

This is the overall structure at goods shipment level.

Goods Shipment Consignment Level

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
No/No	M GSL	M GSL	M GSL	M GSL	M GSL	M GSL	M GSL	**GSL:** Declaration/GoodsShipment/**Consignment**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
None	Consignment	n/a	M	
19 04 001 000	inlandModeOfTransport	n1	MC	G0641 C0625 CL018
19 03 001 000	modeOfTransportAtTheBorder	n1	MC	S0003 C0630 C0627 CL018
18 04 001 000	grossMass	n..16,6	O	G0905
12 08 001 000	referenceNumberUCR	an..35	O	
19 07 000 000	TransportEquipment	n/a	O	G0922
16 15 000 000	LocationOfGoods	n/a	MC	S0024 C0628 C0810
19 06 000 000	ArrivalTransportMeans	n/a	MC	S0009 G0925 C0623 C0646
19 08 000 000	ActiveBorderTransportMeans	n/a	MC	S0020 C0810 C0931
12 05 000 000	TransportDocument	n/a	O	G0007

Description:

This is the overall structure at goods shipment consignment level.

Goods Shipment Item Level

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
No/No	M GIL	M GIL	M GIL	M GIL	M GIL	M GIL	M GIL	**GIL:** Declaration/GoodsShipment/**GoodsShipmentItem**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
None	GoodsShipmentItem	n/a	M	
11 11 001 000	declarationGoodsItemNumber	n..5	M	R0007
11 03 000 000	goodsItemNumber	n..5	MC	R0767 C0731
99 06 000 000	statisticalValue	n..16,2	MC	S0003 G0651 C0627 C0630
99 05 000 000	natureOfTransaction	n..2	MC	R0012 S0031 G0642 G0984 C0002 C0627 C0715 CL091
12 08 000 000	referenceNumberUCR	an..35	O	
12 12 000 000	Authorisation	n/a	MC	R0010 G0930 C0934
11 09 000 000	Procedure	n/a	M	
13 14 000 000	AdditionalSupplyChainActor	n/a	O	G0642 G0654
13 09 000 000	Buyer	n/a	MC	R0012 G0642 G0671 C0728
13 08 000 000	Seller	n/a	MC	R0012 G0642 G0672 C0728
13 01 000 000	Exporter	n/a	MC	S0029 G0642 C0002 C0618
16 08 000 000	Origin	n/a	MC	C0710
16 06 000 000	CountryOfDispatch	n/a	MC	R0012 S0028 G0642 C0002 C0654
16 03 000 000	Destination	n/a	MC	S0027 G0642 C0002 C0627
18 05 000 000	Commodity	n/a	M	
18 06 000 000	Packaging	n/a	M	
12 01 000 000	PreviousDocument	n/a	O	R0010 G0007
12 03 000 000	SupportingDocument	n/a	O	G0007
12 05 000 000	TransportDocument	n/a	O	G0007
12 04 000 000	AdditionalReference	n/a	O	G0007 G0918
12 02 000 000	AdditionalInformation	n/a	O	G0007
14 10 000 000	CustomsValuation	n/a	MC	C0940
14 15 000 000	TransportAndInsur-anceCostsToTheDestination	n/a	O	
14 07 000 000	ValuationAdjustment	n/a	MC	G0616 G0620 C0624
13 16 000 000	AdditionalFiscalReference	n/a	MC	R0010 G0642 G0880 C0834

Description:

This is the overall structure at goods shipment item level.

System specific fields

4

Language Code

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
No/No	M DL	M DL	M DL	M DL	M DL	M DL	M DL	**Basepath:** Declaration/**languageCode**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
None	languageCode	a2	M	R0932 R0933 R0998 G0920 G0930 CL012

Description:

This data element is used to specify the language used in various description fields.

Rules/codes/other relevant information:

XML-examples:

```
<ns3:languageCode>dk</ns3:languageCode>
```

Supervising customs office

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
No/No	M DL	M DL	M DL	M DL	M DL	M DL	n/a	**Basepath:** Declaration/**SupervisingCustomsOffice**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
17 10 000 000	SupervisingCustomsOffice	n/a	O	G0631
17 10 001 000	referenceNumber	an8	M	CL141

Description:

This element is used to define the office of lodgment.

Rules/codes/other relevant information:

Customs office IDs can be found here.

referenceNumber (17 10 001 000):
For Denmark, this will always be DK004700 – Århus.

XML-examples:

```
<ns3:SupervisingCustomsOffice>
  <ns3:referenceNumber>DK004700</ns3:referenceNumber>
</ns3:SupervisingCustomsOffice>
```

MRN

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
No/No	MC DL	MC DL	MC DL	MC DL	MC DL	MC DL	MC DL	**Basepath:** Declaration/ImportOperation/**MRN**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
None	ID	an18	MC	

Description:

The MRN is automatically generated following the EUCDM legislation as a unique combination of 18 characters. The MRN is created by the Customs agency and is sent as part of the validation acceptance.

Rules/codes/other relevant information:

This element is used in all declarations and only used in the following additional messages: correction, amendment, invalidation, invalidation and repayment remission (4c), repayment remission, goods presentation, and supplementary declarations.

The combination of the 18 characters is as follows:

- The last two digits of the year of formal acceptance of the declaration (e.g., '23' for 2023)
    - Consist of 2 digits
- 2. Country where the declaration/proof of the customs status of union goods/notification is lodged (e.g., 'DK' for Denmark)
    - Consist of 2 letters
- 3. Unique identifier based on year and country (e.g., 21DK04K21LO1)
    - Consist of 12 alphanumeric characters
- 4. Procedure identifier (see tables below)
    - Consist of 1 letter
- 5. Check digit (e.g., '6')
    - Consist of 1 alphanumeric character

The following table explains what the digit for the procedure identifier will be:

Code	Procedures	Declarations
R	Import	H1, H2, H3, H4, I1
V	Import	H5
8	Import – Presentation of goods	I2

XML-examples:

```
<ns3:MRN>22DKRQSJFGGNIY8VR1</ns3:MRN>
```

Submitter

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
No/No	M EXT	M EXT	M EXT	M EXT	M EXT	M EXT	M EXT	**Basepath:** Declaration/**Extension**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
None	Submitter	n/a	M	
None	Name	an..70	M	
None	ID	an..17	M	
None	TypeCode	n1	O	

Description:

The name and identifier of the company submitting the declaration.

Rules/codes/other relevant information:

Name: The **CVR/SE-number** to which the client certificate is registered.

ID: The **CVR/SE-number** to which the client certificate is registered.

TypeCode: The type of person submitting the declaration to Customs authorities.

Submitter is not a part of EUCDM, so it must be declared using the extension – shown in the example.

XML-examples:

```
<ns3:Extensions>
  <ns4:SequenceNumeric>1</ns3:SequenceNumeric>
  <ns4:Key>SUBMITTER</ns3:Key>
  <ns4:Value>object</ns3:Value>
  <ns4:DataType>object</ns3:DataType>
  <ns4:Extensions>
    <ns4:SequenceNumeric>1</ns3:SequenceNumeric>
    <ns4:Key>Submitter.Name</ns3:Key>
    <ns4:Value>99999981</ns3:Value>
    <ns4:DataType>text</ns3:DataType>
  </ns4:Extensions>
  <ns4:Extensions>
    <ns4:SequenceNumeric>2</ns3:SequenceNumeric>
    <ns4:Key>Submitter.ID</ns3:Key>
    <ns4:Value>99999981</ns3:Value>
    <ns4:DataType>text</ns3:DataType>
  </ns4:Extensions>
  <ns4:Extensions>
    <ns4:SequenceNumeric>3</ns3:SequenceNumeric>
    <ns4:Key>Submitter.TypeCode</ns3:Key>
    <ns4:Value>6</ns3:Value>
    <ns4:DataType>text</ns3:DataType>
  </ns4:Extensions>
</ns3:Extensions>
```

Extension

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
No/No	O DL	O DL	O DL	O DL	O DL	O DL	O DL	**Basepath:** Declaration/**Extension**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
None	Extensions	n/a	O	
None	SequenceNumeric	n..5	M	
None	ID	an..	O	
None	Key	an..	M	
None	Value	an..	M	
None	DataType	an..8	M	Enumeration: object text numeric decimal date dateTime
None	Extensions	n/a	O	Reference to repetition of present group.

Description:

Fields used to validate Ship supplies/Victualling.

Rules/codes/other relevant information:

All elements **needs** to be here in order to validate Extensions fields. I.e. you need all 15 extensions to have them validated.
If a data field is not relevant for the declaration, write in "0" instead of a value, in the value element.

The data element "Value" is the only one you should change. See descriptions of what each Key element means, in the table below

Meaning	Value
Vehicle driver	VEHC_DRIVER
Vehicle Type	VEHC_TYPE
Home Port	HOME_PORT
Destination of Expedition (Route)	DEST_EXP_R
Duration of expedition	DUR_EXP
Place of loading	PLACE_UNLO
Number of crew	NR_CREW
Liquor – Amount of bottles/liters	LIQ_AMOUNT
Wine – Amount of bottle/liters	WINE_AMOUNT
Cigarettes (units)	CIGARETTE_U
Cigars and Cheroots (units)	CIGAR_U
Tobacco (kilograms)	TOBAC_KG
Beer (bottles/cans)	BEER_AMOUNT
Other supply	OTHER_SUP
Description of desired Victualling	DESC_DES_VIC

XML-examples:

```
<ns2:Extensions>
    <ext:SequenceNumeric>1</ext:SequenceNumeric>
    <ext:ID>IDVALUE42</ext:ID>
    <ext:Key>VEHC_DRIVER</ext:Key>
    <ext:Value>1</ext:Value>
    <ext:DataType>text</ext:DataType>
</ns2:Extensions>
```

```
<ns2:Extensions>
    <ext:SequenceNumeric>2</ext:SequenceNumeric>
    <ext:ID>IDVALUE420</ext:ID>
    <ext:Key>VEHC_TYPE</ext:Key>
    <ext:Value>TYPE</ext:Value>
    <ext:DataType>text</ext:DataType>
</ns2:Extensions>
<ns2:Extensions>
    <ext:SequenceNumeric>3</ext:SequenceNumeric>
    <ext:ID>IDVALUE4200</ext:ID>
    <ext:Key>HOME_PORT</ext:Key>
    <ext:Value>PORT Aalborg</ext:Value>
    <ext:DataType>text</ext:DataType>
</ns2:Extensions>
<ns2:Extensions>
    <ext:SequenceNumeric>4</ext:SequenceNumeric>
    <ext:ID>IDVALUE42000</ext:ID>
    <ext:Key>DEST_EXP_R</ext:Key>
    <ext:Value>København</ext:Value>
    <ext:DataType>text</ext:DataType>
</ns2:Extensions>
<ns2:Extensions>
    <ext:SequenceNumeric>5</ext:SequenceNumeric>
    <ext:ID>IDVALUE43</ext:ID>
    <ext:Key>DUR_EXP</ext:Key>
    <ext:Value>125</ext:Value>
    <ext:DataType>text</ext:DataType>
</ns2:Extensions>
<ns2:Extensions>
    <ext:SequenceNumeric>6</ext:SequenceNumeric>
    <ext:ID>IDVALUE44315</ext:ID>
    <ext:Key>PLACE_UNLO</ext:Key>
    <ext:Value>Aalborg</ext:Value>
    <ext:DataType>text</ext:DataType>
</ns2:Extensions>
<ns2:Extensions>
    <ext:SequenceNumeric>7</ext:SequenceNumeric>
    <ext:ID>IDVALUE4215413</ext:ID>
    <ext:Key>NR_CREW</ext:Key>
    <ext:Value>20</ext:Value>
    <ext:DataType>text</ext:DataType>
</ns2:Extensions>
<ns2:Extensions>
    <ext:SequenceNumeric>8</ext:SequenceNumeric>
    <ext:ID>IDVALUE4fewfw2</ext:ID>
    <ext:Key>LIQ_AMOUNT</ext:Key>
    <ext:Value>484</ext:Value>
    <ext:DataType>text</ext:DataType>
</ns2:Extensions>
```

```
<ns2:Extensions>
    <ext:SequenceNumeric>9</ext:SequenceNumeric>
    <ext:ID>IDVALUEeqwfeqw42</ext:ID>
    <ext:Key>WINE_AMOUNT</ext:Key>
    <ext:Value>15</ext:Value>
    <ext:DataType>text</ext:DataType>
</ns2:Extensions>
<ns2:Extensions>
    <ext:SequenceNumeric>10</ext:SequenceNumeric>
    <ext:ID>IDVALUEf32f2342</ext:ID>
    <ext:Key>CIGARETTE_U</ext:Key>
    <ext:Value>54</ext:Value>
    <ext:DataType>text</ext:DataType>
</ns2:Extensions>
<ns2:Extensions>
    <ext:SequenceNumeric>11</ext:SequenceNumeric>
    <ext:ID>IDVALUE42df2qfqe</ext:ID>
    <ext:Key>CIGAR_U</ext:Key>
    <ext:Value>4</ext:Value>
    <ext:DataType>text</ext:DataType>
</ns2:Extensions>
<ns2:Extensions>
    <ext:SequenceNumeric>12</ext:SequenceNumeric>
    <ext:ID>IDVALUE42d1d12</ext:ID>
    <ext:Key>TOBAC_KG</ext:Key>
    <ext:Value>7</ext:Value>
    <ext:DataType>text</ext:DataType>
</ns2:Extensions>
<ns2:Extensions>
    <ext:SequenceNumeric>13</ext:SequenceNumeric>
    <ext:ID>IDVALUE4221341421</ext:ID>
    <ext:Key>BEER_AMOUNT</ext:Key>
    <ext:Value>74</ext:Value>
    <ext:DataType>text</ext:DataType>
</ns2:Extensions>
<ns2:Extensions>
    <ext:SequenceNumeric>14</ext:SequenceNumeric>
    <ext:ID>IDVALUE4d3d332</ext:ID>
    <ext:Key>OTHER_SUP</ext:Key>
    <ext:Value>0</ext:Value>
    <ext:DataType>text</ext:DataType>
</ns2:Extensions>
<ns2:Extensions>
    <ext:SequenceNumeric>15</ext:SequenceNumeric>
    <ext:ID>few2few</ext:ID>
    <ext:Key>DESC_DES_VIC</ext:Key>
    <ext:Value>86</ext:Value>
    <ext:DataType>text</ext:DataType>
</ns2:Extensions>
```

Group 11 – Message information (including procedure codes)

5

Declaration type/Additional declaration type

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
No/No	M DL	M DL	M DL	M DL	M DL	M DL	M DL	**Basepath:** Declaration/**ImportOperation**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
11 01 001 000	declarationType	an..5	M	CL231
11 02 001 000	additionalDeclarationType	a1	M	CL042

Description:

Indicates what type of action is intended: submission of a pre-lodged/standard, a correction/amendment request or an invalidation/invalidation and repayment request.

Rules/codes/other relevant information:

declarationType (11 01 001 000):

- 'IM' for submitting an import declaration
- 'CO' for submitting a correction/amendment
- 'IN' for submitting an invalidation or invalidation 4c
- 'RR' for submitting a repayment and remission
- 'GP' for presenting goods declared on a pre-lodged declaration
- 'SU' for supplementing a simplified declaration

additionalDeclarationType (11 02 001 000):

- 'A' for submitting a standard declaration
- 'D' for submitting a pre-lodged declaration

For Codelist information, see codelist excel sheet found on GitHub.

For additional messages:
The codes to declare in this field for **additional messages**:

- 'COR' for sending a correction or amendment request to an already existing declaration
- 'INV' for sending an invalidation or invalidation and repayment request to an already existing declaration
- 'RRA' for sending a repayment and remission request to an already existing declaration
- 'GPR' for presenting goods to an already existing pre-lodged declaration
- 'SUP' for supplementing a simplified export declaration

See the list of explanations in Bilag in the section called "Fælles stamdataliste" on the page https://skat.dk/data.aspx?oid=3064

Or on EUCDM, using the ID6 number as search:
https://eucdm.softdev.eu.com/Archive/EUCDM%206.1/EN/EUCDM/Annex-B/e21.htm

XML-examples:

```
<ns3:declarationType>IM</ns3:declarationType>
<ns3:additionalDeclarationType>A</ns3:additionalDeclarationType>
```

Declaration goods item number

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
No/No	M GIL	M GIL	M GIL	M GIL	M GIL	M GIL	M GIL [1]	**GIL**: Declaration/GoodsShipment/GoodsShipmentItem/**declarationGoodsItemNumber**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
None	GoodsShipmentItem	n/a	M	
11 11 001 000	declarationGoodsItemNumber	n..5	M	R0007

Description:

Sequence number of the goods item

Rules/codes/other relevant information:

declarationGoodsItemNumber (11 11 001 000):
Each 'Goods Item Number' is unique throughout the declaration. The items shall be numbered in a sequential fashion, starting from '1' for the first item and incrementing the numbering by '1' for each following item.

For **11 03 001 000** footnote **[1]** applies to **I2** declarations.

XML-examples:

Example of multiple GoodsShipmentItem instances in sequence:

```
<ns3:GoodsShipmentItem>
  <ns3:declarationGoodsItemNumber>1</ns3:declarationGoodsItemNumber>
  ...
</ns3:GoodsShipmentItem>

<ns3:GoodsShipmentItem>
  <ns3:declarationGoodsItemNumber>2</ns3:declarationGoodsItemNumber>
  ...
</ns3:GoodsShipmentItem>

<ns3:GoodsShipmentItem>
  <ns3:declarationGoodsItemNumber>3</ns3:declarationGoodsItemNumber>
  ...
</ns3:GoodsShipmentItem>

<ns3:GoodsShipmentItem>
  <ns3:declarationGoodsItemNumber>4</ns3:declarationGoodsItemNumber>
  ...
</ns3:GoodsShipmentItem>
```

Procedure

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
No/No	M GIL	M GIL	M GIL	M GIL	M GIL	M GIL	M GIL [1]	**GIL**: Declaration/GoodsShipment/GoodsShipmentItem/**Procedure**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
11 09 000 000	Procedure	n/a	M	
11 09 001 000	requestedProcedure – [1]	an2	M	CL092
11 09 002 000	previousProcedure – [1]	an2	M	The procedure under which the goods were placed before being placed under the requested procedure. CL093

Description:

The procedure code for which the goods are declared.

Rules/codes/other relevant information:

requestedProcedure (11 09 001 000):
Fill in the requested procedure under which the goods should be placed.

previousProcedure (11 09 002 000):
Fill in the previous procedure for which the goods previously have been placed.

Valid combinations for requested and previous procedures can be found here: toldst.dk/e
For **11 09 001 000** and **11 09 002 000** footnote **[1]** applies to **I2** declarations.

XML-examples:

```
<ns3:Procedure>
  <ns3:requestedProcedure>10</ns3:requestedProcedure>
  <ns3:previousProcedure>00</ns3:previousProcedure>
</ns3:Procedure>
```

Additional procedure

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
No/No	M GIL [58]	M GIL [58]	M GIL [58]	M GIL [58]	M GIL [58]	M GIL [2] [58]	n/a	**GIL**: Declaration/GoodsShipment/GoodsShipmentItem/Procedure/**AdditionalProcedure**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
11 10 000 000	AdditionalProcedure	n/a	M	
None	sequenceNumber	n..2	M	
11 10 001 000	additionalProcedure – [2]	an3	M	CL457
None	ccQualifier	a2	MC	R0906 G0921 C0917 CL010

Description:

The additional procedure for which the goods are declared. Additional procedure is created re-using the 'Procedure' element but use only requestedProcedure instead of having both.

Rules/codes/other relevant information:

It is **mandatory** to declare at **least one additional procedure** but up to two additional procedures can be declared.

sequenceNumber:
To refer to multiple procedures, repeat this element the required number of times and fill here sequentially starting at 1.

additionalProcedure (11 10 001 000):
Fill in the additional procedure code.

ccQualifier:
The field is used to identify which country (SCI / PCI) a given national subsection applies to when it concerns validation and handling. If common codes from CS/RD2 are used that apply to both countries, the field should be omitted.

For Codelist information, see codelist excel sheet found on GitHub.

For **11 10 001 000** footnote **[2]** applies to **I1** declarations.

XML-examples:

```
<ns3:AdditionaProcedure>
  <ns3:sequenceNumber>1</ns3:sequenceNumber>
  <ns3:additionalProcedure>000</ns3:additionalProcedure>
  <ns3:ccQualifier>DK</ns3:ccQualifier>
</ns3:AdditionaProcedure>
<ns3:AdditionaProcedure>
  <ns3:sequenceNumber>2</ns3:sequenceNumber>
  <ns3:additionalProcedure>100</ns3:additionalProcedure>
  <ns3:ccQualifier>NL</ns3:ccQualifier>
</ns3:AdditionaProcedure>
```

Group 12 – References of messages, documents, certificates, authorizations

Previous Document

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GSL GIL	MC GSL GIL	MC GSL GIL	MC GSL GIL	MC GSL GIL	MC GSL GIL [2]	MC GSL GIL	**GSL:** Declaration/GoodsShipment/**PreviousDocument** **GIL:** Declaration/GoodsShipment/GoodsShipmentItem/**PreviousDocument**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
12 01 000 000	PreviousDocument	n/a	O	G0007
None	sequenceNumber	n..5	M	R0987
12 01 002 000	type –[58]	an4	M	R0868 G0918 CL214
None	ccQualifier	a2	MC	R0906 G0921 C0917 CL010
12 01 001 000	referenceNumber	an..70	M	G0021
12 01 003 000	typeOfPackages	an2	O	G0924 CL017 – **Only on GIL**
12 01 004 000	numberOfPackages	n..8	O	G0019 G0924 – **Only on GIL**
12 01 005 000	measurementUnitAndQualifier	an..4	MC	G0924 C0298 CL349 – **Only on GIL**
None	ccQualifierForMeasurementUnitAndQualifier	a2	MC	R0906 G0921 C0917 CL010 – **Only on GIL**
12 01 006 000	quantity	n..16,6	O	G0924 – **Only on GIL**
12 01 007 000	goodsItemIdentifier	n..5	O	G0037 – **Only on GIL**

Description:

Information relating to a previous document.

Rules/codes/other relevant information:

If one subfield is filled, all subfields must be filled.
For relevant codes to fill in **TypeCode**, see: toldst.dk/erhverv/blanketter-og-koder/koder

sequenceNumber:
To refer to multiple documents, repeat this element the required number of times and fill here sequentially starting at 1.

type (**12 01 002 000**):
For Codelist information, see codelist excel sheet found on GitHub
For **12 01 002 000** footnote **[58]** applies to **H1, H2, H3, H4, H5, I1,** and **I2** declarations.

ccQualifier:
The field is used to identify which country (SCI / PCI) the document type applies to when it concerns validation and handling. If common codes from CS/RD2 are used that apply to both countries, the field should be omitted. In cases where a document has different national type identifiers, this entire group should be repeated.
NB: The submitter is responsible for being aware of any national codes applicable at PCI.

referenceNumber (12 01 001 000):
Can be found here, https://eur-lex.europa.eu/legal-content/EN/TXT/PDF/?uri=CELEX:02015R2447-20210315&qid=1666165195727&from=en on page 314 under "*12 01 001 000* Reference *Number*"

typeOfPackages (**12 01 003 000**):
For Codelist information, see codelist excel sheet found on GitHub

measurementUnitAndQualifier (12 01 005 000):
Unit and qualifier of the quantity.

ccQualifierForMeasurementUnitAndQualifier:
The field is used to identify which country (SCI / PCI) the unit and qualifier applies to when it concerns validation and handling. If common codes from CS/RD2 are used that apply to both countries, the field should be omitted.

quantity (12 01 006 000):
The writing-off quantity addressed by the previous document.

goodsItemIdentifier (12 01 007 000):
Enter the sequential number of the item in the supporting document (e.g., certificate, license, permit, entry document etc.), corresponding to the item in question.

For Codelist information, see codelist excel sheet found on GitHub

XML-examples:

```
<ns3:PreviousDocument>
  <ns3:sequenceNumber>1</ns3:sequenceNumber>
  <ns3:type>N355</ns3:type>
  <ns3:ccQualifier>DK</ns3:ccQualifier>
  <ns3:referenceNumber>PREVDOC123</ns3:referenceNumber>
  <ns3:typeOfPackages>12</ns3:typeOfPackages>
  <ns3:measurementUnitAndQualifier>DKK</ns3:measurementUnitAndQualifier>
  <ns3:ccQualifierForMeasurementUnitAndQualifier>DK</ns3:ccQualifierForMeasurementUnitAndQualifier>
  <ns3:quantity>1000</ns3:quantity>
  <ns3:goodsItemIdentifier>1</ns3:goodsItemIdentifier>
</ns3:PreviousDocument>
```

Additional Information

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	O GSL GIL	O GSL GIL	O GSL GIL	O GSL GIL	O GSL GIL	O GSL GIL	n/a	**GSL:** Declaration/GoodsShipment/**AdditionalInformation** **GIL:** Declaration/GoodsShipment/GoodsShipmentItem/**AdditionalInformation**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
12 02 000 000	AdditionalInformation	n/a	O	G0007
None	sequenceNumber	n..2	M	R0987
12 02 008 000	code – [58]	an5	M	G0918 CL239
None	ccQualifier	a2	MC	R0906 G0921 C0917 CL010
12 02 009 000	text	an..512	O	

Description:

Use this data element to include information for which no field is specified by Union legislation.

Rules/codes/other relevant information:

This element can be used to declare an **SE number**, **other guarantee forms**, or other information for which no field is specified.

Optional to declare and can be declared on GoodsShipment level or GoodsItem level or both.

If given on GoodsShipment level (**GSL**) the information applies to **all** the goods items in the declaration.
If given on GoodsItem level (**GIL**) the information applies to **only** the goods items which it is declared under.

sequenceNumber:
There can be declared multiple additional documents. Number them sequentially here.

code (12 02 008 000):
For Codelist information, see codelist excel sheet found on GitHub
For **12 02 008 000** footnote **[58]** applies to **H1, H2, H3, H4, H5, I1,** and **I2** declarations.

ccQualifier:
The field is used to identify which country (SCI / PCI) a given national code applies to when it concerns validation and handling. If common codes from CS/RD2 are used that apply to both countries, the field should be omitted.
NB: The submitter is responsible for being aware of any national codes applicable at PCI.

text (12 02 009 000):
A short description of the additional information.
If statement code relates to **SE number**, then this field must (only) contain the **SE number**.
If statement code relates to an "**other guarantee form**", then this must contain information or identification of that guarantee.

XML-examples:

```
<ns3:AdditionalInformation>
 <ns3:sequenceNumber>1</ns3:sequenceNumber>
 <ns3:code>00100</ns3:code>
 <ns3:ccQualifier>DK</ns3:ccQualifier>
 <ns3:text>Additional information</ns3:text>
</ns3:AdditionalInformation>
```

Supporting Document

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	O GSL GIL	O GSL GIL	O GSL GIL	O GSL GIL	O GSL GIL	O GSL GIL [4]	n/a	**GSL:** Declaration/GoodsShipment/**SupportingDocument** **GIL:** Declaration/GoodsShipment/GoodsShipmentItem/**SupportingDocument**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
12 03 000 000	SupportingDocument	n/a	O	G0007
None	sequenceNumber	n..2	M	R0987
12 03 002 000	type – [58]	an4	M	G0918 CL213
None	ccQualifier	a2	MC	R0906 G0921 C0917 CL010
12 03 001 000	referenceNumber	an..70	M	G0021
12 03 013 000	documentLineItemNumber	n..5	O	G0881
12 03 010 000	issuingAuthorityName	an..70	O	G0881 – **Only on H1 and I1**
12 03 011 000	dateOfValidity – [4]	an10	O	G0881
12 03 005 000	measurementUnitAndQualifier	an..4	MC	G0673 C0298 CL349 – **Only on GIL**
None	ccQualifierForMeasurementUnitAndQualifier	a2	MC	R0906 G0921 C0917 CL010 – **Only on GIL**
12 03 006 000	quantity –[4]	n..16,6	O	G0673 – **Only on GIL**
12 03 012 000	currency	a3	O	G0673 CL352 – **Only on GIL**
12 03 014 000	amount	n..16,2	O	G0673 – **Only on GIL**

Description:

Identification or reference number of Union or international documents, certificates and authorizations produced in support of the declaration, and additional references.

Rules/codes/other relevant information:

Optional to declare and can be declared on GoodsShipment level or GoodsItem level or both.

If given on GoodsShipment level (**GSL**) the information applies to **all** the goods items in the declaration.
If given on GoodsItem level (**GIL**) the information applies to **only** the goods items which it is declared under.

sequenceNumber:
There can be declared multiple supporting documents. Number them sequentially here.

type (12 03 002 000):
For Codelist information, see codelist excel sheet found on GitHub
For **12 03 002 000** footnote **[58]** applies to **H1, H2, H3, H4, H5,** and **I1** declarations.

ccQualifier:
The field is used to identify which country (SCI / PCI) a given national subsection applies to when it concerns validation and handling. If common codes from CS/RD2 are used that apply to both countries, the field should be omitted.
NB: The submitter is responsible for being aware of any national codes applicable at PCI.

referenceNumber (12 03 001 000):
Is the ID-number of the document.

quantity (12 03 006 000) & **amount** (12 03 014 000)
For Codelist information, see codelist excel sheet found on GitHub
For **12 02 008 000** footnote **[4]** applies to **I1** declarations.

For **12 03 011 000** footnote **[4]** applies to **I1** declarations.

XML-examples:

```
<ns3:SupportingDocument>
  <ns3:sequenceNumber>1</ns3:sequenceNumber>
  <ns3:type>N380</ns3:type>
  <ns3:referenceNumber>SUPPDOC123</ns3:referenceNumber>
  <ns3:documentLineItemNumber>12</ns3:documentLineItemNumber>
  <ns3:issuingAuthorityName>AuthName</ns3:issuingAuthorityName>
  <ns3:dateOfValidity>2026-02-09</ns3:dateOfValidity>
  <ns3:measurementUnitAndQualifier>KGG</ns3:measurementUnitAndQualifier>
  <ns3:ccQualifierForMeasurementUnitAndQualifier>DK</ns3:ccQualifierForMeasurementUnitAndQualifier>
  <ns3:quantity>13.37</ns3:quantity>
  <ns3:currency>DKK</ns3:currency>
  <ns3:amount>100.00</ns3:amount>
</ns3:SupportingDocument>
```

Additional Reference

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	O GSL GIL [58]	O GSL GIL [58]	O GSL GIL [58]	O GSL GIL [58]	O GSL GIL [58]	O GSL GIL [4] [58]	n/a	**GSL:** Declaration/GoodsShipment/**AdditionalReferenc** **GIL:** Declaration/GoodsShipment/GoodsItem/**AdditionalReference**

EUCDM 6.1	XSD/XML-name	Format	M/O	Comment
12 04 000 000	AdditionalReference	n/a	O	G0007 G0918
None	sequenceNumber	n..2	M	R0987
12 04 002 000	type – [58]	an4	M	CL380
None	ccQualifier	a2	MC	R0906 G0921 C0917 CL010
12 04 001 000	referenceNumber – [58]	an..70	M	G0021

Description:

An additional declaration made which is not covered by Supporting Document, Transport Document or Additional Information.

Rules/codes/other relevant information:

Optional to declare and can be declared on GoodsShipment level or GoodsItem level or both.

If given on GoodsShipment level (**GSL**) the information applies to **all** the goods items in the declaration.
If given on GoodsItem level (**GIL**) the information applies to **only** the goods items which it is declared under.

sequenceNumber:
There can be declared multiple additional references. Number them sequentially here.

type (12 04 002 000):
For Codelist information, see codelist excel sheet found on GitHub
For **12 04 002 000** footnote **[58]** applies to **H1, H2, H3, H4, H5,** and **I1** declarations.

ccQualifier:
The field is used to identify which country (SCI / PCI) a given national subsection applies to when it concerns validation and handling. If common codes from CS/RD2 are used that apply to both countries, the field should be omitted.
NB: The submitter is responsible for being aware of any national codes applicable at PCI.

referenceNumber (12 04 001 000):
Is the ID-number of the document.
For **12 04 001 000** footnote **[58]** applies to **I1** declarations.

XML-examples:

```
<ns3:AdditionalReference>
  <ns3:sequenceNumber>1</ns3:sequenceNumber>
  <ns3:type>0100</ns3:type>
  <ns3:ccQualifier>DK</ns3:ccQualifier>
  <ns3:referenceNumber>ADDREFID123</ns3:referenceNumber>
</ns3:AdditionalReference>
```

Transport Document

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GSL GIL	MC GSL GIL	MC GSL GIL	MC GSL GIL	MC GSL GIL	MC GSL GIL	n/a	**GSL:** Declaration/GoodsShipment/Consignment/**TransportDocument** **GIL**: Declaration/GoodsShipment/GoodsShipmentItem/**TransportDocument**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
12 05 000 000	TransportDocument	n/a	MC	G0007
None	sequenceNumber	n..2	M	R0987
12 05 002 000	type	an4	M	CL754
12 05 001 000	referenceNumber	an..70	M	G0021

Description:

Transport document with which the goods have been brought into the customs territory of the Union.

Rules/codes/other relevant information:

sequenceNumber:
There can be declared multiple transport documents. Number them sequentially here.

type (12 05 002 000):
indicate the type of the document. For Codelist information, see codelist excel sheet found on GitHub

referenceNumber (12 05 001 000):
Is the ID-number of the document.

XML-examples:

```
<ns3:TransportDocument>
  <ns3:sequenceNumber>1</ns3:sequenceNumber>
  <ns3:type>N740</ns3:type>
  <ns3:referenceNumber>AWB123</ns3:referenceNumber>
</ns3:TransportDocument>
```

Reference number/UCR

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	O GSL GIL	O GSL GIL	O GSL GIL	O GSL GIL	O GSL GIL	O GSL GIL	n/a	**GSL:** Declaration/GoodsShipment/Consignment/**referenceNumberUCR** **GIL:** Declaration/GoodsShipment/GoodsShipmentItem/**referenceNumberUCR**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
12 08 000 000	referenceNumberUCR	an..35	O	

Description:

Unique number that follows the goods all the way. Used by transporters.

Rules/codes/other relevant information:

Fill in a unique number for identification of the transaction.

referenceNumberUCR (12 08 000 000):
This element can be supplemented and estimated.

XML-examples:

```
<ns3:referenceNumberUCR>P198R65Q29</ns3:referenceNumberUCR>
```

LRN

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC DL	MC DL	MC DL	MC DL	MC DL	MC DL	MC DL	**Basepath:** Declaration/**LRN**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
12 09 001 000	LRN	an..22	MC	C0730

Description:

LRN – The local reference number (LRN) shall be used. It is nationally defined and allocated by the declarant or representative in agreement with the competent authorities to identify each single declaration.

Rules/codes/other relevant information:

No special characters are allowed.

Must be unique on a submitter level but can be reused for resubmission if the declaration has been rejected, **except** for when the declaration has been rejected due to invalidation of a pre-lodged declaration. This means you can submit using the same (accepted) LRN using two different submitters, but never using the same submitter.

XML-examples:

```
<ns3:LRN>140721DKQXYMEEW</ns3:LRN>
```

Warehouse

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GSL [5]	M GSL	MCGSL [5]	MC GSL [5]	n/a GSL [5]	n/a	n/a	**GSL:** Declaration/GoodsShipment/**Warehouse**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
12 11 000 000	Warehouse	n/a	MC	S0017 G0999 C0625 C0626 C0829 C0853
12 11 002 000	type	a1	M	CL099
12 11 015 000	identifier	an..35	M	G0031

Description:

Warehouse where a particular goods shipment will be / is / has been stored

Rules/codes/other relevant information:

Warehouse (12 11 000 000):
This element and sub elements can be supplemented.

type (12 11 002 000):
The character identifying the type of warehouse.
For Codelist information, see codelist excel sheet found on GitHub

identifier (12 11 015 000):
The authorization number of the warehouse or storage facility.

XML-examples:

```
<ns3:Warehouse>
  <ns3:type>R</ns3:type>
  <ns3:identifier>R123456NL</ns3:identifier>
</ns3:Warehouse>
```

Authorisation

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC DL GIL [60]	MC DL GIL [60]	MC DL GIL [60]	MC DL GIL [60]	MC DL GIL [60]	MC DL GIL [60]	MC DL GIL [1] [60]	**Basepath**: Declaration/**Authorisation** **GIL**: Declaration/GoodsShipment/GoodsShipmentItem/**Authorisation**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
12 12 000 000	Authorisation	n/a	MC	R0010 R0932 G0930 C0934
None	sequenceNumber	n1	M	R0987
12 12 002 000	type – [1] [63] [73]	an4	MC	C0923 CL605 CL615
12 12 001 000	referenceNumber – [1] [60]	an..35	M	
12 12 080 000	holderOfTheAuthorisation – [1] [60]	an..17	DL: O GIL: M	R0995 C0848

Description:

Details and reference to authorizations.

Rules/codes/other relevant information:

Be aware that some authorisations may only be available as a Supporting Document (12 03 000 000) when required to be declared on goods item level (GIL) e.g. 'OPO'. Check the related codelists to see which authorisations can be included in each additional document type.

sequenceNumber:
There can be declared multiple authorisations. Number them sequentially here.

type (12 12 002 000)
The code for the specific authorization type.
For **12 12 001 000** footnote **[63]** applies to **H1, H2, H3, H4, H5, I1** and **I2** declarations, footnote **[73]** applies to **H1, I1** and **I2** declarations, and footnote **[1]** applies to **I2** declarations.

referenceNumber (12 12 001 000):
Reference number of the authorization.
For **12 12 001 000** footnote **[60]** applies to **H1, H2, H3, H4, H5, I1** and **I2** declarations.

holderOfTheAuthorisation (12 12 080 000)
The EORI number of the authorisation holder.
For **12 12 080 000** footnote **[60]** applies to **H1, H2, H3, H4, H5, I1** and **I2** declarations, and footnote **[1]** applies to **I2** declarations.

XML-examples:

```
<ns3:Authorisation>
  <ns3:sequenceNumber>1</ns3:sequenceNumber>
  <ns3:type>C512</ns3:type>
  <ns3:referenceNumber>DKRSSDK004700-2020-Test81</ns3:referenceNumber>
  <ns3:holderOfTheAuthorisation>DK12345678</ns3:holderOfTheAuthorisation>
</ns3:Authorisation>
```

Group 13 - Parties

7

Exporter

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M GSL GIL	n/a	M GSL GIL	M GSL GIL	M GSL GIL	M GSL GIL	n/a	**GSL**: Declaration/GoodsShipment/**Exporter** **GIL**: Declaration/GoodsShipment/GoodsShipmentItem/**Exporter**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
13 01 000 000	Exporter	n/a	MC	S0029 G0642 C0002 C0618
13 01 017 000	identificationNumber – [66]	an..17	O	R0928
13 01 016 000	name – [6]	an..70	MC	C0617
13 01 018 000	Address – [6]	n/a	MC	C0617
13 01 018 019	streetAndNumber	an..70	M	
13 01 018 021	postcode	an..17	MC	C0505
13 01 018 022	city	an..35	M	
13 01 018 020	country	a2	M	CL199

Description:

Name and address of the party exporting the good(s) to the union.

Rules/codes/other relevant information:

If Name includes the special character **&**, it should be declared as **&**
For **13 01 016 000** footnote **[6]** applies to **H1, H3, H4, H5** and **I1** declarations.

If **identificationNumber (13 01 017 000)** is provided, name and address shall not be provided: Where the EORI number or a third country unique identification number recognised by the Union is provided, the name and address shall not be provided.
For **13 01 017 000** footnote **[66]** applies to **H1, H3, H4, H5** and **I1** declarations.

If **Address** (**13 01 018 000**) is present, **city** (**13 01 018 022**), **country** (**13 01 018 020**), **Line** (**13 01 018 019**), **postcode** (**13 01 018 021**) are mandatory fields.
For **13 01 018 000** footnote **[6]** applies to **H1, H3, H4, H5** and **I1** declarations.

country (13 01 018 020):
For Codelist information, see codelist excel sheet found on GitHub

For I1 declarations, Consignor is not allowed on Goods Item Level.

XML-examples:

With EORI number **(13 01 017 000)**:

```
<ns3:Exporter>
  <ns3:identificationNumber>DK99999996</ns3:identificationNumber>
</ns3:Exporter>
```

Without EORI number **(13 01 017 000)**:

```
<ns3:Exporter>
  <ns3:name>Exporter Man</ns3:name>
  <ns3:Address>
    <ns3:streetAndNumber>Copenhagen Street 123</ns3:streetAndNumber>
    <ns3:postcode>2300</ns3:postcode>
    <ns3:city>Copenhagen</ns3:city>
    <ns3:country>DK</ns3:country>
  </ns3:Address>
</ns3:Exporter>
```

Importer

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M DL	M DL	M DL	M DL	M DL	M GSL	n/a	**Basepath:** Declaration/**Importer**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
13 04 000 000	Importer	n/a	M	
13 04 017 000	identificationNumber	an..17	O	R0995
13 04 016 000	name	an..70	MC	C0617
13 04 018 000	Address	n/a	MC	C0617
13 04 018 019	streetAndNumber	an..70	M	
13 04 018 021	postcode	an..17	MC	C0505
13 04 018 022	city	an..35	M	
13 04 018 020	country	a2	M	CL199

Description:

Name and address of the party importing the good(s) into the union.

Rules/codes/other relevant information:

If Name includes the special character **&**, it should be declared as **&**
For **13 01 016 000** footnote **[6]** applies to **H1, H3, H4, H5** and **I1** declarations.

If **identificationNumber (13 04 017 000)** is provided, name and address shall not be provided: Where the EORI number or a third country unique identification number recognised by the Union is provided, the name and address shall not be provided. This field is however mandatory for Danish import so the address and name should never be provided.

If **Address** (**13 04 018 000**) is present, **city** (**13 04 018 022**), **country** (**13 04 018 020**), **streetAndNumber** (**13 04 018 019**), **postcode** (**13 04 018 021**) are mandatory fields.
For **13 01 018 000** footnote **[6]** applies to **H1, H3, H4, H5** and **I1** declarations.

country (13 04 018 020):
For Codelist information, see codelist excel sheet found on GitHub.

postcode (13 04 018 021):
can be found on Bilag 2 https://skat.dk/getfile.aspx?id=151338&type=xlsx

XML-examples:

Without EORI number:

```
<ns3:Importer>
    <ns3:name>Importer Man</ns3:name>
    <ns3:Address>
        <ns3:streetAndNumber>Copenhagen Street 123</ns3:streetAndNumber>
        <ns3:postcode>2300</ns3:postcode>
        <ns3:city>Copenhagen</ns3:city>
        <ns3:country>DK</ns3:country>
    </ns3:Address>
</ns3:Importer>
```

With EORI number:

```
<ns3:Importer>
    < ns3:identificationNumber>DK99999996</ns3:identificationNumber>
</ns3:Importer>
```

Declarant

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M DL	M DL	M DL	M DL	M DL	M DL	M DL	**Basepath:** Declaration/**Declarant**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
13 05 000 000	Declarant	n/a	M	R0907
13 05 017 000	identificationNumber	an..17	M	R0995
13 05 016 000	name – [6]	an..70	MC	C0617
13 05 018 000	Address - [6]	n/a	MC	C0617
13 05 018 019	streetAndNumber	an..70	M	
13 05 018 021	postcode	an..17	MC	C0505
13 05 018 022	city	an..35	M	
13 05 018 020	country	a2	M	CL199
13 05 074 000	ContactPerson	n/a	O	G0105
13 05 074 016	name	an..70	M	
13 05 074 075	phoneNumber	an..35	M	
13 05 074 076	eMailAddress	an..256	M	

Description:

ID, name and address of the person or company exporting the goods.
Exporter and declarant can be the same.

Rules/codes/other relevant information:

The required information is specified by the EORI number given in **ID (13 05 017 000)**:

If Name uses the special character **&**, it should be declared as **&**

identificationNumber (13 05 017 000):
This should be the EORI number of the representative party.

country (13 05 018 020):
For Codelist information, see codelist excel sheet found on GitHub

ContactPerson (13 05 074 000):
Declare contact information.

name (13 05 074 016):
Name of the contact person.

phoneNumber (13 05 074 075):
Phone number to reach the contact person.

eMailAddress (13 05 074 076):
E-mail address to reach the contact person.

For **13 05 016 000** footnote **[6]** applies to **H1, H3, H4, H5, I1** and **I2** declarations.
For **13 01 018 000** footnote **[6]** applies to **H1, H3, H4, H5, I1** and **I2** declarations.

XML-examples:

With EORI

```
<ns3:Declarant>
  <ns3:identificationNumber>DK99999981</ns3:identificationNumber>
</ns3:Declarant>
```

Without EORI

```
<ns3:Declarant>
  <ns3:name>Name</ns3:name>
  <ns3:Address>
    <ns3:streetAndNumber>Copenhagen Street 123</ns3:streetAndNumber>
    <ns3:postcode>2300</ns3:postcode>
    <ns3:city>Copenhagen</ns3:city>
    <ns3:country>DK</ns3:country>
  </ns3:Address>
  <ns3:ContactPerson>
    <ns3:name>Contact Namerson</ns3:name>
    <ns3:phoneNumer>12345678</ns3:phoneNumer>
    <ns3:eMailAddress>name@name.dk</ns3:eMailAddress>
  </ns3:ContactPerson>
</ns3:Declarant>
```

Seller

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	O GSL GIL	n/a	n/a	n/a	n/a	n/a	n/a	**GSL:** Declaration/GoodsShipment/**Seller** **GIL:** Declaration/ GoodsShipment/GoodsShipmentItem/**Seller**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
13 08 000 000	Seller	n/a	MC	R0012 G0642 G0672 C0728
13 08 017 000	identificationNumber	an..17	O	R0928
13 08 016 000	name	an..70	MC	C0617
13 08 018 000	Address	n/a	MC	C0617
13 08 018 019	streetAndNumber	an..70	M	
13 08 018 021	postcode	an..17	MC	C0505
13 08 018 022	city	an..35	M	
13 08 018 020	country	a2	M	CL199

Description:

Name and address of the seller of the goods.

Rules/codes/other relevant information:

It is mandatory to declare the name of the seller. If the address is declared the subfields must be declared. The field **country** accepts the GENOM codes for countries.

XML-examples:

```
<ns3:Seller>
    <ns3:identificationNumber>DK99999996</ns3:identificationNumber>
    <ns3:name>Seller Co.</ns3:name>
    <ns3:Address>
        <ns3:streetAndNumber>Copenhagen Street 123</ns3:streetAndNumber>
        <ns3:postcode>2300</ns3:postcode>
        <ns3:city>Copenhagen</ns3:city>
        <ns3:country>DK</ns3:country>
    </ns3:Address>
</ns3:Seller>
```

Representative (Agent)

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	O DL	O DL	O DL	O DL	O DL	O DL	O DL	**Basepath**: Declaration/**Representative**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
13 06 000 000	Representative	n/a	O	R0907
13 06 017 000	identificationNumber	an..17	M	
13 06 030 000	status	n1	M	R0521 CL094
13 06 074 000	ContactPerson	n/a	O	This is not available for I2
13 06 074 016	name	an..70	M	
13 06 074 075	phoneNumber	an..35	M	
13 06 074 076	eMailAddress	an..256	M	

Description:

Identification of party authorized to act on behalf of another party.

Rules/codes/other relevant information:

If Importer (13 04 000 000) and **Declarant (13 05 000 000) (including all their sub-elements)** are **NOT identical**, **there <u>must</u> be declared a Representative/Agent.**

If **Representative (13 06 000 000)** is provided and FunctionCode = 2 (direct representation), then the value **must be different** from **Declarant (13 05 000 000)**.

identificationNumber (13 06 017 000)
This should be the EORI number of the representative party.

status (13 06 030 000)
This is the function / status of the representative. It can <u>only</u> be '**2**' (direct representation).

ContactPerson (13 06 074 000):
Declare contact information.

name (13 06 074 016):
Name of the contact person.

phoneNumber (13 06 074 075):
Phone number to reach the contact person.

eMailAddress (13 06 074 076):
E-mail address to reach the contact person.

XML-examples:
With EORI <ns3:Representative>   <ns3:identificationNumber>DK16152293</ns3:identificationNumber>   <ns3:status>2</ns3:status> </ns3:Representative> Without EORI <ns3:Representative>   <ns3:status>2</ns3:status>   <ns3:ContactPerson>   <ns3:name>Tolder Toldersen</ns3:name>   <ns3:phoneNumber>12345678</ns3:phoneNumber>   <ns3:eMailAddress>tolder@told.dk</ns3:eMailAddress>   </ns3:ContactPerson> </ns3:Representative>

Buyer

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	O GSL GIL	n/a	n/a	n/a	n/a	n/a	n/a	**GSL:** Declaration/GoodsShipment/**Buyer** **GIL:** Declaration/ GoodsShipment/GoodsShipmentItem/**Buyer**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
13 09 000 000	Buyer	n/a	MC	R0012 G0642 G0671 C0728
13 09 017 000	identificationNumber	an..17	O	R0928
13 09 016 000	name	an..70	MC	C0617
13 09 018 000	Address	n/a	MC	C0617
13 09 018 019	streetAndNumber	an..70	M	
13 09 018 021	postcode	an..17	MC	C0505
13 09 018 022	city	an..35	M	
13 09 018 020	country	a2	M	CL199

Description:

Name and address of the one(s) buying the goods.

Rules/codes/other relevant information:

The field has generally the same rules as “Seller” above.

XML-examples:

```
<ns3:Buyer>
    < ns3:identificationNumber>DK09999981</ns3:identificationNumber>
    <ns3:name>Buyer Man</ns3:name>
    <ns3:Address>
        <ns3:streetAndNumber>Odense  Street 123</ns3:streetAndNumber>
        <ns3:postcode>5200</ns3:postcode>
        <ns3:city>Odense</ns3:city>
        <ns3:country>DK</ns3:country>
    </ns3:Address>
</ns3:Buyer>
```

Additional Supply Chain Actor

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	O GSL GIL	O GSL GIL	O GSL GIL	O GSL GIL	O GSL GIL	O GSL GIL	n/a	**GSL:** Declaration/GoodsShipment/**AdditionalSupplyChainActor** **GIL:** Declaration/GoodsShipment/GoodsShipmentItem/**AdditionalSupplyChainActor**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
13 14 000 000	AdditionalSupplyChainActor	n/a	O	G0642 G0654
None	sequenceNumber	n..2	M	R0987
13 14 031 000	role	a..3	M	CL704
13 14 017 000	identificationNumber	an..17	M	R0928

Description:

Details identifying the role of the further parties in the supply chain having obtained a trusted trader certificate but otherwise not being identified in the declarations (e.g., warehouse keeper, freight forwarder)

Rules/codes/other relevant information:

AdditionalSupplyChainActor (13 14 000 000):
This element and sub elements can be supplemented and estimated.

role (13 14 031 000):
For Codelist information, see codelist excel sheet found on GitHub

identificationNumber (13 14 017 000):
The EORI number or third-party country unique identifiers number

XML-examples:

```
<ns3:AdditionalSupplyChainActor>
  <ns3:sequenceNumber>1</ns3:sequenceNumber>
  <ns3:role>MF</ns3:role>
  <ns3:identificationNumber>DK12345678</ns3:identificationNumber>
</ns3:AdditionalSupplyChainActor>
```

Additional fiscal reference

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M GSL GIL	M GSL GIL	M GSL GIL	M GSL GIL	n/a	M GSL GIL	M GSL GIL	**GSL:** Declaration/GoodsShipment/**AdditionalFiscalReference** **GIL:** Declaration/GoodsShipment/GoodsShipmentItem/**AdditionalFiscalReference**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
13 16 000 000	AdditionalFiscalReference	n/a	M	R0010 G0642 G0880 C0834
None	sequenceNumber	n..5	M	R0987
13 16 031 000	role	an3	M	CL149
13 16 034 000	VATIdentificationNumber	an..17	M	

Description:

Person paying VAT in the VAT return.

Rules/codes/other relevant information:

sequenceNumber:
There can be declared multiple additional fiscal references. Number them sequentially here.

role (13 14 031 000):
For Codelist information, see codelist excel sheet found on GitHub

VATIdentificationNumber (13 16 034 000):
VAT identification number of person concerned.

XML-examples:

```
<ns3:AdditionalFiscalReference>
  <ns3:sequenceNumber>1</ns3:sequenceNumber>
  <ns3:role>123</ns3:role>
  <ns3:VATIdentificationNumber>12345678987654321</ns3:VATIdentificationNumber>
</ns3:AdditionalFiscalReference>
```

Person providing a guarantee (Surety)

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	O DL	n/a	O DL	O DL	n/a	n/a	n/a	**DL:** Declaration/**PersonProvidingAGuarantee**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
13 20 000 000	PersonProvidingAGuarantee	n/a	MC	R0995 C0824
12 20 017 000	identificationNumber	an..17	M	

Description:

The EORI number of the person providing the guarantee, if they are different from the declarant.

Rules/codes/other relevant information:

identificationNumber (13 21 017 000):
This is the ID of the person providing the guarantee.

XML-examples:

```
<ns3:PersonProvidingAGuarantee>
    <ns3:identificationNumber>DK123456789</ns3:identificationNumber>
</ns3:PersonProvidingAGuarantee>
```

Person paying the customs duty

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	O DL	n/a	O DL	n/a	O DL	O DL	n/a	**GSL:** Declaration/**PersonPayingCustomsDuty**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
13 21 000 000	PersonPayingCustomsDuty	n/a	MC	R0995 C0809
13 21 017 000	identificationNumber	an..17	M	

Description:

The EORI number of the person paying the customs duty, if they are different from the declarant.

Rules/codes/other relevant information:

identificationNumber (13 21 017 000):
This is the ID of the Payer.

XML-examples:

```
<ns3:PersonPayingCustomsDuty>
    <ns3:identificationNumber>DK123456789</ns3:identificationNumber>
</ns3:PersonPayingCustomsDuty>
```

Group 14 - Valuation information/Taxes

8

Delivery Terms

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M GSL [10]	O GSL	O GSL	M GSL [10]	M GSL	n/a	n/a	**GSL:** Declaration/GoodsShipment/**DeliveryTerms**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
14 01 000 000	DeliveryTerms	n/a	MC	S0016 C0738 C0729 C0627
14 01 035 000	incotermCode	a3	M	CL090
14 01 036 000	UNLOCODE	an..17	O	C0596 CL244
14 01 037 000	location	an..35	O	C0596
14 01 020 000	country	a2	O	C0596 CL199
14 01 009 000	text	an..512	MC	C0596

Description:

Details about the trade terms

Rules/codes/other relevant information:

incotermCode (14 01 035 000):
For Codelist information, see codelist excel sheet found on GitHub

UNLOCODE (14 01 036 000):
UN/LOCODE for the place of destination. In case of:

- Sea traffic, enter the UN/LOCODE for the location where delivery occurs beyond the port of unloading
- Air traffic, enter the destination of goods using the UN/LOCODE

This elements expects input in this format "DKxxx-yyyy" where the x's are alphanumerical and the y's are numerical only.
For Codelist information, see codelist excel sheet found on GitHub

location (14 01 037 000):
If UN/LOCODE is not available, enter the name of the place of destination

country (14 01 020 000):
For Codelist information, see codelist excel sheet found on GitHub

text (14 01 009 000):
Add a description of the teams of delivery, in cases where a sophisticated explanation is needed.

XML-examples:

```
<ns3:DeliveryTerms>
  <ns3:incotermCode>DAP</ns3:incotermCode>
  <ns3:UNLOCODE>DK001-0001</ns3:UNLOCODE>
  <ns3:location>Place name</ns3:location>
  <ns3:country>DK</ns3:country>
</ns3:DeliveryTerms>
```

Calculation of taxes

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GIL	MC GIL	MC GIL	MC GIL	MC GIL	MC GIL	MC GIL	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/Commodity/**CalculationOfTaxes**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
14 16 000 000	CalculationOfTaxes	n/a	MC	G0003 C0691
14 11 001 000	preference	n3	MC	G0985 C0691 CL603
14 16 001 000	totalDutiesAndTaxesAmount	n..16,2	O	G0019 G0617 G0618
14 03 000 000	DutiesAndTaxes	n/a	MC	S0033 G0618 C0627 C0630 C0806

Description:

Rules/codes/other relevant information:

XML-examples:

```
<ns3:CalculationOfTaxes>
  <ns3:preference>100</ns3:preference>
  <ns3:totalDutiesAndTaxesAmount>140.00</ns3:totalDutiesAndTaxesAmount>
  <ns3:DutiesAndTaxes>
    ...
  </ns3:DutiesAndTaxes>
</ns3:CalculationOfTaxes>
```

Duties and Taxes

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GIL [12] [13]	n/a	MC GIL [12] [13]	MC GIL [12] [13]	MC GIL [12] [13]	n/a	n/a	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/Commodity/CalculationOfTaxes/**DutiesAndTaxes**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
14 03 000 000	DutiesAndTaxes	n/a	MC	S0033 G0618 C0627 C0630 C0806
None	sequenceNumber	n..2	M	R0987
14 03 039 000	taxType – [12][13][58]	an3	M	Type of Duty, Tax or Fee G0618 CL098
None	ccQualifier	a2	MC	R0906 G0921 C0917 CL010
14 03 042 000	payableTaxAmount	n..16,2	O	G0019
14 03 038 000	methodOfPayment – [11][12][54]	a1	O	R0014 CL104
14 03 040 000	TaxBase	n/a	MC	S0033 G0618 C0627 C0630 C0806
None	sequenceNumber	n..2	M	R0987
14 03 040 041	taxRate – [11][12]	n..17,3	O	G0618
14 03 040 005	measurementUnitAndQualifier	an..4	MC	G0349 G0918 C0298
None	ccQualifierForMeasurementUnitAndQualifier	a2	MC	R0906 G0921 C0917 CL010
14 03 040 006	quantity	n..16,6	MC	C0850
14 03 040 014	amount	n..16,2	MC	C0852
14 03 040 043	taxAmount – [11]	n..16,2	O	G0617

Description:

Each instance of this class is to be used for a single occurrence of duty, tax or fee.

Rules/codes/other relevant information:

sequenceNumber on duties and taxes level:
There can be declared multiple duties and taxes. Number them sequentially here.

taxType (14 03 039 000):
There are the following TypeCodes in the table below. However, the different countries can create custom National Codes which also applies for those countries, they consist of n1an2.

ccQualifier:
The field is used to identify which country (SCI / PCI) a given national subsection applies to when it concerns validation and handling. If common codes from CS/RD2 are used that apply to both countries, the field should be omitted.
NB: The submitter is responsible for being aware of any national codes applicable at PCI.

payableTaxAmount (14 03 042 000):
Enter amount for each of the duties and taxes applicable.
For **14 03 042 000** footnote **[11]** applies to **H3, H4,** and **H5** declarations, and footnote **[12]** applies to **H1** and **H5** declarations.

methodOfPayment (14 03 038 000):
For Codelist information, see codelist excel sheet found on GitHub
For **14 03 038 000** footnote **[11]** applies to **H3, H4,** and **H5** declarations, and footnote **[12]** applies to **H1** and **H5** declarations.

TaxBase (14 03 040 000):

sequenceNumber on tax base level:
There can be declared multiple tax bases. Number them sequentially here.

taxRate (14 03 040 041):
Enter the rates for each of the duties and taxes of application.
For **14 03 040 041** footnote **[11]** applies to **H1, H3, H4,** and **H5** declarations, and footnote **[12]** applies to **H1** and **H5** declarations.

measurementUnitAndQualifier (14 03 040 005):

ccQualifierForMeasurementUnitAndQualifier:

quantity (14 03 040 006):
Enter quantity concerned.
This data element can be **estimated** on a supplementary declaration for **C1** declarations.

amount (14 03 040 014):
Enter the amount.

taxAmount (14 03 040 043):
Enter the calculated/separate tax amount of duties and/or taxes for each tax base, for the cases when more than one tax base per tax type exist.
For **14 03 040 043** footnote **[11]** applies to **H1, H3, H4,** and **H5** declarations.

For Codelist information, see codelist excel sheet found on GitHub
For **14 03 039 000** footnotes **[12]**, **[13]**, and **[58]** apply to **H1, H3, H4,** and **H5** declarations.

XML-examples:

```
<ns3:DutiesAndTaxes>
  <ns3:sequenceNumber>1</ns3:sequenceNumber>
  <ns3:taxType>A10</ns3:taxType>
  <ns3:ccQualifier>NL</ns3:ccQualifier>
  <ns3:payableTaxAmount>1000.00</ns3:payableTaxAmount>
  <ns3:methodOfPayment>R</ns3:methodOfPayment>
  <ns3:TaxBase>
    <ns3:sequenceNumber>1</ns3:sequenceNumber>
    <ns3:taxRate>1000.00</ns3:taxRate>
    <ns3:measurementUnitAndQualifier>DKK</ns3:measurementUnitAndQualifier>
    <ns3:ccQualifierForMeasurementUnitAndQualifier>DK</ns3:ccQualifierForMeasurementUnitAndQualifier>
    <ns3:quantity>1000.000000</ns3:quantity>
    <ns3:amount>1000.00</ns3:amount>
    <ns3:taxAmount>1000.00</ns3:taxAmount>
  </ns3:TaxBase>
</ns3:DutiesAndTaxes>
```

Additions and deductions

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GSL GIL [10] [14]	n/a	MC GIL	MC GIL	MC GSL GIL	n/a	n/a	**GSL:** Declaration/GoodsShipment/**AdditionsAndDeductions** **GIL:** Declaration/GoodsShipment/GoodsShipmentItem/CustomsValuation/**AdditionsAndDeductions**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
14 04 000 000	AdditionsAndDeductions	n/a	MC	R0010 G0616 G0620 G0642 C0938
None	sequenceNumber	n..2	M	R0987
14 04 008 000	code	a2	M	CL791
14 04 014 000	amount	n..16,2	M	

Description:

Info about the valuation method used and additional charges.

Rules/codes/other relevant information:

sequenceNumber:
There can be declared multiple additions and deductions. Number them sequentially here.

code (14 04 008 000):
For each type of addition or deduction relevant for a given goods item, enter the relevant code. All valid codes are a two-letter code.

amount (14 04 014 000):
For each type of addition or deduction relevant for a given goods item, enter the corresponding amount in national currency that has not yet been included in or deducted from the item price.

The XSD element CustomsValuation appears on two levels but contain different sub-elements on GSL vs SIL. On GSL CustomsValuation appears as on this table. On SIL CustomsValuation contains more elements, see Table Valuation method on page 65.

XML-examples:

```
<ns3:AdditionsAndDeductions>
  <ns3:sequenceNumber>1</ns3:sequenceNumber>
  <ns3:code>AE</ns3:code>
  <ns3:amount>140.00</ns3:amount>
</ns3:AdditionsAndDeductions>
```

Valuation Indicators

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GIL [10] [14]	n/a	n/a	MC GIL	MC GIL	n/a	n/a	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/**ValuationAdjustment**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
14 07 000 000	ValueationAdjustment	n/a	MC	G0616 G0620 C0624
14 07 001 000	valuationIndicators	an4	M	G0010

Description:

This element is used to indicate what factors are used to declare the value of the goods.

Rules/codes/other relevant information:

valuationIndicators (14 07 001 000):

The code comprises four digits, each of which being either a "0" or a "1". Each "1" or "0" digit reflects whether or not a valuation indicator is relevant to the valuation of the goods concerned.

- 1st digit: Party relationship, whether there is price influence or not
- 2nd digit: Restrictions as to the disposal or use of the goods by the buyer in accordance with Article 70(3)(a) of the Code
- 3rd digit: Sale or price is subject to some condition or consideration in accordance with Article 70(3)(b) of the Code.
- 4th digit: The sale is subject to an arrangement under which part of the proceeds of any subsequent resale, disposal or use accrues directly or indirectly to the seller

Example: Goods subject to party relationship, but not to any of the other situations defined under 2nd, 3rd and 4th digits would entail the use of code combination "1000."

```
<ns3:ValueationAdjustment>
    <ns3:valuationIndicators>1000</ns3:valuationIndicators>
</ns3:ValueationAdjustment>
```

Total Amount Invoiced

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M	n/a	M	M	M	O	n/a	**GSL:** Declaration/GoodsShipment

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
14 06 000 000	totalAmountInvoiced	n..16,2	MC	C0619
14 05 000 000	invoiceCurrency	a3	MC	G0907 G0921 C0921 CL352

Description:

Number indicating the total invoice amount of the declaration.

Rules/codes/other relevant information:

totalAmountInvoiced (14 06 000 000):
Enter the total amount of the invoice.

invoiceCurrency (14 05 000 000):
Enter the currency of the invoice amount.

For Codelist information, see codelist excel sheet found on GitHub.
For **14 05 001 000** footnote **[2]** applies to **I1** declarations.

XML-examples:

```
<ns3:totalAmountInvoiced>7442.00</ns3:totalAmountInvoiced>
<ns3:invoiceCurrency>DKK</ns3:invoiceCurrency>
```

Deferred payment

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GSL	MC GSL	MC GSL	MC GSL	MC GSL	MC GSL	MC GSL	**GSL:** Declaration/DeferredPayment

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
12 10 000 000	DeferredPayment	n/a	MC	C0697
None	sequenceNumber	n1	M	R0987
12 10 001 000	deferredPayment	an..35	M	
None	ccQualifier	a2	O	R0906 G0113 CL010

Description:

Rules/codes/other relevant information:

sequenceNumber:
There can be declared multiple deferred payments. Number them sequentially here.

deferredPayment (12 10 001 000):

ccQualifier:
The field is used to identify which country (SCI / PCI) a given national subsection applies to when it concerns validation and handling. If common codes from CS/RD2 are used that apply to both countries, the field should be omitted.

XML-examples:

```
<ns3:DeferredPayment>
  <ns3:sequenceNumber>1</ns3:sequenceNumber>
  <ns3:deferredPayment>DK72474850064021653991</ns3:deferredPayment>
  <ns3:ccQualifier>DK</ns3:ccQualifier>
</ns3:DeferredPayment>
```

Item Amount Invoiced

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M GIL [83]	n/a	M GIL	M GIL	M GIL	MC GIL [2]	n/a	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/Commodity/**InvoiceLine**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
14 08 000 000	InvoiceLine	n/a	MC	S0022 C0710 C0618
14 08 001 000	itemAmountInvoiced	n..16,2	M	G0019

Description:

Price of the goods for the declaration item concerned, expressed in the currency unit declared in D.E. 14 05 000 000 Invoice currency.

Rules/codes/other relevant information:

itemAmountInvoiced (14 08 001 000):
Enter the price of the declared goods.

XML-examples:

```
<ns3:InvoiceLine>
  <ns3:itemAmountInvoiced>7442.00</ns3:itemAmountInvoiced>
</ns3:InvoiceLine>
```

Exchange Rate

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	O DL [15]	n/a	O DL	O DL [15]	n/a	n/a	n/a	**Basepath:** Declaration/**CurrencyExchange**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
14 17 000 000	CurrencyExchange	n/a	O	G0405
14 17 001 000	internalCurrencyUnit	a3	MC	S0023 C0937 C0630 CL048

Description:

This data element contains the rate of exchange fixed in advance by a contract between the parties concerned

Rules/codes/other relevant information:

internalCurrencyUnit (14 17 001 000):
For Codelist information, see codelist excel sheet found on GitHub

XML-examples:

```
<ns3:CurrencyExchange>
  <ns3:internalCurrencyUnit>DKK</ns3:internalCurrencyUnit>
</ns3:CurrencyExchange>
```

Valuation method

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M SIL	n/a	M SIL	M SIL	M SIL	n/a	n/a	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/**CustomsValuation**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
14 10 000 000	CustomsValuation	n/a	MC	C0940
14 10 001 000	valuationMethod	n1	M	CL604

Description:

Info about the valuation method used and additional charges.

Rules/codes/other relevant information:

valuationMethod (14 10 001 000):
The provisions used to determine the customs value of imported goods are to be coded as follows:

Code	Relevant Article of the Code	Method
1	70	Transaction value of the imported goods
2	74(2)a)	Transaction value of identical goods
3	74(2)b)	Transaction value of similar goods
4	74(2)c)	Deductive value method
5	74(2)(d)	Computed value method
6	74(3)	Value based on the data available (“fall-back”method)

The XSD element CustomsValuation appears on two levels but contain different sub-elements on GSL vs SIL. The elements on SIL is only part of CustomsValuation there are more elements namely ChargeDeduction and its sub-elements in it, see Table Additions and deductions on page 59. On GSL level only the elements from Table Additions and deductions is present.

XML-examples:

```
<ns3:CustomsValuation>
  <ns3:valuationMethod>DKK</ns3:valuationMethod>
</ns3:CustomsValuation>
```

Group 15 - Dates – Times – Periods

9

Date of acceptance

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GSL [41]	n/a	MC GSL [41]	MC GSL [41]	MC GSL [41]	n/a	n/a	**GSL:** Declaration/GoodsShipment/**dateOfAcceptance**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
15 09 000 000	dateOfAcceptance	an19	MC	G0981 C0739

Description:

Indication of when the goods were presented to customs.

Rules/codes/other relevant information:

Fill in the time and date for presentation of goods.

XML-examples:

```
<ns3:dateOfAcceptance>2026-01-22T07:27:35</ns3:dateOfAcceptance>
```

Group 16 - Places/Countries/Regions

10

Country of destination

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GSL GIL	MC GSL GIL	MC GSL GIL	MC GSL GIL	MC GSL GIL	M GSL	M GSL	**GSL:** Declaration/GoodsShipment/**Destination** **GIL:** Declaration/GoodsShipment/GoodsShipmentItem/**Destination**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
16 03 000 000 16 04 000 000	Destination	n/a	MC	S0027 G0642 C0002 C0627
16 03 001 000	countryOfDestination	a2	MC	G0009 C0816 CL010
16 04 001 000	regionOfDestination	an..35	MC	S0001 G0918 C0625 C0911
None	ccQualifier	a2	MC	R0906 G0921 G0923 C0918 CL010

Description:

This element contains a union code of a member state, but which member state depends on the type of declaration. See the below section for specifics.

Rules/codes/other relevant information:

countryOfDestination (16 03 001 000):
For Codelist information, see codelist – Import excel sheet found on GitHub.
For H1, H2 and H5: The union code entered in **countryOfDestination** is the code of the member state where the goods are located at the time of release, unless it is known that the goods will be dispatched to another member state after release then the union code for this member state is used instead.

For H3: When goods are imported under the temporary admission procedure the union code entered in **countryOfDestination** is the code of the member state where the goods are used first.

For H4: When the goods are imported under the inward processing procedure the union code entered in **countryOfDestination** is the code of the member state where the first processing activity is carried out.

regionOfDestination (16 04 001 000):
Enter the region name of the destination.

ccQualifier:
The field is used to identify which country (SCI / PCI) the region name applies to when it concerns validation and handling. If the name is identical at both countries, the field can be omitted.

XML-examples:

```
<ns3:Destination>
    <ns3:countryOfDestination>NL</ns3:countryOfDestination>
    <ns3:regionOfDestination>Rotterdam</ns3:regionOfDestination>
    <ns3:ccQualifier>DK</ns3:ccQualifier>
</ns3:Destination>
```

Country of dispatch

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M GSL GIL	MC GSL GIL	M GSL GIL	M GSL GIL	M GSL GIL	MC GSL GIL [2]	n/a	**GSL:** Declaration/GoodsShipment/**CountryOfDispatch** **GIL:** Declaration/GoodsShipment/GoodsShipmentItem/**CountryOfDispatch**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
16 06 000 000	CountryOfDispatch	n/a	MC	R0012 S0028 G0642 C0002 C0654
16 06 001 000	countryOfDispatch	a2	M	G0929 CL008

Description:

The country where goods were initially dispatched from.

Rules/codes/other relevant information:

Enter the relevant union code to indicate the country the goods were dispatched from. Unless a commercial transaction or stoppage unrelated to the transport of goods has occurred in an intermediate country, then enter the union code of the last intermediate country where this toke place.
If a stoppage is to enable the consolidation of the goods en-route it is considered to be related to the transport of the goods.

CountryOfDispatch (16 06 000 000)

- H1 it's mandatory for **GSL** level
- H3 it's mandatory for **GSL** level
- H4 it's mandatory for **GSL** level
- H5 it's mandatory for **GSL** level

countryOfDispatch (16 06 001 000):
For Codelist information, see codelist – Import excel sheet found on GitHub

XML-examples:

```
<ns3:CountryOfDispatch>
  <ns3:countryOfDispatch>NO</ns3:countryOfDispatch>
</ns3:CountryOfDispatch>
```

Origin (Country of Origin)

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GIL [20]	M GIL	MC GIL [20]	M GIL [20]	M GIL [20]	MC GIL [2] [20]	n/a	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/**Origin**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
16 08 000 000	Origin	n/a	M	C0710
16 08 001 000	countryOfOrigin – [2][20]	a2	MC	G0628 C0919 CL008
16 09 001 000	countryOfPreferentialOrigin	an..4	MC	G0907 C0699

Description:

The country from which goods were initially dispatched.

Rules/codes/other relevant information:

The element origin contains info about the **country of origin** and info about the **preferential country of origin** which must be filled out under certain circumstances. The latter is only mentioned under the table **Country of preferential origin**.
For this version of origin, the union code of the country of origin is entered.

countryOfOrigin (16 08 001 000):
For Codelist information, see codelist – Import excel sheet found on GitHub
For **16 08 001 000** footnote **[20]** applies to **H1, H3, H4, H5,** and **I1** declarations, and footnote **[2]** applies to **I1** declarations.

countryOfPreferentialOrigin (16 09 001 000):
If a preferential treatment is requested based on the origin of the goods.

XML-examples:

```
<ns3:Origin>
  <ns3:countryOfOrigin>NO</ns3:countryOfOrigin>
  <ns3:countryOfPreferentialOrigin>1032</ns3:countryOfPreferentialOrigin>
</ns3:Origin>
```

Location of goods

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M GSL	M GSL	M GSL	M GSL	M GSL	M GSL	MC GSL [84]	**GSL:** Declaration/GoodsShipment/Consignment/**GoodsLocation**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
16 15 000 000	LocationOfGoods	n/a	MC	S0024 C0628 C0810
16 15 045 000	typeOfLocation	a1	M	CL347
16 15 046 000	qualifierOfIdentification	a1	M	R0686 CL326
16 15 052 000	authorisationNumber	an..35	MC	C0394
16 15 053 000	additionalIdentifier	an..8	MC	C0926
16 15 036 000	UNLOCODE	an..17	MC	C0394 CL244
16 15 047 000	CustomsOffice	n/a	MC	C0394
16 15 047 001	referenceNumber	an8	M	CL141
16 15 048 000	GNSS	n/a	MC	G0904 C0394
16 15 048 049	latitude	an..17	M	
16 15 048 050	longitude	an..17	M	
16 15 051 000	EconomicOperator	n/a	MC	C0394
16 15 051 017	identificationNumber	an..17	M	
16 15 018 000	Address	n/a	MC	C0394
16 15 018 019	streetAndNumber	an..70	M	
16 15 018 021	postcode	an..17	MC	C0505
16 15 018 022	city	an..35	M	
16 15 018 020	country	a2	M	CL199
16 15 081 000	PostcodeAddress	n/a	MC	C0394
16 15 081 025	houseNumber	an..35	MC	C0382
16 15 081 021	postcode	an..17	M	
16 15 081 020	country	a2	M	CL190

Description:

Information about the place where the goods are located.

Rules/codes/other relevant information:

Using the relevant codes, enter the location where the goods may be examined. This location shall be precise enough to allow customs to carry out the physical control of the goods.

The type of location, and how it is declared, is given by the fields: TypeCode and IdentificationType. For declaring the location of goods there are predefined codes for indicating the type of location and how it is declared with specific possible values and combinations:

typeOfLocation (16 15 045 000)
This TypeCode Indicates the type of location where the goods will be presented. Only one Type is to be used at the same time.
For Codelist information, see codelist - Import excel sheet found on GitHub

The TypeCodes and their types of locations are:
- 'A': Designated place
- 'B': Authorised place
- 'C': Approved place
- 'D': Other

qualifierOfIdentification (16 15 046 000):
Indicates how the location will be declared:
- 'U': UN/LOCODE
- 'V': Customs Office ID
- 'W': GNSS coordinates
- 'X': EORI number
- 'Y': Authorisation number
- 'Z': Free text
- 'T': Postal code

The valid combinations for the two fields are:
- 'A' and 'U': Designated place identified by UN/LOCODE (e.g., DKCPH-0011 for Copenhagen - Langelinje)
- 'A' and 'V': Designated place identified by Customs Office ID (e.g., DK007900 for Skattecenter København)
- 'B' and 'Y': Authorised place identified by Authorisation number.
- 'C' and 'Z': Approved place identified by filling in the address fields.
- 'D' and 'Z': Other place identified by filling in the address fields.
- 'D' and 'W': Other place identified by GNSS coordinates.
- 'D' and 'X': Other place identified by an EORI number.
- 'D' and 'T': Other place identified by a postal code.

authorisationNumber (16 15 052 000):
Authorisation number. Should only be filled when IdentificationType = 'Y'.

additionalIdentifier (16 15 053 000):
What to fill in this field is given by the Type of location, meaning that if:
- IdentificationType = 'U': this field should not be filled.
- IdentificationType = 'V': this field should not be filled.
- IdentificationType = 'W': this field should not be filled.
- IdentificationType = 'X': this field can be filled with an additional identifier to the EconomicOperator element. The EORI number itself should be filled in the identification field of the EconomicOperator element.
- IdentificationType = 'Z' this field should not be filled.

UNLOCODE (16 15 036 000):
For Codelist information, see codelist excel sheet found on GitHub. Should only be filled when IdentificationType = 'U'.

CustomsOffice (16 15 047 000):
referenceNumber (16 15 047 001):
Customs Office ID (e.g., DK007900).
Should only be filled when IdentificationType = 'V'.
See the list of Customs Office ID's here:
https://ec.europa.eu/taxation_customs/dds2/rd/rd_consultation_location.jsp?Lang=en

GNSS (16 15 047 000):
latitude (16 15 048 049):
Latitude coordinate of the location of goods.
longitude (16 15 048 050):
Longitude coordinate of the location of goods.
Should only be filled when IdentificationType = 'W'.

EconomicOperator (16 15 051 000):
identificationNumber (16 15 051 017):
EORI number of Economic Operator.
Should only be filled when IdentificationType = 'X'.

The following subelements of **Address (16 15 018 00**) should be filled when IdentificationType = 'Z':

streetAndNumber (16 15 019 00):
Street name and street number of the location of goods.
postcode (16 15 018 020**):**
Post code of the location of goods.
city (16 15 018 022):
City name of the location of goods.
country (16 15 018 020):
For Codelist information, see codelist excel sheet found on GitHub

The following subelements of **PostcodeAddress (16 15 081 00**) should be filled when IdentificationType = 'T':

houseNumber (16 15 081 025):
Street name and street number of the location of goods.
postcode (16 15 081 021):
Post code of the location of goods.
country (16 15 081 020):
For Codelist information, see codelist excel sheet found on GitHub.

XML-examples:

Designated place identified by Customs Office ID:

```
<ns3:LocationOfGoods>
  <ns3:typeOfLocation>A</ns3:typeOfLocation>
  <ns3:qualifierOfIdentification>V</ns3:qualifierOfIdentification>
  <ns3:CustomsOffice>
    <ns3:referenceNumber>DK005607</ns3:referenceNumber>
  </ns3:CustomsOffice>
</ns3:LocationOfGoods>
```

Approved place identified by GNSS coordinates:

```
<ns3:LocationOfGoods>
  <ns3:typeOfLocation>C</ns3:typeOfLocation>
  <ns3:qualifierOfIdentification>W</ns3:qualifierOfIdentification>
  <ns3:GNSS>
    <ns3:latitude>123</ns3:latitude>
    <ns3:longitude>456</ns3:longitude>
  </ns3:GNSS>
</ns3:LocationOfGoods>
```

Authorised place identified by an EORI number:

```
<ns3:LocationOfGoods>
  <ns3:typeOfLocation>B</ns3:typeOfLocation>
  <ns3:qualifierOfIdentification>X</ns3:qualifierOfIdentification>
  <ns3:EconomicOperator>
    <ns3:identificationNumber>DK12345678</ns3:identificationNumber>
  </ns3:EconomicOperator>
</ns3:LocationOfGoods>
```

Other place identified by filling in the address fields :

```
<ns3:LocationOfGoods>
  <ns3:typeOfLocation>D</ns3:typeOfLocation>
  <ns3:qualifierOfIdentification>Z</ns3:qualifierOfIdentification>
  <ns3:additionalIdentifier>IDloc</ns3:additionalIdentifier>
  <ns3:Address>
    <ns3:streetAndNumber>Line 12</ns3:streetAndNumber>
    <ns3:postcode>Post</ns3:postcode>
    <ns3:city>City</ns3:city>
    <ns3:country>NO</ns3:country>
  </ns3:Address>
</ns3:LocationOfGoods>
```

Mixed data to copy from – not a valid example:

```
<ns3:LocationOfGoods>
  <ns3:typeOfLocation>A</ns3:typeOfLocation>
  <ns3:qualifierOfIdentification>U</ns3:qualifierOfIdentification>
  <ns3:authorisationNumber>ds</ns3:authorisationNumber>
  <ns3:additionalIdentifier>IDloc</ns3:additionalIdentifier>
  <ns3:UNLOCODE>11111</ns3:UNLOCODE>
  <ns3:CustomsOffice>
    <ns3:referenceNumber>DK005607</ns3:referenceNumber>
  </ns3:CustomsOffice>
  <ns3:GNSS>
    <ns3:latitude>123</ns3:latitude>
    <ns3:longitude>456</ns3:longitude>
  </ns3:GNSS>
  <ns3:EconomicOperator>
    <ns3:identificationNumber>ID1</ns3:identificationNumber>
  </ns3:EconomicOperator>
  <ns3:Address>
    <ns3:streetAndNumber>Line 12</ns3:streetAndNumber>
    <ns3:postcode>Post</ns3:postcode>
    <ns3:city>City</ns3:city>
    <ns3:country>NO</ns3:country>
  </ns3:Address>
</ns3:LocationOfGoods>
```

Group 17 – Customs Offices

11

Customs office of presentation

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M DL [22]	M DL [22]	M DL [22]	M DL [22]	M DL [22]	M DL [22]	M DL [22]	**Basepath:** Declaration/**CustomsOfficeOfPresentation**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
17 09 000 000	CustomsOfficeOfPresentation	n/a	M	R0907
17 09 001 000	referenceNumber	an8	M	CL141

Description:

Details identifying the customs office where the goods are presented to place them under a customs procedure or temporary storage.

Rules/codes/other relevant information:

CustomsOfficeOfPresentation (17 09 000 000):
The customs office of presentation (PCI) should always be declared.

referenceNumber (17 09 001 000):
For Codelist information, see codelist – Import excel sheet found on GitHub.

XML-examples:

```
<ns3:CustomsOfficeOfPresentation>
  <ns3:referenceNumber>NL000205</ns3:referenceNumber>
</ns3:CustomsOfficeOfPresentation>
```

Supervising customs office

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	O DL [23]	O DL [23]	O DL [23]	MC DL [23]	n/a	MC DL [23]	n/a	**Basepath:** Declaration/**SupervisingCustomsOffice**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
17 10 000 000	SupervisingCustomsOffice	n/a	O	G0631
17 10 001 000	referenceNumber	an8	M	CL141

Description:

Details identifying the government agency office responsible for supervising the discharge of a government procedure

Rules/codes/other relevant information:

SupervisingCustomsOffice (17 10 000 000):
The supervising customs office of Denmark (SCI) is always the main center at Århus – DK004700

referenceNumber (17 10 017 000):
For Codelist information, see codelist – Import excel sheet found on GitHub.

XML-examples:

```
<ns3:SupervisingCustomsOffice>
  <ns3:referenceNumber>DK004700</ns3:referenceNumber>
</ns3:SupervisingCustomsOffice>
```

Group 18 – Goods identification

12

Goods Measure (Net Mass)

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M GIL	n/a	n/a	M GIL	M GIL [24]	MC GIL [2]	n/a	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/Commodity/**GoodsMeasure**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
18 01 000 000	GoodsMeasure	n/a	M	
18 01 001 000	netMass	n..16,6	MC	G0907 G0984 C0935

Description:

Details about the goods weight, quantities, and amounts.

Rules/codes/other relevant information:

The net mass must contain the weight of the goods concerned with the relevant declaration goods item. The weight must be expressed in kilograms and should be the weight of the goods without the packaging.

Note:
Where a net mass greater than 1 kg includes a fraction of a unit (kg), it may be rounded off in the following manner:
— from 0,001 to 0,499: rounding down to the nearest kg,
— from 0,5 to 0,999: rounding up to the nearest k
A net mass of less than 1 kg should be entered as '0,' followed by a number of decimals up to 6, discarding all "0" at the end of the quantity (e.g. 0,123 for a package of 123 grams, 0,00304 for a package of 3 grams and 40 milligrams or 0,000654 for a package of 654 milligrams).

GoodsMeasure (18 01 000 000):
This element is allowed to be supplemented and estimated.
As seen in the XML-example below, this field shall not be filled out, but the child element **netMass** shall.

netMass (18 01 001 000):
For **18 01 001 000** footnote **[24]** applies to **H5** declarations, and footnote **[2]** applies to **I1** declarations.

XML-examples:

```
<ns3:GoodsMeasure>
    ...
    <ns3:netMass>30000.00</ns3:netMass>
    ...
</ns3:GoodsMeasure>
```

Goods Measure (Supplementary Units)

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GIL	MC GIL	MC GIL	MC GIL	MC GIL [24]	MC GIL [2]	n/a	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/Commosity/**GoodsMeasure**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
18 02 000 000	GoodsMeasure	n/a	M	
18 02 001 000	supplementaryUnits	n..16,6	MC	S0019 G0907 C0905 C0936

Description:

Details about the goods weight, quantities, and amounts.

Rules/codes/other relevant information:

If necessary, this field can be used to enter the quantity of the item in question. It should be expressed using the unit defined by Union legislation as published in TARIC.

supplementaryUnits (18 02 001 000):
For Codelist information, see codelist – Import excel sheet found on GitHub.
This element is allowed to be supplemented and estimated.

For **18 02 000 000** and **18 02 001 000** footnote **[24]** applies to **H5** declarations and footnote **[2]** applies to **I1** declarations.

XML-examples:

```
<ns3:GoodsMeasure>
  ...
  <ns3:supplementaryUnits>30000.00</ns3:supplementaryUnits>
</ns3:GoodsMeasure>
```

Goods Measure (Gross Mass)

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M GSL GIL	M GSL GIL	M GSL GIL	M GSL GIL	M GSL GIL	M GSL GIL	M GSL	**GSL:** Declaration/GoodsShipment/Consignment/**grossMass** **GIL:** Declaration/GoodsShipment/GoodsShipmentItem/Commodity/**GoodsMeasure**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
18 04 000 000	GoodsMeasure	n/a	M	**– Not used at GSL**
18 04 001 000	grossMass	n..16,6	O	G0905

Description:

Details about the goods weight, quantities, and amounts.

Rules/codes/other relevant information:

GoodsMeasure (18 04 000 000):
This element is allowed to be supplemented and estimated.
As seen in the XML-example below, this field shall not be filled out, but the child element **grossMass** shall. Also this field and its child element are the only elements inside **GoodsMeasure** on GSL.

grossMass (18 04 001 000):
The gross mass is the weight of the goods including packaging but excluding the carrier's equipment for the declaration.

Note:
Where a gross mass greater than 1 kg includes a fraction of a unit (kg), it may be rounded off in the following manner:
— from 0,001 to 0,499: rounding down to the nearest kg,
— from 0,5 to 0,999: rounding up to the nearest kg.

A gross mass of less than 1 kg should be entered as '0,' followed by at least one decimal and up to at most 6 decimals, discarding all "0" at the end of the quantity (e.g. 0,123 for a package of 123 grams, 0,00304 for a package of 3 grams and 40 milligrams or. 0,000654 for a package of 654 milligrams).

When the weight of the pallets is included in the transport documents, the weight of the pallets shall also be included in the calculation of the gross mass, except for the following cases:
a) The pallet forms a separate item on the customs declaration.
b) The duty rate for the item in question is based on the gross weight and/or the tariff quota for the item in question is managed in measurement unit 'gross weight'.

Where the declaration comprises several goods items, which concern goods that are packed together in such a way that it is impossible to determine the gross mass of the goods pertaining to any goods item, the total gross mass needs only to be entered on header level.

XML-examples:

On GSL:

```
<ns3:grossMass>30000.00</ns3:grossMass>
```

On GIL:

```
<ns3:GoodsMeasure>
    <ns3:grossMass>100.000</ns3:grossMass>
    ...
</ns3:GoodsMeasure>
```

Description of goods

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M GIL	M GIL	M GIL	M GIL	M GIL	M GIL	M GIL	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/Commodity/**descriptionOfGoods**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
18 05 000 000	Commodity	n/a	M	
18 05 001 000	descriptionOfGoods	an..512	M	

Description:

A description about the properties of the goods

Rules/codes/other relevant information:

Where the declarant provides the CUS code for chemical substances and preparations, Member States may waive the requirement of providing a precise description of the goods.

For H1 to H5 and I1:
The description of the goods means the normal trade description. Except for non-Union goods placed under the customs warehousing procedure in a public customs warehouse type I, II or III or a private customs warehouse, this description must be expressed in terms sufficiently precise to enable immediate and unambiguous identification and classification of the goods.

For H6 and H7:
It is a plain language description that is precise enough for Customs services to be able to identify the goods.

XML-examples:

```
<ns3:Commodity>
  <ns3:descriptionOfGoods>
Heifers of the grey, brown or yellow mountain breeds and spotted Pinzgau breed, other than for slaughter; Of a weight not exceeding 80 kg
  </ns3:descriptionOfGoods>
</ns3:Commodity>
```

Packaging

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M GIL	M GIL	M GIL	M GIL	M GIL	M GIL	M GIL	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/**Packaging**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
18 06 000 000	Packaging	n/a	M	
None	sequenceNumber	n..2	M	R0987
18 06 003 000	typeOfPackages – [25][84][85]	an2	M	CL017 CL181 CL182
18 06 004 000	numberOfPackages – [25]	n..8	MC	R0364 G0019 C0060
18 06 054 000	shippingMarks	an..512	MC	S0025 C0060 C0820

Description:

Details related to packaging.

Rules/codes/other relevant information:

sequenceNumber:
There can be declared multiple packaging details. Number them sequentially here.

typeOfPackages (18 06 003 000):
Code specifing the type of package.
For Codelist information, see codelist - Import excel sheet found on GitHub.
For **18 06 003 000** footnote **[25], [84]** and **[85]** applies to **I2** declarations.

numberOfPackages (18 06 004 000):
Total number of packages based on the smallest external packing unit. This is the number of individual items packaged in such a way that they cannot be divided without first undoing the packing, or the number of pieces, if unpackaged. This information shall not be provided for goods in bulk.
For **18 06 004 000** footnote **[25]** applies to **I2** declarations, and footnote **[57]** applies to **H7** declarations.

shippingMarks (18 06 054 000):
Free form describing the marks and numbers on the transport unit or packages.
For **I1** this information will only be provided for packaged goods where applicable. Where goods are containerized, the container number can replace the shipping marks, which can however be provided by the economic operator where available. A UCR or the references in the transport document that allows the unambiguous identification of all packages in the consignment may replace the shipping marks.

XML-examples:

```
<ns3:Packaging>
  <ns3:sequenceNumber>1</ns3:sequenceNumber>
  <ns3:typeOfPackages>CG</ns3:typeOfPackages>
  <ns3:numberOfPackages>200</ns3:numberOfPackages>
  <ns3:shippingMarks>MarksNumbersID</ns3:shippingMarks>
</ns3:Packaging>
```

Commodity code (CUS Code)

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GIL	O GIL	O GIL	MC GIL	MC GIL	O GIL	n/a	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/**Commodity**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
18 08 000 000	Commodity	n/a	M	
18 08 001 000	CUSCode	an9	O	G0901 CL016

Description:

CUS code is for chemical substances.

Rules/codes/other relevant information:

Commodity (18 08 000 000):
This element and its sub elements are allowed to be supplemented and estimated.

CUSCode (18 08 001 000):
Source: ECICS (European Customs Inventory of Chemical Substances)
Definition: Customs Union and Statistics (CUS) number assigned within the European Customs Inventory of Chemical Substances (ECICS) to mainly chemical substances and preparations.

XML-examples:

```
<ns3:Commodity>
  <ns3:CUSCode>0010013-0</ns3:CUSCode>
</ns3:Commodity>
```

Commodity code (Harmonized system sub-heading code)

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GIL	MC GIL	MC GIL	MC GIL	MC GIL	MC GIL	n/a	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/Commodity/**CommodityCode**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
18 09 000 000	CommodityCode	n/a	MC	C0654
18 09 056 000	harmonizedSystemSubheadingCode	an6	M	CL152

Description:

Type of goods indicated by the commodity code/combined nomenclature code.

Rules/codes/other relevant information:

CommodityCode (18 09 000 000):
This element and its sub elements are allowed to be supplemented and estimated.

harmonizedSystemSubheadingCode (18 09 056 000):
This is the first 6 digits of the Taric commodity code, e.g. if you have a Taric code: 01022110, then HS = 010221
TARIC codes can be found here: https://ec.europa.eu/taxation_customs/dds2/taric/taric_consultation.jsp?Lang=en

XML-examples:

```
<ns3:CommodityCode>
  <ns3:harmonizedSystemSubheadingCode>010221</ns3:harmonizedSystemSubheadingCode>
</ns3:CommodityCode>
```

Commodity code (Combined nomenclature code)

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GIL	MC GIL	MC GIL	MC GIL	MC GIL	MC GIL	n/a	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/Commodity/**CommodityCode**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
18 09 000 000	CommodityCode	n/a	MC	C0654
18 09 057 000	combinedNomenclatureCode	an2	M	

Description:

Type of goods indicated by the combined nomenclature code.

Rules/codes/other relevant information:

Classification (18 09 000 000):
This element and its sub elements are allowed to be supplemented and estimated.

combinedNomenclatureCode (18 09 057 000):
This is the 7th and 8th digit of the Taric commodity code, e.g. if you have a Taric code: 01022110, then CN = 10
TARIC codes can be found here: https://ec.europa.eu/taxation_customs/dds2/taric/taric_consultation.jsp?Lang=en

XML-examples:

```
<ns3:CommodityCode>
   <ns3:combinedNomenclatureCode>10</ns3:combinedNomenclatureCode>
</ns3:CommodityCode>
```

Commodity code (TARIC code)

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GIL	MC GIL	MC GIL	MC GIL	MC GIL	MC GIL	n/a	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/Commodity/**CommodityCode**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
18 09 000 000	CommodityCode	n/a	MC	C0654
18 09 058 000	taricCode	an2	MC	C0820

Description:

The Taric Code used to specify applicable duties and taxes to the imported goods.

Rules/codes/other relevant information:

CommodityCode (18 09 000 000):
This element and its sub elements are allowed to be supplemented and estimated.

taricCode (18 09 059 000):
The identification code for the Taric Code, which can be searched for here:
https://tarif.skat.dk/arctictariff-public-web/#!/taric/measure/mcc/search
Be aware that different Taric Codes have different conditions which apply to the commodity and procedure codes.

XML-examples:

```
<ns3:CommodityCode>
  <ns3:taricCode>90</ns3:taricCode>
</ns3:CommodityCode>
```

Commodity code (TARIC additional code)

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GIL	MC GIL	MC GIL	MC GIL	MC GIL	MC GIL	n/a	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/Commodity/**CommodityCode**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
18 09 000 000	CommodityCode	n/a	M	
None	TaricAdditionalCode	n/a	MC	S0032 C0820 C0869
None	sequenceNumber	n..2	M	R0987
18 09 059 000	taricAdditionalCode	an4	M	

Description:

The Taric Additional Code used to specify more detailed information about the goods, such as measures and provisions affecting the import or export of the goods, and any specific requirements for them.

Rules/codes/other relevant information:

CommodityCode (18 09 000 000):
This element and its sub elements are allowed to be supplemented and estimated.

TaricAdditionalCode:
This is a wrapper group to contain sequenceNumber and taricAdditionalCode, as described below.

sequenceNumber:
There can be declared multiple additional taric codes. Number them sequentially here.

taricAdditionalCode (18 09 059 000):
The identification code for the Taric Additional Code, which can be searched for here:
https://tarif.skat.dk/arctictariff-public-web/#!/taric/measure/mcc/search
Be aware that different Taric Additional Codes have different conditions which apply to the commodity and procedure codes.

XML-examples:

```
<ns3:CommodityCode>
  <ns3:TaricAdditionalCode>
    <ns3:sequenceNumber>1</ns3:sequenceNumber>
    <ns3:taricAdditionalCode>3212</ns3:taricAdditionalCode>
  </ns3:TaricAdditionalCode>
</ns3:CommodityCode>
```

Commodity code (National Additional Code)

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M GIL [58]	M GIL [58]	M GIL [58]	M GIL [58]	M GIL [58]	M GIL [58]	n/a	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/Commodity/**CommodityCode**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
18 09 000 000	CommodityCode	n/a	MC	C0654
None	NationalAdditionalCode	an..4	O	G0918
None	sequenceNumber	n..2	M	R0987
18 09 060 000	nationalAdditionalCode	an..4	M	G0918
None	ccQualifier	a2	MC	R0906 G0921 C0917 CL010

Description:

The National Additional Code used to specify more detailed information about the goods, such as measures and provisions affecting the import or export of the goods, and any specific requirements for them, specifically on a **national** level.

Rules/codes/other relevant information:

Commodity Code (18 09 000 000):
This element and its sub elements are allowed to be supplemented and estimated.

NationalAdditionalCode:
This is a wrapper group to contain sequenceNumber, nationalAdditionalCode and ccQualifier, as described below.

sequenceNumber:
There can be declared multiple additional national codes. Number them sequentially here.

nationalAdditionalCode (18 09 060 000):
The identification code for the National Additional Code, which can be searched for here:
https://tarif.skat.dk/arctictariff-public-web/#!/taric/measure/mcc/search

ccQualifier:
The field is used to identify which country (SCI / PCI) the national additional code applies to when it concerns validation and handling. If common codes from CS/RD2 are used that apply to both countries, the field should be omitted.
NB: The submitter is responsible for being aware of any national codes applicable at PCI and SCI.

XML-examples:

```
<ns3:CommodityCode>
  <ns3:NationalAdditionalCode>
    <ns3:sequenceNumber>1</ns3:sequenceNumber>
    <ns3:nationalAdditionalCode>3212</ns3:nationalAdditionalCode>
    <ns3:ccQualifier>DK</ns3:ccQualifier>
  </ns3:NationalAdditionalCode>
</ns3:CommodityCode>
```

13

Container indicator

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M GSL	M GSL	M GSL	M GSL	n/a	n/a	n/a	**GSL:** Declaration/GoodsShipment/Consignment/**containerIndicator**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
19 01 001 000	containerIndicator	n1	M	CL027

Description:

Data element indicating if the goods are transported in a container or not.

Rules/codes/other relevant information:

containerIndicator (19 01 001 000):
The relevant codes are:
0 - Goods not transported in containers.
1 - Goods transported in container.

XML-examples:

```
<ns3:containerIndicator>1</ns3:containerIndicator>
```

Mode of Transport at the Border

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M GSL	M GSL	M GSL	M GSL	M GSL	n/a	n/a	**GSL:** Declaration/GoodsShipment/Consignment/**modeOfTransportAtTheBorder**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
19 03 001 000	modeOfTransportAtTheBorder	n1	MC	S0003 C0630 C0627 CL018

Description:

Details of the active means of transport crossing the border of the Customs territory.

Rules/codes/other relevant information:

In the case of combined transport or where several means of transport are used, the active means of transport is the one which propels the whole combination. For example, in the case of a lorry on a sea-going vessel, the active means of transport is the ship. In the case of a tractor and trailer, the active means of transport is the tractor. The mode of transport for:

- **H1 – H4**: Enter the mode of transport corresponding to the active means of transport with which the goods entered the customs territory of the Union.
- **H5**: Enter the mode of transport corresponding to the active means of transport with which the goods entered the fiscal territory concerned.

modeOfTransportAtTheBorder (19 03 001 000):
For Codelist information, see codelist – Import excel sheet found on GitHub.

XML-examples:

```
<ns3:modeOfTransportAtTheBorder>5</ns3:modeOfTransportAtTheBorder>
```

Arrival Transport Means (Inland mode of transport)

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GSL [32]	MC GSL [32]	MC GSL [32]	MC GSL [32]	MC GSL	n/a	n/a	**GSL:** Declaration/GoodsShipment/Consignment/**inland-ModeOfTransport**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
19 04 001 000	inlandModeOfTransport	n1	MC	G0641 C0625 CL018

Description:

The mode of transport used upon the goods arrival.

Rules/codes/other relevant information:

inlandModeOfTransport (19 04 001 000):
For codelist information, see codelist – Import excel sheet found on GitHub.
The code that identifies the mode of transportation e.g. '1' for Sea transport.

For **19 04 001 000** footnote **[32]** applies to **H1, H2, H3,** and **H4** declarations.

XML-examples:

```
<ns3:inlandModeOfTransport>9</ns3:inlandModeOfTransport>
```

Arrival Transport Means (identification info)

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GSL [34]	n/a	MC GSL [34]	MC GSL [34]	MC GSL [34]	n/a	n/a	**GSL:** Declaration/GoodsShipment/Consignment/**Arrival-TransportMeans**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
19 06 000 000	ArrivalTransportMeans	n/a	MC	S0009 G0925 C0623 C0646
19 06 061 000	typeOfIdentification	n2	M	CL750
19 06 017 000	identificationNumber	an..35	M	

Description:

Info on identification method based on means of transport and ID

Rules/codes/other relevant information:

identificationNumber (19 06 017 000):
For codelist information, see codelist – Import excel sheet found on GitHub.
Depending on the means of transport concerned, the following details concerning identity shall be entered:
Means of transport - Method of identification

- Sea and inland waterway transport - Name of vessel
- Air transport - Number and date of flight (where there is no flight number, enter the aircraft's registration number)
- Road transport - Vehicle and/or trailer registration number
- Rail transport - Wagon number

typeOfIdentification (19 06 061 000):
The code for the identification type e.g. '10' for Ship Identification Number.
The first digit of this code must be equal to the digit declared in ModeCode.

XML-examples:

```
<ns3:ArrivalTransportMeans>
  <ns3:typeOfIdentification>11</ns3:typeOfIdentification>
  <ns3:identificationNumber>DEPID123</ns3:identificationNumber>
</ns3:ArrivalTransportMeans>
```

Transport equipment

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GSL [62]	MC GSL [62]	MC GSL [62]	MC GSL [62]	MC GSL [62]	MC GSL [62]	n/a	**GSL:** Declaration/GoodsShipment/Consignment/**TransportEquipment**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
19 07 000 000	TransportEquipment	n/a	MC	
None	sequenceNumber	n..5	M	R0987
19 07 063 000	containerIdentificationNumber	an..17	M	
19 07 044 000	GoodsReference	n/a	MC	C0907
None	sequenceNumber	n..5	M	R0987
11 11 001 000	declarationGoodsItemNumber	n..5	M	

Description:

Details of the transport equipment used for the consignment.

Rules/codes/other relevant information:

sequenceNumber (at transport equipment level):
There can be declared multiple transport equipments. Number them sequentially here.

containerIdentificationNumber (19 07 063 000):
Marks (letters and/or numbers) which identify the container.
For modes of transport other than air, a container is a special box to carry freight, strengthened and stackable and allowing horizontal or vertical transfers. In the air mode, containers are special boxes to carry freight, strengthened and allowing horizontal or vertical transfers.

In the context of this data element, the swap bodies and semi-trailers used for road and rail transport shall be considered as containers. For swap bodies and semi-trailers the ILU (Intermodal Loading Units) code as introduced by the European EN 13044 standard shall be used.

If applicable, for containers covered by the standard ISO 6346, the identifier (prefix) allocated by the International Bureau of Containers and Intermodal Transport (BIC) shall also be provided in addition to the container identification number.

sequenceNumber (at goods reference level):
For each container there can be multiple goods referenced. Number them sequentially here.

declarationGoodsItemNumber (11 11 001 000):
Reference of goods in container, as declared in Goods Shipment Item.

XML-examples:

```
<ns3:TransportEquipment>
  <ns3:sequenceNumber>1</ns3:sequenceNumber>
  <ns3:containerIdentificationNumber>AA565AR325</ns3:containerIdentificationNumber>
  <ns3:GoodsReference>
    <ns3:sequenceNumber>1</ns3:sequenceNumber>
    <ns3:declarationGoodsItemNumber>1</ns3:declarationGoodsItemNumber>
  </ns3:GoodsReference>
</ns3:TransportEquipment>
```

Active Border Transport Means

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GSL [37]	n/a	MC GSL [37]	MC GSL [37]	MC GSL [37]	n/a	n/a	**GSL:** Declaration/GoodsShipment/Consignment/**ActiveBorderTransportMeans**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
19 08 000 000	ActiveBorderTransportMeans	n/a	M	S0020 C0810 C0931
19 08 062 000	nationality	a2	M	CL165

Description:

Details of the active means of transport crossing the border of the Customs territory.

Rules/codes/other relevant information:

The nationality code of the active means of transport entering the union. In the case of combined transport or where several means of transport are used, the active means of transport is the one which propels the whole combination. For example, in the case of a lorry on a sea-going vessel, the active means of transport is the ship. In the case of a tractor and trailer, the active means of transport is the tractor.

nationality (19 08 062 000):
For Codelist information, see codelist – Import excel sheet found on GitHub.

XML-examples:

```
<ns3:ActiveBorderTransportMeans>
  <ns3:nationality>NO</ns3:nationality>
</ns3:ActiveBorderTransportMeans>
```

Group 99 – Goods identification

14

Quota order number

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC GIL	n/a	n/a	n/a	n/a	MC GIL [2]	n/a	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/Commodity/**quotaOrderNumber**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
99 01 001 000	quotaOrderNumber	an6	O	

Description:

Code specifying the nature of a transaction associated with a shipment.

Rules/codes/other relevant information:

quotaOrderNumber (99 01 001 000):
Enter the order number of the tariff quota for which the declarant is applying.

XML-examples:

```
<ns3:quotaOrderNumber>000009</ns3:quotaOrderNumber>
```

Guarantee

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	MC DL [39]	n/a	M DL	M DL	n/a	n/a	n/a	**Basepath:** Declaration/**Guarantee**

EUCDM 6.1	XSD/XML-name	Format	M/O	Comment
99 00 000 000	Guarantee	n/a	MC	S0014 C0616 C0697
None	sequenceNumber	n1	M	R0987
99 02 001 000	guaranteeType – [39]	an1	M	CL251
99 03 000 000	GuaranteeReference	n/a	M	

Description:

Using the relevant Union codes, enter the type of guarantee used for the operation.

Rules/codes/other relevant information:

sequenceNumber:
There can be declared multiple guarantees. Number them sequentially here.

guaranteeType (99 02 001 000):
For Codelist information, see codelist - Import excel sheet found on GitHub.
For **99 02 001 000**, footnote **[39]** applies to **H1** declarations.

XML-examples:

```
<ns3:Guarantee>
    <ns3:sequenceNumber>1</ns3:sequenceNumber>
    <ns3:guaranteeType>D</ns3:guaranteeType>
    <ns3:GuaranteeReference>
        ...
    </ns3:GuaranteeReference>
</ns3:Guarantee>
```

Guarantee reference (ObligationGuarantee)

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	O DL [39]	n/a	M DL	M DL	n/a	n/a	n/a	**Basepath:** Declaration/Guarantee/**GuaranteeReference**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
99 03 000 000	GuaranteeReference	n/a	M	
None	sequenceNumber	n..2	M	R0987
99 03 069 000	GRN	an..24	MC	C0648
None	ccQualifier	a2	MC	R0906 G0113 C0130 CL010
99 03 070 000	accessCode	an..4	O	G0647
99 03 012 000	currencyCode	a3	M	CL048
99 03 071 000	amountToBeCovered	n..16,2	M	G0019
99 03 073 000	otherGuaranteeReference	n..35	MC	C0130
99 03 072 000	CustomsOfficeOfGuarantee	n/a	MC	C0925
17 01 001 000	referenceNumber	an8	M	CL141

Description:

Info about a guarantee like reference number, amount, currency type, and more.

Rules/codes/other relevant information:

sequenceNumber:
There can be declared multiple guarantee references. Number them sequentially here.

GRN (guarantee reference number) (99 03 069 000):
The GRN or guarantee reference number used to identify which guarantee the other info relates to

ccQualifier:
The field is used to identify which country (SCI / PCI) either the guarantee reference number or the other guarantee reference, depending on which of these data items is used, applies to when it concerns validation and handling. If common codes from CS/RD2 are used that apply to both countries, the field should be omitted.
NB: The submitter is responsible for being aware of any national codes applicable at PCI.

accessCode (99 03 070 000):
The access code of the guarantee.

currencyCode (99 03 012 000):
For Codelist information, see codelist - Import excel sheet found on GitHub.

amountToBeCovered (99 03 071 000):
The amount of customs debt that can incur or has incurred for this declaration and must be covered by the guarantee.

otherGuaranteeReference (99 03 073 000):
When a guarantee is not valid for all the common transit countries enter the relevant countries or country concerned. Provide the reference number of the guarantee used for the operation and if appropriate the access code and the office of guarantee

CustomsOfficeOfGuarantee (99 03 072 000):
The office where the guarantee is registered, by filling in the **referenceNumber (17 01 001 000)**.

XML-examples:

```
<ns3:GuaranteeReference>
    <ns3:sequenceNumber>1</ns3:sequenceNumber>
    <ns3:GRN>DKTEA16-0838248<ns3:GRN>
    <ns3:ccQualifier>DK</ns3:ccQualifier>
    <ns3:accessCode>12A3</ns3:accessCode>
    <ns3:currencyCode>DKK</ns3:currencyCode>
    <ns3:amountToBeCovered>74429</ns3:amountToBeCovered>
    <ns3:otherGuaranteeReference>ABC123</ns3:otherGuaranteeReference>
    <ns3:CustomsOfficeOfGuarantee>
        <ns3:referenceNumber>DK004700<ns3:referenceNumber>
    </ns3:CustomsOfficeOfGuarantee>
</ns3:GuaranteeReference>
```

Nature of Transaction

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M GSL GIL	O GSL GIL	M GSL GIL	M GSL GIL	M GSL GIL [24]	n/a	n/a	**GSL**: Declaration/GoodsShipment/**natureOfTransaction** **GIL**: Declaration/ GoodsShipment/GoodsShipmentItem/**natureOfTransaction**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
99 05 000 000	natureOfTransaction	n2	MC	R0012 S0031 G0642 G0984 C0002 C0627 C0715 CL091

Description:

Code specifying the nature of a transaction associated with a shipment.

Rules/codes/other relevant information:

natureOfTransaction (99 05 001 000):
For Codelist information, see codelist - Import excel sheet found on GitHub.
For **99 05 001 000**, footnote **[24]** applies to **H5** declarations.

XML-examples:

```
<ns3:natureOfTransaction>11</ns3:natureOfTransaction>
```

Statistical value

C/A	Requirement Overview							XSD-path
	H1	H2	H3	H4	H5	I1	I2	
Yes/Yes	M GIL [40]	M GIL [40]	M GIL [40]	M GIL [40]	M GIL [40]	n/a	n/a	**GIL:** Declaration/GoodsShipment/GoodsShipmentItem/**statisticalValue**

EUCDM 7.0	XSD/XML-name	Format	M/O	Comment
99 06 000 000	statisticalValue	n..16,2	M	

Description:

Value declared for statistical purposes of those goods in a consignment which have the same statistical heading.

Rules/codes/other relevant information:

statisticalValue (99 06 001 000):
Enter the statistical value expressed in the currency unit the code for which may appear in **(14 17 000 000)** Internal currency unit, or, in the absence of such a code in **(14 17 000 000)** Internal currency unit. This currency will be that of the Member State where the import formalities are completed, in accordance with the Union provisions in force.

XML-examples:

```
<ns3:statisticalValue>100.00</ns3:statisticalValue>
```

UDVIKLINGS OG
FORENKLINGS
STYRELSEN

www.ufst.dk
ISBN [000-00-0000-0000-0]

Udviklings- og Forenklings-
styrelsen er en del af
Skatteforvaltningen