

Yes, you can upload a PIN list in bulk from a `.csv` file using SQL.

Because the PIN entries need to be linked to a specific PIN List in the database, you must first create the list in the PBX interface, and then use SQL to upload the actual PINs.

Here is the step-by-step guide on how to do this:

1. Create the PIN List Container

First, log into your CompletePBX web interface and manually create a new, empty PIN List. Give it a description (e.g., "my_pin_list") and save it.

2. Identify the PIN List ID

We need to know the database ID assigned to the list you just created. Connect by SSH to your server's command line and run:

```
mysql ombutel
```

Then run the query

```
SELECT * FROM ombu_pin_lists;
```

Note the `pin_list_id` for your new list (for example, it might be `2`).

3. Format Your CSV File

Create your `.csv` file (e.g., `Pin_List.csv`) with three columns in this exact order: **pin_list_id**, **password**, and **description**.

- **Column A (pin_list_id):** This must be the ID you found in Step 2. *Every row must have this same ID.*
- **Column B (password):** The PIN code.
- **Column C (description):** The name or description of the user.

(Note: It is fine to include a header row like "ID, PIN, Description" at the top of your spreadsheet, as the command below is designed to skip it).

1	pin_list_id	password	description
2	2	4321	General Manager
3	2	6326	Hotel Mgr
4	2	5435	Dir-Finance
5	2	2636	Dir-Rooms
6	2	4417	Dir-Engineering
7	2	2456	Dir-Sales
8	2	5454	Dir-S&M
9	2	5461	Dir-HR
10	2	3232	Dir-B&F
11	2	6541	Dir-Loss Prev.

4. Upload and Execute

Move your `Pin_List.csv` file to an accessible directory on your server (such as `/tmp/`). Then, run the following SQL command to import the data:

```
LOAD DATA LOCAL INFILE '/tmp/Pin_List.csv'
INTO TABLE ombu_pin_list_entries
FIELDS TERMINATED BY ','
LINES TERMINATED BY '\r\n'
IGNORE 1 LINES
(pin_list_id, password, description);
```

Make sure you are connected to the ombutel database before executing the last query

mysql ombutel

```
root@pbx:/tmp# mysql ombutel
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 409
Server version: 10.11.14-MariaDB-0+deb12u2 Debian 12

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [ombutel]> █
```

type exit to close the connection to the ombutel database

Important Notes on the Command:

- `LINES TERMINATED BY '\r\n'` ensures that if the CSV was saved on a Windows machine (like Excel), the line breaks are read correctly.

- `IGNORE 1 LINES` tells the database to skip your header row so it doesn't cause an error.
- Explicitly listing `(pin_list_id, password, description)` is required, otherwise the database will reject the upload.

Once executed, you can refresh your PBX web interface, and you will see all the PINs populated inside your PIN List.