

Project proposal — Fabricator of an pure electric hybrid vehicle

Dr. Suresh Kumar Gadi

Abstract—This document identifies the requirements for fabricating an electric car at FIME, UAdEC. Also, proposes a possible methodology to realize the project.

I. OBJECTIVE

The objective of this project is to model, design and fabricate an pure electric hybrid vehicle with the following functionality.

- Steep acceleration curves similar to the petroleum vehicles (PV).
- Maximizing the energy harvesting at all the times, i.e. during all kinds of the breaking routine.

II. INTRODUCTION

The electric vehicles were introduced in the early nineteenth century; these were holding a greater market in comparison to the internal combustion (IC) ones until the end of that century [1]. However, petroleum vehicles (PV) soon became more common on the roads later, which can be seen from the 2005 estimates, which indicate that the PV constitute a 97% of the vehicles [2]. Recently there is a growing interest in the hybrid vehicles (a hybrid of petroleum and electric) and pure electric vehicles (PEV) [3]–[5].

III. SELECTION OF STORAGE TYPE




Figure 1. Ragone plot — Comparison energy density (specific energy) and power density (specific power) of most common storage domains [6].




Figure 2. Ragone plot — Comparison energy density (specific energy) and power density (specific power) of various electric power storages [7].

Figure 1 shows the Ragone plot for the most common storage domains [7]. It is clear that combustion engines have high specific power and specific energy. In the context of automobiles, specific energy can be associated to the fuel autonomy measure, i.e. the distance it can move by consuming a unit fuel mass, and the specific power can be associated to the acceleration which it can achieve with a given unit fuel mass. So from Figure 1, we see that a petroleum based automobile have an advantage over any other domain. Also, we can see that a properly designed electric hybrid system can perform on par with combustion engines.

Figure 2 shows the Ragone plot of electric storage devices. We can ignore the Li-primary batteries option because they are not rechargeable. So, the solution to achieve high specific energy and specific power is combining the positive trades of the super-capacitors (electrochemical capacitors) and the Li-ion batteries in an hybrid system.

IV. SYSTEM SCHEME

Figure x shows the power flow diagram in an electric vehicle

REFERENCES

- [1] M. Guarnieri, "Looking back to electric cars," in *2012 Third IEEE HISTory of ELECTro-technology CONference (HISTELCON)*, Sept 2012, pp. 1–6.
- [2] J. De Santiago, H. Bernhoff, B. Ekerård, S. Eriksson, S. Ferhatovic, R. Waters, and M. Leijon, "Electrical motor drivelines in commercial all-electric vehicles: a review," *IEEE Transactions on Vehicular Technology*, vol. 61, no. 2, pp. 475–484, 2012.
- [3] Y. Hori, "Future vehicle driven by electricity and control-research on four-wheel-motored" uot electric march ii";" *IEEE Transactions on Industrial Electronics*, vol. 51, no. 5, pp. 954–962, 2004.
- [4] T. Turrentine, "Who will buy electric cars?" *ACCESS Magazine*, vol. 1, no. 6, 1995.
- [5] J. Hildermeier, "Electric vechiles in europe - 2016," 2016. [Online]. Available: <https://www.transportenvironment.org/sites/te/files/publications/TE%20EV%20Report%202016%20FINAL.pdf>
- [6] M. Winter and R. J. Brodd, "What are batteries, fuel cells, and supercapacitors?" *Chemical reviews*, vol. 104, no. 10, pp. 4245–4270, 2004.
- [7] P. Simon and Y. Gogotsi, "Materials for electrochemical capacitors," *Nature materials*, vol. 7, no. 11, pp. 845–854, 2008.