

## Refactoring Activity 2

Here we are continuing the work we started in refactoring activity 1. We will spend some time working on the `NumberPrinter` class and breaking it in various ways.

### Step 4: Working on the `NumberPrinter` class

Let's see if we can do some cleanup of the `NumberPrinter` class:

- The parameter to the `print` method is called `primes`, but it clearly can be any array of numbers. So perform a `Rename` refactoring to change the parameter to `numbers`.
- The other parameter is the number of numbers to print. We don't really need that any more technically, as we can simply use the length of the `numbers` array instead. To do this in a stepwise fashion, do the following:
  - Find the first use of the `number-of-primes` variable, and use “`Extract Variable`” to create a local variable equal to it, and named `numberOfNumbers`. Make sure to replace all 3 occurrences.
  - Change the `numberOfNumbers = ...` assignment to instead be `numberOfNumbers = numbers.length`. (The numbers in the array actually start at index 1) Run your tests to make sure they still work.
  - Now the parameter in the `print` method should be grayed out as it is not being used. Use the “`Safe Delete`” intention on it, and run your tests again.
- Let's continue with refactoring the `print` method into smaller parts. We start with the double `for` loop: Perform the `Extract Method` refactoring to it, to obtain a method `printNumbersOnPage`.
- It seems that the first group of `System.out` calls prints a header, so go ahead and extract the method `printHeader` from it.
- The remaining part of the `while` loops seems to update the counters as we advance through each page. It also seems that the methods we use all need those values. So we should elevate them to fields so that they can be more easily shared. Perform an “`extract field`” refactoring on the `page number`, `page offset` and `number of numbers` variables.
- Extract a method from the last three lines of the `while` loop, call it `moveToNextPage`.
- Now that we are using fields, the `page number` and `number of number` parameters in the `printHeader` method are no longer needed. Perform an “`Inline`” refactoring to them, and remove the superfluous `this.` parts that are added. Run your tests.

- Do the same for the `printNumbersOnPage` method, leaving just the `numbers` parameter to it.
- It feels that `numbers` should also be set to a field. Extract the field from the first occurrence of `numbers`, in the initialization of `numberOfNumbers`. Make sure to tell it to replace all occurrences.
- Run your tests and they should now fail. That's because IntelliJ did not actually add a statement to initialize `this.numbers` to equal the parameter `numbers`. Do so in the `print` method, and check that your tests are back in order.
- The `numbers` parameter in `printNumbersOnPage` should now be redundant. Perform the "Safe delete" intention on it.
- The first four lines of the `print` method are all about initializing fields. Extract them to a method `initialize`.
- The test in the while loop is determining if there are still more numbers to print. Extract it into a method `needToPrintMore` (keep the original signature when asked). This makes it more clear what that test does.
- Let's shift our attention to the `printNumbersOnPage` method. Look at the conditional at the innermost level of the loop. Let's extract it to a method `printNumberAt`.
- Notice that this new method takes two parameters but really only uses one, namely their combination as "row offset plus column offset times rows per page". Extract parameter from that expression, and tell it to replace both occurrences. It should also remove the other two parameters in this case.
- Let's look at the `row-offset` variable of the outer loop. It seems to be initialized as `page offset`, then stop at a boundary similarly depending on `page offset`. It is only used in the index computation. Change it so that it instead starts at 0 and ends at `rows-per-page minus 1`, and change the index computation to include an additional `page-offset`. Run your tests to make sure they still pass. Maybe also perform a `Rename` refactoring to now call the variable `row`.
- Looking at the stopping tests in our for loops, we are more used to seeing them with a `less than` comparison, rather with a "less than or equal to the number minus 1" comparison. So fix those up, and run our tests to make sure they still pass.

## Step 5: Reducing the number of fields

It seems there are still too many fields in the `NumberPrinter` class. A primary example is the `page offset`. It should be simple enough to compute the `page offset` from the `page number`, and it is not really used in too many places. We would like to replace it with a computation. In order to achieve this, we will do the following:

- Use the “Encapsulate Fields” refactoring to encapsulate the get access for page offset. This will replace all accesses to this page offset by a call to `getPageOffset()`. Run your tests to make sure we didn’t break anything yet.
- Now, we can edit the `getPageOffset` method to instead compute the offset from the page number and return it. The computation should be “page number minus 1 then times rows per page and times columns per page, then add one to the result.” Run our tests to make sure this change did not break anything.
- Now, the page offset field should appear grayed out in its declaration point. Go ahead and do the “Safe delete” intention and run the tests again.

Next we have the number of numbers field. It’s not used much, and we can just compute it from the numbers array instead. So let’s do that:

- Use the “Encapsulate Fields” refactoring again, this time to encapsulate the getters of the number of numbers field.
- Replace the body of the new getter to instead return the numbers array length minus one. Run the tests to make sure they still run.
- Notice that the `numberOfNumbers` field appears grayed out now, and perform the “Safe delete” intention. Make sure the tests still run.

## Step 6: Parameterizing the title

The printing of the numbers includes some header information. The first part of that information is the title, the other is the page numbers. We should probably make the title into a parameter that our creators provide, as we don’t know what kinds of numbers they would want us to print. We’ll keep the page number logic as part of our work.

This all will happen in the `printHeader` method, which currently is a series of `System.out.print` calls. Our first task would be to bring them together.

- Step-by-step merge each of the first two calls into the next one, by prepending its string to the front of the argument. For example after the first step the first two line should have become one call, with argument `"The First " + Integer.toString(getNumberOfNumbers())`. Run your tests after each step.
- Do the same to bring the last two calls together.
- Eliminate the `Integer.toString` parts (leaving their arguments intact, letting the plus operator worry about adding strings to integers).
- The `" --- Page "` part belongs with the second statement, not the first, so move it over and make sure your tests still pass.

- You should now have two `System.out...` statements, the first one setting the document title, the other setting the page number. We now want to turn the document title into a parameter. Select it and perform “Extract Parameter”, name the parameter `title`.
- Going up to the `print` method, the title shows up there instead. Do another Extract Parameter to lift it to a parameter of the `print` method. Your tests should now be failing. Go to the `PrimePrinter` method and change the call to `numberPrinter.getNumberOfNumbers` into a reference to the `number of primes` method instead.
- Back in our `printHeader` method, put the two `String.out` statements into one, then go anywhere in the string and use the Replace “+” with `String.format` intention.

## Step 7: Make the main loop clearer

There is something bothering us about the current structure of the main loop: It is supposed to be printing the next page every time, yet somehow its current structure doesn’t allow for that. Part of the problem is that the page number is currently a field value, and getting updated in mysterious intervals: It is initialized in the `initialize` method, though nothing about the name of that method suggests that, then is updated at the end of the while loop, which feels a bit backwards. Ideally our loop, and `print` function, should say:

```
while there is a next page:
    print the next page
```

Even better, we should be able to simply say:

```
for page in pages:
    print page
```

Or in Java syntax:

```
for (int page : getPages())
    printPage(page)
```

In order to achieve this, we need to have an iterator. But before that, we need to have the page number as a parameter to the methods that form our for loop. The page number is used in a number of places:

- `printHeader` uses it to print the page number on the header.
- `printNumbersOnPage` uses it in its `getOffset` calculation.
- `moveToNextPage` actually increments it, which complicates matters considerably.

Let’s work through this refactoring:

- We start with `printHeader`. Find the use of `pageNumber` in `printHeader` and perform Extract Parameter on it. Check that your tests still pass.

- Then, inline the `moveToNextPage` method and remove it. It won't really be doing much after we move around the page increment, so we'll just find a better place for the `System.out` call later. Do the same for the `initialize` method.
- Then look at the `getPageOffset` method, and perform "Extract Parameter" on the `pageNumber` variable there. Then move to the `printNumbersOnPage` method and perform "Extract Parameter" on the `pageNumber` variable from there.
- Finally, the `needToPrintMore` method also uses it via `getPageOffset`, so perform an Extract Parameter from there as well.
- Now we hopefully have isolated all the changes of the `pageNumber` field to the print method. It is set to 1 at the beginning of the print method, then incremented later on. You can confirm that the field is not used elsewhere by moving your cursor over the field declaration and using the "Navigate -> Declaration menu item". It should show you all the usages.
- Now with the cursor on the field declaration, choose the "Convert to local" intention. Then run our tests again to make sure everything works fine.

Thinking through the problem more, it almost feels like we need a separate class to capture the idea of the individual *pages*. Then that class can incorporate the logic about computing indices and knowing when it's done, for example. Perhaps we can call this new class a `Page`.

TODO