MIT 8103 Advanced Database Systems

Real-time Game Leaderboard · Joshua Olajide · Student ID 301922715

Case study

My case study is Real-time Game Leaderboard. I designed the database for players submitting scores and game operators reviewing leaderboards, with separate tables named player, game and score_event. It supports these operations: register players and games; record score updates while retaining history; filter score history and calculate game leaderboards.

Portfolio 1: Database Design and Modelling

I organised the relational design into 3 tables. Primary keys identify records, foreign keys preserve the links, and checks enforce the stated business rules. At most one score event per player and game may be marked current. The normalisation examples show the sample data at 1NF, 2NF and 3NF. All 25 deliberately invalid inserts were rejected without changing the valid sample rows.




Figure 1. Tables, keys and relationships. PK: primary key; FK: foreign key; UK: unique value.

Portfolio 2: Query Processing and Optimisation

I ran three SQL queries against the sample records. The join returned 1 rows and included pixel_pilot. For the index comparison, I used 50,000 separate performance rows. The median lookup time changed from 2.345 ms to 0.317 ms. Both phases returned the same records. The measured plan used the new index. These timings apply to this lookup and environment.

Portfolio 3: Transactions and Concurrency

I used a temporary counter on score_event to test COMMIT, ROLLBACK and READ COMMITTED isolation. The uncommitted update remained hidden from the other session, and ROLLBACK restored the earlier committed value. Without locking, two increments left the counter at 2. With SELECT FOR UPDATE, Session B waited for Session A and the final value was 3. The helper is confined to this exercise; the case's original business fields stay unchanged.

Portfolio 4: NoSQL and Advanced Data Models

I used score_events for the case's event documents. MongoDB inserted 2 sample events and returned the expected results for 4 queries. Validation rejected an invalid date type and a duplicate event ID. Embedded snapshots keep related details with an event, while the details field can differ by event type. These are fictional events; PostgreSQL continues to enforce its relational rules.

Repository and evidence

https://github.com/skillz008/Olajide_Joshua_301922715

The portfolio folders contain the SQL and JavaScript, explanations, query plans, result tables and screenshots.

Portfolio 5: Distributed and Cloud Database Exercise

I proposed three MongoDB replica members across separate failure zones. The discussion covers primary elections, majority acknowledgement, secondary lag and sharding trade-offs for score_events. Replication supports availability, while backups address recovery. PostgreSQL needs its own availability plan. This is the permitted discussion option; no live replica set or failover test was deployed.

Individual reflection

I kept player, game, score_event in separate tables so their details could be maintained without repeating them in every related record. At most one score event per player and game may be marked current. The constraint tests check this alongside the required values and record links. One issue illustrated by the two-session exercise is that both sessions can read the same value before either update is committed. Locking the row before reading preserves both increments. The index comparison also shows why I need to check the execution plan as well as the final answer: the same result can require different amounts of database work.

AI-use declaration

I used GitHub Copilot and the portfolio generator to help prepare the database model, scripts and explanations. The generator ran the PostgreSQL and MongoDB exercises, checked their outputs and captured the result images. I remain responsible for checking and explaining the submitted work.

References

- PostgreSQL: constraints
- PostgreSQL: EXPLAIN
- PostgreSQL: isolation
- PostgreSQL: row locks
- MongoDB: data modelling
- MongoDB: replication
- MongoDB: sharding
- Mermaid: ER diagrams