

# .NET 10 App Dev Hands-On Lab

## RP Lab 1 – The Razor Pages Project

This lab walks you through creating the ASP.NET Core Web Application (Razor Pages) project and adding/updating the NuGet packages. Before starting this lab, you must have completed EF Lab 6.

### Part 1: Create the Project

**NOTE:** The files `createprojects_RP` (with `.ps1`, `.sh`, and `.cmd` extensions) contain all these commands, which can be executed in batch.

- The razor template is highly configurable. Options can be explored by using `-h` (help):

```
dotnet new razor -h
```

- Create the ASP.NET Core web application project using the model-view-controller pattern:

[Windows]

```
dotnet new razor -lang c# -n AutoLot.Web -au none -o .\AutoLot.Web -f net10.0
```

- Add the project to the solution and project references:

```
dotnet sln AutoLot.slnx add AutoLot.Web
```

```
dotnet add AutoLot.Web reference AutoLot.Models
```

```
dotnet add AutoLot.Web reference AutoLot.Dal
```

```
dotnet add AutoLot.Web reference AutoLot.Services
```

- Add the required NuGet packages to the project (if using a regular command prompt, remove the single quotes):

```
dotnet add AutoLot.Web package LigerShark.WebOptimizer.Core -v '[3.*,4)'
```

```
dotnet add AutoLot.Web package Microsoft.Web.LibraryManager.Build -v '[3.*,4.0)'
```

```
dotnet add AutoLot.Web package Microsoft.EntityFrameworkCore.SqlServer -v '[10.*,11.0)'
```

```
dotnet add AutoLot.Web package Microsoft.EntityFrameworkCore.Design -v '[10.*,11.0)'
```

```
dotnet add AutoLot.Web package Microsoft.VisualStudio.Threading.Analyzers -v '[18.*,19.0)'
```

## Part 2: Disable Nullable Reference Types

### Coplot Agent Mode

Prompt:

Update the AutoLot.Web project file to disable nullable reference types (<Nullable>disable</Nullable>) and remove the nullable indicator in Error.cshtml.cs file in the AutoLot.Web project.

### Manual

- Open the new project file (\*.csproj) and update the PropertyGroup to the following (change is in bold):

```
<PropertyGroup>
  <TargetFramework>net10.0</TargetFramework>
  <ImplicitUsings>enable</ImplicitUsings>
  <Nullable>disable</Nullable>
</PropertyGroup>
```

- Remove the nullable reference indicator on the Error.cshtml.cs page in the Pages folder:

```
public string RequestId { get; set; }
```

## Part 3: Adjust the launchsettings.json file

Open the launchsettings.json file (in the project's Properties directory) and move the HTTPS profile to the top.

**NOTE:** In current versions of ASP.NET Core, the IIS profile doesn't exist until you launch your app using IIS in Visual Studio.

## Summary

This lab created the ASP.NET Core Web Application project and added the NuGet packages and the appropriate references.

## Next steps

You will start building the services layer in the next part of this tutorial series.