.NET 9 App Dev Hands-On Lab

Razor Pages Lab 9b - Data Services Part 2

This lab swaps out the repos for the data service. Before starting this lab, you must have completed Razor Pages/MVC Lab 9a.

All work in this lab takes place in the AutoLot. Web project.

Part 1: Update The Base Page

Step 1: Change from Repos to Data Services

Add the following to the GlobalUsings.cs file:

```
global using AutoLot.Services.DataServices.Dal;
global using AutoLot.Services.DataServices.Interfaces;
global using AutoLot.Services.DataServices.Interfaces.Base;
```

• Add the following to the Program.cs file with the other calls to add interfaces to the DI container:

```
builder.Services.AddScoped<ICarDataService, CarDalDataService>();
builder.Services.AddScoped<IMakeDataService, MakeDalDataService>();
```

Step 2: Update the BasePageModel

• Update the primary constructor and field to declare and initialize IDataServiceBase instead of the IBaseRepo:

```
protected virtual Task GetLookupValuesAsync()
{
  LookupValues = null;
  return Task.CompletedTask;
}
```

• Update the CRUD statements to use the new service instead of the repo:

```
Protected virtual async Task GetOneAsync(int? id)
{
  if (!id.HasValue)
  {
    Error = "Invalid request";
    Entity = null;
    return;
  Entity = await MainDataService.FindAsync(id.Value);
  if (Entity == null)
  {
    Error = "Not found";
    return;
  Error = string.Empty;
}
protected virtual async Task<IActionResult> SaveOneAsync(
  Func<TEntity,bool,Task<TEntity>> saveFunction)
{
  if (!ModelState.IsValid)
  {
    return Page();
  }
  try
  {
    var savedEntity = await saveFunction(Entity, true);
    return RedirectToPage("./Details", new { id = savedEntity.Id });
  catch (Exception ex)
    ModelState.AddModelError(string.Empty, ex.Message);
    return HandleErrorReturnPage(ex);
  }
}
protected virtual async Task<IActionResult> SaveWithLookupAsync(
    Func<TEntity,bool,Task<TEntity>> saveFunction)
{
  if (!ModelState.IsValid)
    await GetLookupValuesAsync();
    return Page();
  }
 try
    var savedEntity = await saveFunction(Entity, true);
    return RedirectToPage("./Details", new { id = savedEntity.Id });
  catch (Exception ex)
    ModelState.AddModelError(string.Empty, ex.Message);
    await GetLookupValuesAsync();
    return HandleErrorReturnPage(ex);
  }
}
```

```
protected virtual async Task<IActionResult> DeleteOneAsync(int id)
{
   try
   {
     await MainDataService.DeleteAsync(Entity);
     return RedirectToPage("./Index");
   }
   catch (Exception ex)
   {
      ModelState.Clear();
      Entity = await MainDataService.FindAsync(id);
      return HandleErrorReturnPage(ex);
   }
}
```

Part 2: Update the Cars Pages

Step 1: Update the Index Page

```
namespace AutoLot.Web.Pages.Cars;
public class IndexModel(
  IAppLogging<IndexModel> appLogging,
  ICarDataService dataService)
  : BasePageModel<Car, IndexModel>(appLogging, dataService, "Inventory")
  private readonly IAppLogging<IndexModel> _appLogging = appLogging;
  public string MakeName { get; set; }
  public int? MakeId { get; set; }
  public IEnumerable<Car> CarRecords { get; set; }
  public async Task OnGetAsync(int? makeId, string makeName)
    if (!makeId.HasValue)
     MakeName = "All Makes";
     CarRecords = await MainDataService.GetAllAsync();
      return;
    MakeId = makeId;
    MakeName = makeName;
    CarRecords = await dataService.GetAllByMakeIdAsync(makeId.Value);
}
```

Step 2: Update the Create Page

• Update the code behind to match the following:

```
namespace AutoLot.Web.Pages.Cars;
public class CreateModel(
  IAppLogging<CreateModel> appLogging,
  ICarDataService dataService,
  IMakeDataService makeDataService)
    : BasePageModel<Car, CreateModel>(appLogging, dataService, "Create")
{
  public async Task OnGetAsync()
    await GetLookupValuesAsync();
    Entity = new Car { IsDrivable = true };
  public async Task<IActionResult> OnPostCreateNewCarAsync()
    => await SaveWithLookupAsync(MainDataService.AddAsync);
  protected override async Task GetLookupValuesAsync()
    LookupValues = new SelectList(
      await makeDataService.GetAllAsync(), nameof(Make.Id), nameof(Make.Name));
}
```

Step 3: Update the Delete Page

```
namespace AutoLot.Web.Pages.Cars;
public class DeleteModel(
   IAppLogging<DeleteModel> appLogging,
   ICarDataService dataService)
   : BasePageModel<Car, DeleteModel>(appLogging, dataService, "Delete")
{
   public async Task OnGetAsync(int? id)
   {
      if (!id.HasValue)
      {
        Error = "Invalid request";
        Entity = null;
        return;
      }
      await GetOneAsync(id);
}
   public async Task<IActionResult> OnPostAsync(int id) => await DeleteOneAsync(id);
}
```

Step 4: Update the Details Page

• Update the code behind to match the following:

```
namespace AutoLot.Web.Pages.Cars;
public class DetailsModel(
   IAppLogging<DetailsModel> appLogging,
   ICarDataService dataService)
   : BasePageModel<Car, DetailsModel>(appLogging, dataService, "Details")
{
   public async Task OnGetAsync(int? id) => await GetOneAsync(id);
}
```

Step 5: Update the Edit Page

Part 3: Update the RazorSyntax Page

• Update the code behind to match the following:

Part 4: Update the Makes Pages

Step 1: Update the Index Page

• Update the code behind to match the following:

```
namespace AutoLot.Web.Areas.Admin.Pages.Makes;
public class IndexModel(
   IAppLogging<IndexModel> appLogging,
   IMakeDataService dataService)
   : PageModel
{
   [ViewData]
   public string Title => "Makes";
   public IEnumerable<Make> MakeRecords { get; set; }
   public async Task OnGetAsync() => MakeRecords = await dataService.GetAllAsync();
}
```

Step 2: Update the Create Page

```
namespace AutoLot.Web.Areas.Admin.Pages.Makes;
public class CreateModel(
   IAppLogging<CreateModel> appLogging,
   IMakeDataService dataService)
   : BasePageModel<Make, CreateModel>(appLogging, dataService, "Create")
{
   public void OnGet() => Entity = new Make();
   public async Task<IActionResult> OnPostAsync() => await SaveOneAsync(MainDataService.AddAsync);
}
```

Step 3: Update the Delete Page

• Update the code behind to match the following:

```
namespace AutoLot.Web.Areas.Admin.Pages.Makes;
public class DeleteModel(
   IAppLogging<DeleteModel> appLogging,
   IMakeDataService dataService)
   : BasePageModel<Make, DeleteModel>(appLogging, dataService, "Delete")
{
   public async Task OnGetAsync(int? id) => await GetOneAsync(id);
   public async Task<IActionResult> OnPostAsync(int id) => await DeleteOneAsync(id);
}
```

Step 4: Update the Details Page

• Update the code behind to match the following:

```
namespace AutoLot.Web.Areas.Admin.Pages.Makes;
public class DetailsModel(
   IAppLogging<DetailsModel> appLogging,
   IMakeDataService dataService)
   : BasePageModel<Make, DetailsModel>(appLogging, dataService, "Details")
{
   public async Task OnGetAsync(int? id) => await GetOneAsync(id);
}
```

Step 5: Update the Edit Page

Part 5: Update the MenuViewComponent

• Update the class to the following:

```
namespace AutoLot.Web.ViewComponents;

public class MenuViewComponent(IMakeDataService dataService) : ViewComponent
{
   public async Task<IViewComponentResult> InvokeAsync()
   {
     var makes = (await dataService.GetAllAsync()).ToList();
     if (!makes.Any())
     {
        return new ContentViewComponentResult("Unable to get the makes");
     }
     return View("MenuView", makes);
   }
}
```

Summary

This lab updated the ASP.NET Core Razor Pages web application to use the Data Services.