

.NET 9 App Dev Hands-On Lab

Blazor Lab 1 – The Blazor Projects

This lab walks you through creating the Blazor Web Assembly (WASM) projects and adding/updating the NuGet packages.

Part 1: Creating the Solution and Projects

Visual Studio (all versions) can create and manage projects and solutions, but using the .NET command-line interface (CLI) is much more efficient. When creating projects using the command line, the names of solutions, projects, and directories are case-sensitive.

Step 1: Create the Solution

The templates installed with the .NET SDK range from simple to complex. Creating the `global.json` and `NuGet.config` files are examples of simple templates, as is creating a new solution.

- To create a new solution file named `AutoLot`, enter the following command:

```
dotnet new sln -n AutoLot
```

The following commands are scripted to run in the same directory as the created solution. Each project will be created in a subfolder, added to the solution, and the required NuGet packages will be added.

Step 2: Create the Projects

Note: Non-windows users must adjust the directory separator using the following commands.

Note: PowerShell and bash need quotes around the version monikers.

- Create the Class Library for the entities and add it to the solution:
NOTE: Using PowerShell, the version intervals must be surrounded by single quotes (like `'[17.*,18.0)'`). Run the commands as shown here if using a regular command prompt.

[Windows]

```
dotnet new classlib -lang c# -n AutoLot.Blazor.Models -o .\AutoLot.Blazor.Models -f net9.0
```

```
dotnet sln AutoLot.sln add AutoLot.Blazor.Models
```

```
dotnet add AutoLot.Blazor.Models package Microsoft.VisualStudio.Threading.Analyzers -v [17.*,18.0)
```

- Create the Blazor WebAssembly Standalone App project, add it to the solution, and add a reference to the class library:

```
dotnet new blazorwasm -lang c# -au none -n AutoLot.Blazor -o .\AutoLot.Blazor -f net9.0
```

```
dotnet sln AutoLot.sln add AutoLot.Blazor
```

```
dotnet add AutoLot.Blazor reference AutoLot.Blazor.Models
```

- Add the required NuGet packages to the `AutoLot.Blazor` project (each on only one line):

```
dotnet add AutoLot.Blazor package Microsoft.AspNetCore.Components.WebAssembly -v [9.0.*,10.0)
```

```
dotnet add AutoLot.Blazor package Microsoft.AspNetCore.Components.WebAssembly.DevServer -v [9.0.*,10.0)
dotnet add AutoLot.Blazor package Microsoft.Extensions.Http -v [9.0.*,10.0)
dotnet add AutoLot.Blazor package Microsoft.Extensions.Options.ConfigurationExtensions -v [9.0.*,10.0)
dotnet add AutoLot.Blazor package Microsoft.VisualStudio.Threading.Analyzers -v [17.*,18.0)
dotnet add AutoLot.Blazor package Microsoft.Web.LibraryManager.Build -v [2.*,3.0)
```

Step 3: Disable Nullable Reference Types

- Open the new project files (AutoLot.Blazor.csproj, AutoLot.Blazor.Models.csproj) and update the PropertyGroup to disable nullable reference types. NOTE: The order is different in the two project files. Be careful to disable Nullable and NOT ImplicitUsings:

```
<Nullable>disable</Nullable>
```

- Open the NavMenu.Razor file and update the string property not to be nullable:

```
private string NavMenuCssClass => collapseNavMenu ? "collapse" : null;
```

Step 4: (VS) Set AutoLot.Blazor as the startup project

Right-click on AutoLot.Blazor and select "Set as Startup Project" from the context menu.

Step 5: Adjust the launchsettings.json file

Open the launchsettings.json file (in the Properties directory of the project) and move the HTTPS profile to the top. NOTE: If you want to add the IIS Profile, select IIS Express in Visual Studio, and one will be created.

Part 3: Clean up Unnecessary Scaffolded Code

- Delete Pages\Counter.razor and Pages\Weather.razor files.
- Delete the wwwroot\sample-data folder and the JSON file it contains.
- Delete the following from Layout\NavMenu.razor:

```
<div class="nav-item px-3">
  <NavLink class="nav-link" href="counter">
    <span class="bi bi-plus-square-fill-nav-menu" aria-hidden="true"></span> Counter
  </NavLink>
</div>
<div class="nav-item px-3">
  <NavLink class="nav-link" href="weather">
    <span class="bi bi-list-nested-nav-menu" aria-hidden="true"></span> Weather
  </NavLink>
</div>
```

Part 4: Manage Client-Side Libraries

- Add a JSON file named `libman.json` to the root of the **AutoLot.Blazor** project. Update the file to match the following:

```
{
  "version": "1.0",
  "defaultProvider": "cdnjs",
  "libraries": [
    {
      "library": "twitter-bootstrap@5.3.3",
      "destination": "wwwroot/lib/bootstrap",
      "files": [
        "css/bootstrap.css",
        "css/bootstrap.min.css"
      ]
    },
    {
      "library": "font-awesome@6.7.1",
      "destination": "wwwroot/lib/font-awesome/",
      "files": [
        "css/all.min.css",
        "css/all.css",
        "sprites/regular.svg",
        "sprites/solid.svg",
        "webfonts/fa-solid-900.ttf",
        "webfonts/fa-solid-900.woff2",
        "webfonts/fa-regular-400.ttf",
        "webfonts/fa-regular-400.woff2"
      ]
    }
  ]
}
```

- Delete the `wwwroot\lib\bootstrap\dist` folder from **AutoLot.Blazor**. Right-click on the `libman.json` file and select “Restore Client-Side Libraries”.
- Update the `wwwroot\Index.html` by replacing this line:

```
<link rel="stylesheet" href="lib/bootstrap/dist/bootstrap.min.css" />
```

- With these lines:

```
<link href="lib/bootstrap/css/bootstrap.min.css" rel="stylesheet" />
<link href="lib/font-awesome/css/all.min.css" rel="stylesheet" />
```

Summary

This lab created the Blazor Wasm project and the shared class library for the models.

Next steps

In the next part of this tutorial series, you will start building the Blazor application.