

.NET App Dev Hands-On Lab

EF Lab 5 - Repositories

This lab walks you through creating the repositories and their interfaces for the data access library. Before starting this lab, you must have completed EF Lab 4.

Part 1: Create the Base Repositories

Step 1: Create the Base Repository Interfaces

While the DbContext can be considered an implementation of the repository pattern, it's better to create specific repositories for the entities. These repos will be added to the ASP.NET Core Dependency Injection container later in this workshop.

- Create a new folder in the AutoLot.Dal project named Repos. Create two subfolders under that directory named Base and Interfaces. Add a new folder named Base to the Interfaces folder, and in that folder, add a new interface named IBaseViewRepo.cs.
- Update the code for the IBaseViewRepo.cs interface to the following:

```
namespace AutoLot.Dal.Repos.Interfaces.Base;
public interface IBaseViewRepo<T> : IDisposable where T : class, new()
{
    ApplicationDbContext Context { get; }
    IEnumerable<T> ExecuteSqlString(string sql);
    IEnumerable<T> GetAll();
    IEnumerable<T> GetAllIgnoreQueryFilters();
}
```

- Add a new interface named IBaseRepo.cs and update it to the following:

```
namespace AutoLot.Dal.Repos.Interfaces.Base;
public interface IBaseRepo<T> : IBaseViewRepo<T> where T : BaseEntity, new()
{
    T Find(int? id);
    T FindAsNoTracking(int id);
    T FindIgnoreQueryFilters(int id);
    void ExecuteParameterizedQuery(string sql, object[] sqlParametersObjects);
    int Add(T entity, bool persist = true);
    int AddRange(IEnumerable<T> entities, bool persist = true);
    int Update(T entity, bool persist = true);
    int UpdateRange(IEnumerable<T> entities, bool persist = true);
    int Delete(int id, long timeStamp, bool persist = true);
    int Delete(T entity, bool persist = true);
    int DeleteRange(IEnumerable<T> entities, bool persist = true);
    int ExecuteBulkUpdate(Expression<Func<T, bool>> whereClause,
        Expression<Func<SetPropertyCalls<T>, SetPropertyCalls<T>>> setPropertyCalls);
    int ExecuteBulkDelete(Expression<Func<T, bool>> whereClause);
    int SaveChanges();
}
```

- Add a new interface named `ITemporalTableBaseRepo.cs` interface and update it to the following:

```
namespace AutoLot.Dal.Repos.Base;
public interface ITemporalTableBaseRepo<T> : IBaseRepo<T> where T : BaseEntity, new()
{
    IEnumerable<TemporalViewModel<T>> GetAllHistory();
    IEnumerable<TemporalViewModel<T>> GetHistoryAsOf(DateTime dateTime);
    IEnumerable<TemporalViewModel<T>> GetHistoryBetween(
        DateTime startDateTime, DateTime endDateTime);
    IEnumerable<TemporalViewModel<T>> GetHistoryContainedIn(
        DateTime startDateTime, DateTime endDateTime);
    IEnumerable<TemporalViewModel<T>> GetHistoryFromTo(
        DateTime startDateTime, DateTime endDateTime);
}
```

- Add the following global using statements to the `GlobalUsings.cs` file:

```
global using AutoLot.Dal.Repos;
global using AutoLot.Dal.Repos.Interfaces;
global using AutoLot.Dal.Repos.Interfaces.Base;
```

Step 2: Create the BaseView Repository

- Add a new class to the `Repos/Base` folder named `BaseViewRepo.cs`, make the class public and abstract, generic, and implement `IBaseViewRepo<T>`. Add a Boolean flag for disposing of the context, a protected variable to represent the `DbSet` for the derived repo, and a public property to hold the `ApplicationDbContext`

```
namespace AutoLot.Dal.Repos.Base;
public abstract class BaseViewRepo<T> : IBaseViewRepo<T> where T : class, new()
{
    private readonly bool _disposeContext;
    public DbSet<T> Table {get;}
    public ApplicationDbContext Context { get; }
}
```

- Add a constructor that takes an instance of the `ApplicationDbContext` that sets the `Context` and `Table` properties. A `DbSet<T>` property can be referenced using the `Context.Set<T>()` method.

```
protected BaseViewRepo(ApplicationDbContext context)
{
    Context = context;
    Table = Context.Set<T>();
    _disposeContext = false;
}
```

- Add another constructor that takes in `DbContextOptions`, and calls the previous constructor while creating a new `ApplicationDbContext` using the options. Since this is not used by DI, set the disposal flag to true.

```
protected BaseViewRepo(DbContextOptions<ApplicationDbContext> options)
: this(new ApplicationDbContext(options))
{
    _disposeContext = true;
}
```

- Implement the Dispose pattern:

```
public virtual void Dispose()
{
    Dispose(true);
    GC.SuppressFinalize(this);
}

private bool _isDisposed;
protected virtual void Dispose(bool disposing)
{
    if (_isDisposed) { return; }
    if (disposing)
    {
        if (_disposeContext)
        {
            Context.Dispose();
        }
    }
    _isDisposed = true;
}

~BaseViewRepo()
{
    Dispose(false);
}
```

- Implement the two GetAll() variations:

```
public virtual IEnumerable<T> GetAll() => Table.AsQueryable();
public virtual IEnumerable<T> GetAllIgnoreQueryFilters() => Table.IgnoreQueryFilters();
```

- The final method executes a raw SQL query using FromSqlRaw() to return a list of the entities:

```
public IEnumerable<T> ExecuteSqlString(string sql) => Table.FromSqlRaw(sql);
```

- Add the following global using statement to the GlobalUsings.cs file:

```
global using AutoLot.Dal.Repos.Base;
```

Step 3: Create the Base Repository

- Add a new class to the Repos/Base folder named BaseRepo.cs, make the class public and abstract, generic, inherit from BaseViewRepo<T>, implement IBBaseRepo<T>, and add a default constructor and a constructor that takes an instance of DbContextOptions:

```
namespace AutoLot.Dal.Repos.Base;
public abstract class BaseRepo<T>(ApplicationDbContext context)
    : BaseViewRepo<T>(context), IBBaseRepo<T>
    where T : BaseEntity, new()
{
    protected BaseRepo(DbContextOptions<ApplicationDbContext> options)
        : this(new ApplicationDbContext(options)) { }
}
```

- Implement the three Find variations using the built-in Find method, the AsNoTrackingWithIdentityResolution method, as well as the IgnoreQueryFilters method:

```
public virtual T Find(int? id) => Table.Find(id);
public virtual T FindAsNoTracking(int id)
    => Table.AsNoTrackingWithIdentityResolution().FirstOrDefault(x => x.Id == id);
public virtual T FindIgnoreQueryFilters(int id)
    => Table.IgnoreQueryFilters().FirstOrDefault(x => x.Id == id);
```

- The next method executes a parameterized query:

```
public virtual void ExecuteParameterizedQuery(string sql, object[] sqlParametersObjects)
    => Context.Database.ExecuteSqlRaw(sql, sqlParametersObjects);
```

- The Add()/AddRange(), Update()/UpdateRange(), and Delete()/DeleteRange() methods all take an optional parameter to signal if SaveChanges should be called immediately or not.

```
public virtual int Add(T entity, bool persist = true)
{
    Table.Add(entity);
    return persist ? SaveChanges() : 0;
}
public virtual int AddRange(IEnumerable<T> entities, bool persist = true)
{
    Table.AddRange(entities);
    return persist ? SaveChanges() : 0;
}
public virtual int Update(T entity, bool persist = true)
{
    Table.Update(entity);
    return persist ? SaveChanges() : 0;
}
public virtual int UpdateRange(IEnumerable<T> entities, bool persist = true)
{
    Table.UpdateRange(entities);
    return persist ? SaveChanges() : 0;
}
public virtual int Delete(T entity, bool persist = true)
{
    Table.Remove(entity);
    return persist ? SaveChanges() : 0;
}
public virtual int DeleteRange(IEnumerable<T> entities, bool persist = true)
{
    Table.RemoveRange(entities);
    return persist ? SaveChanges() : 0;
}
```

- The final Delete() method uses EntityState to perform the delete operation:

```
public int Delete(int id, long timeStamp, bool persist = true)
{
    var entity = new T {Id = id, TimeStamp = timeStamp};
    Context.Entry(entity).State = EntityState.Deleted;
    return persist ? SaveChanges() : 0;
}
```

- The BaseRepo SaveChanges() method shells out to the ApplicationDbContext SaveChanges() method:

```
public int SaveChanges()
{
    try
    {
        return Context.SaveChanges();
    }
    catch (CustomException ex)
    {
        //Should handle intelligently - already logged
        throw;
    }
    catch (Exception ex)
    {
        //Should log and handle intelligently
        throw new CustomException("An error occurred updating the database", ex);
    }
}
```

- Implement the ExecuteBulkUpdate() and ExecuteBulkDelete() methods:

```
public int ExecuteBulkUpdate(Expression<Func<T,bool>> whereClause,
    Expression<Func<SetPropertyCalls<T>, SetPropertyCalls<T>>> setPropertyCalls)
=> Table.IgnoreQueryFilters().Where(whereClause).ExecuteUpdate(setPropertyCalls);

public int ExecuteBulkDelete(Expression<Func<T,bool>> whereClause)
=> Table.IgnoreQueryFilters().Where(whereClause).ExecuteDelete();
```

Step 4: Create the Temporal Table Base Repository

- Add a new class to the Repos/Base folder named TemporalTypeBaseRepo.cs, make the class public and abstract, generic, inherit from BaseRepo<T>, and implement ITemporalTableBaseRepo<T>: Add the default constructor and the additional constructor:

```
namespace AutoLot.Dal.Repos.Base;

public abstract class TemporalTypeBaseRepo<T>
    : BaseRepo<T>, ITemporalTableBaseRepo<T> where T : BaseEntity, new()
{
    //implementation goes here
}
```

- Add the two constructors supported by the BaseViewRepo:

```
protected TemporalTypeBaseRepo(ApplicationDbContext context) : base(context) {}
protected TemporalTypeBaseRepo(DbContextOptions<ApplicationDbContext> options)
    : base(options) { }
```

- Add an internal helper to convert the current time to UTC:

```
internal static DateTime ConvertToUtc(DateTime dateTime)
=> TimeZoneInfo.ConvertTimeToUtc(dateTime, TimeZoneInfo.Local);
```

- Add an internal helper to execute one of the temporal queries:

```
internal static IEnumerable<TemporalViewModel<T>> ExecuteQuery(IQueryable<T> query)
=> query.OrderBy(e => EF.Property<DateTime>(e, "ValidFrom"))
    .Select(e => new TemporalViewModel<T>
    {
        Entity = e,
        ValidFrom = EF.Property<DateTime>(e, "ValidFrom"),
        ValidTo = EF.Property<DateTime>(e, "ValidTo")
    });
```

- The public methods execute the five temporal queries:

```
public IEnumerable<TemporalViewModel<T>> GetAllHistory()
=> ExecuteQuery(Table.TemporalAll());
```

```
public IEnumerable<TemporalViewModel<T>> GetHistoryAsOf(DateTime dateTime)
=> ExecuteQuery(Table.TemporalAsOf(ConvertToUtc(dateTime)));
```

```
public IEnumerable<TemporalViewModel<T>> GetHistoryBetween(
    DateTime startDateTime, DateTime endDateTime)
=> ExecuteQuery(Table.TemporalBetween(ConvertToUtc(startDateTime), ConvertToUtc(endDateTime)));
```

```
public IEnumerable<TemporalViewModel<T>> GetHistoryContainedIn(
    DateTime startDateTime, DateTime endDateTime)
=> ExecuteQuery(Table.TemporalContainedIn(ConvertToUtc(startDateTime),
ConvertToUtc(endDateTime)));
```

```
public IEnumerable<TemporalViewModel<T>> GetHistoryFromTo(
    DateTime startDateTime, DateTime endDateTime)
=> ExecuteQuery(Table.TemporalFromTo(ConvertToUtc(startDateTime), ConvertToUtc(endDateTime)));
```

Part 2: Add the Entity-Specific Repo Interfaces

There is an interface and repo for each model that uses the base repository for the common functionality. Each specific repo extends or overwrites that base functionality as needed.

Step 1: Create the Interface Files

- Create a new folder under the Repos folder named Interfaces. Create the following files in the Interfaces folder:

```
//ICarDriverRepo.cs
namespace AutoLot.Dal.Repos.Interfaces;
public interface ICarDriverRepo : ITemporalTableBaseRepo<CarDriver> { }
```

```
//ICarRepo.cs
namespace AutoLot.Dal.Repos.Interfaces;
public interface ICarRepo : ITemporalTableBaseRepo<Car>
{
    IEnumerable<Car> GetAllBy(int makeId);
    string GetPetName(int id);
    int SetAllDrivableCarsColorAndMakeId(string color, int makeId);
    int DeleteNonDrivableCars();
}
```

```
//IDriverRepo.cs
namespace AutoLot.Dal.Repos.Interfaces;
public interface IDriverRepo : ITemporalTableBaseRepo<Driver> { }
```

```
//IMakeRepo.cs
namespace AutoLot.Dal.Repos.Interfaces;
public interface IMakeRepo : ITemporalTableBaseRepo<Make> { }
```

```
//IRadioRepo.cs
namespace AutoLot.Dal.Repos.Interfaces;
public interface IRadioRepo : ITemporalTableBaseRepo<Radio> { }
```

Part 3: Implement the Entity-Specific Repos

Step 1: Create the CarDriverRepo Class

- In the Repos folder, create a new class named CarDriverRepo.cs. Make the class public, inherit TemporalTableBaseRepo<CarDriver>, and implement ICarDriverRepo. Add the two required constructors as follows:

```
namespace AutoLot.Dal.Repos;
public class CarDriverRepo : TemporalTableBaseRepo<CarDriver>, ICarDriverRepo
{
    public CarDriverRepo(ApplicationDbContext context) : base(context) { }
    internal CarDriverRepo(DbContextOptions<ApplicationDbContext> options) : base(options) { }
}
```

- Add a helper method to build a base query that includes the Car and Driver entities:

```
internal IQueryable<CarDriver> BuildBaseQuery()
=> Table.Include(c => c.CarNavigation).Include(d => d.DriverNavigation);
```

- Override the GetAll methods to use the base query builder:

```
public override IEnumerable<CarDriver> GetAll()=> BuildBaseQuery();
public override IEnumerable<CarDriver> GetAllIgnoreQueryFilters()
=> BuildBaseQuery().IgnoreQueryFilters();
```

- Override the Find() method to use the base query builder:

```
public override CarDriver Find(int? id)
=> BuildBaseQuery().IgnoreQueryFilters().FirstOrDefault(x => x.Id == id);
```

Step 2: Create the CarRepo Class

- Make the class public, inherit TemporalTableBaseRepo<Car>, and implement ICarRepo. Add the two required constructors

```
namespace AutoLot.Dal.Repos;
public class CarRepo : TemporalTableBaseRepo<Car>, ICarRepo
{
    public CarRepo(ApplicationDbContext context) : base(context) { }
    internal CarRepo(DbContextOptions<ApplicationDbContext> options) : base(options) { }
}
```

- Add a helper method to build a base query that includes the Make entity:

```
internal IQueryable<Car> BuildBaseQuery()
=> Table.Include(x => x.MakeNavigation).OrderBy(p => p.PetName);
```

- Add overrides for the GetAll methods:

```
public override IEnumerable<Car> GetAll() => BuildBaseQuery();
public override IEnumerable<Car> GetAllIgnoreQueryFilters()
=> BuildBaseQuery().IgnoreQueryFilters();
```

- Add override for the Find method to include the Make information:

```
public override Car Find(int? id)
=> Table.IgnoreQueryFilters()
    .Where(x => x.Id == id)
    .Include(m => m.MakeNavigation)
    .FirstOrDefault();
```

- Add method to get all by Make ID:

```
public IEnumerable<Car> GetAllBy(int makeId)
=> BuildBaseQuery().Where(x => x.MakeId == makeId);
```

- Add the method to update all drivable cars:

```
public int SetAllDrivableCarsColorAndMakeId(string color, int makeId)
=> ExecuteBulkUpdate(x => x.IsDrivable,
    c => c.SetProperty(x => x.Color, color).SetProperty(x=>x.MakeId,makeId));
```


- Add the method to delete all non-drivable cars:

```
public int DeleteNonDrivableCars() => ExecuteBulkDelete(x => !x.IsDrivable);
```

- Add method to get the PetName using the GetPetName sproc:

```
public string GetPetName(int id)
{
    var parameterId = new SqlParameter
    {
        ParameterName = "@carId",
        SqlDbType = SqlDbType.Int,
        Value = id,
    };
    var parameterName = new SqlParameter
    {
        ParameterName = "@petName",
        SqlDbType = SqlDbType.NVarChar,
        Size = 50,
        Direction = ParameterDirection.Output
    };
    ExecuteParameterizedQuery("EXEC [dbo].[GetPetName] @carId, @petName OUTPUT",
        [parameterId, parameterName]);
    return (string)parameterName.Value;
}
```

Step 3: Create the DriverRepo Class

- Make the class public, inherit BaseRepo<Driver> and implement IDriverRepo. Add the two required constructors as follows:

```
namespace AutoLot.Dal.Repos;
public class DriverRepo : TemporalTableBaseRepo<Driver>, IDriverRepo
{
    public DriverRepo(ApplicationDbContext context) : base(context) { }
    internal DriverRepo(DbContextOptions<ApplicationDbContext> options) : base(options) { }
}
```

- Add a helper method to build a base query that orders by LastName then Firstname:

```
internal IOrderedQueryable<Driver> BuildQuery()
=> Table.OrderBy(m => m.PersonInformation.LastName).ThenBy(f => f.PersonInformation.FirstName);
```

- Override the GetAll() methods to use the base query builder:

```
public override IEnumerable<Driver> GetAll() => BuildQuery();
public override IEnumerable<Driver> GetAllIgnoreQueryFilters()
=> BuildQuery().IgnoreQueryFilters();
```

Step 4: Create the MakeRepo Class

- Make the class public, inherit TemporalTableBaseRepo<Make>, and implement IMakeRepo. Add the required constructors as follows:

```
namespace AutoLot.Dal.Repos;
public class MakeRepo : TemporalTableBaseRepo<Make>, IMakeRepo
{
    public MakeRepo(ApplicationDbContext context) : base(context) { }
    internal MakeRepo(DbContextOptions<ApplicationDbContext> options) : base(options) { }
}
```

- Add a helper method to build a base query that orders by Name:

```
internal IOrderedQueryable<Make> BuildQuery() => Table.OrderBy(m => m.Name);
```

- Override the GetAll() methods to use the base query builder:

```
public override IEnumerable<Make> GetAll() => BuildQuery();
public override IEnumerable<Make> GetAllIgnoreQueryFilters()
    => BuildQuery().IgnoreQueryFilters();
```

Step 5: Create the RadioRepo Class

- Make the class public, inherit TemporalTableBaseRepo<Radio>, and implement IRadioRepo. Add the standard constructors, as shown below.

```
namespace AutoLot.Dal.Repos;
public class RadioRepo : TemporalTableBaseRepo<Radio>, IRadioRepo
{
    public RadioRepo(ApplicationDbContext context) : base(context) { }
    internal RadioRepo(DbContextOptions<ApplicationDbContext> options) : base(options) { }
}
```

Summary

The lab created the repositories and their interfaces.

Next steps

In the next part of this tutorial series, you will create a data initializer.