

Scenario Summary

Wi-Fi Mesh Hotspot (meshConfig 0)

- Field: 400 × 400 × 30 m
- Mesh: 3×3 HWMP grid, spacing 200 m, AP height 1.5 m
- Buildings: Hybrid layout, cluster blocks shifted north
- Hotspot: 10 STAs (node 8 hosts two), IP 192.168.1.0/24
- Traffic window: 5–9 s (mesh settle 0–5 s)

STA	Traffic	Proto	Tx	Rx	PDR %	Delay ms	Throughput Mbps
0							
1							
2							
3							
4							
5							
6							
7							
8							
9							

5G NR Playfield

- Field: 400 × 400 × 30 m urban macro
- gNBs: (-100,200,30) and (500,200,30)
- UEs: 10, Gauss–Markov 0.3–0.8 m/s
- Traffic: HTTP/HTTPS 2 MB, Video 3 MB, VoIP UDP 1.5 MB, HTTP 2.5 MB, Mixed 2 MB

UE	Traffic	Proto	PDR %	Delay ms	Throughput Mbps
0					
1					
2					
3					
4					
5					
6					
7					
8					
9					

LTE Playfield

- Field: 400 × 400 × 30 m urban macro
- eNBs: dual macro sites aligned with NR scenario
- Traffic: identical to NR (HTTP/HTTPS/Video TCP, VoIP UDP, Mixed TCP)

UE	Traffic	Proto	PDR %	Delay ms	Throughput Mbps
0					
1					
2					
3					
4					
5					
6					
7					
8					
9					