

Simulation Summary Report

Wi-Fi Mesh Hotspot (meshConfig 0)

- Field: 400 × 400 × 30 m (3×3 HWMP mesh, node spacing 200 m, AP height 1.5 m)
- Buildings: Hybrid layout with cluster blocks shifted north ($y \approx 300$ m)
- Hotspot overlay: 10 STAs (one per mesh node; node 8 hosts two), traffic window 5–9 s
- Traffic mix: HTTP/HTTPS/Video TCP bursts (10 KB or 1 MB) plus one UDP VoIP (10 KB)

STA							

UE	Traffic	Proto	PDR %	Delay ms	Throughput Mbps
0	HTTP	TCP	94.48	40.57	0.88
1	HTTP	TCP	94.15	21.97	1.46
2	HTTPS	TCP	94.14	17.75	1.45
3	HTTPS	TCP	94.08	25.92	1.36
4	Video	TCP	94.51	17.68	2.19
5	Video	TCP	96.05	11.72	2.76
6	VoIP	UDP	99.82	13.54	1.35
7	VoIP	UDP	96.85	37.73	1.29
8	HTTP	TCP	0.00	0.00	0.00
9	Mixed	TCP	94.34	17.18	1.83

LTE Playfield

- Field: 400 × 400 × 30 m urban macro; dual eNBs mirroring the NR layout
- Traffic: same mix as NR (HTTP/HTTPS/Video TCP bursts, VoIP UDP, Mixed TCP)
- UEs: 10, Gauss–Markov mobility (0.3–0.8 m/s)

UE	Traffic	Proto	PDR %	Delay ms	Throughput Mbps
0	HTTP	TCP	94.11	88.69	0.55
1	HTTP	TCP	93.44	147.41	0.37

LTE Playfield (cont.)

3	HTTPS	TCP	95.94	73.16	0.71
4	Video	TCP	93.29	91.20	0.54
5	Video	TCP	95.58	71.96	0.70
6	VoIP	UDP	16.28	322.98	0.22
7	VoIP	UDP	50.95	105.77	0.68
8	HTTP	TCP	76.13	53.46	0.08
9	Mixed	TCP	94.29	99.16	0.49

2	HTTPS	TCP	84.48	28.34	0.12
---	-------	-----	-------	-------	------