



Oracle SQL – Joins

Stephan Karrer

Beziehungen zwischen Tabellen

Tabelle: EMPLOYEES

EMPLOYEE_ID	FIRST_NAME	LAST_NAME	DEPARTMENT_ID
174	Ellen	Abel	80
142	Curtis	Davies	50
102	Lex	De Haan	90
104	Bruce	Ernst	60
202	Pat	Fay	20
206	William	Gietz	110



Primärschlüssel



Fremdschlüssel

Tabelle: DEPARTMENTS

DEPARTMENT_ID	DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
10	Administration	200	1700
20	Marketing	201	1800
50	Shipping	124	1500
60	IT	103	1400
80	Sales	149	2500
90	Executive	100	1700
110	Accounting	205	1700
190	Contracting		1700



Primärschlüssel

- Die Daten werden in der Regel auf mehrere Tabellen verteilt, um Redundanzen zu vermeiden (sog. Normalisierung)
- Der Wert in der Fremdschlüsselspalte der Tabelle "EMPLOYEES" verweist auf den zugehörigen Datensatz (Primärschlüssel) in der Tabelle "DEPARTMENTS"
- Diese Daten wieder zusammenzuführen ist der häufigste Anwendungsfall des Joins

Joins unter Oracle

```
FROM first_table <JOIN_TYPE> second_table  
      [ON (<JOIN_CONDITION>)]
```

join_type gibt an, welche Art der Verknüpfung

- Oracle-eigene Syntax oder ANSI SQL Syntax ist möglich
- Unterstützte Arten:
 - Inner Join (Equi Join als Spezialform)
 - Self Join
 - Kartesisches Produkt
 - Ein- und zweiseitige Outer Joins
 - Inner und Outer Joins mit beliebigen Bedingungen

Equi-Join (Spezialform des Inner-Join)

```
SELECT employees.employee_id, employees.last_name,  
employees.department_id, departments.location_id  
  
FROM employees INNER JOIN departments  
ON (employees.department_id = departments.department_id);
```

```
SELECT e.employee_id, e.last_name, e.department_id,  
d.location_id  
  
FROM employees e JOIN departments d  
ON (e.department_id = d.department_id);
```

Equi-Join über WHERE-Klausel: alte Schreibweise

```
SELECT  e.employee_id, e.last_name, e.department_id,  
        d.location_id  
  
FROM    employees e, departments d  
  
WHERE   e.department_id = d.department_id  
  
        AND d.location_id > 1000;
```

Mehrfach-Join

```
/* Das Schlüsselwort "ON" muss nach dem jeweiligen "JOIN"
folgen */
```

```
SELECT e.last_name, d.department_name, l.city, c.country_name
FROM employees e INNER JOIN departments d
        ON e.department_id = d.department_id
INNER JOIN locations l
        ON d.location_id = l.location_id
INNER JOIN countries c
        ON l.country_id = c.country_id ;
```

Non-Equi Join

```
select e.last_name, e.department_id,  
       d.department_id, d.department_name  
from employees e JOIN departments d  
       ON e.department_id > d.department_id  
WHERE e.department_id = 50 and e.employee_id = 140;
```

Outer Joins

```
SELECT e.employee_id, e.last_name, e.department_id,  
       d.department_id, d.department_name  
  
FROM employees e LEFT OUTER JOIN departments d  
ON (e.department_id = d.department_id);
```

```
SELECT d.department_id, e.last_name      -- Oracle-spez. Syntax  
FROM departments d, employees e  
WHERE d.department_id = e.department_id(+)  
ORDER BY d.department_id, e.last_name;
```

```
SELECT e.employee_id, e.last_name, d.department_id,  
       d.department_name  
  
FROM employees e FULL OUTER JOIN departments d  
ON (e.department_id = d.department_id);
```


Cross Join (Kartesisches Produkt)

```
SELECT e.employee_id, e.last_name, e.department_id,  
       d.department_id, d.department_name  
FROM employees e CROSS JOIN departments d  
WHERE e.department_id = d.department_id  
ORDER BY e.employee_id ;
```

Self Join

```
SELECT e.last_name AS emp, m.last_name AS man  
      FROM employees e INNER JOIN employees m  
      ON (e.manager_id = m.employee_id) ;
```