PRODUCT & ENGINEERING DIRECTIVE

SKULBUY

Website Audit, Implementation Plan & Launch Readiness

A task-focused working document for the product, design, engineering, QA, operations and launch teams.

DOCUMENT CONTROL	DETAIL
Product	SkulBuy student marketplace and SkulBox programme
Current public URL	https://skulbuy.vercel.app/
Prepared for	Product owner and development team
Version / date	1.0 | 29 October 2026
Purpose	Turn the website audit into prioritised implementation tasks with testable acceptance criteria.
Status	Working directive. Owners, sprint dates and final scope to be assigned by the team.

IMPORTANT BASELINE NOTE The audit used the publicly accessible site view. Several private or authenticated routes, backend operations, and real payment flows could not be independently verified. Treat visible issues as observations to reproduce, and treat unverified functions as test items, not as confirmed defects.

How to use this document

- First map the existing routes, backend services, data model, roles and payment integrations before editing code.
- Create development tickets from each task ID. Assign one owner, priority, sprint, dependencies and test evidence to each ticket.
- Implement in priority order. Do not start optional growth features while Priority 0 security, data integrity or launch blockers remain open.
- Mark a task complete only after its acceptance criteria pass in a test environment and the evidence is recorded.

1. Executive Summary and Delivery Rules

The goal is to make SkulBuy a trustworthy, mobile-first student marketplace that students can actually use to discover products, contact sellers, list items, and complete supported transactions. SkulBox should operate as a clearly explained programme with accurate cycle, payment and fulfilment information.

PRODUCT RULE Do not add features just because they look good in a demo. Complete the existing critical journeys, protect user information, verify transaction states, and make each feature operational before promoting it.

1.1 Initial observations to reproduce

ID	Observation from public view	Required action
OBS-01	Multiple functions appear together in one public view, including marketplace, listing form, SkulBox, points, wallet/profile and internal tools.	Verify intended routing and access behaviour. Separate public, authenticated and admin experiences where required.
OBS-02	A SkulBox cycle displayed a March closing date.	Check source data, current cycle, time zone, and date rendering. Replace stale hard-coded dates with managed cycle data.
OBS-03	A marketplace category displayed “No items found”.	Determine whether inventory is genuinely empty or filtering/API/loading is failing. Improve empty, loading and error states.
OBS-04	Sample-looking profile/account values were visible.	Determine whether this is seeded data, a preview, or real user data. Ensure no private account data is exposed publicly.

These observations are not a substitute for reproducing the issue in the deployed app, reviewing source code, and checking behaviour with authenticated test accounts.

1.2 Priority definitions

Priority	Meaning	Release rule
P0 — Blocker	Security exposure, privacy breach, incorrect money state, broken core navigation, stale financial terms or release-critical failures.	Must be resolved before public launch or broader rollout.
P1 — Core marketplace	Search, product detail, listings, authentication, messaging, order flow and responsive behaviour.	Must pass before treating the core marketplace as ready.
P2 — Programme and operations	SkulBox, wallet/points separation, admin operations, analytics and support processes.	Launch only the parts with complete and verified workflows.
P3 — Growth and optimisation	SEO, referral tracking, campus ambassadors and additional service categories.	Schedule after core reliability and safety are established.

2. Phase 0 — Technical Discovery Before Changes

Owner: Tech lead / full-stack lead. Deliver a short current-state report before major implementation. The team may fix an urgent exposure immediately, but should preserve evidence and record the change.

Task ID	Required action	Output / acceptance evidence	Priority
DISC-01	List every public, authenticated and admin route. Include redirects, 404 routes, mobile navigation and direct-URL access.	Route inventory with purpose, role access, current state and owner.	P0
DISC-02	Trace frontend pages to APIs, database tables, server actions and third-party integrations.	Architecture map identifying data owner, dependencies and failure points.	P0
DISC-03	Identify authentication provider, user roles, session behaviour and verification rules.	Role/permission matrix and account-flow test results.	P0
DISC-04	Identify payment provider(s), webhook endpoints, wallet/points logic and any funds-holding arrangement.	Written transaction-state map; unknowns flagged for provider/legal review.	P0
DISC-05	Inspect database access rules, private file storage, environment variables and admin protections.	Security findings with severity and remediation owner.	P0
DISC-06	Locate sample/seed data and check whether production builds load it.	Evidence that demo data is disabled or clearly isolated from production.	P0
DISC-07	Capture desktop and mobile screenshots of current pages and document reproducible defects.	Before-state evidence and issue log with steps to reproduce.	P1
DISC-08	Confirm deployment process, environment separation, backups, monitoring and rollback.	Release and rollback checklist approved by engineering lead.	P0

2.1 Required discovery deliverables

[ ] A route map showing who may access each page and what the route is meant to do.

[ ] A table of existing features marked Working, Partial, Broken, Not Implemented, or Needs Verification.

[ ] A data-flow map for listings, user verification, messaging, orders, payments, SkulBox and rewards.

[ ] A ranked defect backlog linked to the relevant task IDs in this directive.

[ ] A list of external dependencies, credentials owners, test-mode access and any provider/legal decisions required.

STOP CONDITION If the team discovers exposed account information, unauthorised administrative access, incorrect monetary balances, or unverified payment confirmation, treat it as a release blocker. Restrict exposure and correct it before adding optional features.

3. Phase 1 — Priority 0 Launch and Trust Blockers

Goal: eliminate avoidable exposure, stale operational information, broken public states and misleading financial interactions.

Task ID	Implementation directive	Acceptance criteria	Priority
PUB-01	Separate the public website, authenticated application and admin panel.	Anonymous visitors cannot view private profile/balance/notification data or invoke internal tools. Private routes and API requests reject unauthorised access.	P0
DATA-01	Remove demo account data from production.	Production uses real persisted records or honest empty states. Seed data is isolated to development/demo environments. No real user private data appears in public HTML/API responses.	P0
BOX-01	Correct SkulBox cycle dates and lifecycle status.	Cycle dates/status come from managed data, render in West Africa Time, and update correctly when cycles change. Closed or missing cycles are represented honestly.	P0
MKT-01	Diagnose empty category / inventory views.	The team documents root cause. Search and filtering work with seeded test inventory. Empty inventory, no-match results, loading and API error have separate UI states.	P0
PAY-01	Audit all payment, wallet, top-up, redeem, contribution and payout actions.	Each financial action is either wired to the real verified process or visibly unavailable. No simulated success or fabricated balances.	P0
SEC-01	Enforce server-side access control and validate record ownership.	A user cannot read or edit another user's profile, listings, conversations, orders, payment records or files by changing an ID/URL. Admin APIs reject ordinary users.	P0
POL-01	Publish accurate essential legal and support pages.	Privacy notice, terms, marketplace rules, safety, refund/dispute policy and support contact are accessible from footer and relevant purchase flows. Terms match actual operations.	P0
REL-01	Confirm production release controls.	Staging test passes, backup/rollback steps are recorded, errors are monitored and a responsible person approves release.	P0

3.1 Policy and funds-holding decision gate

Before implementing a real-money wallet, third-party funds holding, conditional release, or SkulBox contribution arrangement, confirm the proposed flow with the payment provider and qualified Nigerian legal/compliance advisers. Payment splitting is not automatically escrow. Do not call a flow "escrow", "locked savings" or "cooperative" unless the underlying arrangement and terms support that description.

4. Phase 2 — Public Website and Marketplace

4.1 Homepage

Task ID	Directive	Acceptance criteria
HOME-01	Explain SkulBuy immediately with a clear headline and supporting text.	A first-time visitor can explain what SkulBuy does without scrolling through several sections.
HOME-02	Add primary actions: Explore Marketplace and Sell an Item.	Buttons navigate correctly. Sign-in is requested only when required and return flow is preserved.
HOME-03	Provide visible search and category discovery.	Search submits a query and category links open the appropriate results.
HOME-04	Show recent/featured genuine listings, service categories where available, and a distinct SkulBox section.	Only published eligible records appear. No fake reviews, invented inventory or unverified statistics.
HOME-05	Add how-it-works, safety, FAQs, support and footer/legal links.	Links work on desktop/mobile and provide useful content, not empty placeholders.

4.2 Marketplace and category pages

- [ ] Implement keyword search and filters for category, price, condition, campus/location, and sale/rental type where those types are supported.
- [ ] Provide sorting by newest, price low-to-high, price high-to-low and relevance when relevance is available.
- [ ] Show the product image, title, NGN price, condition, location and seller status on product cards.
- [ ] Provide active filter chips, a clear-filters action, pagination or reliable incremental loading, and stable back-navigation.
- [ ] Distinguish loading, truly empty inventory, no filter matches, network/API failure, and a removed listing.
- [ ] Check search and filter combinations against database results. Do not silently show unrelated listings or return success after an API error.

4.3 Product details page

- [ ] Give every published listing a stable, shareable URL.
- [ ] Show title, price, pictures, description, condition, location, availability, seller profile and appropriate verification status.
- [ ] Provide save, share, report and contact/message actions where implemented.
- [ ] For rentals, show duration, total amount, deposit if applicable, return/damage terms and availability.
- [ ] Prevent sold, withdrawn, reserved or deleted listings from being presented as available for immediate purchase.
- [ ] Display only ratings and reviews tied to real eligible activity under the published review policy.

4.4 Create, edit and publish a listing

- [ ] Move listing creation into a dedicated authenticated flow, not a form embedded in the public homepage.
- [ ] Validate title, description, price, category, image type/size, location, condition and supported listing type.
- [ ] Support multiple-image preview, upload progress, remove-image controls, useful validation and a final preview.
- [ ] Prevent duplicate publishes; preserve the draft if login is required mid-flow where practical.
- [ ] Allow the owner to edit, pause, withdraw or mark the listing sold; confirm changes persisted.
- [ ] Use transparent moderation/boosting rules. Do not promise guaranteed views or sales.

5. Phase 3 — Accounts, Messaging and Core User Journeys

5.1 Registration and student verification

Task ID	Requirement	Acceptance criteria
AUTH-01	Complete signup, login, logout, password reset and verification.	Happy paths, invalid inputs, expired links and failure states are tested. Sessions behave correctly.
AUTH-02	Design student verification with institutional email where possible and manual fallback when necessary.	User sees Not verified, Pending, Verified or Rejected. Staff actions are permission-controlled and auditable.
AUTH-03	Protect verification files and data.	Only authorised reviewers can access submitted files. Retention and deletion rules are documented.
AUTH-04	Preserve the intended route after authentication.	When a user is asked to sign in from a product/listing flow, they return to the correct next step without losing safe form data.

5.2 User dashboard and profile

Organise the dashboard into Overview, My Listings, Orders/Purchases, Sales, Messages, Saved Items, Notifications, Rewards, Payment History where applicable, Profile/Verification, and Settings. Show only functions relevant to the user's role and actual product scope.

- [ ] Provide helpful first-use states when the user has no listings, orders, saved items or messages.
- [ ] Allow users to update permitted profile fields and contact preferences, and manage their listings.
- [ ] Show transaction and account status from persisted backend data; never hard-code a user balance or sales count.
- [ ] Provide account security controls, session logout, and clear confirmation for consequential actions.

5.3 Messaging and offers

- [ ] Build conversation history linked to the relevant listing, with timestamps, unread status and clear loading/error states.
- [ ] Provide message notifications without exposing sensitive content on public pages or unauthorised accounts.
- [ ] If offers are supported, implement submit, accept, reject and counter-offer state transitions with clear history.
- [ ] Include report and block controls, basic spam limits, and an operations process for reported abuse.
- [ ] Enforce conversation access: only authorised participants and specifically authorised moderators may access content.

5.4 Notifications

Use in-app notification states based on real events such as new message, listing approval/rejection, order status change, payment confirmation, refund update and SkulBox cycle deadline. Notifications must deep-link only to a route the recipient is authorised to view.

6. Phase 4 — Orders, Payments, Wallet and Rewards

6.1 Order lifecycle

Define the order statuses the actual business process needs, then implement one consistent state model across the buyer screen, seller screen, admin panel and backend. Suggested states include: Pending Payment, Payment Confirmed, Seller Confirmed, Ready for Collection/Dispatch, Completed, Cancelled, Refund Pending, Refunded and Disputed. Use only states that match the real flow.

6.2 Payment integrity

- [ ] Use the provider's official server-side payment verification and signed/verified webhook process.
- [ ] Make webhook and callback handling idempotent: duplicate notifications must not create duplicate orders, points, credits, or payouts.
- [ ] Keep payment secrets server-side. Never trust a frontend success URL as payment proof.
- [ ] Test successful, failed, pending, delayed, duplicated, cancelled and refunded payment events in test mode.
- [ ] Make fees, payment timing, collection/delivery responsibilities, refund conditions, dispute deadlines and payout timing visible before payment.
- [ ] Create reconciliation evidence linking each order to provider references and internal transaction records.
- [ ] Do not hold or release third-party funds through a custom wallet unless the arrangement is confirmed as legally and operationally appropriate.

6.3 Wallet and reward points

Item	Required separation and behaviour
Reward points	A promotional/loyalty unit, separate from cash. Display balance, earn rules, redemption value, expiry if relevant and history.
Real monetary balance	Only implement with a compliant provider/settlement model, auditable ledger, reconciliation, refund/withdrawal rules and required controls.
SkulBox contributions	Track against a named package/cycle and actual contribution record. Do not present as a conventional bank savings account without a basis for that claim.
Pending payment/payout	Show separately from completed amounts. State changes only when supported by the backend/provider process.

6.4 Minimum acceptance criteria

- [ ] Every displayed transaction maps to a persisted record and provider reference where relevant.
- [ ] Users can view their own order/payment history but cannot access another user's transactions.
- [ ] Retries and duplicate webhooks do not duplicate money-related records or side effects.
- [ ] Failures show a recoverable message and do not falsely indicate success.
- [ ] Refunds and disputes are reflected consistently in buyer, seller and authorised admin views.

7. Phase 5 — SkulBox and Administration

7.1 SkulBox cycle and fulfilment

Task ID	Requirement	Acceptance criteria
BOX-02	Separate SkulBox from general marketplace browsing while preserving shared branding/navigation.	Dedicated explanation, packages, cycle detail, contributions, fulfilment and support journey.
BOX-03	Manage package contents, amounts, dates, status and eligibility from the backend/admin.	Changes made by authorised staff are reflected correctly without code edits or stale cached dates.
BOX-04	Explain all costs and rules before taking contribution/payment.	User can see package contents, total payable, schedule, deadlines, late/missed-payment rules, cancellation/refund terms and pickup/delivery method.
BOX-05	Record and reconcile each contribution.	Every contribution is attributable to a user, package/cycle and payment reference; duplicate callbacks do not duplicate contributions.
BOX-06	Track supplier, order preparation and fulfilment status.	Users see accurate status and a support path. No invented supplier verification or delivery promises.
BOX-07	Keep money handling within an approved arrangement.	Provider/compliance decision is documented before live contributions or third-party funds are accepted.

7.2 Administration panel

Admin-only tools must live behind authentication and server-side roles. Use role separation for administrators, moderators, support and finance operations. Do not grant every staff member unrestricted access.

- [ ] User and verification queue with reasons, review status and audit trail.
- [ ] Listing moderation, user reports, complaints, suspicious-activity review and appeal/escalation path.
- [ ] Order, payment, refund and dispute views with safe, auditable actions and reconciliation references.
- [ ] SkulBox package/cycle, supplier and fulfilment management.
- [ ] Category, announcements, promotions and configuration management.
- [ ] Operational metrics with date range, source, definition and last-updated timestamp.
- [ ] Audit logs for sensitive changes such as verification decisions, money-related actions, permissions and listing removals.

7.3 Trust and safety operations

Provide a safety centre with marketplace rules and practical guidance for campus collection, suspicious requests, proof of payment and reporting. Verification is one layer of protection, not a guarantee that all users or transactions are safe. Define who handles reports, target acknowledgement/review times, escalation and user communications.

8. Phase 6 — Interface, Accessibility, Privacy and SEO

8.1 Interface and mobile usability

- [ ] Use a consistent design system for colours, type, spacing, buttons, cards, form controls, dialogs, alerts and status labels. Retain recognisable SkulBuy branding.
- [ ] Keep search, categories, product information, prices and core actions prominent on small screens.
- [ ] Use consistent navigation across public and signed-in pages. Do not let bottom navigation or sticky actions cover content.
- [ ] Support loading, empty, success, error and offline/slow-network states for all key flows.
- [ ] Compress and resize images appropriately; avoid shipping oversized assets and unnecessary scripts to mobile users.
- [ ] Check text contrast, form labels, keyboard access, visible focus, error descriptions and touch target usability. Target WCAG 2.2 AA practices.
- [ ] Test small-screen layout stability, long titles, empty categories, large prices, failed image loads and low-bandwidth conditions.

8.2 Privacy and security

- [ ] Review applicable Nigerian data protection requirements, including the Nigeria Data Protection Act 2023, with qualified advice where needed.
- [ ] Explain what data is collected, the purpose, sharing, retention, user rights and contact route in the privacy notice.
- [ ] Restrict private files, validate upload types and sizes, and set a defensible retention/deletion schedule.
- [ ] Review database access policies, ID-based access, rate limits, authentication recovery, logging and error messages.
- [ ] Protect API credentials and private keys using server-side environment/secret management.
- [ ] Document backups, restoration tests, incident ownership and production rollback.

8.3 SEO and sharing

- [ ] Provide unique titles, descriptions, sensible URL patterns and canonical URLs where appropriate.
- [ ] Make public listing pages shareable on WhatsApp and other channels with accurate title, price, description and preview image.
- [ ] Use descriptive alternative text and valid structured data only where the page content supports it.
- [ ] Keep private dashboard/account routes out of search indexing and prevent sensitive content from appearing in metadata.
- [ ] Verify that social preview metadata updates correctly for different product pages, not the same default preview each time.

9. Phase 7 — Analytics and Growth

Do not treat registrations, listings, reward points and transactions as interchangeable indicators of success. The core marketplace outcome is legitimate completed transactions, protected by trust, repeat usage and low dispute rates.

Metric	Working definition / event to track	Owner
Visitor → registration	Eligible public visitors who complete registration, by time period and channel.	Product / Analytics
Registration → verification	Registered users who reach the required verification state.	Product / Operations
Search success	Searches resulting in useful listing opens, enquiries or no-results events.	Product / Engineering
Listing completion	Listing drafts started and successfully published, including failure stage.	Product / Engineering
Active inventory	Published, available listings by campus/category, excluding sold/withdrawn/duplicate items.	Marketplace Operations
Buyer enquiries	Legitimate enquiries per listing and time to first enquiry.	Product / Growth
Completed transactions	Orders confirmed completed under the actual business definition.	Product / Operations
Repeat usage	Returning buyers/sellers and repeat completed transactions over a defined period.	Product / Analytics
Trust indicators	Reports, disputes, cancellations, refunds and response time.	Trust & Safety
SkulBox outcomes	Participants, verified contributions, completed cycles and fulfilled packages; reported separately.	SkulBox Operations

9.1 Campus launch and referrals

- [ ] Start with a strong pilot campus and validate real demand, inventory depth, response times, successful handovers and safety issues before scaling.
- [ ] Where referrals are introduced, use unique attribution, published reward rules, fraud checks and a way to validate genuine participation.
- [ ] Use student ambassadors with approved materials and a tracked code or link; do not reward spam, duplicate accounts or fake transactions.
- [ ] Use real user feedback and observed usage to prioritise changes. Avoid publishing unverified platform-size claims.

9.2 Analytics implementation criteria

- [ ] Each event has a name, trigger, required fields and definition in an event dictionary.
- [ ] Events do not contain passwords, payment secrets, full student IDs or unnecessary personal information.
- [ ] Dashboards show date range, last updated time, metric definitions and source.
- [ ] Test events in staging are distinguishable from production data.

10. End-to-End QA Test Plan

QA owner: assign before any release. Run on staging with approved test accounts and payment-provider test mode. Record evidence, including screen recording/screenshots where useful, logs/request IDs for backend failures, and the build/version tested.

Test ID	Scenario	Pass condition	Result / evidence
QA-01	Anonymous visitor opens homepage and browses categories.	Only public information is shown; links and public states work.	Pass / Fail: _____
QA-02	Search by keyword; apply and clear several filters.	Correct results appear; filters combine correctly; error/no-match states differ.	Pass / Fail: _____
QA-03	Open and share a product detail URL.	Correct listing preview appears; unavailable item cannot be purchased as active.	Pass / Fail: _____
QA-04	Register, verify, log in, reset password and log out.	Expected account states work; invalid/expired links fail safely.	Pass / Fail: _____
QA-05	Create, preview, publish, edit and mark a listing sold.	Record is persisted; images validate; no duplicate submission; owner permissions hold.	Pass / Fail: _____
QA-06	Buyer messages seller; recipient replies; user reports/blocks.	Only participants have access; notifications and controls work.	Pass / Fail: _____
QA-07	Run payment success, failure, pending, duplicate webhook and refund tests.	Balances/orders update exactly once; all states reconcile; no false success.	Pass / Fail: _____
QA-08	Open SkulBox cycle, inspect package and make test contribution.	Terms and deadlines are accurate; one contribution record persists; status updates honestly.	Pass / Fail: _____
QA-09	Attempt to access another user's records by URL/API ID.	Access is denied and event logged as appropriate.	Pass / Fail: _____
QA-10	Attempt admin routes as ordinary user.	UI and API access are denied server-side.	Pass / Fail: _____
QA-11	Test small mobile viewport and slow/failed network.	No blocking overflow; core actions are usable; loading/error recovery works.	Pass / Fail: _____
QA-12	Check privacy/footer/legal/support links and public indexing rules.	Links are accessible; no private pages expose data or indexable content.	Pass / Fail: _____

10.1 Minimum regression rule

Every bug fix must include a reproduction step, expected behaviour, test evidence, and a regression check for related flows. Critical failures must be retested after deployment to staging and again after production rollout, without using live-money transactions unless explicitly approved and safe.

11. Delivery Plan, Ownership and Sign-off

11.1 Recommended implementation sequence

Stage	Work package	Exit gate
A. Discover	Route map, backend/data map, role matrix, payment flow, baseline defects.	Tech lead and product owner approve findings and ticket list.
B. Secure and stabilise	Public/private separation, demo-data control, access control, stale cycle data, payment claims, legal/support basics.	All P0 tickets pass acceptance and security review.
C. Core marketplace	Homepage, categories, search, detail pages, listing management, accounts and messaging.	Buyer, seller and account journeys pass end-to-end QA.
D. Transactions and SkulBox	Order states, payment verification, points separation, cycle/contribution/fulfilment workflows.	Provider and compliance decisions documented; test reconciliation passes.
E. Operational readiness	Admin panel, moderation, reporting, support processes, analytics and backup/rollback.	Operations can handle real reports, disputes and routine configuration.
F. Pilot and growth	Mobile/performance polish, SEO/share metadata, campus pilot and referrals.	Pilot metrics and user feedback reviewed; scale decision recorded.

11.2 Ticket format required for every task

Field	What the ticket must contain
Task ID / title	Use the ID in this directive where it matches, e.g. SEC-01: enforce record ownership checks.
Owner / reviewer	One accountable developer and one reviewer or QA owner.
Priority / sprint	P0, P1, P2 or P3, with an assigned sprint/release target.
Current behaviour	Reproducible description and environment/version.
Expected behaviour	Specific result, including permissions and failure states.
Dependencies / risks	Backend, provider, legal, data migration or design dependencies.
Acceptance criteria	Observable, testable conditions that determine pass/fail.
Test evidence	Test account/role, screenshots/logs/request IDs, test result, build version.
Release / rollback	Migration notes, feature flag or rollback step if relevant.

11.3 Release checklist

- [ ] All P0 blockers closed and reviewed by an accountable person.
- [ ] Critical buyer, seller, authentication, admin-permission and payment tests pass.
- [ ] No unexplained production demo data or public exposure of private records.
- [ ] Terms and operational policies match the functions that are actually available.
- [ ] Monitoring, backup, rollback and support ownership are documented.
- [ ] Production configuration and credentials have been reviewed; no secrets are included in frontend bundles or repository history.
- [ ] Product owner accepts the known limitations and signs off on the release scope.

11.4 Sign-off

Role	Name	Decision / outstanding items	Date
Product owner	_____	Approved / Not approved: _____	_____
Engineering lead	_____	Approved / Not approved: _____	_____
QA lead	_____	Approved / Not approved: _____	_____
Operations / support	_____	Ready / Not ready: _____	_____

11.5 Release record

Release field	Record before deployment
Release version / build	_____
Target environment	Staging / Production / Other: _____
Deployment date and time (WAT)	_____
Database changes / migrations	_____
P0 and P1 ticket status	Open items and approved exceptions: _____
Known limitations / mitigation	_____
Rollback owner and trigger	_____
Post-release smoke-test result	Pass / Fail; tester and evidence link: _____

Appendix A — Definition of Done

A task is complete only when all relevant points below are true. “The page looks correct” or “the button responds” is not enough.

- [ ] The requirement and expected behaviour are documented.
- [ ] The implementation is connected to the correct source of truth and persists changes where applicable.
- [ ] Authorisation and validation are enforced server-side for protected operations.
- [ ] Loading, empty, error, success and unavailable states are handled correctly for the feature.
- [ ] Desktop and mobile views have been checked for the affected flow.
- [ ] Relevant accessibility, privacy, security and performance implications have been reviewed.
- [ ] Automated tests exist where practical and manual acceptance tests pass.
- [ ] No unrelated feature or existing working flow has regressed.
- [ ] The reviewer has approved the change and test evidence is linked in the ticket.
- [ ] Release notes, migration and rollback instructions are added where necessary.

Appendix B — Defect log template

Field	Entry
Issue ID	BUG-____
Page / route / component	_____
Severity / priority	Critical / High / Medium / Low	P0 / P1 / P2 / P3
Environment and build	_____
Steps to reproduce	1. _____ 2. _____ 3. _____
Expected vs actual	_____
Evidence	Screenshot / screen recording / logs / request ID: _____
Root cause / fix	_____
Owner / reviewer	_____
Retest result / date	Pass / Fail: _____ Date: _____

Appendix C — Product-owner decisions to resolve

The team should not silently invent policy or commercial rules. Record explicit decisions for the following before implementing related functionality:

- [ ] Which schools/campuses are included in the initial pilot, and what qualifies a user as verified?
- [ ] Which categories and listing types are in the first release: sale, rental, service, or all of them?
- [ ] Is checkout performed on-platform or are buyers initially connected to sellers through messages?
- [ ] What payment provider and exact transaction model are approved? Is any third-party fund holding proposed?
- [ ] What are the authoritative SkulBox package contents, amounts, contribution schedule, missed-payment rules, refund rules and fulfilment method?
- [ ] What do points represent, how are they earned, and can they be redeemed for anything of monetary value?
- [ ] Who handles moderation, support, refunds, disputes and payment reconciliation, and what response targets are realistic?
- [ ] What are the pilot launch criteria and which metrics trigger expansion to another campus?