
When you set up <u>Windows authentication</u>, you can use the authentication only for specific sections of the live website. This leads to the following scenario:

- The live website is accessible anonymously, except for the specified sections that require Windows authentication
- Windows authentication is required for access to the Kentico administration interface
- The site cannot contain other sections secured using standard Forms authentication

The following example demonstrates how to set Windows authentication for the **Products** section of the sample **Corporate site**:

Configuring IIS

- 1. Locate your web project on the disk (typically c:\Inetpub\www.root\<web project>).
- 2. Create a new directory in your web project's **CMS** folder, named according to the URL path of the site section that you want to secure. In this case, the path is /*Products*, so create a folder named **Products**.
- 3. Open Internet Information Services (IIS) Manager.
- 4. Locate the new **Products** folder in the tree and select it.
- 5. Open the **Authentication** configuration.
 - Disable Anonymous Authentication for the folder
 - Make sure that Windows Authentication is enabled



Configuring the web.config file

- 1. Edit the web.config file of your web project.
- 2. Set the mode attribute of the <authentication> element in the <system.web> section to Windows:

```
<authentication mode="Windows">
```

3. Find the section marked with **Windows authentication BEGIN** and set the **path** parameter of the **<location>** element to the name of the created directory (**Products** in the example):


https://docs.xperience.io

4. Save the web.config file.

The authentication is now configured. If you try to access any of the pages placed under the **Products** section, the system requires **Wi ndows authentication**.

If you also want the authentication to be required for the **Products** main page, you need to use the following workaround:

- 1. Create a child under the **Products** page with identical content (you can use the **Copy** (**b**) action).
 - You may need to adjust the <u>page nesting</u> settings and the configuration of certain web parts to get the page to work correctly.
- 2. Select the original **Products** page and open the **Properties -> Navigation** tab.
- 3. Select Redirect to first child in the Menu actions section.
- 4. Click Save.



Because the new page is located under the **Products** section, windows authentication is required to access it.

https://docs.xperience.io 2