



General	
Unsubscription page URL	<p>Sets the URL of the page where users can unsubscribe from an <a href="#">email feed</a>. The <b>Email feed unsubscription</b> web part must be placed on the specified page to ensure the required functionality.</p> <p>The value of this setting is inherited by individual email feeds if their <b>Unsubscription page URL</b> property is not set. If empty, the <code>~/CMSPages/Unsubscribe.aspx</code> default page is used.</p>
Double opt-in approval page URL	<p>Sets the URL of the page where users can confirm their subscription to an email feed with double opt-in enabled. The <b>Subscription approval</b> web part must be placed on the specified page to ensure the required functionality.</p> <p>The value of this setting is inherited by individual email feeds if their <b>Approval page URL</b> property is not set. If empty, the <code>~/CMSModules/Newsletters/CMSPages/SubscriptionApproval.aspx</code> default page is used.</p>
Double optin interval	<p>Sets the length (in hours) of the time interval during which users will be allowed to confirm their subscription to an email feed that uses double optin. If a user does not activate their subscription within the specified number of hours, the link in their confirmation email will expire and become invalid.</p>
Generate marketing emails if emails are disabled	<p>If enabled, marketing emails will be generated and saved into the <a href="#">Email queue</a> even if sending of emails is disabled in <b>Settings -&gt; System -&gt; Emails</b>.</p>
Bounced emails	
Monitor bounced emails	<p>Indicates if bounced emails should be tracked for marketing email recipients. Bounced emails are received whenever there is a problem with the delivery of a marketing email to a contact.</p>
Bounced email address	<p>Sets the address to which bounced emails are sent when the delivery of a marketing email to a recipient fails. If set, this address is used in the <b>From</b> field of marketing emails.</p>
Bounced email limit	<p>Sets the amount of bounced emails that can be counted for a recipient before the system blocks them from receiving further emails. This limit is set for all email feeds under the selected site.</p> <p>If 0 is entered, recipients will never be blocked automatically, but their bounced email count will still be tracked and displayed in the <b>Email marketing</b> application.</p>
Block recipients globally	<p>If checked, bounces will be added to all recipients that have the same email address. This is applied across all sites in the system.</p> <p><b>Note:</b> this setting does not ensure consistency between the bounce counts of all recipients with a shared email address, only that new bounces will be added to all of them.</p> <p>This field is only available when defining global settings, i.e. when the <i>(global)</i> option is selected from the <b>Site</b> drop-down list.</p>
POP3 settings	
Server name	<p>Sets the address of the mail server where the bounced emails are stored. POP3 is used to check the server and monitor bounced emails.</p>
Server port	<p>Specifies the number of the port used to connect to the mail server.</p>
User name	<p>Sets the user name used for authentication against the mail server.</p>
Password	<p>Sets the password used for authentication against the mail server.</p>
Use SSL	<p>Indicates whether the connection to the mail server should be secured using SSL.</p>

Authentication method	<p>Allows the selection of the authentication method used for the connection to the mail server. Options include basic user name and password authentication and several challenge response mechanisms.</p> <p>The <i>Auto</i> option uses APOP if the server supports it and plain text user name and password authentication otherwise.</p>
-----------------------	---