Madelyn Novelli
CS 4675

The Illusion of Online Privacy and Data Mining: Why the Internet Knows You Better Than Your Family

Abstract

Modern Internet applications collect vast amounts of user data, often with users unaware and with no control. Through data mining techniques, companies can make strikingly accurate inferences about the personal information of a customer or user, such as predicting pregnancy before a family knows—as demonstrated by Target's now-infamous case. Meanwhile, poorly anonymized datasets, like the AOL search history leak, show how easily users can be re-identified using both leaked information and auxiliary knowledge. This paper explores the mechanisms behind data mining, including key algorithms like logistic regression, association rule mining, and temporal pattern analysis, while also examining real-world privacy risks. Additionally, this paper will evaluate technical solutions and mitigations such as k-anonymity, differential privacy, and federated learning, while offering other everyday solutions for users. While these solutions offer promising safeguards for users of the Internet, this paper concludes that without strong, privacy-preserving systems, true online privacy remains an illusion.

1. Introduction

In 2012, a furious father walked into a Target store in Minneapolis and demanded to speak with a manager. Why? He was angry that his teenage daughter was receiving coupons for baby clothes and cribs, and adamant that this was inappropriate and offensive. As it turned out, Target's data systems had identified that she was pregnant—before she had even told anyone [10]. This story isn't just a corporate PR nightmare—it's a striking example of how data mining and predictive modeling can reveal deeply personal insights with surprising accuracy, and in turn invade our privacy without us even knowing.

Data mining is the use of machine learning and statistical analysis to extract knowledge or insights from large datasets [19]. This process involves accessing and processing large amounts of personal and confidential information, posing serious risks to privacy if not handled securely or ethically. This paper explores how such statistical analyses are generated, why privacy on the Internet is increasingly fragile as technology continues to advance rapidly, and what tools are available, both currently and in the future, to protect users.

After taking Intro to Info Security here at Georgia Tech, my eyes were opened to how much companies and even the government know about us, and how little control we actually have. Through this technology review, I aim to demystify the technology behind data mining and anonymization, and highlight the urgent need for better privacy tools in modern Internet systems, as well as empower users, developers, and policymakers alike to demand transparency and stronger protections in an era where the Internet knows us better than we know ourselves.

2. Main Technical Components

2.1 Data Mining for Gold

At its core, data mining involves identifying and extracting patterns from large datasets using statistical methods and machine learning techniques [19]. The process often includes analyzing historical data to make predictions about future behavior—a practice known as predictive analytics.

In Target's case, their analysts used purchase histories across millions of customers to build a predictive model identifying correlations between product purchases and stages of pregnancy. Target statistician Andrew Pole used personal identifiable information (PII) to notice women on baby registries buying large quantities of unscented lotion at the beginning of their second trimester, as well as large amounts of calcium, magnesium, and zinc. Using this data, Pole was able to assign pregnancy prediction scores to customers based on the purchase and purchase volume of about 25 different in-store products. Target then utilized this prediction model to target pregnant women with advertisements for baby products, which could lead to unfortunate mishaps such as the scenario aforementioned [5].

But this story isn't just limited to Target—these predictive systems continuously refine themselves with more data, often without explicit user consent, and have been developed for decades now. In the 1990s, a shocking phenomenon hit retail stores, now known as the "beer & diapers correlation" or "diaper-beer syndrome." Through the use of data mining, a major retail chain discovered that the sales of diapers and beer were correlated on Friday nights between 5:00 and 7:00 pm. Capitalizing on the discovery, the store placed the two items together and sales blossomed [17]. Why? Young fathers were often responsible for picking up diapers on their way home from work, and often grabbed a pack of beer as a personal treat.

The most common example of data mining is in retail and e-commerce. Businesses track and analyze people's behavior in order to [20]:

- Deliver targeted advertising
- Recommend products to buy
- Develop better products
- Perform differential pricing
- Obtain competitive intelligence
- Make investment decisions
- Influence public opinion (e.g., political microtargeting)
- Make decisions about you (e.g., employment, insurance, credit)

Companies are able to learn about users through data given directly (e.g., search queries and social media profiles), data they passively collect (e.g., geolocation and online behavior), and data they buy from others (e.g., consumer profiles). But what's most frightening of all is that the lifecycle of data—data collection, resale, aggregation, and use—almost always occurs without people's knowledge.

2.2 The Algorithms Behind the Predictions

Predictive modeling in data mining relies on a wide range of algorithms that help systems make educated guesses about future behavior based on past data. In the case of Target's pregnancy prediction, their data science team used a combination of regression models, classification algorithms, and association rule mining to identify behavioral signals correlated with early pregnancy stages.

2.2.1 Classification Algorithms

Classification is a technique in which machine learning (ML) models use classification algorithms to assign categories (or "labels") to data [13]. In Target's case, the goal was to assign a "pregnant" or "not pregnant" label to a customer based on their purchasing behavior.

No two machine learning classification algorithms are the same, but they all follow the same general two-step process:

1. Learning
2. Classification

Step 1 involves training the model. In this phase, the model is fed a dataset where the "correct" answer is already known. For instance, Target might train a model on historical purchase data from users who later used a baby registry, and thus were confirmed to be pregnant. The algorithm would then analyze which products are statistically correlated with pregnancy. By learning patterns from this data, the model can minimize prediction error in the future.

Step 2 entails the actual process of making classifications. Once trained, the model is used on new, unlabeled data to make predictions. For instance, if a customer suddenly started buying products that strongly matched the pregnancy pattern previously identified in Step 1, the model would assign a high probability to the "pregnant" label. This prediction could then lead to targeted ads or coupons, which, while effective for marketing, also cross a line in terms of privacy.

There are multiple types of classification, including binary classification, which sorts data into two exclusive categories, and multiclass classification, which sorts data into more than two exclusive categories. There is even multilabel classification, which sorts data into nonexclusive categories. One commonly used binary classification algorithm is the Decision Tree. Decision trees split data across different attributes (e.g., purchasing unscented lotion, vitamin supplements, or cotton balls), gradually narrowing down to a prediction. For example:

- If a customer starts buying large amounts of unscented lotion,
- and then later starts buying calcium or magnesium supplements,
- and then switches to oversized handbags,
- then they may be in the second trimester of pregnancy.

Each of these choices creates a "node" in the tree, which eventually leads to a "leaf" that is the predicted class label.




Fig. 1: Decision Tree Classification Algorithm

Other commonly used classification algorithms include:

- **Random Forest**: a technique that combines the output of multiple decision trees and chooses the most popular answer as the result. This improves prediction accuracy and reduces overfitting, which is when a model learns the training data too well.
- **Support Vector Machine (SVM)**: an algorithm that plots data points into a multidimensional space and finds the optimal boundary, or hyperplane, that best separates the categories. The optimal hyperplane has the largest distance between the hyperplane and the closest data points from each class.

- **k-Nearest Neighbors (KNN)**: an algorithm that plots data points into a multidimensional space and groups data points with similar feature values into different classes. It assigns new data points to whichever class comprises the majority of that point's neighbors.
- **Naive Bayes**: an algorithm based on Bayes' Theorem that calculates the probability that a data point belongs to a certain class given its features.

2.2.2 Logistic Regression

Logistic regression algorithms are often used to perform classification tasks, and in Target's actual system, it played a key role. Logistic regression is used to estimate the probability of an event occurring—in this case, the probability that a shopper is pregnant—based on input variables (predictors). These predictors could include the individual products purchased or even the timing and frequency of purchases [15].

Both linear and logistic regression are popular models in data science, but while linear regression models identify the relationship between a dependent variable and independent variable, logistic regression models can be used to make predictions.

Mathematically, logistic regression uses the following function:

$$P(y=1) = \frac{1}{1 + e^{-(\beta_0+\beta_1 x_1+\beta_2 x_2+\cdots+\beta_n x_n)}}$$

Fig. 2: Logistic Regression Function

Where:

- $P(y = 1)$ is the probability the customer is pregnant,
- β_0 is the bias term,
- $\beta_1, \beta_2, ..., \beta_n$ are the weights for each feature,
- $x_1, x_2, ..., x_n$ are the feature values (e.g., purchase frequency of unscented lotion, folic acid, etc.).

The result is a score between 0 and 1, which can be interpreted as the probability of pregnancy. This is an example of binary logistic regression, the most commonly used approach within logistic regression. The two other types include multinomial logistic regression, in which the dependent variable has three or more possible outcomes, and ordinal logistic regression, in which the response variable has three or more possible outcomes but with a defined order, such as grading scales from A to F.




Fig. 3: Logistic Regression Models

2.2.3 Association Rule Mining

Association rule mining is a technique in data mining that identifies certain patterns of items that occur together frequently in datasets [21]. Introduced in 1994 by Rakesh Agrawal and Ramakrishnan Srikant, the Apriori algorithm comprises 3 steps to associate items with each other [12]:

1. Frequent itemsets generation
2. Expand and then prune itemsets
3. Repeat steps 1 and 2

In step 1, the algorithm identifies the unique items in the dataset along with their frequencies, or how often they appear. Then, in a process called frequent itemset mining, it combines items that appear together with a certain threshold probability and filters out the infrequent itemsets, thus ending up with itemsets with only meaningful frequencies.

Step 2 entails combining these frequent itemsets together to form larger itemsets, which are then checked against and pruned if it has a lower probability.

Steps 1 and 2 are then repeated until all frequent itemsets meet the specified threshold probability. To improve performance efficiency, the Apriori algorithm uses the following metrics:

- **Support**: the ratio of the number of times an item occurs in a transaction to the total number of transactions (i.e., how frequently the item appears)
- **Confidence**: the probability of items occurring in the itemsets together
- **Lift**: the increase in the probability of the outcome given what comes before (i.e. item A leading to item B has a higher likelihood)

A classic example of this algorithm is the market basket analysis: if someone buys jeans and shoes, they're more likely to buy a shirt—this is evident in the beer and diapers example mentioned earlier [4].




Fig. 4: Association Rule Mining: The Market Basket Analysis

Transaction ID	Items Purchased
T1	Milk, Bread, Butter
T2	Bread, Diapers, Beer
T3	Milk, Diapers, Beer, Cola
T4	Bread, Milk, Diapers, Beer
T5	Bread, Milk, Diapers, Cola

Fig. 5: Sample Transaction Table

In the above transaction table, each row represents a transaction with a unique Transaction ID and a list of items bought in that transaction. By applying association rules, we can see that customers who buy Diapers and Beer together are more likely to buy Milk too, or: {Diapers} + {Beer} → {Milk}.

In Target's case, their data scientists likely used association rules to discover "pregnancy indicator" bundles, for example: {Folic Acid Vitamins} + {Cocoa Butter Lotion} → {Diapers}.

2.2.4 Temporal Pattern Mining

Pregnancy unfolds in stages, and Target didn't just look at what women were buying, but *when* they were buying it. Temporal data mining is the process of analyzing time series data to detect patterns over time [23]. For instance, if a customer's purchases shift from energy bars to prenatal vitamins and then to baby clothes over 12 weeks, this progression becomes a strong signal.

There are three key temporal patterns that scientists identify:

1. **Frequent Temporal Patterns (FTPs)**: occur regularly over time
2. **Rare Temporal Patterns (RTPs)**: occur infrequently but are still significant
3. **Seasonal Temporal Patterns (STPs)**: repeat over regular intervals

The process of temporal pattern mining is often used in everyday situations, such as predicting the weather based on past weather observations and the probabilities of different weather outcomes. Temporal models like Hidden Markov Models (HMMs) are especially useful in predicting such behaviors over time. And while Target may not have used deep learning models at the time, modern companies certainly do.

A Hidden Markov Model is a statistical model that models the probability of transitioning from one unobserved (hidden) state to another based on observable actions. In the context of consumer behavior, the hidden state could include pregnancy status, health status, or even intent to relocate, all of which are not directly observed but directly influence a customer's decisions and actions. The observable actions we can see include purchases of prenatal vitamins, unscented lotions, and maternity clothes. In the Target case, even if a customer never outright searches for "pregnancy test," their next purchases (supplements → unscented lotion → large handbag → prenatal vitamins) could be mapped onto a probable hidden state of "early pregnancy" by a well-trained HMM.




Fig. 6: Sample Hidden Markov Model

In the above model, “Rainy” and “Sunny” are hidden states, while “Walk,” “Shop,” and “Clean” are known observations. If a person is walking outside, there is a good chance it is sunny, whereas if they are shopping or cleaning, there is a better chance it is rainy than sunny. This same premise can be applied to the purchasing habits of customers as well as innumerable other scenarios where data mining is used and users’ privacies are infringed upon.

2.2.5 Clustering-Based Customer Segmentation

Customer segmentation is a technique companies use to better understand their users and customers. Before even running predictions, companies often segment their customers into different groups, or clusters, of customers who behave similarly [18]. The four major types of segmentation bases include demographics like age, gender, and income, geographics like country, region, and size of population, psychographics like attitudes, beliefs, and personality attributes, and behavioral like usage frequency, level of user engagement, and the tendency to retain the product or service.

One of the most frequently applied behavioral segmentation approaches is the Recency, Frequency Monetary (RFM) model:

- **Recency**: measures how recently the customer used the product or service
- **Frequency**: measures how frequently the customer used the product or service
- **Monetary**: measures how much monetary value was invested toward the product or service

Clustering and segmentation allows businesses to fine-tune their predictions for different groups. For insurance, young professionals and new parents tend to have quite different lifestyles. If a customer is assigned to a “young expecting parent” cluster, they will be targeted by vastly different products and advertisements than someone who is not expecting a baby.

2.3 Cookies: Not So Sweet

While algorithms like logistic regression and association rule mining power the backend of data-driven predictions, modern surveillance extends far beyond what a user buys and into how users browse. For instance, “cookies” may sound tasty but they can actually be quite malicious.

A cookie is a piece of data that a server sends to the browser, which the browser may store and return in later requests to the same server [20]. Cookies can be quite useful and are used for a number of different tasks, such as maintaining session state across HTTP requests (e.g., logins, shopping carts, etc.) and personalization (e.g., storing preferences). However, they can also be used for tracking user behavior on or across sites.

Third-party cookies are an example of a cookie that could be used maliciously. When a page loads a resource (e.g., image, script, iframe, etc.) from another site, the browser sends the cookies set by that third-party origin. For example:

- AdTracker.com sets a tracking cookie the first time you visit a website that loads one of its ads.
- Later, when you browse other websites that also include resources from AdTracker, such as a news site or a blog, your browser automatically sends that same cookie back to AdTracker.
- AdTracker sees your activity on that second site as well and links it to the same profile, allowing it to refine ad targeting or infer sensitive information about your interests, income level, relationship status, or political learnings.

Even if you don't click the buttons, social media "Like" buttons send third-party cookies when they load, allowing these sites to track what pages you visit [16]. With an entire profile built up, websites can target ads to you or even sell it to other data aggregators. Data brokers such as Acxiom and Oracle aggregate data sources to create detailed profiles about billions of people, which they sell to businesses and governments.

This kind of tracking is often invisible to users and nearly impossible to avoid without technical countermeasures. While third-party cookies are being phased out in some browsers, technologies like browser fingerprinting, tracking pixels, and other workarounds continue to blur the line between personalization and surveillance.

2.4 Digital Fingerprinting

In cases where visitors intentionally attempt to block cookies or obscure their identity, browser fingerprinting is an alternative means of tracking users. Browser fingerprinting is "a set of tools and techniques that can capture data through a web user's browsing activity" [8]. Everyday, pages read hundreds of attributes about a person's computer configuration, such as a user's operating system, browser type, screen resolution, time zone, keyboard layout, and more. Taken together, they are often globally unique, creating a unique identifier, or "digital fingerprint," for each user.




Fig. 7: Example of a Browser Fingerprint

Canvas fingerprinting is a common browser fingerprinting method that uses the HTML5 canvas element to detect subtle rendering differences caused by different GPUs and graphics drivers, which in turn creates a unique fingerprint [20]. It's almost impossible to block or spoof without breaking the browser. This enables companies to track users across the web—even in private browsing mode.

2.5 Tracking Pixels

A tracking pixel, also known as a spy pixel, is a tiny graphic with dimensions of just 1x1 pixels that is embedded in the HTML code of a website or email and automatically loaded when a user visits that page [20]. It is so small that it can hardly be seen by email recipients or visitors of a website, yet is powerful enough to collect a wide range of information, including:

- Operating system of the user
- Type of client (e.g., email like Gmail or Outlook or web browser)
- Time and date the email was opened or the website was visited

- IP address
- User behavior, such as clicks, scrolls, or time spent on a page




Fig. 8: How a Tracking Pixel Works

One of the most infamous implementations of a tracking pixel is Meta Pixel (formerly Facebook Pixel). When websites embed this pixel, they can track users' actions and use that data to implement personalized ads on social media sites like Facebook and Instagram. This is the reason why if you view a product on one website, you might see that exact same product across your social media feeds the next day.

3. Anonymization: A False Sense of Privacy

One approach to protecting privacy is to remove identifying information from datasets collected or shared through a process called data anonymization. However, this is considered a naive approach, as stripping names, addresses, and birthdays is often not sufficient. For instance, in March 2014, the New York City Taxi & Limousine Commission (TLC) published a database of over 173 million taxi rides for research purposes. The collection of released information included a unique code for each taxi and taxi driver, the latitude, longitude, and time of the pick up, the latitude, longitude, and time of the drop-off, and the number of passengers. In theory, the identity of each taxi and taxi driver had been anonymized through hashing, which is a one-way encryption technique that can't be reverse-engineered to determine the original information [22].

Sounds safe, right?

Wrong. As a computer scientist pointed out, hashing is not a good solution when someone knows what the original input might have looked like, such as taxi numbers (which are printed on the side of a taxi). By running the hash against all possible taxi numbers, a software developer was able to re-identify each vehicle and driver for all 173 million trips.

Even further, even if TLC *had* removed all information about the driver and taxi, people could still use geolocation data to identify taxi passengers. One postgrad student googled images of celebrities getting in or out of taxis in New York during 2013 and could identify exactly where celebrities went and how much they paid. And with only a small amount of auxiliary information, which are facts obtained from other sources, this dataset also allowed people to cross-reference drop-offs at known adult entertainment venues with times and patterns, effectively deanonymizing individuals and drivers.

Even when companies properly anonymize data, poor techniques can lead to re-identification. In 2006, AOL published several months of search engine queries for millions of users, where usernames were replaced with pseudonyms that allowed searches to be aggregated. In many cases,

the data gave a chillingly detailed picture of the user's personal life, and some users could be identified using auxiliary information, such as property records or social media profiles. One of the most prominent examples of this is AOL searcher No. 4417749, who became infamous for hundreds of searches over a three-month period that ranged from "numb fingers" to "60 single men" to "dog that urinates on everything." With each search, the identity of searcher No. 4417749 became easier to discern, and it was eventually found to be Thelma Arnold, a 62 year-old widow from Lilburn, Georgia [1].

```
4417749 clothes for age 60
4417749 60 single men
4417749 best retirement city
4417749 jarret arnold
4417749 jack t. arnold
4417749 jaylene and jarrett arnold
4417749 gwinnett county yellow pages
4417749 rescue of older dogs
4417749 movies for dogs
4417749 mini strokes
4417749 dog that urinates on everything
```

Fig. 9: Searches from AOL Searcher No. 4417749

This breakdown in anonymity often comes down to the uniqueness of human behavior. Research has shown that 87% of Americans can be uniquely identified by just three attributes: their 5-digit ZIP code, birth date, and gender [3], which have come to be known as quasi-identifiers. Even sparse data, like GPS coordinates or timestamps, can act like digital fingerprints.

3.1 Defense Mechanisms

3.1.1 k-Anonymity

A stronger way to anonymize a dataset is to ensure each record is indistinguishable from at least k - 1 other records or people in the dataset. This can be done through a process called k-anonymity, which is often referred to as the power of "hiding in the crowd" [9]. If k = 2, the data is said to be 2-anonymous, which means that there are at least two sets of every combination of data in the dataset.

With k-anonymity, either quasi-identifiers can be completely removed, or their granularity is sufficiently reduced by using partial zip codes, removing birth month/day, etc. In suppression, an attribute's value is removed entirely from a dataset, and is only used for data that is not relevant to the purpose of the data collection. In data generalization, specific values are substituted for a more general one, such as changing the zip code 01234 to 012XX or grouping the age 35 into an age group 30-39.

Key Attribute	Quasi-identifier			Sensitive attribute
Name	DOB	Gender	Zipcode	Disease
Andre	1/21/76	Male	53715	Heart Disease
Beth	4/13/86	Female	53715	Hepatitis
Carol	2/28/76	Male	53703	Brochitis
Dan	1/21/76	Male	53703	Broken Arm
Ellen	4/13/86	Female	53706	Flu
Eric	2/28/76	Female	53706	Hang Nail

Fig. 10: Example of Information to be Anonymized

There are many caveats to k-anonymity, however. For instance, it only protects identity disclosure and not attribute disclosure, which is when people can learn things about a person other than which record is theirs. There can also be a tradeoff between privacy and utility.

3.1.2 Differential Privacy

Imagine that you have two identical datasets, one with your information in it, and one without. Differential privacy ensures that a person attempting to discern information about an individual within the protected dataset cannot do so by comparing the data with other datasets [11]. It is a rigorous mathematical framework that protects individual privacy while still allowing for useful statistical analysis.

The Laplace mechanism is a mathematical formula that achieves differential privacy by adding noise to a dataset [25]. The amount of noise added is the privacy budget, which quantifies the level of privacy protection.




Fig. 11: Laplace Mechanism for Differential Privacy

Differential privacy and the Laplace mechanism have been applied in various domains, such as in healthcare, finance, and the government, and is famously used by Apple, Google, and the US Census Bureau.

3.1.3 Federated Learning

Training and testing ML models involves the use of data that is sometimes dispersed amongst millions of devices. Federated learning is a new way of developing ML models in which models are trained locally on user devices rather than transferring raw data [7]. Google uses this technique in Gboard to improve next-word prediction while keeping keystrokes on the device.

While federated learning can be quite useful, it is important to recognize that these systems are not without their faults. In a situation where a subset of participants have been compromised by attackers or are malicious themselves, these participants can essentially poison the trained global model by having poisonous samples in their own local training data. This occurred in the training of Microsoft's AI chatbot Tay, which interacted with malicious users on Twitter and was quickly manipulated to learn offensive and racist language [24].

4. Building Privacy from the Ground Up

4.1 Solutions and Mitigations for Everyday Users

It can be scary to know that companies and the government can access your data and that perfect privacy is nearly impossible, but there are a plethora of tools that can help users significantly reduce their digital footprints.

4.1.1 Block Third-Party Cookies

Most browsers offer the option to block third-party cookies, which were mentioned earlier as a common threat of tracking user behavior. In Chrome, for instance, users can go to Settings → Privacy and Security → Cookies and other site data and select "Block third-party cookies."

4.1.2 Use Private Browsers

Anonymous networking is the ability to communicate online with the identity of the source and/or destination concealed. One naive approach many users use is a Virtual Private Network (VPN), which makes it so that the server doesn't learn the user's real IP address. However, the VPN provider knows who a user is and where they are going, so anonymity and privacy can be compromised in certain situations.

One example of a browser that is built with privacy in mind is Tor Browser. Tor is a distributed anonymity service based on a network of volunteer-run relay servers across the world [20]. A user's connection travels over a randomly selected path of three relays:

1. **Entry node**: knows the user's address and the identity of the middle node, but not the destination
2. **Middle node**: the middle man between the entry node and the exit node
3. **Exit node**: knows a Tor user is connecting to the destination, but doesn't know the user's address




Fig. 12: Tor Browser Relays

This process uses an "onion-routing" technique with nested encrypted tunnels, which means that no Tor relay knows both the user's address and their destination address.

4.1.3 Install Tracker Blockers

Privacy Badger is a browser extension created by the Electronic Frontier Foundation (EFF) that uses behavioral detection to identify trackers. When it detects that a server is attempting third-party tracking or canvas fingerprinting, that server is added to a blocklist. What makes Privacy Badger differ from traditional ad-blocking extensions is that it only blocks ads unless they are tracking a user, thus incentivizing advertisers to adopt better privacy practices [6].

4.1.4 Stay Alert

As always, it is important for users to do their due diligence when interacting with a website and using the Internet. There are numerous threats that can cause users to share personal information without their consent, such as phishing scams, malicious downloads, and fake login pages. Phishing attacks are a form of social engineering that tricks a user into revealing sensitive information such as their usernames, passwords, and even credit card information. Spear phishing involves more sophisticated forgery and tricks that tend to be tailored to a specific individual victim [20].

Users should always double-check URLs, avoid clicking suspicious links, and be cautious when entering sensitive information.

4.2 Current Research

Currently, researchers and scientists are working on innovative ways to promote privacy. In fact, there is an entire branch of research entitled privacy-preserving data mining (PPDM) with the intent of enhancing privacy while extracting valuable information during data mining processes. As discussed earlier, federated learning and differential privacy are just two such techniques, but there are numerous other promising developments.

4.2.1 Zero-Knowledge Proofs

In cryptography, a zero-knowledge proof allows one party (the prover) to demonstrate to another person (the verifier) that they know something without revealing the actual information [2]. For this proof to work, there are three criteria that must be satisfied:

1. **Completeness**: if the statement is true, the verifier will be convinced
2. **Soundness**: if the statement is false, the verifier won't be fooled
3. **Zero Knowledge**: the verifier learns nothing beyond the fact that the statement is true

A common example of zero-knowledge proofs is the Ali Baba cave. In this example, Peggy and Victor find a cave with two paths, A and B, leading to a magic door. Peggy claims to know the secret word to open the door but doesn't want to tell Victor, and Victor wants to learn if Peggy actually knows the secret word or not. Peggy takes any path into the cave and Victor tells her which path to take to exit the cave, knowing that the magic door will block her if she does not actually know the secret word. By repeating this a few times, Victor is able to see if Peggy actually knows the secret word when she takes the correct path back every time. If she takes the wrong path, it is improbable that Peggy knows the secret word.




Fig. 13: Ali Baba Cave Example of Zero-Knowledge Proofs

This kind of privacy-protecting proof is currently being used in advanced blockchain protocols like Zcash. It ensures that a person's wallet balance and transaction history are accurate without actually revealing this private information, so that if a person tries to send Zcash to someone, the blockchain network is assured that the Zcash is authentic.

4.2.2 Homomorphic Encryption

Homomorphic encryption allows computations to be made on encrypted data without decrypting it first [14]. This makes the handling of user data by third parties much safer, as they can process data without ever seeing the raw, sensitive information. There are three main types of homomorphic encryption:

1. **Partially homomorphic encryption**: only supports one type of operation (e.g., addition or multiplication) on ciphertexts
2. **Somewhat homomorphic encryption**: allows both addition and multiplication but only for a limited number of operations before the ciphertext is unusable
3. **Fully homomorphic encryption**: supports an unlimited number of operations on encrypted data

Currently, companies like Microsoft, IBM, and Google have active research in the field of fully homomorphic encryption.

5. Conclusion

The stories of Target's pregnancy prediction, the AOL data leak, and the NYC taxi ride database are often told as cautionary tales of the digital age, yet they represent just the tip of the iceberg and underscore a serious truth: our online behavior is constantly mined and analyzed, and potentially could be exposed without our awareness or consent. While data mining undeniably offers valuable services such as personalized recommendations and medical breakthroughs, its unchecked use has turned privacy into a luxury rather than a right.

Fortunately, privacy-preserving data mining is an up-and-coming field of research designed to accommodate both the practice of data mining as well as users' privacy. Emerging tools like differential privacy and federated learning offer ways to unite unity with anonymity, but their effectiveness relies on widespread adoption and enforcement. For instance, differential privacy can obscure individual identities in datasets, but only if companies prioritize privacy over profit. Federated learning decentralizes the training of ML models, but its security depends on safeguards against poisoning and leaks. To be a promising solution, these tools require careful implementation and commitment from developers and organizations.

Ultimately, the connection and convenience of the Internet should not require everyday users to forfeit our fundamental right to privacy. Without change, the digital world will continue to exploit user data while offering an illusion of control. The choice is clear: we can either accept privacy as a thing of the past, or we can fight to make it the foundation of our future.

6. References

1. Barbaro, M., & Zeller, T. (2006, August 9). A face is exposed for AOL searcher no. 4417749. *The New York Times.* https://www.nytimes.com/2006/08/09/technology/09aol.html
2. Byont. (n.d.). *Zero knowledge proof: How it works and the Alibaba cave experiment.* https://www.byont.io/blog/zero-knowledge-proof-how-it-works-and-the-alibaba-cave-experiment

3. Data Privacy Lab. (2000). *Simple Demographics Often Identify People Uniquely*. https://dataprivacylab.org/projects/identifiability/paper1.pdf
4. DATAtab. (2025). *Market basket analysis*. https://datatab.net/tutorial/market-basket-analysis
5. Drive Research. (2023, January 8). *How Target used data analytics to predict pregnancies.* https://www.driveresearch.com/market-research-company-blog/how-target-used-data-analytics-to-predict-pregnancies/
6. Electronic Frontier Foundation. (2025). *Privacy Badger*. https://privacybadger.org/
7. European Data Protection Supervisor. (n.d.). *Federated learning*. https://www.edps.europa.eu/press-publications/publications/techsonar/federated-learning_en
8. Fingerprint. (2024, June 21). *Browser fingerprinting techniques*. https://fingerprint.com/blog/browser-fingerprinting-techniques/
9. Google Cloud. (n.d.). *Compute k-anonymity*. https://cloud.google.com/sensitive-data-protection/docs/compute-k-anonymity
10. Hill, K. (2012, February 16). How Target figured out a teen girl was pregnant before her father did. *Forbes*. https://www.forbes.com/sites/kashmirhill/2012/02/16/how-target-figured-out-a-teen-girl-was-pregnant-before-her-father-did/
11. IEEE Digital Privacy. (n.d.). *What is differential privacy?* https://digitalprivacy.ieee.org/publications/topics/what-is-differential-privacy
12. IBM. (2024, June 9). *Apriori algorithm*. https://www.ibm.com/think/topics/apriori-algorithm
13. IBM. (2024, October 15). *Classification in machine learning.* https://www.ibm.com/think/topics/classification-machine-learning
14. IBM. (n.d.). *Homomorphic encryption*. https://www.ibm.com/think/topics/homomorphic-encryption
15. IBM. (n.d.). *Logistic regression*. https://www.ibm.com/think/topics/logistic-regression
16. Kosinski, M., & Wang, Y. (2018). *The Internet knows you better than your spouse does*. Scientific American. https://www.scientificamerican.com/article/the-internet-knows-you-better-than-your-spouse-does/
17. Matthews, R. (2016, November 15). Beer and diapers: The impossible correlation. TDWI. https://tdwi.org/articles/2016/11/15/beer-and-diapers-impossible-correlation.aspx
18. Microsoft Data Science. (2023, November 7). *Introduction to clustering-based customer segmentation.* https://medium.com/data-science-at-microsoft/introduction-to-clustering-based-customer-segmentation-2fac61e80100
19. NNLM. (2022, June 13). *Data mining*. https://www.nnlm.gov/guides/data-glossary/data-mining
20. Pearce, P., & Specter, M. (2025, April 1). CS 3235 lecture 21: Privacy & anonymity [PowerPoint slides]. School of Computer Science, Georgia Institute of Technology.
21. Pérez, J. (2024, January 20). *Fundamentals of associate rule mining*. Medium. https://medium.com/image-processing-with-python/fundaments-of-associate-rule-mining-468801ec0a29
22. Salinger, L. (2015, April 19). *Bradley Cooper's taxi ride: A lesson in privacy risk.* https://www.salingerprivacy.com.au/2015/04/19/bradley-coopers-taxi-ride-a-lesson-in-privacy-risk/

23. ScienceDirect. (2017). *Temporal data mining.* https://www.sciencedirect.com/topics/computer-science/temporal-data-mining
24. Tolpegin, V., et al. (2020). *Data poisoning attacks against federated learning systems.* arXiv. https://arxiv.org/pdf/2007.08432
25. Zhang, A. (2024, February 11). *Understanding differential privacy and Laplace distribution*. Medium. https://medium.com/@amydata/understanding-differential-privacy-and-laplace-distribution-c9fc9d7117f3