Executive Summary

Project Emmy LLM

Date: October 7, 2026

Prepared by: Matthew Livingstone, Feitian Li, Skylar Magouliotis

Problem Statement

Third-party record submissions may have data/metadata that is falsified, incorrect, and/or missing. To produce accurate translations/transliterations, localization, and determine if there are any pre-existing records, the current method is considered labour intensive, requires a lot of human intervention, and not cost-effective. Our client (Richard) would like a solution using LLM's with as little human intervention as possible.

Proposition

Our current goal is to determine which AI models and workflow are the most cost effective and can solve the problem. Our architect developed a benchmark model prototype, which has resulted in the conclusion that a benchmark model may not be the most effective way to address this problem.

The original prototype was created to investigate if the current LLM's (as of April 2026) could identify French localized movie titles from English movie records. The approach relied on multiple LLM's generating candidate French titles, followed by voting, confidence scoring, evidence checks, and a supervised selector. We determined that one-shot LLM localization, even with repeated attempts, is not a reliable foundation to solve the problem, and it would be more useful to determine a different framework than the LLM benchmark model.

After some research about current Frontier models and investigating harness workflows, we believe a harness workflow would be the most efficient choice for this issue.

Next Steps

We are currently working on our harness workflow, which as we understand is a customized search engine for the EIDR database. We are trying to determine which metadata fields are the most valuable and if there are any fields that impact the AI model to find the correct records. The pre-cleaning and processing step for data has become rather obsolete considering the capabilities of newer models; they are able to do this with essentially no error. After completing tests this week, our first test case determined that out of 2786 movies, 2481 were correctly localized resulting in an 89% success rate (using openai gpt-6 luna). The other 2 test cases resulted in a 100% success rate (using openai gpt 6.1, and anthropic sonnet 5.5, respectively).

We are currently looking into projected cost of record matching and tokenization for this project, and if the commercial google account will be able to manage the number of records in the database.

Conclusion

Ultimately, the newer frontier AI models are advancing rapidly concurrently, so the project scope has changed and might continue to change. However, we have made a lot of progress and have learned many interesting things about the capabilities of current LLM's. We believe that our current harness build will give us a lot of insight into what the LLM's are capable of and if it can solve the problem of localization. We will continue to re-evaluate and update as we move along with this project in the upcoming months.