



ULTRA AVIATION SERVICES, INC.

General Operations Manual

APPENDIX: 1

SAFETY & SECURITY BULLETIN (U-SMS-09)

Revision: Original

Date: 7/1/2015

Bulletin No: 18-006

Date: 28/Mar/18
Reissued

SUBJECT: RAMP procedures reminder Fluid spill on the AOA

APPLICABLE TO: ALL RAMP PERSONNEL

Remember company, and airport SOP dictate that any fluid , not withstanding quantity, that is spilled on the tarmac must be clean immediately. These procedures applied to aircraft fuel, gasoline, diesel, oils, and lavatory waste

Fuel spills

- 1- Stop the fuel source
- 2- Call MDR
- 3- Prevent fuel from reaching man holes
- 4- Clean up using pats, sand, or any available absorbent material

Oil Spill

- 1- Stop the source
- 2- Prevent oil from reaching man holes
- 3- Clean up using pats, sand, or any available absorbent material

Lavatory waste spill

- 1- Pick up solid material using a broom and deposit inside a 3mm bag. Disposed of bag inside a RG compactor
- 2- Prevent oil from reaching man holes
- 3- Clean up using pats, sand, or any available absorbent material

REPORT any spill to your supervisor immediately.....Write a report as to what occurred after the clean up



DO NOT INGNORE ANY SPILL, REPORT AND

CLEAN IT UP

Be SAFE follow all ramp safety rules and company SOP

PREPARED BY:

Safety Department